



**NSAI**  
Standards

Irish Standard  
I.S. EN 13803:2017

Railway applications - Track - Track  
alignment design parameters - Track gauges  
1 435 mm and wider

**I.S. EN 13803:2017**

*Incorporating amendments/corrigenda/National Annexes issued since publication:*

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard — national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

*This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):*

*NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.*

*This document is based on:*

EN 13803:2017

*Published:*

2017-04-26

*This document was published under the authority of the NSAI and comes into effect on:*

2017-05-14

ICS number:

93.100

NOTE: If blank see CEN/CENELEC cover page

NSAI  
1 Swift Square,  
Northwood, Santry  
Dublin 9

T +353 1 807 3800  
F +353 1 807 3838  
E standards@nsai.ie  
W NSAI.ie

Sales:  
T +353 1 857 6730  
F +353 1 857 6729  
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

## National Foreword

I.S. EN 13803:2017 is the adopted Irish version of the European Document EN 13803:2017, Railway applications - Track - Track alignment design parameters - Track gauges 1 435 mm and wider

This document does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

For relationships with other publications refer to the NSAI web store.

**Compliance with this document does not of itself confer immunity from legal obligations.**

*In line with international standards practice the decimal point is shown as a comma (,) throughout this document.*

This page is intentionally left blank

EUROPEAN STANDARD

**EN 13803**

NORME EUROPÉENNE

EUROPÄISCHE NORM

April 2017

ICS 93.100

Supersedes EN 13803-1:2010, EN 13803-2:2006+A1:2009

English Version

## Railway applications - Track - Track alignment design parameters - Track gauges 1 435 mm and wider

Applications ferroviaires - Voie - Paramètres de conception du tracé de la voie - Écartement 1 435 mm et plus large

Bahnwendungen - Oberbau - Trassierungsparameter - Spurweiten 1 435 mm und größer

This European Standard was approved by CEN on 21 December 2016.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels**

## Contents

Page

European foreword.....	6
<b>1</b> Scope.....	<b>7</b>
<b>2</b> Normative references.....	<b>7</b>
<b>3</b> Terms and definitions.....	<b>7</b>
<b>4</b> Symbols and abbreviations.....	<b>10</b>
<b>5</b> General.....	<b>11</b>
5.1 Background.....	11
5.2 Alignment characteristics.....	11
<b>6</b> Limits for 1 435 mm gauge.....	<b>13</b>
6.1 Radius of horizontal curve $R$ .....	13
6.2 Cant $D$ .....	13
6.3 Cant deficiency $I$ .....	14
6.4 Cant excess $E$ .....	16
6.5 Length of cant transitions $L_D$ and transition curves in the horizontal plane $L_K$ .....	17
6.5.1 General.....	17
6.5.2 Lengths of linear cant transitions and clothoids.....	17
6.5.3 Lengths of transition curves with non-constant gradient of curvature and cant.....	18
6.6 Cant gradient $dD/ds$ .....	19
6.7 Rate of change of cant $dD/dt$ .....	19
6.8 Rate of change of cant deficiency $dI/dt$ .....	20
6.9 Length of constant cant between two linear cant transitions $L_i$ .....	21
6.10 Abrupt change of horizontal curvature.....	22
6.11 Abrupt change of cant deficiency $\Delta I$ .....	22
6.12 Length between two abrupt changes of horizontal curvature $L_c$ .....	22
6.13 Length between two abrupt changes of cant deficiency $L_s$ .....	23
6.14 Track gradients $p$ .....	24
6.15 Vertical radius $R_v$ .....	25
6.16 Length of vertical curves $L_v$ .....	25
6.17 Abrupt change of track gradient $\Delta p$ .....	26
<b>Annex A (normative) Rules for converting parameter values for track gauges wider than 1 435 mm.....</b>	<b>27</b>
A.1 Scope.....	27
A.2 Symbols and abbreviations.....	27
A.3 Basic assumptions and equivalence rules.....	29
A.3.1 General.....	29
A.3.2 Basic formulae.....	29
A.3.3 Basic data.....	30
A.4 Detailed conversion rules.....	30
A.4.1 General.....	30
A.4.2 Cant $D_1$ (Subclause 6.2 of the main body of the standard).....	30
A.4.3 Cant deficiency $I_1$ (Subclause 6.3 of the main body of the standard).....	32
A.4.4 Cant excess $E_1$ (Subclause 6.4 of the main body of the standard).....	33
A.4.5 Lengths of cant transitions $L_D$ and transition curves in the horizontal plane $L_K$ (Subclause 6.5 of the main body of the standard).....	33

A.4.6	Cant gradient $dD_1/ds$ (Subclause 6.6 of the main body of the standard) .....	34
A.4.7	Rate of change of cant $dD_1/dt$ (Subclause 6.7 of the main body of the standard) .....	34
A.4.8	Rate of change of cant deficiency $dI_1/dt$ (Subclause 6.8 of the main body of the standard) .....	35
A.4.9	Abrupt change of curvature and abrupt change of cant deficiency $\Delta I_1$ (Subclauses 6.10 and 6.11 of the main body of the standard).....	36
A.4.10	Other parameters (Subclauses 6.1, 6.9, 6.12, 6.13, 6.14, 6.15, 6.16 and 6.17 of the main body of the standard).....	36
<b>Annex B (normative) Track alignment design parameter limits for track gauges wider than 1 435 mm .....</b>		
B.1	Scope .....	37
B.2	Requirements for a gauge of 1 520 mm and 1 524 mm .....	37
B.2.1	General .....	37
B.2.2	Radius of horizontal curve $R_1$ .....	37
B.2.3	Cant $D_1$ .....	37
B.2.4	Cant deficiency $I_1$ .....	38
B.2.5	Cant excess $E_1$ .....	39
B.2.6	Length of cant transitions $L_{D1}$ and transition curves in the horizontal plane $L_{K1}$ .....	39
B.2.7	Cant gradient $dD_1/ds$ .....	40
B.2.8	Rate of change of cant $dD_1/dt$ .....	41
B.2.9	Rate of change of cant deficiency $dI_1/dt$ .....	41
B.2.10	Length of constant cant between two linear cant transitions $L_{i1}$ .....	42
B.2.11	Abrupt change of horizontal curvature .....	43
B.2.12	Abrupt change of cant deficiency $\Delta I_1$ .....	43
B.2.13	Length between two abrupt changes of horizontal curvature $L_{C1}$ .....	43
B.2.14	Length between two abrupt changes of cant deficiency $L_{s1}$ .....	43
B.2.15	Track gradients $p_1$ .....	44
B.2.16	Vertical radius $R_{v1}$ .....	44
B.2.17	Length vertical curves $L_{v1}$ .....	44
B.2.18	Abrupt change of track gradient $\Delta p_1$ .....	44
B.3	Requirements for a gauge of 1 668 mm.....	44
B.3.1	General .....	44
B.3.2	Radius of horizontal curve $R_1$ .....	44
B.3.3	Cant $D_1$ .....	44
B.3.4	Cant deficiency $I_1$ .....	45
B.3.5	Cant excess $E_1$ .....	46
B.3.6	Length of cant transitions $L_{D1}$ and transition curves in the horizontal plane $L_{K1}$ .....	46
B.3.7	Cant gradient $dD_1/ds$ .....	47
B.3.8	Rate of change of cant $dD_1/dt$ .....	48
B.3.9	Rate of change of cant deficiency $dI_1/dt$ .....	49
B.3.10	Length of constant cant between two linear cant transitions $L_{i1}$ .....	50
B.3.11	Abrupt change of horizontal curvature .....	50
B.3.12	Abrupt change of cant deficiency $\Delta I_1$ .....	50
B.3.13	Length between two abrupt changes of horizontal curvature $L_{C1}$ .....	51
B.3.14	Length between two abrupt changes of cant deficiency $L_{s1}$ .....	51
B.3.15	Track gradients $p_1$ .....	51
B.3.16	Vertical radius $R_{v1}$ .....	51
B.3.17	Length vertical curves $L_{v1}$ .....	52
B.3.18	Abrupt change of track gradient $\Delta p_1$ .....	52
<b>Annex C (informative) Supplementary information about shape and length of transition curves.....</b>		
C.1	General .....	53

## EN 13803:2017 (E)

C.2	Definitions and properties of different transition curves and cant transitions.....	53
C.2.1	Definitions .....	53
C.2.2	Properties .....	54
C.3	Further aspects that may be considered for a progressive track alignment design .....	59
C.3.1	Background .....	59
C.3.2	Progressive track alignment design.....	59
Annex D (informative) Constraints and risks associated with the use of exceptional limits .....		62
Annex E (informative) Evaluation of conditions at the toe of a switch .....		63
E.1	General.....	63
E.2	Method based on effective radius .....	63
Annex F (informative) Design considerations for switch and crossing units.....		65
F.1	Examples of common switch and crossing units .....	65
F.2	Use of diamond crossings, diamond crossings with slips and tandem turnouts .....	67
F.3	Switch and crossing units on, or near, under-bridges .....	67
F.4	Abutting switch and crossing units.....	67
F.5	Switch and crossing units on horizontal curves.....	67
F.6	Switch and crossing units on canted track.....	68
F.7	Vertical alignments and switch and crossing units .....	68
Annex G (informative) Examples of applications .....		71
G.1	General.....	71
G.2	Example of crossover on horizontal curve.....	71
G.3	Example of bi-linear cant transition .....	72
G.4	Example where a cant transition is designed without a coinciding transition curve .....	73
G.5	Example of substandard transition curve.....	74
G.6	Example where several alignment elements forms an intermediate length.....	75
Annex H (informative) Examples of local limits for cant deficiency.....		76
Annex I (informative) Considerations regarding cant deficiency and cant excess .....		77
I.1	Introduction .....	77
I.2	Cant deficiency .....	77
I.3	Cant excess.....	77
I.4	Wheel climb criterion.....	77
I.5	Vehicle overturning.....	78
I.6	The lateral strength of a track under loading ( <i>Prud'homme limit</i> ).....	78
I.7	Cant deficiency at switch and crossing layouts on curves.....	78
Annex J (informative) Passenger comfort on curves.....		79
J.1	General.....	79
J.2	Lateral acceleration .....	79
J.3	Lateral jerk .....	79
J.3.1	Lateral jerk as a function of rate of change of cant deficiency.....	79
J.3.2	Lateral jerk as a function of an abrupt change of cant deficiency .....	80
J.4	Roll motions .....	80
Annex K (normative) Sign rules for calculation of $\Delta D$ , $\Delta I$ and $\Delta p$ .....		81
K.1	General regarding the sign rules.....	81
K.2	Sign rules for calculation of $\Delta D$ .....	81
K.3	Sign rules for calculation of $\Delta I$ .....	81
K.4	Sign rules for calculation of $\Delta p$ .....	82
Annex L (informative) Length of constant cant between two linear cant transitions $L_i$ .....		84
Annex M (informative) The principle of virtual transition.....		85



<b>M.1</b>	<b>Virtual transition at an abrupt change of cant deficiency.....</b>	<b>85</b>
<b>M.2</b>	<b>Virtual transition at a short intermediate length between two abrupt changes of cant deficiency.....</b>	<b>86</b>
<b>M.3</b>	<b>Limits based on the principle of the virtual transition.....</b>	<b>87</b>
<b>M.3.1</b>	<b>General .....</b>	<b>87</b>
<b>M.3.2</b>	<b>Characteristic vehicle with a distance of 20 m between bogie centres.....</b>	<b>87</b>
<b>M.3.3</b>	<b>Characteristic vehicle with a distance of 12,2 m and 10,06 m between bogie centres .....</b>	<b>87</b>
<b>Annex N (normative)</b>	<b>Lengths of intermediate elements <math>L_c</math> to prevent buffer locking.....</b>	<b>89</b>
<b>N.1</b>	<b>General .....</b>	<b>89</b>
<b>N.2</b>	<b>Basic vehicles and running conditions .....</b>	<b>89</b>
<b>N.3</b>	<b>Lengths <math>L_c</math> of an intermediate straight track between two long circular curves in the opposite directions .....</b>	<b>89</b>
<b>N.4</b>	<b>General cases for end throw differences.....</b>	<b>90</b>
<b>Annex O (informative)</b>	<b>Considerations for track gradients.....</b>	<b>93</b>
<b>O.1</b>	<b>Uphill gradients.....</b>	<b>93</b>
<b>O.2</b>	<b>Downhill gradients.....</b>	<b>93</b>
<b>O.3</b>	<b>Gradients for stabling tracks and at platforms.....</b>	<b>93</b>
<b>Annex ZA (informative)</b>	<b>Relationship between this European Standard and the Essential Requirements of EU Directive 2008/57/EC.....</b>	<b>94</b>
<b>Bibliography</b>	<b>.....</b>	<b>97</b>

## **EN 13803:2017 (E)**

### **European foreword**

This document (EN 13803:2017) has been prepared by Technical Committee CEN/TC 256 “Railway applications”, the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2017, and conflicting national standards shall be withdrawn at the latest by October 2017.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 13803-1:2010 and EN 13803-2:2006+A1:2009.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive 2008/57/EC.

For relationship with EU Directive 2008/57/EC, see informative Annex ZA, which is an integral part of this document.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

## 1 Scope

The purpose of this European Standard is to specify rules and limits for track alignment design parameters, including alignments within switches and crossings. Several of these limits are functions of speed. Alternatively, for a given track alignment, it specifies rules and limits that determine permissible speed.

This European Standard applies to nominal track gauges 1 435 mm and wider with speeds up to 360 km/h. Normative Annex A describes the conversion rules which shall be applied for tracks with nominal gauges wider than 1 435 mm. Normative Annex B is applied for nominal track gauges 1 520 mm, 1 524 mm and 1 668 mm.

This European Standard is also applicable where track alignment takes into account vehicles that have been approved for high cant deficiencies (including tilting trains).

More restrictive requirements of Technical specifications for interoperability relating to the 'infrastructure' subsystem of the rail system in the European Union (TSI INF) and other (national, company, etc.) rules will apply.

This European Standard need not be applicable to lines, or dedicated parts of railway infrastructure that are not interoperable with railway vehicles tested and approved according to EN 14363.

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13848-5, *Railway applications — Track — Track geometry quality — Part 5: Geometric quality levels — Plain line*

EN 14363, *Railway applications - Testing and Simulation for the acceptance of running characteristics of railway vehicles - Running Behaviour and stationary tests*

EN 15273-1, *Railway applications — Gauges — Part 1: General — Common rules for infrastructure and rolling stock*

EN 15273-2, *Railway applications — Gauges — Part 2: Rolling stock gauge*

EN ISO 80000-3, *Quantities and units - Part 3: Space and time (ISO 80000-3)*

## 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

### 3.1

#### **track gauge**

distance between the corresponding running edges of the two rails

### 3.2

#### **nominal track gauge**

single value which identifies the track gauge but may differ from the design track gauge, e.g. the most widely used track gauge in Europe that has a nominal value of 1 435 mm although this is not the design track gauge normally specified

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

- 
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
  - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-