



**NSAI**  
Standards

Irish Standard  
I.S. EN 1111:2017

# Sanitary tapware - Thermostatic mixing valves (PN 10) - General technical specification

**I.S. EN 1111:2017**

*Incorporating amendments/corrigenda/National Annexes issued since publication:*

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard — national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

*This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):*

*NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.*

*This document is based on:*

EN 1111:2017

*Published:*

2017-08-09

*This document was published under the authority of the NSAI and comes into effect on:*

2017-08-27

ICS number:

91.140.70

NOTE: If blank see CEN/CENELEC cover page

NSAI  
1 Swift Square,  
Northwood, Santry  
Dublin 9

T +353 1 807 3800  
F +353 1 807 3838  
E standards@nsai.ie  
W NSAI.ie

Sales:  
T +353 1 857 6730  
F +353 1 857 6729  
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

## National Foreword

I.S. EN 1111:2017 is the adopted Irish version of the European Document EN 1111:2017, Sanitary tapware - Thermostatic mixing valves (PN 10) - General technical specification

This document does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

For relationships with other publications refer to the NSAI web store.

**Compliance with this document does not of itself confer immunity from legal obligations.**

*In line with international standards practice the decimal point is shown as a comma (,) throughout this document.*

This page is intentionally left blank

EUROPEAN STANDARD

EN 1111

NORME EUROPÉENNE

EUROPÄISCHE NORM

August 2017

ICS 91.140.70

Supersedes EN 1111:1998

English Version

## Sanitary tapware - Thermostatic mixing valves (PN 10) - General technical specification

Robinetterie sanitaire - Mitigeurs thermostatiques (PN 10) -  
Spécifications techniques générales

Sanitärarmaturen - Thermostatische Mischer (PN 10) -  
Allgemeine technische Spezifikation

This European Standard was approved by CEN on 24 April 2017.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels**

<b>Contents</b>		<b>Page</b>
<b>European Foreword</b> .....		<b>6</b>
<b>Introduction</b> .....		<b>7</b>
<b>1</b>	<b>Scope</b> .....	<b>8</b>
<b>2</b>	<b>Normative references</b> .....	<b>8</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>9</b>
<b>4</b>	<b>Symbols and units</b> .....	<b>10</b>
<b>5</b>	<b>Classification</b> .....	<b>11</b>
<b>6</b>	<b>Designation</b> .....	<b>11</b>
<b>7</b>	<b>Marking/identification</b> .....	<b>12</b>
<b>7.1</b>	<b>Marking</b> .....	<b>12</b>
<b>7.2</b>	<b>Identification</b> .....	<b>12</b>
<b>8</b>	<b>Materials</b> .....	<b>12</b>
<b>8.1</b>	<b>Chemical and hygiene requirements</b> .....	<b>12</b>
<b>8.2</b>	<b>Exposed surface condition and quality of coating</b> .....	<b>12</b>
<b>9</b>	<b>Dimensional characteristics</b> .....	<b>13</b>
<b>9.1</b>	<b>General remarks</b> .....	<b>13</b>
<b>9.2</b>	<b>Inlet dimensions</b> .....	<b>13</b>
<b>9.3</b>	<b>Outlet dimensions</b> .....	<b>15</b>
<b>9.4</b>	<b>Mounting dimensions</b> .....	<b>17</b>
<b>9.5</b>	<b>Special cases</b> .....	<b>20</b>
<b>9.6</b>	<b>Flexible hoses for outlet 2</b> .....	<b>20</b>
<b>9.7</b>	<b>Outlet 2</b> .....	<b>20</b>
<b>10</b>	<b>Backflow protection</b> .....	<b>20</b>
<b>11</b>	<b>Test sequence</b> .....	<b>21</b>
<b>12</b>	<b>Leaktightness</b> .....	<b>21</b>
<b>12.1</b>	<b>General</b> .....	<b>21</b>
<b>12.1.1</b>	<b>Principle</b> .....	<b>21</b>
<b>12.1.2</b>	<b>Apparatus</b> .....	<b>21</b>
<b>12.2</b>	<b>Leaktightness of the obturator and upstream thereof</b> .....	<b>21</b>
<b>12.2.1</b>	<b>General</b> .....	<b>21</b>
<b>12.2.2</b>	<b>Procedure</b> .....	<b>21</b>
<b>12.2.3</b>	<b>Requirements</b> .....	<b>21</b>
<b>12.3</b>	<b>Cross-flow between inlets</b> .....	<b>22</b>
<b>12.3.1</b>	<b>General</b> .....	<b>22</b>
<b>12.3.2</b>	<b>Procedure</b> .....	<b>22</b>
<b>12.3.3</b>	<b>Requirements</b> .....	<b>22</b>
<b>12.4</b>	<b>Leaktightness downstream of the obturator</b> .....	<b>22</b>
<b>12.4.1</b>	<b>Procedure</b> .....	<b>22</b>
<b>12.4.2</b>	<b>Requirements</b> .....	<b>22</b>
<b>12.5</b>	<b>Leaktightness of manually operated diverter</b> .....	<b>22</b>
<b>12.5.1</b>	<b>Procedure</b> .....	<b>22</b>
<b>12.5.2</b>	<b>Requirement</b> .....	<b>23</b>

<b>12.6</b>	<b>Leaktightness of diverters with automatic return .....</b>	<b>23</b>
12.6.1	Procedure .....	23
12.6.2	Requirement.....	23
<b>13</b>	<b>Performance .....</b>	<b>23</b>
13.1	General .....	23
13.1.1	Initial settings .....	23
13.1.2	Apparatus .....	24
13.1.3	Procedure .....	24
13.2	Determination of flow rate.....	25
13.2.1	Principle.....	25
13.2.2	Procedure .....	25
13.2.3	Evaluation of the results .....	26
13.2.4	Requirements.....	26
13.3	Sensitivity .....	26
13.3.1	General .....	26
13.3.2	Principle.....	26
13.3.3	Procedure .....	26
13.3.4	Evaluation of results.....	27
13.3.5	Requirements.....	27
13.4	Fidelity.....	28
13.4.1	General .....	28
13.4.2	Principle.....	28
13.4.3	Procedure .....	28
13.4.4	Evaluation of results.....	28
13.4.5	Requirements.....	28
13.5	Temperature stability.....	29
13.5.1	Temperature control operation .....	29
13.5.2	Flow rate reduction.....	29
13.5.3	Cold supply failure and restoration.....	30
13.5.4	Supply pressure variation .....	31
13.5.5	Supply temperature variation .....	32
13.5.6	Temperature Override Stops .....	32
<b>14</b>	<b>Pressure resistance.....</b>	<b>33</b>
14.1	General .....	33
14.2	Apparatus .....	33
14.3	Testing of mechanical performance of the thermostatic mixing valve upstream of the obturator in the closed position.....	33
14.3.1	Procedure .....	33
14.3.2	Requirement.....	33
14.4	Mechanical behaviour downstream of the obturator – Obturator in the open position ....	33
14.4.1	Procedure .....	33
14.4.2	Requirement.....	34
<b>15</b>	<b>Torsional resistance of the operating controls.....</b>	<b>34</b>
15.1	General .....	34
15.2	Test method .....	34
15.2.1	Principle of the test.....	34
15.2.2	Apparatus .....	34
15.2.3	Procedure .....	34
<b>16</b>	<b>Mechanical endurance characteristics .....</b>	<b>35</b>
16.1	General .....	35
16.2	Endurance test for single sequential control device.....	35

## EN 1111:2017 (E)

16.2.1	Principle .....	35
16.2.2	Apparatus.....	35
16.2.3	Procedure.....	35
16.2.4	Requirement.....	36
16.3	Endurance test for on/off flow control device operated by rotating the control handle.....	36
16.3.1	Principle .....	36
16.3.2	General.....	36
16.4	Endurance test for on/off flow control device, combined with diverter mechanism .....	36
16.4.1	Principle .....	36
16.4.2	Apparatus.....	36
16.4.3	Procedure.....	36
16.4.4	Requirement.....	37
16.5	Endurance test for other on-off flow control device .....	37
16.5.1	Principle .....	37
16.5.2	Apparatus.....	37
16.5.3	Procedure.....	37
16.5.4	Requirement.....	37
16.6	Mechanical endurance of diverters of thermostatic mixing valves .....	38
16.6.1	General.....	38
16.6.2	Test method .....	38
16.6.3	Requirements .....	39
16.7	Mechanical endurance of swivel spouts .....	39
16.7.1	General.....	39
16.7.2	Test method .....	39
16.7.3	Requirements .....	40
16.8	Thermal Element.....	40
16.8.1	Principle .....	40
16.8.2	Temperature adjustable valves (Type 1, 2, 4) .....	40
16.8.3	Temperature set valves (Type 5) .....	41
16.8.4	Other valves with special control devices (Type 6).....	41
17	Acoustic characteristics.....	42
17.1	General.....	42
17.2	Procedure.....	42
17.2.1	Fitting and operating conditions for thermostatic mixing valves.....	42
17.2.2	Test method .....	42
17.3	Requirements .....	42
17.3.1	Expression of results.....	42
17.3.2	Determination of acoustic groups.....	42
17.3.3	Flow rate classes (thermostatic mixing valves Type 1, 2, 3) .....	42
Annex A	(normative) Test Set-up Descriptions.....	44
A.1	General.....	44
A.2	Inlet pipework.....	44
A.2.1	Thermostat endurance.....	44
A.2.2	Performance .....	45
A.3	Outlet pipework.....	45
A.3.1	General.....	45
A.3.2	Outlet for valves without integral atmospheric discharge spouts .....	46



<b>A.3.3</b>	<b>Outlet for valves with atmospheric discharge nozzles .....</b>	<b>48</b>
	<b>Annex B (normative) Measurements.....</b>	<b>49</b>
<b>B.1</b>	<b>Pressure .....</b>	<b>49</b>
<b>B.2</b>	<b>Flow .....</b>	<b>49</b>
<b>B.3</b>	<b>Temperature .....</b>	<b>49</b>
<b>B.3.1</b>	<b>Mounting.....</b>	<b>49</b>
<b>B.3.2</b>	<b>Accuracy.....</b>	<b>49</b>
<b>B.3.3</b>	<b>Response time.....</b>	<b>49</b>
<b>B.4</b>	<b>Angular position.....</b>	<b>49</b>
<b>B.5</b>	<b>Duration of transients.....</b>	<b>49</b>
	<b>Annex C (informative) Temperature transient.....</b>	<b>52</b>
<b>C.1</b>	<b>Positive temperature transient.....</b>	<b>52</b>
<b>C.2</b>	<b>Negative temperature transient.....</b>	<b>53</b>
	<b>Annex D (informative) Acoustic classification (example) .....</b>	<b>54</b>
<b>D.1</b>	<b>Thermostatic mixing valve with nozzle.....</b>	<b>54</b>
<b>D.2</b>	<b>Thermostatic mixing valves with shower or shower head outlet.....</b>	<b>54</b>
<b>D.3</b>	<b>Thermostatic mixing valves with nozzle and shower or shower head outlet .....</b>	<b>54</b>
	<b>Bibliography .....</b>	<b>56</b>

## **EN 1111:2017 (E)**

### **European Foreword**

This document (EN 1111:2017) has been prepared by Technical Committee CEN/TC 164 “Water Supply”, the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by February 2018, and conflicting national standards shall be withdrawn at the latest by February 2018.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 1111:1998.

The main technical changes compared to the previous version are the following:

- a) the introduction of Clause 10 on backflow protection;
- b) the introduction of Clause 11 on test sequence;
- c) the introduction of Clause 13 on performance;
- d) the update of chapters on pressure resistance, torsional resistance and mechanical resistance;
- e) new Annexes A, B, C and D.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

## **Introduction**

In respect of potential adverse effects on the quality of water intended for human consumption, caused by the product covered by this standard, the following should be noted:

- this standard provides no information as to whether the product can be used without restriction in any of the Member state of the EU or EFTA;
- it should be noted that, while awaiting the adoption of verifiable European criteria, existing national regulations concerning the use and/or the characteristics of this product remain in force.

**EN 1111:2017 (E)****1 Scope**

This European Standard specifies general construction, performance and material requirements for PN 10 thermostatic mixing valves (TMV) and includes test methods for the verification of mixed water temperature performance at the point of use below 45 °C. This does not exclude the selection of higher temperatures where available. When these devices are used to provide anti-scald protection for children, elderly and disabled persons the mixed water temperature needs to be set at a suitable bathing temperature (body temperature approximately 38 °C) as children are at risk to scalding at lower temperatures than adults. This does not obviate the need for supervision of young children during bathing.

It applies to valves intended for use on sanitary appliances in kitchens, washrooms (incl. all rooms with sanitary tapware, e.g. toilets and cloakrooms) and bath rooms operating under the conditions specified in Table 1.

This standard allows TMVs to supply a single outlet or a small number of outlets in a “domestic” application (e.g. one valve controlling a shower, bath, basin and/or bidet), excluding valves specifically designed for supplying a large number of outlets (i.e. for institutional use).

The tests described are type tests (laboratory tests) and not quality control tests carried out during manufacture.

**Table 1 — Conditions of use**

Supply	Operating range	
	limits	recommended
Pressure		
Static	≤ 1 MPa [≤10 bar]	
Dynamic	≥ 0,05 MPa [≥0,5 bar]	(0,1 to 0,5) MPa [(1 to 5) bar]
Temperature		
Hot	≤ 90°C	(55 to 65) °C
Cold	≤ 25°C	(5 to 20) °C

**2 Normative references**

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 200, *Sanitary tapware - Single taps and combination taps for water supply systems of type 1 and type 2 - General technical specification*

EN 246, *Sanitary tapware - General specifications for flow rate regulators*

EN 248, *Sanitary tapware - General specification for electrodeposited coatings of Ni-Cr*

EN 1057, *Copper and copper alloys — Seamless, round copper tubes for water and gas in sanitary and heating applications*

EN 1112, *Sanitary tapware - Shower outlets for sanitary tapware for water supply systems of type 1 and type 2 - General technical specification*

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

- 
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
  - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-