



NSAI
Standards

Irish Standard
I.S. EN 62439-2:2010

Industrial communication networks -
High availability automation networks
-- Part 2: Media Redundancy Protocol
(MRP) (IEC 62439-2:2010 (EQV))

I.S. EN 62439-2:2010

Incorporating amendments/corrigenda issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

<p><i>This document replaces:</i> EN 62439:2008 (partially)</p>	<p><i>This document is based on:</i> EN 62439-2:2010</p>	<p><i>Published:</i> 19 March, 2010</p>
<p>This document was published under the authority of the NSAI and comes into effect on: 9 April, 2010</p>		<p>ICS number: 25.040; 35.040</p>
<p>NSAI 1 Swift Square, Northwood, Santry Dublin 9</p>	<p>T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie</p>	<p>Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie</p>
<p>Údarás um Chaighdeáin Náisiúnta na hÉireann</p>		

English version

**Industrial communication networks -
High availability automation networks -
Part 2: Media Redundancy Protocol (MRP)
(IEC 62439-2:2010)**

Réseaux de communication industrielle –
Réseaux d'automatisme à haute
disponibilité –
Partie 2 : Protocol de redondance
de média (MRP)
(CEI 62439-2:2010)

Industrielle Kommunikationsnetze -
Hochverfügbare Automatisierungsnetze -
Teil 2: Medienredundanz-Protokoll (MRP)
(IEC 62439-2:2010)

This European Standard was approved by CENELEC on 2010-03-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: Avenue Marnix 17, B - 1000 Brussels

Foreword

The text of document 65C/583/FDIS, future edition 1 of IEC 62439-2, prepared by SC 65C, Industrial networks, of IEC TC 65, Industrial-process measurement, control and automation, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 62439-2 on 2010-03-01.

This EN 62439-2 together with EN 62439-1, EN 62439-3, EN 62439-4, EN 62439-5 and EN 62439-6 supersedes EN 62439:2008.

EN 62439-2:2010 includes the following significant technical changes with respect to EN 62439:2008:

- adding a calculation method for RSTP (rapid spanning tree protocol, IEEE 802.1Q),
- adding two new redundancy protocols: HSR (High-availability Seamless Redundancy) and DRP (Distributed Redundancy Protocol),
- moving former Clauses 1 to 4 (introduction, definitions, general aspects) and the Annexes (taxonomy, availability calculation) to EN 62439-1, which serves now as a base for the other documents,
- moving Clause 5 (MRP) to EN 62439-2 with minor editorial changes,
- moving Clause 6 (PRP) was to EN 62439-3 with minor editorial changes,
- moving Clause 7 (CRP) was to EN 62439-4 with minor editorial changes, and
- moving Clause 8 (BRP) was to EN 62439-5 with minor editorial changes,
- adding a method to calculate the maximum recovery time of RSTP in a restricted configuration (ring) to EN 62439-1 as Clause 8,
- adding specifications of the HSR (High-availability Seamless Redundancy) protocol, which shares the principles of PRP to EN 62439-3 as Clause 5, and
- introducing the DRP protocol as EN 62439-6.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent rights.

The following dates were fixed:

- latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2010-12-01
- latest date by which the national standards conflicting with the EN have to be withdrawn (dow) 2013-03-01

Annex ZA has been added by CENELEC.

Endorsement notice

The text of the International Standard IEC 62439-2:2010 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61158-2:2007	NOTE	Harmonized as EN 61158-2:2008 (not modified).
IEC 61158-5-10	NOTE	Harmonized as EN 61158-5-10.
IEC 61784-1:2007	NOTE	Harmonized as EN 61784-1:2008 (not modified).
IEC 61784-2:2007	NOTE	Harmonized as EN 61784-2:2008 (not modified).
IEC 62439-3	NOTE	Harmonized as EN 62439-3.
IEC 62439-4	NOTE	Harmonized as EN 62439-4.
IEC 62439-5	NOTE	Harmonized as EN 62439-5.
IEC 62439-6	NOTE	Harmonized as EN 62439-6.

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC 60050-191	1990	International Electrotechnical Vocabulary (IEV) - Chapter 191: Dependability and quality of service	-	-
IEC 61158-6-10	-	Industrial communication networks - Fieldbus specifications - Part 6-10: Application layer protocol specification - Type 10 elements	EN 61158-6-10	-
IEC 62439-1	2010	Industrial communication networks - High availability automation networks - Part 1: General concepts and calculation methods	EN 62439-1	2010
ISO/IEC 8802-3	2000	Information technology - Telecommunications - and information exchange between systems - Local and metropolitan area networks - Specific requirements - Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications	-	-
IEEE 802.1D	2004	IEEE Standard for Local and Metropolitan Area Networks - Media Access Control (MAC) Bridges	-	-
IEEE 802.1Q	-	IEEE Standard for Local and Metropolitan Area Networks - Virtual Bridged Local Area Networks	-	-

CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope.....	8
2 Normative references	8
3 Terms, definitions, abbreviations, acronyms, and conventions	8
3.1 Terms and definitions	8
3.2 Abbreviations and acronyms.....	8
3.3 Conventions	9
4 MRP Overview.....	9
5 MRP Media redundancy behavior	10
5.1 Ring ports	10
5.2 Media Redundancy Manager (MRM).....	11
5.3 Media Redundancy Client (MRC).....	12
5.4 Redundancy domain.....	12
5.5 Usage with diagnosis and alarms	12
5.6 Ring diagnosis.....	13
5.7 Multiple MRM in a single ring	13
5.8 BLOCKED not supported (option).....	13
6 MRP Class specification	14
6.1 General.....	14
6.2 Template	14
6.3 Attributes.....	14
7 MRP service specification.....	17
7.1 Start MRM.....	17
7.2 Stop MRM	18
7.3 State Change	19
7.4 Start MRC	20
7.5 Stop MRC.....	21
7.6 Read MRM	22
7.7 Read MRC	24
8 MRP protocol specification	25
8.1 PDU description	25
8.1.1 Basic data types	25
8.1.2 DLPDU abstract syntax reference.....	25
8.1.3 Coding of the DLPDU field SourceAddress	26
8.1.4 Coding of the DLPDU field DestinationAddress.....	26
8.1.5 Coding of the field TagControlInformation.....	27
8.1.6 Coding of the field LT	27
8.1.7 MRP APDU abstract syntax	27
8.1.8 Coding of the field MRP_TLVHeader	28
8.1.9 Coding of the field MRP_Version	29
8.1.10 Coding of the field MRP_SequenceID	29
8.1.11 Coding of the field MRP_SA	29
8.1.12 Coding of the field MRP_Prio.....	29
8.1.13 Coding of the field MRP_PortRole	29
8.1.14 Coding of the field MRP_RingState.....	29

8.1.15	Coding of the field MRP_Interval	30
8.1.16	Coding of the field MRP_Transition	30
8.1.17	Coding of the field MRP_TimeStamp	30
8.1.18	Coding of the field MRP_Blocked	30
8.1.19	Coding of the field MRP_ManufacturerOUI	31
8.1.20	Coding of the field MRP_ManufacturerData	31
8.1.21	Coding of the field MRP_DomainUUID	31
8.2	Protocol machines	31
8.2.1	MRM protocol machine	31
8.2.2	MRC protocol machine	41
8.2.3	MRM and MRC functions	48
8.2.4	FDB clear timer	51
8.2.5	Topology change timer	51
9	MRP installation, configuration and repair	51
9.1	Ring port parameters	51
9.2	Ring topology parameters	52
9.3	MRM parameters	52
9.4	MRC parameters and constraints	52
9.5	Calculation of MRP ring recovery time	53
9.5.1	Overview	53
9.5.2	Deduction of formula	53
9.5.3	Worst case calculation for recovery time of 10 ms	55
9.5.4	Worst case calculation for 50 devices	56
10	MRP Management Information Base (MIB)	56
10.1	General	56
10.2	MRP MIB with a monitoring view	56
10.3	MRP MIB with a management and monitoring view	64
	Bibliography	73
	Figure 1 – MRP stack	10
	Figure 2 – MRP ring topology with one manager and clients	11
	Figure 3 – MRP open ring with MRM	11
	Figure 4 – MRP ring with more than one MRM	13
	Figure 5 – MRP protocol machine for MRM	32
	Figure 6 – MRP protocol machine for MRC	42
	Table 1 – MRP Start MRM	17
	Table 2 – MRP Stop MRM	18
	Table 3 – MRP Change State	19
	Table 4 – MRP Start MRC	20
	Table 5 – MRP Stop MRC	21
	Table 6 – MRP Read MRM	22
	Table 7 – MRP Read MRC	24
	Table 8 – MRP DLPDU syntax for ISO/IEC 8802-3 (IEEE 802.3)	26
	Table 9 – MRP OUI	26
	Table 10 – MRP MulticastMACAddress	27

Table 11 – MRP TagControllInformation.Priority field.....	27
Table 12 – MRP LT field	27
Table 13 – MRP APDU syntax	28
Table 14 – MRP Substitutions.....	28
Table 15 – MRP_TLVHeader.Type.....	28
Table 16 – MRP_Version	29
Table 17 – MRP_Prio.....	29
Table 18 – MRP_PortRole	29
Table 19 – MRP_RingState.....	30
Table 20 – MRP_Interval	30
Table 21 – MRP_Transition.....	30
Table 22 – MRP_TimeStamp	30
Table 23 – MRP_Blocked.....	31
Table 24 – MRP_DomainUUID.....	31
Table 25 – MRP Local variables of MRM protocol machine	33
Table 26 – MRM State machine	34
Table 27 – MRP Local variables of MRC protocol machine	43
Table 28 – MRC state machine	43
Table 29 – MRP functions.....	49
Table 30 – MRP FDB clear timer.....	51
Table 31 – MRP topology change timer.....	51
Table 32 – MRP Network/Connection parameters	52
Table 33 – MRP MRM parameters	52
Table 34 – MRP MRC parameters.....	53

INTERNATIONAL ELECTROTECHNICAL COMMISSION

**INDUSTRIAL COMMUNICATION NETWORKS –
HIGH AVAILABILITY AUTOMATION NETWORKS –**

Part 2: Media Redundancy Protocol (MRP)

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

International Standard 62439-2 has been prepared by subcommittee 65C: Industrial Networks, of IEC technical committee 65: Industrial-process measurement, control and automation.

This standard cancels and replaces IEC 62439 published in 2008. This first edition constitutes a technical revision.

This edition includes the following significant technical changes with respect to IEC 62439 (2008):

- adding a calculation method for RSTP (rapid spanning tree protocol, IEEE 802.1Q),
- adding two new redundancy protocols: HSR (High-availability Seamless Redundancy) and DRP (Distributed Redundancy Protocol),
- moving former Clauses 1 to 4 (introduction, definitions, general aspects) and the Annexes (taxonomy, availability calculation) to IEC 62439-1, which serves now as a base for the other documents,
- moving Clause 5 (MRP) to IEC 62439-2 with minor editorial changes,
- moving Clause 6 (PRP) was to IEC 62439-3 with minor editorial changes,
- moving Clause 7 (CRP) was to IEC 62439-4 with minor editorial changes, and

- moving Clause 8 (BRP) was to IEC 62439-5 with minor editorial changes,
- adding a method to calculate the maximum recovery time of RSTP in a restricted configuration (ring) to IEC 62439-1 as Clause 8,
- adding specifications of the HSR (High-availability Seamless Redundancy) protocol, which shares the principles of PRP to IEC 62439-3 as Clause 5, and
- introducing the DRP protocol as IEC 62439-6.

The text of this standard is based on the following documents:

FDIS	Report on voting
65C/583/FDIS	65C/589/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This International Standard is to be read in conjunction with IEC 62439-1:2010, *Industrial communication networks – High availability automation networks – Part 1: General concepts and calculation methods*.

A list of the IEC 62439 series can be found, under the general title *Industrial communication networks – High availability automation networks*, on the IEC website.

This publication has been drafted in accordance with ISO/IEC Directives, Part 2.

The committee has decided that the contents of this amendment and the base publication will remain unchanged until the stability date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this standard may be issued at a later date.

INTRODUCTION

The IEC 62439 series specifies relevant principles for high availability networks that meet the requirements for industrial automation networks.

In the fault-free state of the network, the protocols of the IEC 62439 series provide ISO/IEC 8802-3 (IEEE 802.3) compatible, reliable data communication, and preserve determinism of real-time data communication. In cases of fault, removal, and insertion of a component, they provide deterministic recovery times.

These protocols retain fully the typical Ethernet communication capabilities as used in the office world, so that the software involved remains applicable.

The market is in need of several network solutions, each with different performance characteristics and functional capabilities, matching diverse application requirements. These solutions support different redundancy topologies and mechanisms which are introduced in IEC 62439-1 and specified in the other Parts of the IEC 62439 series. IEC 62439-1 also distinguishes between the different solutions, giving guidance to the user.

The IEC 62439 series follows the general structure and terms of IEC 61158 series.

The International Electrotechnical Commission (IEC) draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent concerning ring protocol given in Clause 5.

IEC takes no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured the IEC that he/she is willing to negotiate licences either free of charge or under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with IEC. Information may be obtained from:

Siemens AG A&D
Gleiwitzerstr. 555
Nürnberg 90475
Germany

and

Hirschmann Automation and Control GmbH
Stuttgarter Strasse 45-51
Neckartenzlingen 72654
Germany

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. IEC shall not be held responsible for identifying any or all such patent rights.

ISO (www.iso.org/patents) and IEC (http://www.iec.ch/tctools/patent_decl.htm) maintain on-line data bases of patents relevant to their standards. Users are encouraged to consult the data bases for the most up to date information concerning patents.

INDUSTRIAL COMMUNICATION NETWORKS – HIGH AVAILABILITY AUTOMATION NETWORKS –

Part 2: Media Redundancy Protocol (MRP)

1 Scope

The IEC 62439 series is applicable to high-availability automation networks based on the ISO/IEC 8802-3 (IEEE 802.3) (Ethernet) technology.

This part of the IEC 62439 series specifies a recovery protocol based on a ring topology, designed to react deterministically on a single failure of an inter-switch link or switch in the network, under the control of a dedicated media redundancy manager node.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-191:1990, *International Electrotechnical Vocabulary – Chapter 191: Dependability and quality of service*

IEC 61158-6-10, *Industrial communication networks – Fieldbus specifications – Part 6-10: Application layer protocol specification – Type 10 elements*

IEC 62439-1:2010, *Industrial communication networks – High availability automation networks – Part 1: General concepts and calculation methods*

ISO/IEC 8802-3:2000, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 3: Carrier sense multiple access with collision detection (CSMA/CD) access method and physical layer specifications*

IEEE 802.1Q, *IEEE standards for local and metropolitan area network. Virtual bridged local area networks*

IEEE 802.1D:2004, *IEEE standard for local Local and metropolitan area networks Media Access Control (MAC) Bridges*

3 Terms, definitions, abbreviations, acronyms, and conventions

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in IEC 60050-191, as well as in IEC 62439-1, apply.

3.2 Abbreviations and acronyms

For the purposes of this document, the abbreviations and acronyms given in IEC 62439-1 apply, in addition to the following.

MRC Media Redundancy Client

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-