

Irish Standard I.S. EN ISO 10819:2013

Mechanical vibration and shock - Handarm vibration - Measurement and evaluation of the vibration transmissibility of gloves at the palm of the hand (ISO 10819:2013)

© CEN 2013

No copying without NSAI permission except as permitted by copyright law.

Incorporating amendments/corrigenda/National Annexes issued since publication:

# The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWIFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

<i>This document replaces:</i> EN ISO 10819:1996				
<i>This document is based o</i> EN ISO 10819:2013	<i>n: Published:</i> 1 August, 2013			
This document was publi under the authority of th and comes into effect on 1 August, 2013	shed e NSAI :		<u>ICS number:</u> 13.160 13.340.40	
<b>NSAI</b> 1 Swift Square, Northwood, Santry Dublin 9	T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W <b>NSAI.ie</b>	<b>Sales:</b> T +353 1 857 6730 F +353 1 857 6729 W standards.ie		
Údarás um Chaighdeáin Náisiúnta na hÉireann				

# EUROPEAN STANDARD

# EN ISO 10819

# NORME EUROPÉENNE

EUROPÄISCHE NORM

July 2013

ICS 13.340.40; 13.160

Supersedes EN ISO 10819:1996

**English Version** 

## Mechanical vibration and shock - Hand-arm vibration -Measurement and evaluation of the vibration transmissibility of gloves at the palm of the hand (ISO 10819:2013)

Vibrations et chocs mécaniques - Vibrations main-bras -Mesurage et évaluation du facteur de transmission des vibrations par les gants à la paume de la main (ISO 10819:2013) Mechanische Schwingungen und Stöße - Hand-Arm-Schwingungen - Verfahren für die Messung und Bewertung der Schwingungsübertragung von Handschuhen in der Handfläche (ISO 10819:2013)

This European Standard was approved by CEN on 29 May 2013.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

EN ISO 10819:2013 (E)

Contents

Contents	
Foreword	3
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 89/686/EEC	4

## Foreword

This document (EN ISO 10819:2013) has been prepared by Technical Committee ISO/TC 108 "Mechanical vibration, shock and condition monitoring" in collaboration with Technical Committee CEN/TC 231 "Mechanical vibration and shock" the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2014, and conflicting national standards shall be withdrawn at the latest by January 2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 10819:1996.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive.

For relationship with EU Directive, see informative Annex ZA, which is an integral part of this document.

According to the CEN-CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

#### Endorsement notice

The text of ISO 10819:2013 has been approved by CEN as EN ISO 10819:2013 without any modification.

## Annex ZA

## (informative)

## Relationship between this European Standard and the Essential Requirements of EU Directive 89/686/EEC

This European Standard has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association to provide one means of conforming to Essential Requirements of the New Approach Directive 89/686/EEC on Personal protective equipment.

Once this standard is cited in the Official Journal of the European Union under that Directive and has been implemented as a national standard in at least one Member State, compliance with the normative clauses of this standard confers, within the limits of the scope of this standard, a presumption of conformity with the corresponding Essential Requirements of that Directive and associated EFTA regulations.

**WARNING** Other requirements and other EU Directives may be applicable to the products falling within the scope of this standard.

# I.S. EN ISO 10819:2013 INTERNATIONAL STANDARD

ISO 10819

Second edition 2013-07-15

## Mechanical vibration and shock — Hand-arm vibration — Measurement and evaluation of the vibration transmissibility of gloves at the palm of the hand

Vibrations et chocs mécaniques — Vibrations main-bras — Mesurage et évaluation du facteur de transmission des vibrations par les gants à la paume de la main



Reference number ISO 10819:2013(E)

ISO 10819:2013(E)



## **COPYRIGHT PROTECTED DOCUMENT**

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Case postale 56 • CH-1211 Geneva 20 Tel. + 41 22 749 01 11 Fax + 41 22 749 09 47 E-mail copyright@iso.org Web www.iso.org

Published in Switzerland

Page

# **Contents**

3

9

Foreword	iv
Introduction	<b>v</b>
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Symbols and abbreviations	2
<ul> <li>5 Measuring principle and equipment.</li> <li>5.1 General principle and setup.</li> <li>5.2 Measuring equipment.</li> <li>5.3 Vibration excitation system.</li> </ul>	3 3 7
<ul> <li>6 Measurement conditions and procedure</li> <li>6.1 Measurement conditions</li> <li>6.2 Vibration signal</li> <li>6.3 Test procedure</li> </ul>	8 
<ul> <li>Final Strain S</li></ul>	<b>13</b> 13 15 16 16
<ul> <li>8 Calculation of statistical values.</li> <li>8.1 General.</li> <li>8.2 One-third-octave vibration transmissibility.</li> <li>8.3 Frequency-weighted vibration transmissibility.</li> </ul>	<b>17</b> 17 17
<ul> <li>9 Criteria for designating gloves as antivibration gloves</li> <li>9.1 General</li> <li>9.2 Vibration transmissibility of the gloves</li> <li>9.3 Construction of the gloves</li> </ul>	<b>18</b> 18 18 19
10 Test report	21
Annex A (informative) Examples of handles with force and acceleration measuring systems	23
Bibliography	26

ISO 10819:2013(E)

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2, www.iso.org/directives.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received, www.iso.org/patents.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

The committee responsible for this document is ISO/TC 108, *Mechanical vibration, shock and condition monitoring*, Subcommittee SC 4, *Human exposure to mechanical vibration and shock*.

This second edition cancels and replaces the first edition (ISO 10819:1996), of which it constitutes a technical revision. The main changes are stronger criteria for antivibration gloves and the addition of a method for measuring the material thickness.

## Introduction

Because of the growing demand to reduce health risks associated with exposure to hand-transmitted vibration, gloves with vibration-reducing materials are often used to attenuate vibration transmitted to the hands. These gloves normally provide little reduction in hand-transmitted vibration at frequencies below 150 Hz. Some gloves can increase the vibration transmitted to the hands at these low frequencies. Gloves with vibration-reducing materials that meet the requirements of this International Standard to be classified as an antivibration glove can be expected to reduce hand-transmitted vibration at frequencies above 150 Hz. These gloves can reduce but not eliminate health risks associated with hand-transmitted vibration exposure.

Field observations indicate that gloves with vibration-reducing materials can result in positive and negative health effects. Positive health effects can occur with gloves that reduce finger tingling and numbness and that keep the hands warm and dry. Negative health effects can occur with gloves that increase the vibration transmitted to the hands at low frequencies and that increase hand and arm fatigue because they increase the hand grip effort required to control a vibrating machine.

Gloves tested in accordance with the requirements of this International Standard are evaluated in a controlled laboratory environment. The actual vibration attenuation of a glove in a work environment can differ from that measured in a controlled laboratory environment.

Vibration transmissibility measurements made in accordance with the requirements of this International Standard are performed only at the palm of the hand. The transmission of vibration to the fingers is not measured. When evaluating the effectiveness of a glove with a vibration-reducing material used to reduce vibration transmitted to the hand, vibration transmission to the fingers should also be assessed. However, research subsequent to the publication of this International Standard is needed to develop a measurement procedure that can be used to measure the vibration transmissibility of gloves at the fingers.

The measurement procedure specified in this International Standard only addresses glove properties that can reduce health risks associated with hand-transmitted vibration in work environments. It does not address glove properties necessary to reduce other hand-related health and safety risks in work environments.

The measurement procedure specified in this International Standard can also be used to measure the vibration transmissibility of a material that is being evaluated for use to cover a handle of a machine or for potential use in a glove.

This is a free page sample. Access the full version online.

### I.S. EN ISO 10819:2013

## Mechanical vibration and shock — Hand-arm vibration — Measurement and evaluation of the vibration transmissibility of gloves at the palm of the hand

WARNING — This International Standard defines a screening test procedure for measuring the vibration transmission through gloves with an embedded vibration-reducing material. Many factors not addressed in this International Standard can influence the transmission of vibration through these gloves. Therefore, use the vibration transmissibility values obtained in accordance with this International Standard with caution in the assessment of the vibration-reducing effects of gloves.

### 1 Scope

This International Standard specifies a method for the laboratory measurement, data analysis, and reporting of the vibration transmissibility of a glove with a vibration-reducing material that covers the palm, fingers, and thumb of the hand. This International Standard specifies vibration transmissibility in terms of vibration transmitted from a handle through a glove to the palm of the hand in one-third-octave frequency bands with centre frequencies of 25 Hz to 1 250 Hz.

The measurement procedure specified in this International Standard can also be used to measure the vibration transmissibility of a material that is being evaluated for use to cover a handle of a machine or for potential use in a glove. However, results from this test cannot be used to certify that a material used to cover a handle meets the requirements of this International Standard to be classified as an antivibration covering. A material tested in this manner could later be placed in a glove. When this is the case, the glove needs to be tested in accordance with the measurement procedure of this International Standard and needs to meet the vibration attenuation performance requirements of this International Standard in order to be classified as an antivibration glove.

NOTE ISO 13753<sup>[1]</sup> defines a method for screening materials used for vibration attenuation on the handles of machines and for gloves.

#### 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2041, Mechanical vibration, shock and condition monitoring — Vocabulary

ISO 5349-1, Mechanical vibration — Measurement and evaluation of human exposure to hand-transmitted vibration — Part 1: General requirements

ISO 5805, Mechanical vibration and shock — Human exposure — Vocabulary

ISO 8041, Human response to vibration — Measuring instrumentation

IEC 61260, Electroacoustics — Octave-band and fractional-octave-band filters

EN 388, Protective gloves against mechanical risks

EN 420, Protective gloves — General requirements and test methods

ISO 10819:2013(E)

### 3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 2041, ISO 5805 and the following apply.

#### 3.1

#### glove vibration transmissibility

ratio of the acceleration measured on the palm adaptor of the gloved hand to the acceleration measured on the instrumented handle

Note 1 to entry: Glove vibration transmissibility values greater than 1 indicate that the glove amplifies the vibration, and values lower than 1 indicate that the glove attenuates the vibration.

### 4 Symbols and abbreviations

The following symbols and abbreviations are used.

$a_{h(Pb)}(f_i)$	unweighted r.m.s. acceleration measured on the bare adaptor in the <i>i</i> th one-third-octave band
$a_{h(Pbx,y,z)}(f_i)$	value of $a_{h(Pb)}(f_i)$ on three mutually orthogonal axes, respectively
$a_{h(Pg)}(f_i)$	unweighted r.m.s. acceleration measured on the palm adaptor of the gloved hand in the <i>i</i> th one-third-octave band
$a_{h(Pgx,y,z)}(f_i)$	value of $a_{h(Pg)}(f_i)$ on three mutually orthogonal axes, respectively
$a_{h(S)}(f_i)$	unweighted r.m.s. acceleration for spectrum <i>S</i> in the <i>i</i> th one-third-octave band
$a_{\mathrm{hw}(S)}(f_i)$	frequency-weighted r.m.s. acceleration for spectrum <i>S</i> in the <i>i</i> th one-third-octave band
$a_{\rm R}(f_i)$	unweighted r.m.s. acceleration measured at the reference position on the handle in the <i>i</i> th one-third-octave band
$C_{V,T}(f_i)$	coefficient of variation for the corrected handle-gloved hand transmissibility in the <i>i</i> th one-third-octave band
$C_{V,T(S)}$	coefficient of variation for the handle-gloved ISO-weighted hand transmissibility for spectrum ${\cal S}$
fi	centre frequency of the <i>i</i> th one-third-octave band
Н	subscript representing one-third-octave frequency bands from 200 Hz to 1 250 Hz
iL	frequency band number of the lowest one-third-octave band associated with each spectrum $S$ according to $\underline{\text{Table 2}}$
iU	frequency band number of the uppermost one-third-octave band associated with each spectrum $S$ according to Table 2
М	subscript representing one-third-octave frequency bands from 25 Hz to 200 Hz
S	spectrum, $S = S_M$ or $S_H$
$s_T(f_i)$	standard deviation for the corrected handle-gloved hand transmissibility in the <i>i</i> th one-third- octave band
$S_{T(S)}$	standard deviation for the handle-gloved ISO-weighted hand transmissibility for spectrum $S$
$T_{\rm b}(f_i)$	handle-adaptor bare adaptor transmissibility in the <i>i</i> th one-third-octave band
$T_{\rm g}(f_i)$	handle-gloved hand transmissibility in the <i>i</i> th one-third-octave band

$T_{b(S)}$	handle-adaptor bare adaptor ISO weighted transmissibility for spectrum S
------------	--

- $T_{g(S)}$  uncorrected handle-gloved hand ISO weighted transmissibility for spectrum S
- *T*(*f*<sub>*i*</sub>) corrected handle-gloved hand transmissibility in the *i*th one-third-octave band
- $T_{(S)}$  corrected handle-gloved ISO weighted hand transmissibility for spectrum S
- $\overline{T}(f_i)$  mean value for the corrected handle-gloved hand transmissibility in the *i*th one-third-octave band
- $\overline{T}_{(S)}$  mean value for the handle-gloved ISO-weighted hand transmissibility for spectrum S
- *W*<sub>hi</sub> ISO frequency-weighting factor specified in ISO 5349-1 for the *i*th one third-octave frequency band associated with each spectrum *S*

### 5 Measuring principle and equipment

#### 5.1 General principle and setup

The method specified in this International Standard is used to measure the vibration input to a gloved hand that is transmitted through the glove at the palm of the hand, which grips and pushes on an instrumented handle. The glove vibration transmissibility (3.1) measured at the palm is used as an index to judge the vibration-reducing effectiveness of the glove. A vibration excitation system (normally an electromechanical shaker) shall be used to generate the required vibration input. The vibration in the direction of the excitation shall be simultaneously measured at the middle point of the top of the instrumented handle (see <u>Annex A</u>) and between the palm of the hand and glove by means of a palm adaptor. The adaptor shall contain an accelerometer and shall be placed inside the glove between the hand and handle. To compensate for the frequency response of the palm adaptor, the glove vibration transmissibility is calculated as the ratio of the vibration transmissibility values at the palm of the hand with a glove, as measured with the palm adaptor, divided by the corresponding transmissibility values associated with the bare palm adaptor attached to the handle.

A schematic drawing of a recommended vibration measurement setup is shown in Figure 1. The acceleration at the reference point in the instrumented handle,  $a_R(f_i)$ , and the vibration at the palm of the hand,  $a_{h(Pb)}(f_i)$  or  $a_{h(Pg)}(f_i)$ , shall be measured simultaneously. Annex A shows examples of instrumented handles. The diameter of that part of the instrumented handle that is clasped by the hand shall be (40 ± 0,5) mm.

The values of the grip and feed forces shall be displayed continuously so the test subject can continually monitor them and consistently apply the required grip and feed forces throughout a test.



This is a free preview. Purchase the entire publication at the link below:

**Product Page** 

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation