

Irish Standard I.S. EN 50342-6:2015

Lead-acid starter batteries - Part 6: Batteries for Micro-Cycle Applications

 $\ensuremath{\mathbb C}$ CENELEC 2015 $\hfill No copying without NSAI permission except as permitted by copyright law.$

I.S. EN 50342-6:2015

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWIFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):

NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.

This document is based on: EN 50342-6:2015

2015-12-08

Published: 2015-11-20

This document was published under the authority of the NSAI and comes into effect on:

ICS number:

NOTE: If blank see CEN/CENELEC cover page

NSAI	T +353 1 807 3800	Sales:
1 Swift Square,	F +353 1 807 3838	T +353 1 857 6730
Northwood, Santry	E standards@nsai.ie	F +353 1 857 6729
Dublin 9	W NSAI.ie	W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

National Foreword

I.S. EN 50342-6:2015 is the adopted Irish version of the European Document EN 50342-6:2015, Lead-acid starter batteries - Part 6: Batteries for Micro-Cycle Applications

This document does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

Compliance with this document does not of itself confer immunity from legal obligations.

In line with international standards practice the decimal point is shown as a comma (,) throughout this document.

This is a free page sample. Access the full version online.

This page is intentionally left blank

EUROPEAN STANDARD

EN 50342-6

EUROPÄISCHE NORM

November 2015

ICS 29.220.20

English Version

Lead-acid starter batteries - Part 6: Batteries for Micro-Cycle Applications

Batteries d'accumulateurs de démarrage au plomb - Partie 6: Batteries pour applications micro-cycles Blei-Akkumulatoren-Starterbatterien - Teil 6 : Batterien für Mikrozyklen-Anwendungen

This European Standard was approved by CENELEC on 2015-10-05. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

© 2015 CENELEC All rights of exploitation in any form and by any means reserved worldwide for CENELEC Members.

Contents

Europe	an foreword4		
1	Scope 5		
2	Normative references 5		
3	General5		
3.1	Designation of starter batteries		
3.2	Condition on delivery5		
4	General requirements — Identification and labelling		
5	General test conditions		
5.1 5.1.1 5.1.2	Characteristics and abbreviations 6 Nominal capacity C _n 6 Cranking current I _{CC} 6		
5.2	Syntax of test descriptions		
5.3 5.3.1 5.3.2 5.3.3 5.3.4	Requirements for measuring equipment capability		
5.4	Sampling of batteries9		
6	Test sequence9		
7	Inspections and test procedures 11		
7.1	Charging of batteries 11		
7.2 7.2.1 7.2.2 7.2.3 7.2.4 7.2.5 7.2.6	Micro-hybrid test (MHT)11Purpose11Procedure11Battery preparation11Micro-cycles11Check-up after cycling12Data evaluation13		
7.3	Dynamic Charge acceptance test (DCA) 13		
7.4	Endurance in cycle test with 17,5 % depth of discharge (DoD) 17		
7.5	Endurance in cycle test with 50 % depth of discharge (DoD) at 40 °C and preceded deep discharge		
8	Requirements and battery performance levels		
8.1	General		
8.2	Tests to be passed (no performance differentiation)		
8.3	Tests determining the micro-cycle performance level		
Annex A (normative) Flow charts of DCA test procedure, 7.3			
Annex B (normative) Marking / Labelling of Batteries			
Bibliog	Bibliography27		

Tables

Table 1 — Test steps6
Table 2 — Description of columns7
Table 3 — Acronyms and Symbols
Table 4 — Equipment requirements for the micro-hybrid test MHT
Table 5 — Equipment requirements for the dynamic charge acceptance test DCA9
Table 6 — Test sequence10
Table 7 — MHT – Battery preparation11
Table 8 — MHT – Micro-cycle12
Table 9 — MHT – Check-up after cycling12
Table 10 — DCA – Pre-cycling14
Table 11 — DCA – Charge Acceptance qDCA procedure14
Table 12 — DCA – The DCA _{pp} procedure15
Table 13 — DCA – The DCR _{ss} part16
Table 14 — Endurance 17,5 % DoD – Cycling units18
Table 15 — Endurance 50 % DoD – Deep discharge part19
Table 16 — Endurance 50 % DoD – Cycling part20
Table 17 — Requirements of tests to be passed21
Table 18 — Requirements of tests determining the micro-cycle performance level M1M321

Figures

Figure 1 — Sub-phases of the DCRss part	17
Figure B.1 — Optional Start-Stop logo	26

European foreword

This document (EN 50342-6:2015) has been prepared by CLC/TC 21X "Secondary cells and batteries".

The following dates are fixed:

latest date by which this document has (dop) 2016-10-05 to be implemented at national level by publication of an identical national standard or by endorsement
latest date by which the national (dow) 2018-10-05 standards conflicting with this document have to be withdrawn

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

EN 50342, Lead-acid starter batteries, is currently composed of the following parts:

- Part 1: General requirements and methods of test [currently at Formal Vote stage];
- Part 2: Dimensions of batteries and marking of terminals;
- Part 3: Terminal system for batteries with 36 V nominal voltage;
- Part 4: Dimensions of batteries for heavy vehicles;
- Part 5: Properties of battery housings and handles;
- Part 6: Batteries for Micro-Cycle Applications [the present document];
- *Part 7: General requirements and methods of tests for motorcycle batteries* [currently at Formal Vote stage].

1 Scope

This European Standard is applicable to lead-acid batteries with a nominal voltage of 12 V, used primarily as power source for the starting of internal combustion engines (ICE), lighting and also for auxiliary equipment of ICE vehicles. These batteries are commonly called "starter batteries". Batteries with a nominal voltage of 6 V are also included in the scope of this standard. All referenced voltages need to be divided by two for 6 V batteries. The batteries under scope of this standard are used for micro-cycle applications in vehicles which can also be called Start-Stop (or Stop-Start, idling-stop system, micro-hybrid or idle-stop-and-go) applications. In cars with this special capability, the internal combustion engine is switched off during a complete vehicle stop, during idling with low speed or during idling without the need of supporting the vehicle movement by the internal combustion engine. During the phases in which the engine is switched off, most of the electric and electronic components of the car need to be supplied by the battery without support of the alternator. In addition, in most cases an additional regenerative braking (recuperation or regeneration of braking energy) function is installed. The batteries under these applications are stressed in a completely different way compared to classical starter batteries. Aside of these additional properties, those batteries need to crank the ICE and support the lighting and also auxiliary functions in a standard operating mode with support of the alternator when the internal combustion engine is switched on. All batteries under this scope need to fulfil basic functions, which are tested under application of EN 50342-1:2015.

This European Standard is applicable to batteries for the following purposes:

- Lead-acid batteries of the dimensions according to EN 50342-2 for vehicles with the capability to automatically switch off the ICE during vehicle operation either in standstill or moving ("Start-Stop");
- Lead-acid batteries of the dimensions according to EN 50342-2 for vehicles with Start-Stop applications with the capability to recover braking energy or energy from other sources.

This standard is not applicable to batteries for purposes other than mentioned above, but it is applicable to EFB delivered in dry-charged conditions according to EN 50342-1:2015, Clause 7.

NOTE The applicability of this standard also for batteries according to EN 50342-4 is under consideration.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50342-1:2015, Lead-acid starter batteries — Part 1: General requirements and methods of test

3 General

3.1 Designation of starter batteries

Regarding the designation of starter batteries, refer to EN 50342-1:2015, 3.2.

3.2 Condition on delivery

Regarding the condition on delivery, refer to EN 50342-1:2015, 3.3.

4 General requirements — Identification and labelling

The batteries shall be identified according to the legal demands within the European community.

NOTE The regulations of the battery directive 2006/66/EC and the amendment 2008/12/EC or their equivalent national laws need to be applied.



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation