

Irish Standard I.S. EN 14972-9:2020

Fixed firefighting systems - Water mist systems - Part 9: Test protocol for machinery in enclosures not exceeding 260 m³ for open nozzle systems

 $\ensuremath{\mathbb C}$ CEN 2020 $\hfill No copying without NSAI permission except as permitted by copyright law.$

I.S. EN 14972-9:2020

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):

NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.

This document is based on: EN 14972-9:2020 *Published:* 2020-01-22

This document was published under the authority of the NSAI and comes into effect on:

2020-02-09

ICS number:

13.220.20

NOTE: If blank see CEN/CENELEC cover page

NSAI	T +353 1 807 3800	Sales:
1 Swift Square,	F +353 1 807 3838	T +353 1 857 6730
Northwood, Santry	E standards@nsai.ie	F +353 1 857 6729
Dublin 9	W NSAI.ie	W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

National Foreword

I.S. EN 14972-9:2020 is the adopted Irish version of the European Document EN 14972-9:2020, Fixed firefighting systems - Water mist systems - Part 9: Test protocol for machinery in enclosures not exceeding 260 m³ for open nozzle systems

This document does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

For relationships with other publications refer to the NSAI web store.

Compliance with this document does not of itself confer immunity from legal obligations.

In line with international standards practice the decimal point is shown as a comma (,) throughout this document.

This is a free page sample. Access the full version online.

This page is intentionally left blank

EUROPEAN STANDARD NORME EUROPÉENNE

EN 14972-9

EUROPÄISCHE NORM

January 2020

ICS 13.220.20

English Version

Fixed firefighting systems - Water mist systems - Part 9: Test protocol for machinery in enclosures not exceeding 260 m³ for open nozzle systems

Installations fixes de lutte contre l'incendie - Systèmes à brouillard d'eau - Partie 9 : Protocole d'essai des systèmes à buses ouvertes pour machines situées dans des enceintes ne dépassant pas 260 m³ Ortsfeste Brandbekämpfungsanlagen - Feinsprüh-Löschanlagen - Teil 9: Prüfprotokoll für Maschinen in Gehäusen bis 260 m³ für offene Düsensysteme

This European Standard was approved by CEN on 11 November 2019.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

This is a free page sample. Access the full version online. $I.S.\ EN\ 14972-9:2020$

EN 14972-9:2020 (E)

Contents

Europ	ean foreword	.3
1	Scope	.4
2	Normative references	.4
3	Terms and definitions	.4
4	General requirements	.4
5	Test enclosure requirements	. 5
6	Machinery mock-up requirement	.6
7	Test equipment requirements	.7
8	Instrumentation requirements	.8
9 0 1	Fire test requirements	.9
9.1 9.2	Unshielded 1 MW diesel sprav fire	.9
9.3	Shielded 1 MW diesel spray fire	10
9.4	Shielded 1 m ² diesel pool fire	10
9.5	Shielded 2 MW diesel spray fire, system performance under limited natural	
	ventilation	11
9.6	Shielded 2 MW diesel spray fire, system performance at smaller enclosure volumes	11
9.7	Unshielded 1 MW heptane spray fire	12
9.8	Shielded 1 MW heptane spray fire	12
9.9	Shielded 1 m ² heptane pool fire	13
9.10	Shielded 2 MW heptane spray fire, system performance under limited natural	
	ventilation	13
9.11	Shielded 2 MW heptane spray fire, system performance at smaller enclosure	14
	voluiiics	14
10	Test report	14

European foreword

This document (EN 14972-9:2020) has been prepared by Technical Committee CEN/TC 191 "Fixed firefighting systems", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by July 2020 and conflicting national standards shall be withdrawn at the latest by July 2020.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN shall not be held responsible for identifying any or all such patent rights.

EN 14972, *Fixed firefighting systems — Water mist systems* consists of the following parts:

- Part 1: Design, installation, inspection and maintenance;
- Part 2: Test protocol for shopping areas for automatic nozzle systems;
- Part 3: Test protocol for office, school and hotel for automatic nozzle systems;
- Part 4: Test protocol for non-storage occupancies for automatic nozzle systems;
- Part 5: Test protocol for car garages for automatic nozzle systems;
- Part 6: Test protocol for false floors and false ceilings for automatic nozzle systems;
- Part 7: Test protocol for commercial low hazard occupancies for automatic nozzle systems;
- Part 8: Test protocol for machinery in enclosures exceeding 260 m³ for open nozzle systems;
- Part 9: Test protocol for machinery in enclosures not exceeding 260 m³ for open nozzle systems;
- Part 10: Test protocol for atrium protection with sidewall nozzles for open nozzle systems;
- Part 11: Test protocol for cable tunnels for open nozzle systems;
- Part 12: Test protocol for commercial deep fat cooking fryers for open nozzle systems;
- Part 13: Test protocol for wet benches and other similar processing equipment for open nozzle systems;
- Part 14: Test protocol for combustion turbines in enclosures exceeding 260 m³ for open nozzle systems;
- Part 15: Test protocol for combustion turbines in enclosures not exceeding 260 m³ for open nozzle systems;
- Part 16: Test protocol for industrial oil cookers for open nozzle systems;
- Part 17: Test protocol for residential occupancies for automatic nozzle systems.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

This document specifies fire testing requirements for water mist systems used for fire protection of machinery in enclosures with volumes not exceeding 260 m³.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 14972-1:-1, Fixed firefighting systems — Water mist systems — Part 1: Design, installation, inspection and maintenance

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 14972-1¹) and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <u>https://www.iso.org/obp</u>

— IEC Electropedia: available at <u>http://www.electropedia.org/</u>

3.1

machinery enclosure

<water mist systems>

any enclosure containing equipment that uses fuel and/or lubrication fluids with volatilities less than or equal to heptane

4 General requirements

4.1 The water mist system, operating without manual intervention, shall successfully complete all described performance fire tests for their specific applications.

4.2 The fire tests shall be conducted until the fire is extinguished, as required by the applicable fire test.

4.3 System components, component locations, operating conditions and test enclosure details shall remain unaltered throughout all of the fire tests for a given application.

4.4 All fire tests shall be conducted using the specifications from the manufacturer's DIOM manual in regard to nozzle placement, spray flux, and spray duration. Sprays can be continuous or intermittent in time. In the case of intermittent, or cycled, sprays, the time period during which the system is not discharging shall not be greater than 50 % of one complete on/off cycle. The system off period shall not exceed one minute.

4.5 In conjunction with the performance fire tests, all twin fluid water mist systems (except for those applying compressed air) shall be subjected to a straight discharge test with no fire to evaluate the resulting discharge and oxygen concentration. This evaluation shall be conducted using the maximum extinguishing agent flow and pressure. The discharge duration for the test shall be the maximum

¹⁾ Under preparation. Stage at the time of publication: prEN 14972-1:2019.



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation