

Irish Standard Recommendation S.R. CLC/TS 51643-32:2020

Low-voltage surge protective devices -Part 32: Surge protective devices connected to the DC side of photovoltaic installations - Selection and application principles

 $\ensuremath{\mathbb C}$ CENELEC 2020 $\hfill No copying without NSAI permission except as permitted by copyright law.$

S.R. CLC/TS 51643-32:2020

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWIFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):

NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.

This document is based on: CLC/TS 51643-32:2020 *Published:* 2020-07-17

This document was published		ICS number:	
and comes into effect on:		27.160	
		29.120.50	
2020-08-14			
		NOTE: If blank see CEN/CENELEC cover page	
	`		
NSAI	T +353 1	1 807 3800 Sales:	
1 Swift Square,	F +353 1	1 807 3838 T +353 1 857 6730	
Northwood, Santry	E standa	ards@nsai.ie F +353 1 857 6729	
Dublin 9	W NSAI.i	ie W standards.ie	
Úda	rás um Cha	aighdeáin Náisiúnta na hÉireann	

National Foreword

S.R. CLC/TS 51643-32:2020 is the adopted Irish version of the European Document CLC/TS 51643-32:2020, Low-voltage surge protective devices - Part 32: Surge protective devices connected to the DC side of photovoltaic installations - Selection and application principles

This document does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

For relationships with other publications refer to the NSAI web store.

Compliance with this document does not of itself confer immunity from legal obligations.

In line with international standards practice the decimal point is shown as a comma (,) throughout this document.

This is a free page sample. Access the full version online.

This page is intentionally left blank

This is a free page sample. Access the full version online. S.R. CLC/TS 51643-32:2020

TECHNICAL SPECIFICATION SPÉCIFICATION TECHNIQUE TECHNISCHE SPEZIFIKATION

CLC/TS 51643-32

July 2020

ICS 27.160; 29.120.50

Supersedes CLC/TS 50539-12:2013

English Version

Low-voltage surge protective devices - Part 32: Surge protective devices connected to the DC side of photovoltaic installations - Selection and application principles

Parafoudres basse tension - Partie 32 : Parafoudres connectés au côté courant continu des installations photovoltaïques - Principes de choix et d'application Überspannungsschutzgeräte für Niederspannung - Teil 32: Überspannungsschutzgeräte für den Einsatz auf der Gleichstromseite von Photovoltaik-Installationen - Auswahl und Anwendungsgrundsätze

This Technical Specification was approved by CENELEC on 2020-05-25.

CENELEC members are required to announce the existence of this TS in the same way as for an EN and to make the TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

© 2020 CENELEC All rights of exploitation in any form and by any means reserved worldwide for CENELEC Members.

Page

CLC/TS 51643-32:2020 (E)

Contents

			-
Eur	opean fore	word	5
Intro	oduction		6
1	Scope		7
2	Normativ	e references	7
3	Terms ar	nd definitions	8
4	Systems	and equipment to be protected	11
5	Overvolta	ages in a PV installation	12
6	Selection	and erection of SPDs	12
6	6.1 Ge	neral	12
Tab	le 1 — Sel	ection of SPD type and cross section of bonding conductor	13
6	6.2 Re	quirements for different PV installations	13
	6.2.1	General	13
<u> </u>	6.2.2	PV installation without an external LPS	14
Figu	ire 1 — Ins	stallation of SPDs in the case of a building without an external LPS	14
	6.2.3	PV installation with an external LPS when the separation distance (s) is maintained (excluding multi-earthed solar systems, such as PV power plants)	
Figu	ure 2 — Ins	stallation of SPDs in the case of a PV installation with an external LPS where the	
_	separatio	n distance (<i>s</i>) is maintained	15
	6.2.4	PV installation with an external LPS where the separation distance (<i>s</i>) cannot be maintained (including multi-earthed systems, such as PV power plants)	16
Figu	ure 3 — Ins	stallation of SPDs in the case of a PV-installation with an external LPS where the	
	separatio	n distance (s) cannot be maintained	16
	6.2.5	PV installation including communication and signalling circuits	16
t	0.3 Se	Conoral	17 17
	6.3.2	Selection of SPDs with regard to nominal discharge current I_n and impulse	17
	6.0.0	Culterit / _{imp}	17
	6.3.3	Selection of SPDs with regard to voltage protection level U_p	17
Figu	6.3.4 ure 4 — Ins	Installation of SPDs on the AC side stallation of SPDs on the AC side with a short distance between the origin of the	17
	installatio	on and the PV inverter (E < 10 m)	18
Figu	ure 5 — Ins installatio	stallation of SPDs on the AC side with a long distance between the origin of the on and the PV inverter (E \ge 10 m)	18
6	6.4 Se	lection and erection of SPDs installed on the DC side	19
	6.4.1	General	19
	6.4.2	Selection of SPDs with regard to nominal discharge current <i>I</i> _n and impulse current <i>I</i> _{imp}	19
	6.4.3	Selection of U _{CPV} of SPDs on the DC side	19
	6.4.4	Selection of SPDs with regard to its leakage current <i>I</i> _{PF}	19
	6.4.5	Selection of SPDs with regard to voltage protection level Un	19
Tab	le 2 — Ra	ted impulse voltage U_{W} for equipment between PV array and inverter (where no	00
		Installation of SDDs on the DC side	20
	0.4.0	Instanation of ords on the do side	∠0

CLC/TS 51643-32:2020 (E)

Figu	re 6 — Example of overvoltage protection on the DC side of a PV installation	21
	6.4.7 Cross-sections of connecting conductors for SPDs on the DC side	21
	6.4.8 Connection schemes of assemblies of SPDs on the DC side	22
Figu	re 7 — Example of connections (Y, D and U) on the DC side of a PV source	23
Figu	re 8 — Example of connections (L and I) on the DC side of a reliable earthed PV source when distance between SPDs and the reliable earthing is less than 1 m	23
	6.4.9 Selection of <i>I</i> _{SCPV} of SPDs on the DC side	23
6	5.5 Coordination of SPDs	24
7	Earthing Arrangement	24
8	Requirements for the installation of surge protective devices (SPDs) in a PV system	25
9	Maintenance	25
Ann	ex A (normative) Determination of the value of <i>l_{imp}</i> or <i>l_n</i> for SPDs according to the	
	simplified approach for different structures protected by an LPS	26
A.1	Introduction	26
A.2	Building with a PV installation on the roof according to 6.2.4	27
Figu	re A.1 — Example of a structure with two external down conductors to determine the value of the discharge current for the selection of SPDs	29
Tabl	le A.1 — Values of $I_{\rm imp}$ ($I_{10/350}$) and $I_{\rm n}$ ($I_{8/20}$) for voltage limiting SPDs on the DC side of	
	a PV installation mounted on the roof of a building with an external LPS if the separation distance is not maintained.	29
Tabl	le A.2 — Values of $I_{\rm imp}$ ($I_{10/350}$) for voltage switching SPDs on the DC side of a PV	
	installation mounted on the roof of a building with an external LPS, if the separation	
	distance is not maintained	30
A.3	Free- field PV power plant	30
Figu	re A.2 — Example of the structure of an extended PV installation — A PV power plant with multiple earthing and a meshed earthing system	32
Tabl	le A.3 — Values of $I_{\rm imp}$ ($I_{10/350}$) and $I_{\rm n}$ ($I_{8/20}$) for SPDs used on the DC side in PV	
	power plants with a central inverter, multiple earthing and a meshed earthing system	33
A.4	Selection of Type 1 SPDs impulse current <i>l</i> _{imp} when A.2 or A.3 cannot be applied.	34
Ann	ex B (informative) Characteristics of a PV source	35
B.1	PV source characteristics	35
Figu	re B.1 — Equivalent circuit diagram of a PV current source	35
Figu	re B.2 — I/U characteristics of a PV source at different conditions	36
Figu	re B.3 — Comparison of I/U characteristics of a PV source at different radiation conditions and linear DC sources for SPD testing.	37
B.2	Calculation of U _{OC MAX}	38
B.3	Calculation of I _{SC MAX}	38
Ann	ex C (informative) Additional information to Clause 6: Selection and erection of SPDs and to Clause 7: Earthing Arrangement	39
C.1	PV installation including communication and signalling circuits	39
Figu	re C 1 — Example of SPDs installed on a PV system protected by an external LPS where	
i igu	the separation distance (s) is maintained – Installation includes data acquisition and control system	40
C.2	PV installation and dimensions of equipotential bonding conductors	41
	σσ	-

This is a free page sample. Access the full version online. S.R. CLC/TS 51643-32:2020

CLC/TS 51643-32:2020 (E)

Figure C.2 — Example of a building with an external LPS – Dimensions of equipotential bonding conductors when the separation distance (s) is maintained, or an isolated LPS is	
used	41
Figure C.3 — Example of a building with an external LPS – Dimensions of equipotential bonding conductors when the separation distance (s) is not maintained	42
Bibliography	43

This is a free page sample. Access the full version online. S.R. CLC/TS 51643-32:2020

CLC/TS 51643-32:2020 (E)

European foreword

This document (CLC/TS 51643-32:2020) has been prepared by CLC/TC 37A "Low-voltage surge protective devices".

This document supersedes CLC/TS 50539-12:2013 and all of its amendments and corrigenda (if any).

CLC/TS 51643-32:2020 includes the following significant technical changes with respect to CLC/TS 50539-12:2013:

- slight restructuring without impact on the content (such as changing the title of a clause by changing the text of one clause to another),
- deletion of the current branch concept of an SPD,
- referring to EN 61634-11:2019 instead of EN 50539-11:2013,
- referring to OCFM, SCFM instead of acronyms and concepts SCM and OCM,
- deletion of Annex C relating to the simplified risk assessment A,
- addition of a new annex dealing with telecommunication circuits.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

CLC/TS 51643-32:2020 (E)

Introduction

This document provides useful information for the selection of SPDs connected to photovoltaic installations.

This document does not address the fundamentals of SPDs that are addressed in CLC/TS 61643-12 which are necessary for its correct understanding and application.

This document provides information to evaluate, with reference to the documents listed in Clause 2, the additional needs for surge protective devices (SPDs) to be installed on the DC side and on the AC side of a photovoltaic (PV) system, to protect against induced and direct lightning effects. It gives guidance for selection, operation and installation of SPDs, including the selection of SPD type, surge current values and cross sections of bonding conductors.

The specific electrical parameters of a PV array or a PV source require specific SPDs on the DC side.

This document considers SPDs used in different locations and in different kinds of PV systems. It gives examples and provides a simplified and common approach to determine impulse discharge current values for the DC side of different PV installations.

CLC/TS 51643-32:2020 (E)

1 Scope

This document describes the principles for selection, installation and coordination of SPDs intended for use in Photovoltaic (PV) systems up to 1500 V DC and for the AC side of the PV system rated up to 1000 V RMS 50/60 Hz.

The photovoltaic installation extends from a PV array or a set of interconnected PV-modules to include the associated cabling and protective devices and the converter up to the connection point in the distribution board or the utility supply point.

This document considers SPDs used in different locations and in different kinds of PV systems:

PV systems located on the top of a building;

 PV systems located on the ground like free field power plants characterized by multiple earthing and a meshed earthing system.

The term PV installation is used to refer to both kinds of PV systems. The term PV power plant is only used for extended free-field multi-earthed power systems located on the ground.

For PV installations including batteries additional requirements could be necessary.

NOTE 1 The HD 60364 series, EN 62305 series and CLC/TS 61643-12 also apply.

NOTE 2 This document deals only with SPDs and not with surge protective components integrated inside equipment (e.g. inverters, (PCE) power conversion equipment).

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

HD 60364-5-534:2016, Low-voltage electrical installations - Part 5-53: Selection and erection of electrical equipment - Isolation, switching and control - Clause 534: Devices for protection against transient overvoltages (IEC 60364-5-53:2001/A2:2015, modified)

EN 60664-1:2007, Insulation coordination for equipment within low-voltage systems - Part 1: Principles, requirements and tests (IEC 60664-1:2007)

EN 61000-4-5, *Electromagnetic compatibility (EMC) - Part 4-5: Testing and measurement techniques - Surge immunity test (IEC 61000-4-5)*

CLC/TS 61643-12, Low-voltage surge protective devices - Part 12: Surge protective devices connected to low-voltage power distribution systems - Selection and application principles (IEC 61643-12)

EN 61643-31:2019, Low-voltage surge protective devices - Part 31: Requirements and test methods for SPDs for photovoltaic installations (IEC 61643-31:2018)

ITU-T K.20, Resistibility of telecommunication equipment installed in a telecommunications centre to overvoltages and overcurrents

ITU-T K.21, Resistibility of telecommunication equipment installed in customer premises to overvoltages and overcurrents



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation