

Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Engineering/survey methods for use *in situ* in a reverberant environment



#### AS 5339:2019

This Australian Standard® was prepared by EV-010, Acoustics Community Noise. It was approved on behalf of the Council of Standards Australia on 5 April 2019.

This Standard was published on 8 May 2019.

The following are represented on Committee EV-010:
Association of Australasian Acoustical Consultants
Australian Acoustical Society
Austroads
Bureau of Steel Manufacturers of Australia
Department of Defence (Australian Government)
Engineers Australia
Master Builders Australia
University of Sydney

This Standard was issued in draft form for comment as DR AS/NZS ISO 3747:2019.

#### **Keeping Standards up-to-date**

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting: <a href="https://www.standards.org.au">www.standards.org.au</a>



Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Engineering/survey methods for use *in situ* in a reverberant environment

First published as AS 5339:2019.

### **COPYRIGHT**

© ISO 2019 — All rights reserved

© Standards Australia Limited 2019

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

## **Preface**

This Standard was prepared by the Australian members of the Joint Standards Australia/Standards New Zealand Committee EV-010, Acoustics Community Noise.

After consultation with stakeholders in both countries, Standards Australia and Standards New Zealand decided to develop this Standard as an Australian Standard rather than an Australian/New Zealand Standard.

The objective of this Standard is to specify a method for determining the sound power level or sound energy level of a noise source by comparing measured sound pressure levels emitted by a noise source (machinery or equipment) mounted *in situ* in a reverberant environment, with those from a calibrated reference sound source. The sound power level (or, in the case of noise bursts or transient noise emission, the sound energy level) produced by the noise source, in frequency bands of width one octave, is calculated using those measurements. The sound power level or sound energy level with frequency A-weighting applied is calculated using the octave-band levels.

This Standard is identical with, and has been reproduced from, ISO 3747:2010, *Acoustics* — *Determination* of sound power levels and sound energy levels of noise sources using sound pressure — Engineering/survey methods for use in situ in a reverberant environment.

As this document has been reproduced from an International Standard, the following applies:

- (a) In the source text "this International Standard" should read "this Australian Standard".
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms "normative" and "informative" are used in Standards to define the application of the appendices or annexes to which they apply. A "normative" appendix or annex is an integral part of a Standard, whereas an "informative" appendix or annex is only for information and guidance.

# **Contents**

Pr	eface		ii				
Fo	reword		<b>v</b>				
In	troductio	on	vi				
1	1.1 1.2 1.3 1.4	General Types of noise and noise sources Test environment Measurement uncertainty	1 1 1				
2	Normative references						
3	Terms a	and definitions	2				
4	4.1	vironment Criterion for acoustic adequacy of test environment Criterion for background noise	6				
5	5.1 5.2	nentation and measurement equipment General Calibration	6				
6	6.1 6.2 6.3	n, installation and operation of noise source under test Source location and installation Auxiliary equipment Operation of source during test	7 7				
7	7.1 7.2 7.3 7.4	General Characterization of noise source under test Locations of the reference sound source 7.3.1 General 7.3.2 One location 7.3.3 More than one location Microphone positions 7.4.1 General 7.4.2 Zoning 7.4.3 Selection of microphone positions Measurement of sound pressure levels for a noise source which emits steady or non-steady noise Measurement of sound pressure levels for a noise source which emits impulsive noise	8 8 8 9 9 9 9				
8	8.1 8.2 8.3 8.4 8.5	tion of sound power levels and sound energy levels  Corrections for background noise  Mean time-averaged sound pressure levels for a noise source which emits steady or non-steady noise  Sound power levels  8.3.1 One location of reference sound source  8.3.2 Several locations of reference sound source  Mean single event sound pressure level for a noise source which emits impulsive noise.  Sound energy levels  8.5.1 One location of reference sound source	11 13 13 13 13				
9	8.6 <b>Measur</b> 9.1	8.5.2 Several locations of reference sound source	15 15 <b>15</b>				
	9.2 9.3	Determination of $\sigma_{ m omc}$ Determination of $\sigma_{R0}$	16				



The is a new provider i arenade and chare publication at the limit below	This is a free preview.	Purchase the	entire publication	at the link below:
--	-------------------------	--------------	--------------------	--------------------

**Product Page** 

- Dooking for additional Standards? Visit Intertek Inform Infostore
- Dearn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation