

AS 3778.2.3—2001
ISO 1100-2:1998
ISO 1100-2:1998/Cor.1:2000

AS 3778.2.3

Australian Standard™

Measurement of water flow in open channels

Part 2.3: General—Determination of the stage-discharge relationship

[ISO title: Liquid flow measurement in open channels, Part 2: Determination of the stage-discharge relationship]



S t a n d a r d s Australia

This Australian Standard was prepared by Committee CE-024, Measurement of Water Flow in Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 25 September 2000 and published on 12 March 2001.

The following interests are represented on Committee CE-024:

Australian Water and Wastewater Association
Department of Natural Resources, Qld
Institute of Instrumentation and Control Australia
Department of Land and Water Conservation, New South Wales
Department of Public Works and Services, New South Wales
South Australian Water Corporation
Sydney Water Corporation
University of New South Wales
University of Adelaide
University of Technology, Sydney

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

AS 3778.2.3—2001

Australian Standard™

Measurement of water flow in open channels

Part 2.3: General—Determination of the stage-discharge relationship

Originated as AS 3778.2.3—1990.
Second edition 2001.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 3645 9

PREFACE

This Standard was prepared by the Standards Australia Committee CE-024, Measurement of Water Flow in Open Channels and Closed Conduits.

This Standard is identical to and is reproduced from ISO 1100-2:1983, *Liquid flow measurement in open channels*, Part 2: *Determination of the stage-discharge relationship*

This Standard is Part 2.3 of AS 3778, *Measurement of water flow in open channels*, which is published in parts as follows:

AS

| | | |
|-----------|------------|---|
| 3778 | | Measurement of water flow in open channels |
| 3778.1 | Part 1: | Vocabulary and symbols |
| 3778.2 | Part 2: | General |
| 3778.2.1 | Part 2.1: | Guidelines for the selection of methods of measurement |
| 3778.2.2 | Part 2.2: | Establishment and operation of a gauging station |
| 3778.2.3 | Part 2.3: | Determination of the stage-discharge relation (this Standard) |
| 3778.2.4 | Part 2.4: | Estimation of uncertainty of a flow-rate measurement |
| 3778.2.5 | Part 2.5: | Guidelines for the selection of flow gauging structures |
| 3778.3 | Part 3: | Velocity-area method |
| 3778.3.1 | Part 3.1: | Measurement by current meters and floats |
| 3778.3.2 | Part 3.2: | Measurement by moving boat method |
| 3778.3.3 | Part 3.3: | Measurement by slope-area method |
| 3778.3.4 | Part 3.4: | Collection and processing of data for determination of errors in measurement |
| 3778.3.5 | Part 3.5: | Investigation of total error |
| 3778.3.6 | Part 3.6: | Measurement of flow in tidal channels |
| 3778.3.7 | Part 3.7: | Measurement by ultrasonic (acoustic) method |
| 3778.3.8 | Part 3.8: | Electromagnetic method using a full-channel-width coil |
| 3778.4 | Part 4: | Measurement using flow gauging structures |
| 3778.4.1 | Part 4.1: | Thin-plate weirs |
| 3778.4.2 | Part 4.2: | Rectangular broad-crested weirs |
| 3778.4.3 | Part 4.3: | Round-nose horizontal broad-crested weirs` |
| 3778.4.4 | Part 4.4: | V-shaped broad-crested weirs |
| 3778.4.5 | Part 4.5: | Triangular profile weirs |
| 3778.4.6 | Part 4.6: | Flat-V weirs |
| 3778.4.7 | Part 4.7: | Rectangular, trapezoidal and U-shaped flumes |
| 3778.4.8 | Part 4.8: | Trapezoidal profile weirs |
| 3778.4.9 | Part 4.9: | Parshall and Saniiri flumes |
| 3778.4.10 | Part 4.10: | End-depth method for estimation of flow in rectangular channels with a free overfall |
| 3778.4.11 | Part 4.11 | End-depth method for estimation of flow in rectangular channels with a free overfall (approximate method) |
| 3778.5 | Part 5: | Dilution method |
| 3778.5.1 | Part 5.1: | Constant-rate injection method for the measurement of steady flow |
| 3778.5.2 | Part 5.2: | Integration method for the measurement of steady flow |
| 3778.6 | Part 6: | Measuring devices, instruments and equipment |
| 3778.6.1 | Part 6.1: | Rotating element current-meters |
| 3778.6.2 | Part 6.2: | Direct depth sounding and suspension equipment |
| 3778.6.3 | Part 6.3: | Calibration of rotating element current meters in straight open tanks |
| 3778.6.4 | Part 6.4: | Echo sounders for water depth measurements |
| 3778.6.5 | Part 6.5: | Water level measuring devices |
| 3778.6.6 | Part 6.6: | Cableway system for stream gauging |
| 3778.6.7 | Part 6.7: | Ultrasonic (acoustic) velocity meters |
| 3778.6.8 | Part 6.8: | Position fixing equipment for hydrometric boats |

Under arrangements made between Standards Australia and the international Standards bodies, ISO and IEC, as well as certain other Standards organisations, users of this Australian Standard are advised of the following:

- (a) Copyright is vested in Standards Australia.
- (b) The number of this Standard is not reproduced on each page, its identity is shown only on the cover and title pages.
- (c) In the source text 'this standard' should read 'this Australian Standard'.
- (d) Where the word 'fluid' appears, it should read 'water'.
- (e) A full point should be substituted for a comma when referring to a decimal marker.

References to International Standards should be replaced by references to equivalent Australian Standards, as follows:

| <i>Reference to International Standard</i> | | <i>Australian Standard</i> | |
|--|---|----------------------------|---|
| ISO | | AS | |
| 1000 | SI units and recommendations for the use of their multiples and of certain other units | 1000 | The international system of units (SI) and its application |
| 31 | Quantities, units and symbols | 2900 | Quantities, units and symbols |
| 772 | Liquid flow measurement in open channels—Vocabulary and symbols | 3778 | Measurement of water flow in open channels |
| 1100 | Liquid flow measurement in open channels | 3778.1 | Part 1: Vocabulary and symbols |
| 1100-1 | Part 1: Establishment and operation of a gauging station | 3778.2.2 | Part 2.2: General—Establishment and operation of a gauging station |
| 5168 | Measurement of fluid flow—Estimation of uncertainty of a flow-rate measurement | 3778.2.4 | Part 2.4: General—Estimation of uncertainty of a flow rate measurement |
| 748 | Liquid flow measurement in open channels-Velocity area methods | 3778.3.1 | Part 3.1: Velocity-area methods — Measurement by current-meters and floats |
| 4369 | Liquid flow measurement in open channels-The moving-boat method | 3778.3.2 | Part 3.2: Velocity-area methods — Measurement by moving boat method |
| 1070 | Liquid flow measurement in open channels—Slope-area method | 3778.3.3 | Part 3.3: Velocity-area methods— Measurement by slope-area method |
| 1088 | Liquid flow measurement in open channels—Velocity-area methods— Collection of data for determination of errors in measurement | 3778.3.4 | Part 3.4: Velocity-area methods— Collection and processing of data for determination of errors in measurement |
| TR 7178 | Measurement of liquid in open channels—Investigation of the total error in measurement of flow by velocity-area methods | 3778.3.5 | Part 3.5: Velocity-area methods— Investigation of total error |

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- Looking for additional Standards? Visit Intertek Inform Infostore
 - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-