## Australian Standard®

Electric cables—Polymeric insulated

Part 1: For working voltages 1.9/3.3 (3.6) kV up to and including 19/33 (36) kV This Australian Standard was prepared by Committee EL/3, Electric Wires and Cables. It was approved on behalf of the Council of Standards Australia on 31 August 1993 and published on 20 December 1993.

The following interests are represented on Committee EL/3:

Australian Electrical and Electronic Manufacturers Association

Department of Defence

Electrical regulatory authorities

Electricity Supply Association of Australia

Office of Energy, N.S.W.

Railways of Australia Committee

Testing interests

**Review of Australian Standards.** To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 92043.

## Australian Standard®

# Electric cables—Polymeric insulated

Part 1: For working voltages 1.9/3.3 (3.6) kV up to and including 19/33 (36) kV

First published as AS 1429.1 — 1979. Revised and redesignated AS 1429— 1985. Revised and redesignated AS 1429.1 — 1993.

Incorporating: Amdt 1—1995

PUBLISHED BY STANDARDS AUSTRALIA (STANDARDS ASSOCIATION OF AUSTRALIA) 1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 8567 6

2

### PREFACE

This Standard was prepared by the Standards Australia Committee on Electric Wires and Cables to supersede AS 1429—1985, *Polymeric insulated cables for electricity supply at working voltages 1.9/3.3 kV up to and including 19/33 kV.* 

In the Standard, Sections 1 to 3 cover the general requirements for cables with individually or collectively screened cores, Section 4 requirements are specific to cables with individually screened cores, and Section 5 requirements are specific to three-core cables with collectively screened cores.

This revised Standard differs from the previous edition in the following significant ways:

- (a) The low density polyethylene insulation, the conductor and insulation thermoplastic screens, and the 75°C rated PVC sheath have been deleted.
- (b) More detailed requirements and recommendations are specified for the (metallic) individual or collective screens. Copper tape screens have been deleted.
- (c) Provision (optional) has been made for the water-blocking of single-core cables, for protection from boring insects, and for the metre marking of cables.
- (d) Some changes have been made to cable tests and criteria.
- (e) Requirements for high voltage d.c. test after installation have been deleted.
- (f) The Standard now includes all the necessary data for determining the dimensions of protective coverings, and test requirements have been combined into one table.

In the preparation of this Standard, consideration was given to the following publications and acknowledgment is made of the assistance received:

IEC 229	Tests on cable oversheaths which have a special protective function and
	are applied by extrusion

- IEC 502 Extruded solid dielectric insulated power cables for rated voltages from 1 kV up to 30 kV
- IEC 811 Common test methods for insulating and sheathing materials of electric cables
- AEIC CS5 Thermoplastic and crosslinked polyethylene insulated shielded power cables rated 5 kV through 35 kV
- AEIC CS6 Ethylene propylene rubber insulated shielded power cables rated 5 kV through 69 kV
- NEMA No WC 7 Cross-linked-thermosetting-polyethylene-insulated wire and cable for the transmission and distribution of electrical energy
- NEMA No WC 8 Ethylene-propylene-rubber-insulated wire and cable for the transmission and distribution of electrical energy

The nominal cross-sectional areas of the conductors specified herein are identical with the values specified in AS 1125, *Conductors in insulated electric cables and flexible cords*. The dimensions for insulation and non-metallic sheath thicknesses are identical with the values recommended in IEC 502. Certain tests and criteria in this Standard are more stringent than those in IEC 502.

Two types of insulation and non-metallic sheath compounds are specified in this Standard, namely insulation comprising cross-linked polyethylene (XLPE) or ethylene propylene rubber (EPR) and non-metallic sheath comprising polyvinyl chloride (PVC) or high density polyethylene (HDPE).

Although the Standard provides tables of insulation thicknesses and the necessary information to establish precisely the dimensions of the cable protective coverings, no cable dimension tables are provided owing to the variety of cable constructions that could possibly affect such dimensions.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

#### © Copyright - STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.



This is a free preview. Purchase the entire publication at the link below:

**Product Page** 

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation