AS 60470-2001 IEC 60470:2000

# Australian Standard<sup>™</sup>

# High-voltage alternating current contactors and contactor-based motor-starters



This Australian Standard was prepared by Committee EL-007, Power Switchgear. It was approved on behalf of the Council of Standards Australia on 20 August 2001 and published on 12 October 2001.

The following interests are represented on Committee EL-007:

Australasian Railway Association

Australian British Chamber of Commerce

Australian Electrical and Electronic Manufacturers Association

Electricity Supply Association of Australia

Institution of Engineers Australia

Testing Interests (Australia)

Transpower New Zealand Limited

WorkCover N.S.W.

#### Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

This Standard was issued in draft form for comment as DR 01039.

# Australian Standard<sup>™</sup>

# High-voltage alternating current contactors and contactor-based motor-starters

Originated as part of AS 1864—1976 and AS 2232.1—1979. AS 1864—1976 and AS 2232.1—1979 revised, amalgamated and redesignated as AS 60470—2001.

#### COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd GPO Box 5420, Sydney, NSW 2001, Australia ISBN 0 7337 4111 8 ii

### PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee EL-007, Power Switchgear, to supersede AS 1864—1976 and AS 2232.1—1979.

This Standard is the result of a consensus among representatives on the Joint Committee to produce it as an Australian Standard.

The objective of this Standard is to state the characteristics of contactors, starters and associated equipment, the conditions with which contactors or starters shall comply, the tests intended for confirming that these conditions have been met and the methods to be adopted for these tests and the information to be given with the equipment or in the manufacturer's literature.

This Standard is identical in technical content with and has been reproduced from IEC 60470:2000, *High-voltage alternating current contactors and contactor-based motor-starters*.

An informative Australian only Annex ZA has been added to inform the reader of items to be agreed between manufacturer and user. Annex ZA has been shaded to emphasize that it is additional information.

This Standard differs from AS 1864—1976 and AS 2232.1—1979 in the following areas:

- (a) Vacuum and SF6 contactors are included.
- (b) Additional utilization categories.
- (c) Conditions for construction and operation in service.
- (d) Type and routine tests.
- (e) Requirements for transport, storage, erection, operation, maintenance and safety.
- (f) Guide to the selection of contactors and motor-starters for service.

A reference to an International Standard identified in the Normative References Clause by strikethrough (example) is replaced by a reference to the Australian or Australian/New Zealand Standard(s) listed immediately thereafter and identified by shading (example). Where the struck-through referenced document and the referenced Australian or Australian/New Zealand Standard are identical, this is indicated in parenthesis after the title of the latter.

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number does not appear on each page of text and its identity is shown only on the cover and title page.
- (b) In the source text 'this standard' should read 'this Australian Standard'.
- (c) A full point should be substituted for a comma when referring to a decimal marker.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the annex to which they apply. A 'normative' annex is an integral part of a Standard, whereas an 'informative annex' is only for information and guidance.

iii

## CONTENTS

## Page

		3-
1	General	
1.1	Scope and object	1
1.2	Normative references	3
2	Normal and special service conditions	4
2.1	Normal service conditions	4
2.2	Special service conditions	4
3	Definitions	5
3.1	General terms	5
3.2	Assemblies of switchgear and controlgear	5
3.3	Parts of assemblies	5
3.4	Switching devices	5
3.5	Parts of switchgear and controlgear	8
3.6	Operation	9
3.7	Characteristic quantities	11
3.101	Fuses	14
4	Ratings	15
4.1	Rated voltage (U <sub>r</sub> )	17
4.2	Rated insulation level	17
4.3	Rated frequency (f <sub>r</sub> )	18
4.4	Rated normal current and temperature rise	18
4.5	Rated short-time withstand current ( <i>I</i> <sub>k</sub> )	18
4.6	Rated peak withstand current ( <i>I</i> <sub>p</sub> )	19
4.7	Rated duration of short circuit (t <sub>k</sub> )	19
4.8	Rated supply voltage of closing and opening devices, and of auxiliary and control circuits $(U_a)$	19
4.9	Rated supply frequency of closing and opening devices, and of auxiliary circuits	19
4.10	Rated pressure of compressed gas supply for insulation and/or operation	19
4.101	Rated operational current ( $I_e$ ) or rated operational power	19
4.102	Rated duties	20
4.103	Rated load and overload characteristics	21
4.104	Utilization category	22
4.105	Mechanical endurance	23
4.106	Electrical endurance	23
4.107	Coordination with short-circuit protective devices	23
4.108	Types and characteristics of automatic change-over devices and automatic acceleration control devices	25
4.109	Types and characteristics of starting auto-transformers or reactors	26
	Types and characteristics of starting resistors for rheostatic rotor starters	
4.111	Characteristics dependent on starter type	26



This is a free preview. Purchase the entire publication at the link below:

**Product Page** 

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation