

Australian/New Zealand Standard™

**Acoustics—Measurement of the
reverberation time in rooms**



standards Australia



STANDARDS
NEW ZEALAND
Te Kaitiaki Take Kōwhiri

AS/NZS 2460:2002

This Joint Australian/New Zealand Standard was prepared by Joint Technical Committee AV-004, Acoustics, Architectural. It was approved on behalf of the Council of Standards Australia on 29 June 2001 and on behalf of the Council of Standards New Zealand on 1 February 2002. It was published on 21 February 2002.

The following interests are represented on Committee AV-004:

Association of Australian Acoustical Consultants
Australian Acoustical Society
Australian Building Codes Board
Australian Chamber of Commerce and Industry
Australian Defence Force Academy
Australian Hearing
Building Industry Authority New Zealand
CSIRO Building, Construction and Engineering
Department of Public Works and Services, N.S.W.
New Zealand Acoustical Society
RMIT University
The Royal Australian Institute of Architects
University of Auckland
University of Sydney

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about joint Australian/New Zealand Standards can be found by visiting the Standards Australia web site at www.standards.com.au or Standards New Zealand web site at www.standards.co.nz and looking up the relevant Standard in the on-line catalogue.

Alternatively, both organizations publish an annual printed Catalogue with full details of all current Standards. For more frequent listings or notification of revisions, amendments and withdrawals, Standards Australia and Standards New Zealand offer a number of update options. For information about these services, users should contact their respective national Standards organization.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Please address your comments to the Chief Executive of either Standards Australia International or Standards New Zealand at the address shown on the back cover.

Australian/New Zealand Standard™

Acoustics—Measurement of the reverberation time in rooms

Originated as AS 2460—1981.
Jointly revised and designated AS/NZS 2460:2002.

COPYRIGHT

© Standards Australia/Standards New Zealand

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Jointly published by Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001 and Standards New Zealand, Private Bag 2439, Wellington 6020

ISBN 0 7337 4048 0

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee, AV-004, Acoustics, Architectural, to supersede AS 2460—1981, *Acoustics—Measurement of reverberation time in enclosures*.

The objective of this Standard is to specify methods for the measurement of reverberation time in rooms. This Standard applies to any room in which reverberation time is an important factor affecting the quality of sound in the room, or where reverberation control is used for noise control purposes.

During preparation of this Standard, cognizance was taken of ISO 3382:1997, *Acoustics—Measurement of the reverberation time of rooms with reference to other acoustical parameters*. This Standard incorporates a number of technical changes from ISO 3382:1997, most notably the specification for the nature of the sound source. Conventional loudspeakers, properly located and oriented, may be used as the test sound source in lieu of omnidirectional loudspeakers, where appropriate. An installed sound system may be used to excite the room under certain circumstances.

This Standard should be read by a person who has acquired through training, qualifications or experience, or a combination of these, the knowledge and skills enabling that person to perform the task required.

Appendix B, *Auditorium measures derived from impulse responses*, is technically equivalent to Annex A of ISO 3382:1997. It presents several quantities that can be obtained from measured impulse responses, namely, a further measure of reverberation (early decay time) and measures of relative sound levels, early/late energy fractions and lateral energy fractions. Subjective studies of the acoustical characteristics of auditoria have shown that these quantities are correlated with particular subjective aspects of the acoustical character of an auditorium. However, there is still work to be done in determining which measures are the most suitable as bases for standardization.

The term ‘informative’ has been used in this Standard to define the application of the appendix to which it applies. An ‘informative’ appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
1 SCOPE	4
2 APPLICATION.....	4
3 REFERENCED DOCUMENTS	4
4 DEFINITIONS.....	5
5 EQUIPMENT.....	6
6 MEASUREMENT CONDITIONS	8
7 MEASUREMENT PROCEDURES	9
8 EVALUATION.....	11
9 STATEMENT OF RESULTS	11
 APPENDICES	
A GUIDANCE ON THE CHOICE OF MEASUREMENT POSITIONS.....	13
B AUDITORIUM MEASURES DERIVED FROM IMPULSE RESPONSES	15
C BIBLIOGRAPHY	23

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-