

AS 3778.2.2—2001  
ISO 1100-1:1996

AS 3778.2.2

Australian Standard™

## **Measurement of water flow in open channels**

### **Part 2.2: General—Establishment and operation of a gauging station**

[ISO title: Liquid flow measurement in open channels, Part 2: Determination of the stage-discharge relationship]



**S t a n d a r d s** Australia

This Australian Standard was prepared by Committee CE-024, Measurement of Water Flow in Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 25 September 2000 and published on 12 March 2001.

---

The following interests are represented on Committee CE-024:

Australian Water and Wastewater Association  
Department of Natural Resources, Qld  
Institute of Instrumentation and Control Australia  
Department of Land and Water Conservation, New South Wales  
Department of Public Works and Services, New South Wales  
South Australian Water Corporation  
Sydney Water Corporation  
University of New South Wales  
University of Adelaide  
University of Technology, Sydney

---

### **Keeping Standards up-to-date**

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at [www.standards.com.au](http://www.standards.com.au) and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at [mail@standards.com.au](mailto:mail@standards.com.au), or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

---

AS 3778.2.2—2001

Australian Standard™

## **Measurement of water flow in open channels**

### **Part 2.2: General—Establishment and operation of a gauging station**

Originated as AS 3778.2.2—1990.  
Second edition 2001.

#### **COPYRIGHT**

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd  
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 3644 0

## PREFACE

This Standard was prepared by the Standards Australia Committee, CE-024—Measurement of Water Flow in Open Channels and Closed Conduits.

The Standard is identical to and is reproduced from ISO 1100-1:1996, *Liquid flow measurement in open channels*, Part 2: *Determination of the stage-discharge relationship*.

This Standard is Part 2.3 of AS 3778, *Measurement of water flow in open channels*, which is published in parts as follows:

### AS

3778		Measurement of water flow in open channels
3778.1	Part 1:	Vocabulary and symbols
3778.2	Part 2:	General
3778.2.1	Part 2.1:	Guidelines for the selection of methods of measurement
3778.2.2	Part 2.2:	Establishment and operation of a gauging station (this Standard)
3778.2.3	Part 2.3:	Determination of the stage-discharge relation)
3778.2.4	Part 2.4:	Estimation of uncertainty of a flow-rate measurement
3778.2.5	Part 2.5:	Guidelines for the selection of flow gauging structures
3778.3	Part 3:	Velocity-area method
3778.3.1	Part 3.1:	Measurement by current meters and floats
3778.3.2	Part 3.2:	Measurement by moving boat method
3778.3.3	Part 3.3:	Measurement by slope-area method
3778.3.4	Part 3.4:	Collection and processing of data for determination of errors in measurement
3778.3.5	Part 3.5:	Investigation of total error
3778.3.6	Part 3.6:	Measurement of flow in tidal channels
3778.3.7	Part 3.7:	Measurement by ultrasonic (acoustic) method
3778.3.8	Part 3.8:	Electromagnetic method using a full-channel-width coil
3778.4	Part 4:	Measurement using flow gauging structures
3778.4.1	Part 4.1:	Thin-plate weirs
3778.4.2	Part 4.2:	Rectangular broad-crested weirs
3778.4.3	Part 4.3:	Round-nose horizontal broad-crested weirs`
3778.4.4	Part 4.4:	V-shaped broad-crested weirs
3778.4.5	Part 4.5:	Triangular profile weirs
3778.4.6	Part 4.6:	Flat-V weirs
3778.4.7	Part 4.7:	Rectangular, trapezoidal and U-shaped flumes
3778.4.8	Part 4.8:	Trapezoidal profile weirs
3778.4.9	Part 4.9:	Parshall and Saniiri flumes
3778.4.10	Part 4.10:	End-depth method for estimation of flow in rectangular channels with a free overfall
3778.4.11	Part 4.11:	End-depth method for estimation of flow in rectangular channels with a free overfall (approximate method)
3778.5	Part 5:	Dilution method
3778.5.1	Part 5.1:	Constant-rate injection method for the measurement of steady flow
3778.5.2	Part 5.2:	Integration method for the measurement of steady flow
3778.6	Part 6:	Measuring devices, instruments and equipment
3778.6.1	Part 6.1:	Rotating element current-meters
3778.6.2	Part 6.2:	Direct depth sounding and suspension equipment
3778.6.3	Part 6.3:	Calibration of rotating element current meters in straight open tanks
3778.6.4	Part 6.4:	Echo sounders for water depth measurements
3778.6.5	Part 6.5:	Water level measuring devices
3778.6.6	Part 6.6:	Cableway system for stream gauging
3778.6.7	Part 6.7:	Ultrasonic (acoustic) velocity meters
3778.6.8	Part 6.8:	Position fixing equipment for hydrometric boats

Under arrangements made between Standards Australia and the international Standards bodies, ISO and IEC, as well as certain other Standards organisations, users of this Australian Standard are advised of the following:

- (a) Copyright is vested in Standards Australia.
- (b) The number of this Standard is not reproduced on each page, its identity is shown only on the cover and title pages.
- (c) In the source text 'this standard' should read 'this Australian Standard'.
- (d) Where the word 'fluid' appears, it should read 'water'.
- (e) A full point should be substituted for a comma when referring to a decimal marker.

References to International Standards should be replaced by references to equivalent Australian Standards, as follows:

<i>Reference to International Standard</i>		<i>Australian Standard</i>	
ISO		AS	
1000	SI units and recommendations for the use of their multiples and of certain other units	1000	The international system of units (SI) and its application
31	Quantities, units and symbols	2900	Quantities, units and symbols
		3778	Measurement of water flow in open channels
772	Liquid flow measurement in open channels—Vocabulary and symbols	3778.1	Part 1: Vocabulary and symbols
1100	Liquid flow measurement in open channels		
		3778.2.2	Part 2.2: General—Establishment and operation of a gauging station
1100-1	Part 1: Establishment and operation of a gauging station		
		3778.2.4	Part 2.4: General—Estimation of uncertainty of a flow rate measurement
5168	Measurement of fluid flow—Estimation of uncertainty of a flow-rate measurement		
		3778.3.1	Part 3.1: Velocity-area methods — Measurement by current-meters and floats
748	Liquid flow measurement in open channels-Velocity area methods		
		3778.3.2	Part 3.2: Velocity-area methods — Measurement by moving boat method
4369	Liquid flow measurement in open channels-The moving-boat method		
		3778.3.3	Part 3.3: Velocity-area methods— Measurement by slope-area method
1070	Liquid flow measurement in open channels—Slope-area method		
		3778.3.4	Part 3.4: Velocity-area methods— Collection and processing of data for determination of errors in measurement
1088	Liquid flow measurement in open channels—Velocity-area methods— Collection of data for determination of errors in measurement		
		3778.3.5	Part 3.5: Velocity-area methods— Investigation of total error
TR 7178	Measurement of liquid in open channels—Investigation of the total error in measurement of flow by velocity-area methods		
		3778.3.6	Part 3.6: Velocity-area methods — Measurement of flow in tidal channels
2425	Measurement of flow in tidal channels		

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

- 
- Looking for additional Standards? Visit Intertek Inform Infostore
  - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-