AS 60146.1.1—2002 IEC 60146-1-1:1991

# Australian Standard<sup>™</sup>

# **Semiconductor converters**

Part 1.1: General requirements and line commutated converters—Specifications of basic requirements



This Australian Standard was prepared by Committee EL-027, Power Electronics. It was approved on behalf of the Council of Standards Australia on 4 June 2002 and published on 4 July 2002.

The following are represented on Committee EL-027:

Australian Communications Authority

Australian Electrical and Electronic Manufacturers Association

Bureau of Steel Manufacturers of Australia

Electricity Supply Association of Australia

Monash University

University of Wollongong

#### **Keeping Standards up-to-date**

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

This Standard was issued in draft form for comment as DR 02098.

Australian Standard™

## **Semiconductor converters**

# Part 1.1: General requirements and line commutated converters—Specifications of basic requirements

Originated as part of AS 1955.1—1977. Revised and redesignated in part as AS 60146.1.1—2002.

#### COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd GPO Box 5420, Sydney, NSW 2001, Australia ISBN 0 7337 4488 5 ii

#### PREFACE

This Standard was prepared by the Standards Australia Committee EL-027, Power Electronics to partially supersede AS 1955.1—1977, *Semiconductor converters*, Part 1: *General* six months after publication.

The objective of this Standard is to provide system designers, manufacturers and users with performance requirements for all electronic power converters and switches.

This Standard is the first part of a three part Standard; the parts of which are as follows:

- AS 60146 Semiconductor converters
- AS 60146.1.1 Part 1.1: General requirements and line commutated converters—Specifications of basic requirements (this Standard)
- AS 60146.1.2 Part 1.2: General requirements and line commutated converters—Application guide
- AS 60146.1.3 Part 1.3: General requirements and line commutated converters—Transformers and reactors

This Standard is technically identical with, and has been reproduced from, IEC 60146-1-1:1991, *Semiconductor converters*, Part 1-1: *General requirements and line commutated converters*— *Specifications of basic requirements*, including Corrigendum:1993 and Amendment 1:1996 (marked with a marginal bar in the right hand margin). Minor editorial changes have been made to the text such as the use of the word 'converter' throughout the document (to standardize spelling across this series of Standards).

A reference to an International Standard identified in the Normative References Clause by strikethrough (example) is replaced by a reference to the Australian or Australian/New Zealand Standard(s) listed immediately thereafter and identified by shading (example). Where the struck-through referenced document and the referenced Australian or Australian/New Zealand Standard are identical, this is indicated in parenthesis after the title of the latter.

In January 1997, the IEC commenced numbering its Standards from 60000 by adding 60000 to the number of each existing Standard. This coordinates IEC numbering with ISO numbering. During the transition period an IEC Standard might be identified by its new number or its old number (for example, IEC 60050 or IEC 50).

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number does not appear on each page of text and its identity is shown only on the cover and title page.
- (b) In the source text 'this International Standard' should read 'this Australian Standard'.
- (c) A full point should be substituted for a comma when referring to a decimal marker.

The term 'informative' has been used in this Standard to define the application of the annex to which it applies. An 'informative' annex is only for information and guidance.

iii

## CONTENTS

## Page

### SECTION 1 - GENERAL

1.2 Normative references 2   1.3 Classification of semiconductor power equipment and valves 3   1.3.1 Classification of semiconductor valves 5   1.4 List of principal letter symbols and subscripts 5   1.4.1 List of symbols (self evident symbols are not listed) 5   1.4.2 List of symbols (self evident symbols are not listed) 7   1.5.1 Semiconductor device (IEV 551-03-05, modified) 7   1.5.2 Power semiconductor diode 7   1.5.3 Thyristor 7   1.5.4 Reverse blocking triode thyristor 8   1.5.5 Reverse conducting triode thyristor 8   1.5.6 Bidirectional triode thyristor (triac) 8   1.5.6 Borner connection (IEV 551-04-17) 8   1.5.10 Converter cincuit elements 8   1.5.12 Quadrants of operation (on d. c. side) 9   1.5.13 Commutation and quenching (see figure 1) 9   1.5.14 Type of commutation 10   1.5.15 Self commutation (IEV 551-05-06) 10   1.5.16 Type of quenching 1	1.1	Scope and object1		
1.3 Classification of semiconductor power equipment and valves 3   1.3.1 Classification of semiconductor valves 5   1.4 List of principal letter symbols and subscripts 5   1.4.1 List of subscripts 5   1.4.2 List of symbols (self evident symbols are not listed) 5   1.5 Definitions 7   1.5.1 Semiconductor device (IEV 551-03-05, modified) 7   1.5.2 Power semiconductor diode 7   1.5.3 Thyristor 7   1.5.4 Reverse blocking triode thyristor 8   1.5.5 Reverse blocking triode thyristor 8   1.5.6 Bidirectional triode thyristor (triac) 8   1.5.7 Turn-off thyristor (GTO = Gate Turn Off) 8   1.5.8 Combination of semiconductor devices 8   1.5.9 Converter circuit elements 8   1.5.10 Converter connection (IEV 551-04-17) 9   1.5.11 Controllability of converter arms 9   1.5.12 Quadrants of operation (on d.c. side) 9   1.5.13 Commutation 10 <td< td=""><td>1.2</td><td>Norma</td><td colspan="2">rmative references</td></td<>	1.2	Norma	rmative references	
1.3.1Classification of semiconductor power equipment.31.3.2Classification of semiconductor valves.51.4.1List of principal letter symbols and subscripts.51.4.1List of subscripts.51.4.2List of symbols (self evident symbols are not listed).51.5Definitions.71.5.1Semiconductor device (IEV 551-03-05, modified).71.5.2Power semiconductor diode.71.5.3Thyristor.71.5.4Reverse blocking triode thyristor.81.5.5Reverse conducting triode thyristor.81.5.6Bidirectional triode thyristor (triac).81.5.7Turn-off thyristor (GTO = Gate Turn Off).81.5.8Converter circuit elements.81.5.9Converter connection (IEV 551-04-17).91.5.11Controllability of converter arms.91.5.12Quadrants of operation (on d.c. side).91.5.13Commutation and quenching (see figure 1).91.5.14Type of commutation (IEV 551-05-06).101.5.15Self commutation (IEV 551-05-29, modified).111.5.19Trigger advance angle $\beta$ .121.5.20Inherent delay angle $\alpha_p$ .121.5.31Trigger advance angle $\beta$ .121.5.4Efficiency definitions.131.5.5Self commutation sirelated values.131.5.6Inherent delay angle $\alpha_p$ .121.5.7Terms used in connection with convert	1.3	Classif	ication of semiconductor power equipment and valves	
1.3.2Classification of semiconductor valves51.4List of principal letter symbols and subscripts51.4.1List of subscripts51.4.2List of symbols (self evident symbols are not listed)51.5Definitions71.5.1Semiconductor device (IEV 551-03-05, modified)71.5.2Power semiconductor diode71.5.3Thyristor71.5.4Reverse blocking triode thyristor81.5.5Reverse conducting triode thyristor81.5.6Bidirectional triode thyristor (triac)81.5.7Turn-off thyristor (GTO = Gate Turn Off)81.5.8Combination of semiconductor devices81.5.9Converter connection (IEV 551-04-17)91.5.11Controllability of converter arms91.5.12Quadrants of operation (on d.c. side)91.5.13Commutation and quenching (see figure 1)91.5.14Type of commutation (IEV 551-05-06)101.5.15Self commutation (IEV 551-05-29, modified)111.5.19Trigger advance angle $\beta$ 121.5.20Inherent delay angle $\alpha_p$ 121.5.21Definitions of rated values131.5.22Definitions of rated values141.5.23Terms used in connection with converter faults141.5.24Efficiency definitions141.5.25Terms used in connection with direct voltage regulation161.5.23Terms used in connection		1.3.1	Classification of semiconductor power equipment	
1.4List of principal letter symbols and subscripts.51.4.1List of subscripts.51.4.2List of symbols (self evident symbols are not listed).51.5Definitions.71.5.1Semiconductor device (IEV 551-03-05, modified).71.5.2Power semiconductor diode.71.5.3Thyristor.71.5.4Reverse blocking triode thyristor.81.5.5Reverse conducting triode thyristor.81.5.6Bidirectional triode thyristor (triac).81.5.7Turn-off thyristor (GTO = Gate Turn Off).81.5.8Combination of semiconductor devices.81.5.9Converter circuit elements81.5.10Converter connection (IEV 551-04-17).91.5.11Controllability of converter arms91.5.12Quadrants of operation (on d. c. side).91.5.13Commutation and quenching (see figure 1).91.5.14Type of commutation (IEV 551-05-09).111.5.15Self commutation (IEV 551-05-09).111.5.14Type of quenching121.5.20Inherent delay angle $\alpha_p$ .121.5.21Extinction and que $\alpha_p$ .121.5.22Definitions of rated values131.5.23Definitions of rated values131.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.27<		1.3.2	Classification of semiconductor valves	
1.4.1List of subscripts.51.4.2List of symbols (self evident symbols are not listed)51.5Definitions.71.5.1Semiconductor device (IEV 551-03-05, modified)71.5.2Power semiconductor diode71.5.3Thyristor.71.5.4Reverse blocking triode thyristor81.5.5Reverse conducting triode thyristor81.5.6Bidirectional triode thyristor (triac)81.5.7Turn-off thyristor (GTO = Gate Turn Off)81.5.8Combination of semiconductor devices81.5.9Converter circuit elements81.5.10Converter connection (IEV 551-04-17)91.5.11Controllability of converter arms91.5.12Quadrants of operation (on d. c. side)91.5.13Commutation and quenching (see figure 1)91.5.14Type of commutation101.5.15Self commutation (IEV 551-05-06)101.5.16Tyge of quenching101.5.17Commutation circuit (IEV 551-05-29, modified)111.5.20Inherent delay angle $\alpha$ 121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values121.5.23Definitions of rated values for assemblies and equipment141.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side14<	1.4	List of	principal letter symbols and subscripts5	
1.4.2List of symbols (self evident symbols are not listed).51.5Definitions.71.5.1Semiconductor device (IEV 551-03-05, modified).71.5.2Power semiconductor diode.71.5.3Thyristor.71.5.4Reverse blocking triode thyristor.81.5.5Reverse conducting triode thyristor.81.5.6Bidirectional triode thyristor (triac).81.5.7Turn-off thyristor (GTO = Gate Turn Off).81.5.8Combination of semiconductor devices.81.5.9Converter circuit elements.81.5.10Converter connection (IEV 551-04-17).91.5.11Controllability of converter arms.91.5.12Quadrants of operation (on d.c. side).91.5.13Commutation and quenching (see figure 1).91.5.14Type of commutation.101.5.15Self commutation (IEV 551-05-06).101.5.16Type of quenching.101.5.17Commutation circuit (IEV 551-05-09).111.5.18Trigger advance angle $\beta$ .121.5.20Inherent delay angle $\alpha$ (IEV 551-05-29, modified).121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified).121.5.22Definitions of rated values.131.5.23Definitions of rated values for assemblies and equipment.141.5.24Efficiency definitions.141.5.25Terms used in connection with converter faults.141.5.26 <td< td=""><td></td><td>1.4.1</td><td>List of subscripts</td></td<>		1.4.1	List of subscripts	
1.5Definitions71.5.1Semiconductor device (IEV 551-03-05, modified)71.5.2Power semiconductor diode71.5.3Thyristor71.5.4Reverse blocking triode thyristor81.5.5Reverse conducting triode thyristor81.5.6Bidirectional triode thyristor (triac)81.5.7Turn-off thyristor (GTO = Gate Turn Off)81.5.8Combination of semiconductor devices81.5.9Converter circuit elements81.5.10Converter connection (IEV 551-04-17)91.5.11Controllability of converter arms91.5.12Quadrants of operation (on d.c. side)91.5.13Commutation101.5.14Type of commutation101.5.15Self commutation direuti (IEV 551-05-06)101.5.16Type of quenching101.5.17Commutation circuit (IEV 551-05-29, modified)111.5.20Inherent delay angle $\alpha$ (IEV 551-05-30, modified)121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.23Definitions of rated values131.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.27Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17 </td <td></td> <td>1.4.2</td> <td>List of symbols (self evident symbols are not listed)5</td>		1.4.2	List of symbols (self evident symbols are not listed)5	
1.5.1Semiconductor device (IEV 551-03-05, modified)	1.5	Definitions		
1.5.2Power semiconductor diode71.5.3Thyristor71.5.4Reverse blocking triode thyristor81.5.5Reverse conducting triode thyristor81.5.6Bidirectional triode thyristor (triac)81.5.7Turn-off thyristor (GTO = Gate Turn Off)81.5.8Combination of semiconductor devices81.5.9Converter circuit elements81.5.10Converter connection (IEV 551-04-17)91.5.11Controllability of converter arms91.5.12Quadrants of operation (on d.c. side)91.5.13Commutation and quenching (see figure 1)91.5.14Type of commutation (IEV 551-05-06)101.5.15Self commutation (IEV 551-05-09)111.5.16Type of quenching101.5.17Commutation circuit (IEV 551-05-09)111.5.18Trigger advance angle $\beta$ 121.5.20Inherent delay angle $\alpha_p$ 121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.23Definitions of rated values for assemblies and equipment141.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.27Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.1	Semiconductor device (IEV 551-03-05, modified)7	
1.5.3Thyristor71.5.4Reverse blocking triode thyristor81.5.5Reverse conducting triode thyristor81.5.6Bidirectional triode thyristor (triac)81.5.7Turn-off thyristor (GTO = Gate Turn Off)81.5.8Combination of semiconductor devices81.5.9Converter circuit elements81.5.10Converter connection (IEV 551-04-17)91.5.11Controllability of converter arms91.5.12Quadrants of operation (on d.c. side)91.5.13Commutation and quenching (see figure 1)91.5.14Type of commutation101.5.15Self commutation (IEV 551-05-06)101.5.16Type of quenching101.5.17Commutation circuit (IEV 551-05-29, modified)111.5.20Inherent delay angle $\alpha_p$ 121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.27Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.2	Power semiconductor diode	
1.5.4Reverse blocking triode thyristor81.5.5Reverse conducting triode thyristor81.5.6Bidirectional triode thyristor (triac)81.5.7Turn-off thyristor (GTO = Gate Turn Off)81.5.8Combination of semiconductor devices81.5.9Converter circuit elements81.5.10Converter connection (IEV 551-04-17)91.5.11Controllability of converter arms91.5.12Quadrants of operation (on d.c. side)91.5.13Commutation and quenching (see figure 1)91.5.14Type of commutation (IEV 551-05-06)101.5.15Self commutation (IEV 551-05-06)101.5.16Type of quenching101.5.17Commutation circuit (IEV 551-05-29, modified)111.5.18Trigger delay angle $\alpha$ 121.5.20Inherent delay angle $\alpha_p$ 121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.23Definitions of rated values131.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.27Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.3	Thyristor	
1.5.5Reverse conducting triode thyristor81.5.6Bidirectional triode thyristor (triac)81.5.7Turn-off thyristor (GTO = Gate Turn Off)81.5.8Combination of semiconductor devices81.5.9Converter circuit elements81.5.10Converter connection (IEV 551-04-17)91.5.11Controllability of converter arms91.5.12Quadrants of operation (on d.c. side)91.5.13Commutation and quenching (see figure 1)91.5.14Type of commutation101.5.15Self commutation (IEV 551-05-06)101.5.16Type of quenching101.5.17Commutation circuit (IEV 551-05-29, modified)111.5.18Trigger delay angle $\alpha$ 121.5.20Inherent delay angle $\alpha_p$ 121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.23Definitions of rated values141.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.28Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.4	Reverse blocking triode thyristor	
1.5.6Bidirectional triode thyristor (triac)81.5.7Turn-off thyristor (GTO = Gate Turn Off)81.5.8Combination of semiconductor devices81.5.9Converter circuit elements81.5.10Converter connection (IEV 551-04-17)91.5.11Controllability of converter arms91.5.12Quadrants of operation (on d.c. side)91.5.13Commutation and quenching (see figure 1)91.5.14Type of commutation101.5.15Self commutation (IEV 551-05-06)101.5.16Type of quenching101.5.17Commutation circuit (IEV 551-05-09)111.5.18Trigger delay angle $\alpha$ (IEV 551-05-29, modified)111.5.20Inherent delay angle $\alpha_p$ 121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.23Definitions of rated values for assemblies and equipment141.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.28Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.5	Reverse conducting triode thyristor	
1.5.7Turn-off thyristor (GTO = Gate Turn Off)81.5.8Combination of semiconductor devices81.5.9Converter circuit elements81.5.10Converter connection (IEV 551-04-17)91.5.11Controllability of converter arms91.5.12Quadrants of operation (on d.c. side)91.5.13Commutation and quenching (see figure 1)91.5.14Type of commutation101.5.15Self commutation (IEV 551-05-06)101.5.16Type of quenching101.5.17Commutation circuit (IEV 551-05-09)111.5.18Trigger delay angle $\alpha$ (IEV 551-05-29, modified)111.5.19Trigger advance angle $\beta$ 121.5.20Inherent delay angle $\alpha_p$ 121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.23Definitions of rated values141.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.28Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.6	Bidirectional triode thyristor (triac)8	
1.5.8Combination of semiconductor devices81.5.9Converter circuit elements81.5.10Converter connection (IEV 551-04-17)91.5.11Controllability of converter arms91.5.12Quadrants of operation (on d.c. side)91.5.13Commutation and quenching (see figure 1)91.5.14Type of commutation101.5.15Self commutation (IEV 551-05-06)101.5.16Type of quenching101.5.17Commutation circuit (IEV 551-05-09)111.5.18Trigger delay angle $\alpha$ (IEV 551-05-29, modified)111.5.19Trigger advance angle $\beta$ 121.5.20Inherent delay angle $\alpha_p$ .121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.23Definitions of rated values131.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.28Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.7	Turn-off thyristor (GTO = Gate Turn Off)	
1.5.9Converter circuit elements81.5.10Converter connection (IEV 551-04-17)91.5.11Controllability of converter arms91.5.12Quadrants of operation (on d.c. side)91.5.13Commutation and quenching (see figure 1)91.5.14Type of commutation101.5.15Self commutation (IEV 551-05-06)101.5.16Type of quenching101.5.17Commutation circuit (IEV 551-05-09)111.5.18Trigger delay angle $\alpha$ (IEV 551-05-29, modified)111.5.19Trigger advance angle $\beta$ 121.5.20Inherent delay angle $\alpha_p$ 121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.23Definitions of rated values for assemblies and equipment141.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.28Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.8	Combination of semiconductor devices	
1.5.10 Converter connection (IEV 551-04-17) 9   1.5.11 Controllability of converter arms 9   1.5.12 Quadrants of operation (on d.c. side) 9   1.5.13 Commutation and quenching (see figure 1) 9   1.5.14 Type of commutation 10   1.5.15 Self commutation (IEV 551-05-06) 10   1.5.16 Type of quenching 10   1.5.17 Commutation circuit (IEV 551-05-09) 11   1.5.18 Trigger delay angle $\alpha$ (IEV 551-05-29, modified) 11   1.5.19 Trigger advance angle $\beta$ 12   1.5.20 Inherent delay angle $\alpha_p$ 12   1.5.21 Extinction angle $\gamma$ (IEV 551-05-30, modified) 12   1.5.22 Definitions of rated values 13   1.5.23 Definitions of rated values for assemblies and equipment 14   1.5.24 Efficiency definitions 14   1.5.25 Terms used in connection with converter faults 14   1.5.26 Factors on the a.c. side 14   1.5.27 Terms used in connection with direct voltage regulation 16   1.5.29 Definitions related t		1.5.9	Converter circuit elements	
1.5.11Controllability of converter arms91.5.12Quadrants of operation (on d.c. side)91.5.13Commutation and quenching (see figure 1)91.5.14Type of commutation101.5.15Self commutation (IEV 551-05-06)101.5.16Type of quenching101.5.17Commutation circuit (IEV 551-05-09)111.5.18Trigger delay angle $\alpha$ (IEV 551-05-29, modified)111.5.19Trigger advance angle $\beta$ 121.5.20Inherent delay angle $\alpha_p$ 121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.23Definitions of rated values for assemblies and equipment141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.27Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.10	Converter connection (IEV 551-04-17)9	
1.5.12 Quadrants of operation (on d.c. side) 9   1.5.13 Commutation and quenching (see figure 1) 9   1.5.14 Type of commutation 10   1.5.15 Self commutation (IEV 551-05-06) 10   1.5.16 Type of quenching 10   1.5.17 Commutation circuit (IEV 551-05-09) 11   1.5.18 Trigger delay angle $\alpha$ (IEV 551-05-29, modified) 11   1.5.19 Trigger advance angle $\beta$ 12   1.5.20 Inherent delay angle $\alpha_p$ . 12   1.5.21 Extinction angle $\gamma$ (IEV 551-05-30, modified) 12   1.5.22 Definitions of rated values 13   1.5.23 Definitions of rated values 14   1.5.24 Efficiency definitions 14   1.5.25 Terms used in connection with converter faults 14   1.5.26 Factors on the a.c. side 14   1.5.27 Terms used in connection with direct voltage 15   1.5.28 Terms used in connection with direct voltage regulation 16   1.5.29 Definitions related to cooling 17		1.5.11	Controllability of converter arms9	
1.5.13 Commutation and quenching (see figure 1)		1.5.12	Quadrants of operation (on d.c. side)9	
1.5.14 Type of commutation 10   1.5.15 Self commutation (IEV 551-05-06) 10   1.5.16 Type of quenching 10   1.5.17 Commutation circuit (IEV 551-05-09) 11   1.5.18 Trigger delay angle $\alpha$ (IEV 551-05-29, modified) 11   1.5.19 Trigger advance angle $\beta$ 12   1.5.20 Inherent delay angle $\alpha_p$ 12   1.5.21 Extinction angle $\gamma$ (IEV 551-05-30, modified) 12   1.5.22 Definitions of rated values 13   1.5.23 Definitions of rated values for assemblies and equipment 14   1.5.24 Efficiency definitions 14   1.5.25 Terms used in connection with converter faults 14   1.5.26 Factors on the a.c. side 14   1.5.27 Terms used in connection with d.c. voltage 15   1.5.28 Terms used in connection with direct voltage regulation 16   1.5.29 Definitions related to cooling 17		1.5.13	Commutation and quenching (see figure 1)9	
1.5.15 Self commutation (IEV 551-05-06) 10   1.5.16 Type of quenching 10   1.5.17 Commutation circuit (IEV 551-05-09) 11   1.5.18 Trigger delay angle $\alpha$ (IEV 551-05-29, modified) 11   1.5.19 Trigger advance angle $\beta$ 12   1.5.20 Inherent delay angle $\alpha_p$ 12   1.5.21 Extinction angle $\gamma$ (IEV 551-05-30, modified) 12   1.5.22 Definitions of rated values 13   1.5.23 Definitions of rated values for assemblies and equipment 14   1.5.24 Efficiency definitions 14   1.5.25 Terms used in connection with converter faults 14   1.5.26 Factors on the a.c. side 14   1.5.27 Terms used in connection with d.c. voltage 15   1.5.28 Terms used in connection with direct voltage regulation 16   1.5.29 Definitions related to cooling 17		1.5.14	Type of commutation10	
1.5.16Type of quenching101.5.17Commutation circuit (IEV 551-05-09)111.5.18Trigger delay angle $\alpha$ (IEV 551-05-29, modified)111.5.19Trigger advance angle $\beta$ 121.5.20Inherent delay angle $\alpha_p$ 121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.23Definitions of rated values for assemblies and equipment141.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.27Terms used in connection with d.c. voltage151.5.28Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.15	Self commutation (IEV 551-05-06)10	
1.5.17Commutation circuit (IEV 551-05-09)111.5.18Trigger delay angle $\alpha$ (IEV 551-05-29, modified)111.5.19Trigger advance angle $\beta$ 121.5.20Inherent delay angle $\alpha_p$ 121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.23Definitions of rated values for assemblies and equipment141.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.27Terms used in connection with d.c. voltage151.5.28Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.16	Type of quenching	
1.5.18Trigger delay angle $\alpha$ (IEV 551-05-29, modified)111.5.19Trigger advance angle $\beta$ 121.5.20Inherent delay angle $\alpha_p$ 121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.23Definitions of rated values for assemblies and equipment141.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.27Terms used in connection with d.c. voltage151.5.28Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.17	Commutation circuit (IEV 551-05-09)11	
1.5.19Trigger advance angle $\beta$ .121.5.20Inherent delay angle $\alpha_p$ .121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.23Definitions of rated values for assemblies and equipment141.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.27Terms used in connection with d.c. voltage151.5.28Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.18	Trigger delay angle $\alpha$ (IEV 551-05-29, modified)11	
1.5.20Inherent delay angle $\alpha_p$ .121.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.23Definitions of rated values for assemblies and equipment141.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.27Terms used in connection with d.c. voltage151.5.28Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.19	Trigger advance angle $\beta$	
1.5.21Extinction angle $\gamma$ (IEV 551-05-30, modified)121.5.22Definitions of rated values131.5.23Definitions of rated values for assemblies and equipment141.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.27Terms used in connection with d.c. voltage151.5.28Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.20	Inherent delay angle $\alpha_{\rm p}$	
1.5.22Definitions of rated values131.5.23Definitions of rated values for assemblies and equipment141.5.24Efficiency definitions141.5.25Terms used in connection with converter faults141.5.26Factors on the a.c. side141.5.27Terms used in connection with d.c. voltage151.5.28Terms used in connection with direct voltage regulation161.5.29Definitions related to cooling17		1.5.21	Extinction angle $\gamma$ (IEV 551-05-30, modified)	
1.5.23 Definitions of rated values for assemblies and equipment141.5.24 Efficiency definitions141.5.25 Terms used in connection with converter faults141.5.26 Factors on the a.c. side141.5.27 Terms used in connection with d.c. voltage151.5.28 Terms used in connection with direct voltage regulation161.5.29 Definitions related to cooling17		1.5.22	Definitions of rated values	
1.5.24 Efficiency definitions141.5.25 Terms used in connection with converter faults141.5.26 Factors on the a.c. side141.5.27 Terms used in connection with d.c. voltage151.5.28 Terms used in connection with direct voltage regulation161.5.29 Definitions related to cooling17		1.5.23	Definitions of rated values for assemblies and equipment	
1.5.25 Terms used in connection with converter faults		1.5.24	Efficiency definitions	
1.5.26 Factors on the a.c. side141.5.27 Terms used in connection with d.c. voltage151.5.28 Terms used in connection with direct voltage regulation161.5.29 Definitions related to cooling17		1.5.25	Terms used in connection with converter faults	
1.5.27 Terms used in connection with d.c. voltage151.5.28 Terms used in connection with direct voltage regulation161.5.29 Definitions related to cooling17		1.5.26	Factors on the a.c. side	
1.5.28 Terms used in connection with direct voltage regulation		1.5.27	Terms used in connection with d.c. voltage	
1.5.29 Definitions related to cooling.		1.5.28	Terms used in connection with direct voltage regulation	
		1.5.29	Definitions related to cooling	
1.5.30 Temperature definitions		1.5.30	Temperature definitions	
1.5.31 Electrical disturbance		1.5.31	Electrical disturbance	
1.5.32 Level of immunity of a converter		1.5.32	Level of immunity of a converter	
1.5.33 Level of generated disturbance of a converter		1.5.33	Level of generated disturbance of a converter	



This is a free preview. Purchase the entire publication at the link below:

**Product Page** 

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation