
WITH DEAWN TAS TECHNIBLE PATT CLEST AC 2314.7-1997 DE 9646 AS 2374.7 - 1997 FWD 970825

> AS 1078—1984 UDC 621.314.212.016.3

Australian Standard® 1078—1984



# GUIDE TO LOADING OF OIL-IMMERSED TRANSFORMERS





STANDARDS ASSOCIATION OF AUSTRALIA

Incorporated by Royal Charter

This Australian standard was prepared by Committee EL/8, Static Electrical Machinery. It was approved on behalf of the Council of the Standards Association of Australia on 6 August 1984 and published on 9 November 1984.

The following interests are represented on Committee EL/8:

Australian British Trade Association

Australian Electrical and Electronic Manufacturers Association Ltd

Confederation of Australian Industry

Defence Standardization Committee

Electrical Testing Laboratories

Electricity Supply Association of Australia

Institution of Engineers, Australia

Railways of Australia Committee

Review of Australian Standards. To keep abreast of progress in industry, Australian standards are subject to periodic review and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all SAA publications will be found in the Catalogue of SAA Publications; this information is supplemented each month by SAA's journal 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn standards.

Suggestions for improvements to Australian standards, addressed to the head office of the Association, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian standard should be made without delay in order that the matter may be investigated and appropriate action taken.

## **AUSTRALIAN STANDARD**

# GUIDE TO LOADING OF OIL-IMMERSED TRANSFORMERS

AS 1078-1984

First published (as AS CC10)	. 1965
AS 1078, Part 1 first published	
AS 1078 first published	

PUBLISHED BY THE STANDARDS ASSOCIATION OF AUSTRALIA STANDARDS HOUSE, 80 ARTHUR ST, NORTH SYDNEY, N.S.W.

### **PREFACE**

This standard was prepared by the Association's Committee on Static Electrical Machinery. It supersedes AS 1078, Guide to Loading of Oil-immersed Transformers, Part 1—1972, Transformers to AS C61—1963. This guide applies directly to transformers manufactured to AS C61—1970, Power Transformers, but may be used for transformers manufactured to AS 2374—1982, Power Transformers, and earlier editions of AS C61.

The guide is based on the revised 1969 Draft Loading Guide for Oil Immersed Transformers, prepared for the Electricity Supply Association of Australia (ESAA) by the Sydney County Council and acknowledgement is made of the assistance received therefrom.

It is stressed that the language used in this guide is much freer than is customary in a standard specification and for this reason no attempt has been made to give a list of defined terms.

The life-expectancy curve (see Fig. A2) used as a basis of the guide to arrive at the cyclic loading values given in Tables 2.4 to 2.15 inclusive, is based on the ageing curve used in IEC 354, Loading Guide for Oil-immersed Transformers.

©Copyright — STANDARDS ASSOCIATION OF AUSTRALIA 1984

Users of standards are reminded that copyright subsists in all SAA publications. No part of this publication may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing of the Standards Association of Australia.

# **CONTENTS**

ECTIO	N 1. SCOPE AND GENERAL	Pe
1.1	Scope	(
1.2	Purpose	
1.3		
1.4	Application	
1.5	Referenced Documents	
		•••
	N 2. CYCLIC LOADINGS	
2.1	Permissible Cyclic Loading of a Transformer	•••
2.2	Data Necessary for Determination of Cyclic Loading	•••
2.3	Flow Diagram	
2.4	Determination of Continuous Rating of a Transformer Corresponing to 55° C Top-oil Rise (Step 1)	a- 
2.5	Determination of Winding Hotspot Gradient (Differential) Abo	***
2.5	Top Oil Corresponding to the Continuous Rating for 55°C Top-	oil
	Temperature Rise (Step 2)	
2.6	Method of Representing Actual Load Cycles by Equivalent Blo	ck
	Shapes (Step 3)	1
2.7		1
2.8	Correction to Selected Weighted Average Ambient Temperatu	
	Due to Enclosure (Step 5)	
2.9		1
2.10	Method of Adjustment to Allow for Different Values of Assign	∌d
	Normal Life or the Application of a Less Conservative Ageing Cur	
	(Step 7)	l
2.11	Method of Adjustment to Take into Account Different Value Thermal Time-constant (Step 8)	01
2.12		
2.12	the Insulation with Various Cyclic Loads (Step 9)	<i>2</i>
2.13		
2.15	Normally Unloaded (Step 10)	2
2.14		ıd
	(Step 11)	2
2.15	Adjustment of Cyclic Loading to take Account of Load Growth as	ıd
	Relief (Step 12)	2
2.16	Adjustment of Cyclic Loading to take Account of Periods	of
	Abnormal Loading (Step 13)	2
CTIO	n 3. Examples of Determination of $K$	
3.1	Example No 1: Determination of K Where Minimum Data a Available	re 2
3.2	Example No 2: Determination of K Where Complete Test Data as	
3.Z	Loading Data are Available	2
ECTION	n 4. Short-time Emergency Loadings	
4.1	General	3
4.2	Data Necessary for Determination of Permissible Short-time	
7.2	Emergency Loading	3
4.3		
4.4	Permissible Reduction of Life Expectancy for Short-time Emergence	
<b>₹.</b> ₹	Loading	., ., 3
4.5	Determination of Top-oil Temperature Rise Prior to Emergence	
7.3	(0)	3
4.6	Determination of the Ultimate Top-oil Temperature Rise if the	
	Short-time Load were Applied Continuously (Step 2)	
4.7	Determination of Thermal Time-constant Corresponding to the	
	Initial and Ultimate Top-oil Temperature Rises (Step 3)	3
4.8	Determination of Top-oil Temperature Rise after Short-time Perio	d
-	at Emergency Loading (Step 4)	3



	This is a free preview.	Purchase the e	entire publication	at the link below:
--	-------------------------	----------------	--------------------	--------------------

**Product Page** 

- Dooking for additional Standards? Visit Intertek Inform Infostore
- Dearn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation