

Irish Standard Recommendation S.R. CEN/CLC/TR 17603-20-05:2021

# Space engineering - High voltage engineering and design handbook

© CENELEC 2021 No copying without NSAI permission except as permitted by copyright law.

#### S.R. CEN/CLC/TR 17603-20-05:2021

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard — national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):

NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.

This document is based on:

Published:

CEN/CLC/TR 17603-20-05:2021

2021-08-04

This document was published under the authority of the NSAI and comes into effect on:

ICS number:

2021-08-23

NOTE: If blank see CEN/CENELEC cover page

NSAI T +353 1 807 3800 Sales:

 1 Swift Square,
 F +353 1 807 3838
 T +353 1 857 6730

 Northwood, Santry
 E standards@nsai.ie
 F +353 1 857 6729

 Dublin 9
 W NSAI.ie
 W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

This is a free page sample. Access the full version online.

#### **National Foreword**

S.R. CEN/CLC/TR 17603-20-05:2021 is the adopted Irish version of the European Document CEN/CLC/TR 17603-20-05:2021, Space engineering - High voltage engineering and design handbook

This document does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

For relationships with other publications refer to the NSAI web store.

Compliance with this document does not of itself confer immunity from legal obligations.

In line with international standards practice the decimal point is shown as a comma (,) throughout this document.

This is a free page sample. Access the full version online.

This page is intentionally left blank

TECHNICAL REPORT RAPPORT TECHNIQUE TECHNISCHER BERICHT

CEN/CLC/TR 17603-20-05

August 2021

ICS 49.140

#### **English version**

## Space engineering - High voltage engineering and design handbook

Ingénierie spatiale - Manuel d'ingénierie et de conception haute tension

Raumfahrttechnik - Handbuch für Hochspannungstechnik und Design

This Technical Report was approved by CEN on 14 June 2021. It has been drawn up by the Technical Committee CEN/CLC/JTC 5.

CEN and CENELEC members are the national standards bodies and national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.





**CEN-CENELEC Management Centre:** Rue de la Science 23, B-1040 Brussels

# **Table of contents**

Europ	uropean Foreword		10
Introd	uction.		11
1 Sco	oe		12
2 Refe	rences	;	13
3 Tern	ns, defi	nitions and abbreviated terms	17
3.1	Terms	from other documents	17
3.2	Terms	specific to the present document	17
3.3	Abbrev	viated terms	21
4 High	voltag	ge design considerations	23
4.1	Enviro	nment	23
	4.1.1	Impact of environment	23
	4.1.2	Pressure	23
	4.1.3	Temperature	25
	4.1.4	Energetic Particle Radiation	26
	4.1.5	Space Debris and Micrometeoroids	27
	4.1.6	Plasma	27
	4.1.7	Mechanical	28
4.2	Electri	cal insulation	28
	4.2.1	Categories of insulation	28
	4.2.2	Gaseous insulation	28
	4.2.3	Liquid insulation	31
	4.2.4	Solid insulation	32
	4.2.5	Vacuum insulation	35
	4.2.6	Composites	36
4.3	Life lim	niting factors	36
	4.3.1	Perspective	36
	4.3.2	Electrical breakdown	37
	4.3.3	Partial discharges	43
	4.3.4	Paschen breakdown	46

	4.3.5	Ageing	48
4.4	Typical	applications	54
	4.4.1	DC-DC High voltage power conditioners	54
	4.4.2	Electronic power conditioners for TWTA	56
	4.4.3	Electric propulsion	63
	4.4.4	Microwave tubes	70
	4.4.5	Scientific instruments and experiments	73
5 High	voltage	e design principles	75
5.1	Basic d	lesign principles	75
	5.1.1	Control of voltage	75
	5.1.2	Control of electrical field strengths	76
	5.1.3	Control of electrical field distribution	87
	5.1.4	Control of insulation properties	89
	5.1.5	Control of surface properties	92
	5.1.6	Control of partial discharges	93
	5.1.7	Control of corona effects	95
	5.1.8	Control of Paschen breakdown	95
	5.1.9	Control of triple junction effects	98
	5.1.10	Control of creepage path	99
	5.1.11	Control of surface charging	100
	5.1.12	Control of interferences	102
5.2	High vo	oltage assemblies	105
	5.2.1	Solid insulation: potted modules	105
	5.2.2	Solid insulation: others	125
	5.2.3	Gaseous insulation	127
	5.2.4	Liquid insulation (Oil)	132
	5.2.5	Space vacuum insulation	133
5.3	High vo	oltage components	141
	5.3.1	Transformers and inductors	141
	5.3.2	Capacitors	144
	5.3.3	Resistors	147
	5.3.4	Semiconductors	149
	5.3.5	Wires and cables	149
	5.3.6	Connectors	154
	5.3.7	Interconnections	155
	5.3.8	Insulators and spacers	157
	5.3.9	Feedthroughs	158

	5.3.10	Printed circuit boards	159
	5.3.11	Other components	161
6 Higl	h voltage	e testing	162
6.1	Non-De	estructive Testing	162
	6.1.1	Insulation Resistance Test (INR)	162
	6.1.2	Bulk Resistance Measurement (BRM)	163
	6.1.3	Surface Resistance Measurement (SRM)	164
	6.1.4	Polarisation and Depolarisation Current Measurement (PDC)	165
	6.1.5	Dielectric Loss Factor Test (DLF)	166
	6.1.6	Partial Discharge Test (PDT)	167
	6.1.7	Dielectric Withstanding Voltage Test (DWV)	173
	6.1.8	Triple Junction Test (TRJ)	175
	6.1.9	Critical pressure testing/Corona testing (CPT)	177
	6.1.10	Life testing (LIT)	180
	6.1.11	Accelerated life testing (ALT)	181
	6.1.12	Burn-in testing (BIT)	182
6.2	Destruc	ctive Testing	183
	6.2.1	Breakdown Voltage Test (BVT)	183
	6.2.2	Lifetime evaluation testing (LET)	184
6.3	Supple	mentary Methods	185
6.4	Testing	strategy	186
7 Higl	h voltage	e product aspects	189
	7.1.1	Best practice for materials and processes selection	189
	7.1.2	Best practice for design	191
	7.1.3	Best practice for qualification	193
	7.1.4	Best practice for flight acceptance	194
	7.1.5	Best practice for verification	195
	7.1.6	PID	196
	7.1.7	Evaluation Plan	197
8 Spe	cific pro	blem areas	198
	8.1.1	High voltage converters	198
	8.1.2	Electric propulsion	200
	8.1.3	Electron devices (tubes)	205
	8.1.4	Scientific instruments and experiments	205
	8.1.5	EMC aspects	205
9 Haz	ards and	d safety	207

9.1	Hazard	ls	207
9.2	Safety		207
Annex	A High	Voltage Field Calculation Tables	. 208
A.1	Princip	les of field efficiency factors for spheres and cylindrical geometries	208
A.2	Spheric	cal geometries	209
A.3	Cylindr	ical geometries	210
Annex	B Best	t Practice References	. 212
B.1	High V	oltage Evaluation Plan	212
	B.1.1	Evaluation Activities	212
	B.1.2	Evaluation Plan	212
	B.1.3	Manufacturing of Evaluation Samples	213
	B.1.4	Test and Characterisation	213
	B.1.5	Evaluation Review	213
B.2	Materia	als Evaluation	214
B.3	PID – F	Process Identification Document	218
Figure	es		
•		Caused by Particle Bridge	27
Figure		charge (breakdown) development in a gas volume between two ectrodes by electron avalanche process	38
Figure	ga	etrical strengths of a liquid insulation (here: transformer oil in 2,5 mr p) in relation to voltage exposure time and assumed breakdown echanism	
Figure	4-4: Vac	uum breakdown phenomena	42
Figure	4-5: Typi	ical partial discharge configurations	44
Figure	4-6: Elec	ctrical model of partial discharges for a gas-bubble in a solid	45
Figure		akdown voltage of gases vs. the product of pressure times gap	
	-	acing	
_		ctrical treeing caused by partial discharges	
Figure	ex	mple: Fatigue (thermo-mechanical stress-related) failures in assem pressed as stress ( $\Delta T$ – temperature cycle amplitude) over number ermal cycles	r of
Figure	as	ample: Fatigue (thermo-mechanical stress-related) failures in semblies expressed as stress (∆T – temperature cycle amplitude) of thermal cycles	
Figure	4-11: Ele	ectrical field strengths over time curve according to the Crine model	l54
Figure	4-12: DC	C/DC power conversion chains for high voltage of an EPC	55
Figure	4-13: To	pologies of electronic power conditioners	56
Figure	4-14: Fu	nctional block diagram of an EPC	57

Figure 4-15: Example for a high voltage generation of an EPC	59
Figure 4-16: Example of a high voltage transformer for an EPC	60
Figure 4-17: Example of a FEM calculation result: Equipotential Lines for a Plane-to Plane configuration with spherical edges of the upper plane	
Figure 4-18: Principle of Electrical Propulsion vs. Chemical Propulsion	63
Figure 4-19: FEEP Ion Emitter Principle	65
Figure 4-20: FEEP Ion Emitter Load – Equivalent Circuit	65
Figure 4-21: Hall Effect Thruster Principle	66
Figure 4-22: HEMP Thruster Principle	67
Figure 4-23: Ion Thruster Principle (Kaufmann)	68
Figure 4-24: Radio Frequency Ion Thruster (RIT) Principle	70
Figure 4-25: Schematic layout of a TWT	71
Figure 4-26: Principle of the electron gun of a TWT	72
Figure 4-27: Principle of the collector stage of a TWT	72
Figure 5-1: Electrical field strength depending on voltage and geometrical paramete (Examples)	
Figure 5-2: Uniform electrical field for indefinite parallel planes	79
Figure 5-3: Sphere-inside-sphere electrical field	80
Figure 5-4: Examples for practical use of field equations for spheres	81
Figure 5-5: Examples for practical: connections of wires by using spherical solder joints	82
Figure 5-6: Cylinder-inside-cylinder electrical field	82
Figure 5-7: Space charge formation on an isolating surface	84
Figure 5-8: Space charge formation on sharp-edged structures in various environments	85
Figure 5-9: Surface charging of an isolator	85
Figure 5-10: Correct meshing of shapes	87
Figure 5-11: General: E-Field and voltage for a three-dimensional path	87
Figure 5-12: E-Field and voltage for gap lengths (straight path)	88
Figure 5-13: Control of electrical field distribution - Examples	89
Figure 5-14: Avoiding fibre bridging effect in liquid insulation	90
Figure 5-15: Optimum design of interfaces between materials w.r.t. the electrical fiel	d92
Figure 5-16: Limit critical Paschen breakdown pressure range by limitation of maxim gap	
Figure 5-17: Paschen discharge in a gap between solid insulation and ground	97
Figure 5-18: Triggered Paschen discharge in a gap between solid insulation and ground	97
Figure 5-19: Critical triple-junction point/area in an interface between solid - gaseous/liquid/vacuum insulation - metal conductor	98
Figure 5-20: Methods to reduce the influence of the triple junction zone by design	99

Figure 5-21:	Impact of creepage path on electrical field distribution	99
Figure 5-22:	Designs to reduce impact of creepage path on electric insulation	.100
Figure 5-23:	Designs to reduce impact of surface charging on electric insulation	.101
Figure 5-24:	Segmenting of insulator to influence surface charging	.102
Figure 5-25:	Implementation of design measures minimizing interference problems a typical high voltage power conditioner (regulated DC-DC converter for high voltage as an example)	or
Figure 5-26:	Designs example: potting of embedded aluminium structure, i.e. an HV terminal	
Figure 5-27:	Designs example: potting of embedded aluminium structure, i.e. HV terminal	.112
Figure 5-28:	Shielding necessary to avoid exposure of an electronic part to excessive electrical field stress	
Figure 5-29:	Potting of PCB's: typical design aspects	.115
Figure 5-30:	Transformer with rectifier and filter designed as two separate modules using open terminals for interconnecting HV harness	.117
Figure 5-31:	Transformer and rectifier filter designed as two separate modules using potted terminals for interconnecting HV harness	
Figure 5-32:	Transformer and rectifier filter designed as one combined module potter in (a) one or (b) two and more sequential potting processes	
Figure 5-33:	Designs example: Spherical solder ball	.119
Figure 5-34:	Fitting a potted assembly to partial discharge testing (Example of a pot transformer winding)	
Figure 5-35:	Examples for thermal drains embedded in potted modules	.123
Figure 5-36:	Relative Dielectric Strength of a SF <sub>6</sub> -N <sub>2</sub> -Mixture versus Composition of Mixture	
Figure 5-37:	Surface flashover process in a vacuum environment	.134
Figure 5-38:	Surface shapes for insulators	.136
Figure 5-39:	Arrangement of cylindrically layers of windings	.141
Figure 5-40:	Arrangement of windings in discs of a bobbin	.143
Figure 5-41:	Partial discharge test aspects of a high voltage transformer	.144
Figure 5-42:	Critical electrical field stress in the surrounding of high voltage capacitor and proposed measures	
Figure 5-43:	Basic high voltage resistor design variants	.147
Figure 5-44:	High voltage resistor design aspects	.148
Figure 5-45:	Suitable partial discharge test setup for high voltage wires	.150
Figure 5-46:	Critical stress cases for high voltage wires	.151
Figure 5-47:	Critical stress cases for high voltage wires terminations	.152
Figure 5-48:	Interconnection of high voltage harness via soldering or crimping/boltin terminals	
Figure 5-49:	Flying lead interconnections	.157

Figure 5-50: Suitable insulator design variants	158
Figure 5-51: Suitable feedthrough design variants	159
Figure 6-1: Guard ring test set-up for bulk resistance measurement	163
Figure 6-2: Partial discharge test set-up	169
Figure 6-3: Typical partial discharge test flow	170
Figure 6-4: Partial discharge testing aspects. Example: High voltage transformer	171
Figure 6-5: Dielectric Withstand Voltage Test Electrical Schematic	174
Figure 6-6: Triple Junction Test Electrical Schematic	176
Figure 6-7: Critical Pressure Test Electrical Schematic	178
Figure 6-8: Breakdown Voltage Test Electrical Schematic	183
Figure 8-1: High voltage conditioner with grounding at converter – load floating	199
Figure 8-2: High voltage conditioner with grounding at load side – including a cla device at the conditioner	
Figure 8-3: High voltage conditioner with grounding at load side – including a cla device at the conditioner and triax HV cable for load connection	
Figure A-1 : Field efficiency factors (Schwaiger factors) $\eta$ as a function of geome parameter $p$ for spheres	
Figure A-2 : Field efficiency factors (Schwaiger factors) $\eta$ as a function of geome parameter $p$ for cylinders	•
Figure A-3 : Field efficiency factors (Schwaiger factors) $\eta$ as a function of geome parameter $p$ for cylinders	
Figure B-1 : Typical material evaluation flow	216
Figure B-2 : Potted Rogowsky-profile electrodes	217
Figure B-3 : Crossed wire electrode	217
Figure B-4 : Material disk between electrodes	217
Tables	
Table 4-1: Course Classification of the potential impact to electrical insulations by environmental type	
Table 4-2: Properties of gaseous insulations	30
Table 4-3: Properties of liquid insulations	31
Table 4-4: Properties of EP, PUR and SI	33
Table 4-5: Properties of various polymers	34
Table 4-6: Properties of porcelain and alumina	35
Table 4-7: Paschen Minimum for various gases	48
Table 4-8: Overview on Electrical Propulsion Principles, Thruster Type and Elect Physical Parameters	
Table 5-1: Critical "thresholds" for high voltage	75
Table 5-2: Orientation "map" for maximum electrical field strengths in electrical insulation	77

Table 5-3: Orientation values (examples) for selection sphere structures to limit the maximum electrical field of a high voltage assembly	
Table 5-4: Dew point of SF <sub>6</sub> -N <sub>2</sub> -mixtures versus pressure and depending of composition	130
Table 5-5: Surface shapes for insulators in combination with selected materials comparing the relative surface flashover strengths of +/- 45 degree co insulators for various voltage waveforms w.r.t pure cylindrical shapes.	
Table 5-6: Theoretical predictions and experimental consequences of methods to improve the surface flashover strengths in vacuum	138
Table 5-7: Application matrix for PCB with high voltage	160
Table 6-1: Test methods, levels and acceptance criteria for partial discharge testing	g 172
Table 6-2: Assessment of test methods w.r.t. its application	186
Table 7-1: Typical material properties and reference test methods for high voltage insulation materials	189
Table 7-2: Best practice of verification for high voltage design aspects	196
Table A-1 : Sphere geometries	209
Table A-2 : Cylinder-parallel-to-a-cylinder geometries	210
Table A-3 : Cylinder-inside-a-cylinder geometries	210
Table B-1: Product categories according to heritage (Ref.: ECSS-E-ST-10-02)	214

#### CEN/CLC/TR 17603-20-05:2021 (E)

## **European Foreword**

This document (CEN/CLC//TR 17603-20-05:2021) has been prepared by Technical Committee CEN/CLC/JTC 5 "Space", the secretariat of which is held by DIN.

It is highlighted that this technical report does not contain any requirement but only collection of data or descriptions and guidelines about how to organize and perform the work in support of EN 16603-20.

This Technical report (TR 17603-20-05:2021) originates from ECSS-E-HB-20-05A.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

This document has been developed to cover specifically space systems and has therefore precedence over any TR covering the same scope but with a wider domain of applicability (e.g.: aerospace).

## Introduction

The subject of high voltage engineering and design has been part of the spacecraft design process since the early times of spaceflight.

This was due to need for high voltage power conditioners being a key element of communication links. The relate expertise was built up in Europe in the decade of the 1980 with the support of the development of modern Electronic Power Conditioners (EPC's), to operate Travelling Wave Tube Amplifiers for telecommunication satellites and for high power radar applications.

In 1989 ESA launched its first high power radar for earth observation onboard the ERS-1 (European Remote Sensing Satellite), achieving a technology for 15 kV – 17 kV in space.

Today typically between some ten and over hundred EPC's with operating voltages of 5 kV - 8 kV are placed on many of the telecommunications satellites.

Several space borne radars with travelling wave tubes and klystrons are in orbit using voltage up to 20 kV. Various detectors for various kind of space environment with voltage between a few hundred volts and up to 30 kV are used in many missions, high power lasers up to 150 kV were studied, and even some experiments onboard the International Space Station using fancy high voltage sources.

The latest trend is the increasing use of electric propulsion for satellites dealing with supply voltage in the range between a few hundred volts and above 10 kV. High voltage related anomalies have been observed only a few times, some in the early years of building up experience, some also later, especially when new developments were done with new teams inexperienced in the field.

A need was identified for a standard already in the early years of the space flight, the US air force and NASA presented a series design and test handbook in the 1970's and 1980's. In Europe, ESA started discussing a draft standard with industry: the PSS-02-303 draft 2 from 1992 "Requirements for High Voltage Transformer and Components used in Electronic Power Conditioners for ESA Space Systems" this became a quasi standard reference in many space projects, even if it was never formally released. The growing diversity of high voltage application gave finally the urgency to make a new approach for standardization. The discussion started in 2007 with ECSS who led to the conclusion, that a standard would not satisfy the immediate needs for projects, as it would be too wide to cover the diverse applications and also would not be suitable to transfer the "know-how" of high voltage engineering and design. Therefore it was decided to produce a handbook to give a broad scope of knowledge and recommendations for design and test of high voltage equipment and components.

This document aims to satisfy these needs and provides a detailed view of high voltage knowledge aspects as well as giving a guideline to identify suitable design rules.

Proper design of high voltage effects of these processes is part of the system engineering process as defined in ECSS-E-ST-20, where only a small subset of high voltage requirements is given.

For new projects involving high voltage equipment and design it is useful to provide this handbook as a reference to generate suitable requirements specific to the targeted high voltage application.

Chapter 7 of this document gives some "best practice" statements.

Only a smart answer can be given to the definition of the range of voltages which should be considered as high voltages: The ECSS-E-ST-20C states for the definition of a high voltage "AC or DC voltage at which partial discharges, corona, arcing or high electrical fields can occur". For space environment this can occur ". This in fact can already appear at 60 V - 80 V if a low pressure environment in an inert gas provides a critical pressure for "Paschen Breakdown". Under air  $(N_2/O_2 \text{ mixtures})$  this can occur for voltage of above 300 V.

#### CEN/CLC/TR 17603-20-05:2021 (E)

# 1 Scope

This Handbook establishes guidelines to ensure a reliable design, manufacturing and testing of high voltage electronic equipment and covers:

- Design
- Manufacturing
- Verification/Testing

of equipment generating, carrying or consuming high voltage, like: high voltage power conditioner, high voltage distribution (cables and connectors).

This Handbook is dedicated to all parties involved at all levels in the realization of space segment hardware and its interface with high voltage for which ECSS-E-ST-20C is applicable.

This handbook sets out to:

- summarize most relevant aspects and data of high voltage insulation
- provide design guidelines for high voltage insulation
- provide design guidelines for high voltage electronic equipment
- give an overview of appropriate high voltage test methods
- establish a set of recommendations for generation design and verification rules and methods
- provide best practices

Applicability is mainly focused on power conditioning equipment but may be also applicable for all other high voltage electric and electronic power equipment used on space missions, except items of experimental nature.



The is a new provider i arenade and chare publication at the limit below	This is a free preview.	Purchase the	entire publication	at the link below:
--	-------------------------	--------------	--------------------	--------------------

**Product Page** 

- Dooking for additional Standards? Visit Intertek Inform Infostore
- Dearn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation