



NSAI
Standards

Irish Standard Recommendation
S.R. CEN/CLC/TR 17603-20-01:2021

Space engineering - Multipactor handbook

S.R. CEN/CLC/TR 17603-20-01:2021

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard — national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):

NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.

This document is based on:

CEN/CLC/TR 17603-20-01:2021

Published:

2021-09-29

This document was published under the authority of the NSAI and comes into effect on:

2021-10-18

ICS number:

49.140

NOTE: If blank see CEN/CENELEC cover page

NSAI
1 Swift Square,
Northwood, Santry
Dublin 9

T +353 1 807 3800
F +353 1 807 3838
E standards@nsai.ie
W NSAI.ie

Sales:
T +353 1 857 6730
F +353 1 857 6729
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

National Foreword

S.R. CEN/CLC/TR 17603-20-01:2021 is the adopted Irish version of the European Document CEN/CLC/TR 17603-20-01:2021, Space engineering - Multipactor handbook

This document does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

For relationships with other publications refer to the NSAI web store.

Compliance with this document does not of itself confer immunity from legal obligations.

In line with international standards practice the decimal point is shown as a comma (,) throughout this document.

This page is intentionally left blank

TECHNICAL REPORT
RAPPORT TECHNIQUE
TECHNISCHER BERICHT

**CEN/CLC/TR 17603-20-
01**

September 2021

ICS 49.140

English version

Space engineering - Multipactor handbook

Ingénierie spatiale - Manuel sur l'effet Multipactor

Raumfahrttechnik - Multipactorhandbuch

This Technical Report was approved by CEN on 13 September 2021. It has been drawn up by the Technical Committee CEN/CLC/JTC 5.

CEN and CENELEC members are the national standards bodies and national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



**CEN-CENELEC Management Centre:
Rue de la Science 23, B-1040 Brussels**

Table of contents

European Foreword	9
Introduction	10
1 Scope	11
2 References	12
3 Terms, definitions and abbreviated terms	14
3.1 Terms from other documents.....	14
3.2 Abbreviated terms.....	15
4 Verification	16
4.1 Verification process	16
4.2 Multipactor verification plan	16
4.2.1 Generation and updating.....	16
4.2.2 Description.....	16
4.3 Power requirements.....	16
4.3.1 General power requirements.....	16
4.4 Classification of equipment or component type.....	17
4.4.1 General classification of equipment or component type	17
4.5 Verification routes.....	20
4.6 Single carrier	20
4.6.1 General.....	20
4.6.2 Verification by analysis.....	20
4.6.3 Verification by test.....	20
4.7 Multicarrier.....	22
4.7.1 General.....	22
4.7.2 Verification by analysis.....	22
4.7.3 Verification by test.....	22
4.8 Bibliography for clause 4.....	23
5 Design analysis	24
5.1 Overview	24
5.2 Field analysis.....	24

5.3	Multipactor design analysis.....	24
5.3.1	Frequency selection.....	24
5.3.2	Design analysis levels.....	24
5.3.3	Available data for Multipactor analysis.....	58
5.4	Bibliography for clause 5.....	62
6	Multipactor - Test conditions.....	64
6.1	Cleanliness.....	64
6.2	Pressure.....	65
6.3	Temperature.....	66
6.4	Signal characteristics.....	67
6.4.1	Applicable bandwidth.....	67
6.4.2	Single-frequency test case.....	67
6.4.3	Multi-frequency test case.....	68
6.4.4	Pulsed testing.....	73
6.5	Electron seeding.....	74
6.5.1	General.....	74
6.5.2	Multipactor test in CW operation.....	74
6.5.3	Multipactor test in pulsed operation.....	74
6.5.4	Multipactor test in multi-carrier operation.....	74
6.5.5	Seeding sources.....	74
6.5.6	Seeding verification.....	82
6.6	Bibliography for clause 6.....	82
7	Multipactor - Methods of detection.....	83
7.1	General.....	83
7.2	Detection methods.....	83
7.2.1	Introduction.....	83
7.2.2	Global detection methods.....	84
7.2.3	Local detection methods.....	86
7.3	Detection method parameters.....	87
7.3.1	Verification.....	87
7.3.2	Sensitivity.....	87
7.3.3	Rise time.....	87
8	Multipactor - test procedure.....	88
8.1	General.....	88
8.2	Test bed configuration.....	89
8.3	Test bed validation.....	89

CEN/CLC/TR 17603-20-01:2021 (E)

8.3.1	Reference multipactor test	89
8.4	Test sequence	93
8.4.1	Power profile	93
8.5	Acceptance criteria	93
8.5.1	Definitions	93
8.5.2	Multipactor Free Equipment or component.....	93
8.5.3	Steps in case of Discharges or Events during test.....	93
8.5.4	Investigation of Test Anomalies.....	93
8.6	Test procedure	93
8.6.1	Test procedure for high power loads	93
8.7	Test reporting	97
8.8	Bibliography for clause 8.....	99
9	Secondary electron emission yield requirements	100
9.1	General.....	100
9.1.1	SEY definition and properties	100
9.1.2	SEY and Multipactor	101
9.1.3	Factors affecting SEY	102
9.1.4	SEY testing	103
9.2	SEY measurements justification	106
9.3	Worst case SEY measurement.....	106
9.4	SEY measurements conditions	106
9.4.1	Environmental conditions	106
9.4.2	SEY test bed conditions	115
9.4.3	SEY sample characteristics.....	118
9.5	SEY measurements procedure	119
9.5.1	SEY Measurements procedure documents	119
9.5.2	SEY measurement calibration	119
9.6	ECSS SEY data selection.....	120
9.7	Bibliography for clause 9.....	139
Figures		
Figure 4-1: Component assembly with consideration of reflection coefficient		
Figure 4-2: Isolator block diagram		
Figure 4-3: Tested component – Coaxial filter		
Figure 4-4: Multipactor simulations and multipactor measurements with and without thermal baking for a RF component with different dielectric materials		
Figure 4-5: Schematic diagram of discharge at a triple point in the inverted voltage gradient configuration with potential contours indicated by colour scale.		

Figure 4-6: Component assembly with consideration of the reflection coefficient of the downstream component assembly for test margin.....	21
Figure 4-7: Power correction with respect to mismatch of the payload downstream component assembly	21
Figure 5-1: 2D schematic of a typical iris-like structure	25
Figure 5-2: 2D Typical Sombrin chart with fringing field effect for different d/l ratios.	27
Figure 5-3: 2D Typical multipactor chart computed with non-stationary theory with fringing field effect for different d/l ratios.	28
Figure 5-4: 2D Experimental results corresponding to EVEREST project [5-12]	29
Figure 5-5: 2D Experimental results corresponding to ESA-TESAT activity [5-10].....	29
Figure 5-6: 2D Experimental results corresponding to ESA-AURORASAT activity [5-11].....	30
Figure 5-7: 2D Numerical results corresponding to ESA-AURORASAT activity [5-11].	30
Figure 5-8: 2D Analytical results corresponding to ESA-AURORASAT activity [5-11]..	31
Figure 5-9: Fringing field analysis method 1 for L1 analysis type.....	32
Figure 5-10: Fringing field analysis method 2 for L1 analysis type.	33
Figure 5-11: Single-carrier L1 analysis flow diagram.	34
Figure 5-12: Schematic network used for multipactor analysis.	36
Figure 5-13: Example of multicarrier signal and corresponding pulse approximation. ...	37
Figure 5-14: Electron absorption rate for zero applied voltage.....	38
Figure 5-15: L1 analysis for multicarrier, Pulsed model flow chart	39
Figure 5-16: 3D view of Ku-band transformer of ESA TRP activity [5-19]	40
Figure 5-17: Pulse amplitude and carrier amplitude vs t_{on}	41
Figure 5-18: Example with 3 different “on intervals” corresponding to 10%, 30% and 70% of the envelope period together with the theoretical limit (boundary) .	42
Figure 5-19: 3D of Ku band bandpass filter of ESA TRP activity [5-19].....	43
Figure 5-20: Hybrid L1/L2 multi-carrier analysis steps.	45
Figure 5-21: Electron growth over 10 envelope periods for 10 different “on intervals” for one amplitude factor.....	47
Figure 5-22: Convergence of the amplitude factor, showing also how Γ converges towards one electron	47
Figure 5-23: Hatch and William chart with the multicarrier in-phase amplitude indicated by a green circle. The red dashed line is the fd-product of the average multicarrier frequency and the critical gap size	48
Figure 5-24: KS3 sample geometry.	49
Figure 5-25: KS3 sample simulated RF performance	50
Figure 5-26: 3D view of L-band sample	51
Figure 5-27: Predicted S-parameter Performance of Preliminary L-band RF Device Design.....	52
Figure 5-28: Predicted Voltage Distribution in Preliminary L-band RF Device Design..	53

CEN/CLC/TR 17603-20-01:2021 (E)

Figure 5-29: Predicted S-parameter Performance of Finalised L-band RF Device (1525 MHz)53

Figure 5-30: Predicted Voltage Distribution in Finalised L-band RF Device (1525 MHz)54

Figure 5-31: Predicted S-parameter Performance of Finalised L-band RF Device (1405 MHz)54

Figure 5-32: Predicted Voltage Distribution in Finalised L-band RF Device (1405 MHz)55

Figure 5-33: Variation of peak voltage on each resonator with frequency – 30 MHz design bandwidth56

Figure 5-34: Variation of peak voltage on each resonator with frequency – 10 MHz design bandwidth56

Figure 5-35: Variation of peak voltage on central resonator with bandwidth change ($F_c = 1525$ MHz)57

Figure 5-36: RF performances with machining tolerances (Resonant reference sample S-3 and S-4).....58

Figure 5-37: Electric field (12,75 GHz – samples S-3 and S-4).....59

Figure 5-38: Voltage inside critical gap (samples S-3 and S-4).....59

Figure 5-39: Nominal model60

Figure 5-40: Re-tuned model.....61

Figure 5-41: Return Loss nominal (red) and tuned (pink).....61

Figure 6-1: Work in a clean room environment.64

Figure 6-2: Screenshot of clean room monitoring. The pressure reading corresponds to the overpressure delta in the clean room.....64

Figure 6-3: A pressure gauge.65

Figure 6-4: Picture of a typical pressure profile for a P1 component or equipment.65

Figure 6-5: Picture of a typical pressure profile for a P2/P3 component or equipment with pressure spikes related to outgassing.66

Figure 6-6: RF cable with thermocouples.66

Figure 6-7: RF cable with thermocouples.67

Figure 6-8: A multicarrier test facility.....68

Figure 6-9: Schematic of a three-carrier multipactor test bed.....68

Figure 6-10: Error probability distributions for different $f \cdot d$ 69

Figure 6-11: Error dependency on the similarity degree70

Figure 6-12: Margin definition with respect pulsed model and CW operation.....71

Figure 6-13: Typical pulse parameters during multipactor test.....73

Figure 6-14: Decay of Strontium-90.....75

Figure 6-15: Picture of an encapsulated radioactive source.75

Figure 6-16: Sketch of the photoelectric effect.....77

Figure 6-17: Picture of the UV lamp as part of a test bed.77

Figure 6-18: Spectrum of the typical lamps used for electron seeding.78

Figure 6-19: Diagram of an electron gun.	79
Figure 6-20: Sketch of the functioning of an electron gun.	79
Figure 6-21: Picture of an electron gun installed into a test bed.	80
Figure 7-1: Schematic of global detection systems implemented in a typical test bed.	84
Figure 7-2: Electron probe circuit diagram.	86
Figure 8-1: Multipactor test procedure overview.	89
Figure 8-2: Example of an L- and S-band reference sample.	90
Figure 8-3: Measured S-parameter performance of broadband multipactor sample.	91
Figure 8-4: Ku-band Broadband Multipactor Sample.	91
Figure 8-5: Multipactor threshold variation vs. gap height.	92
Figure 8-6: Ku-band reference sample dimensions.	92
Figure 8-7: Heat pipe.	94
Figure 9-1: Typical dependence of SEY coefficients on primary electron energy.	101
Figure 9-2: Energy distribution curve of emitted electron from gold target surface submitted to 112 eV electron irradiation [9-1]	101
Figure 9-3: Experimental arrangement for SEY test with emission collector	103
Figure 9-4: SEY experimental setup (without collector around the sample)	105
Figure 9-5: Typical composition of exposed to air metal surface.	107
Figure 9-6: Measured SEY of metals exposed to air without a specific surface cleaning procedure.	108
Figure 9-7: Schematic view of material exposed to atmosphere: the case of silver.	109
Figure 9-8: Effect of cleaning of the surface by heating on the SEY of Nb.	110
Figure 9-9: Effect of the water absorption on the SEY.	110
Figure 9-10: Effect of baking on the SEY of dielectrics.	111
Figure 9-11: Evolution of the SEY of the technical silver versus pressure.	112
Figure 9-12: Effect of the temperature on the SEY of silver. Figure extracted from [9- 18].	113
Figure 9-13: Effect of the temperature on the SEY of MgO and BN-SiO ₂ ceramics.	114
Figure 9-14: Effect of the temperature on the SEY of coverglass and CVD diamond.	115
Figure 9-15: Effect of the incidence angle variations on the SEY of silver	116
Figure 9-16: Effect of electron irradiation on SEY (CERN).	116
Figure 9-17: Influence of the primary electron energy on the charging process. TEEY = SEY, $E_{C1} = E1$ and $E_{C2}=E2$	117
Figure 9-18: Influence of the primary electron energy on the charging process, EEY = SEY, $E_{C1} = E1$ and $E_{C2}=E2$	118
Figure 9-19: SEY as a function of the primary electron energy for aluminium.	120
Figure 9-20: SEY as a function of the primary electron energy for copper	121
Figure 9-21: SEY as a function of the primary electron energy for gold	121
Figure 9-22: SEY as a function of the primary electron energy for silver coatings.	122

CEN/CLC/TR 17603-20-01:2021 (E)

Figure 9-23: Comparison of the SEY curves for Cu, Al, Ag and Au 122

Tables

Table 4-1: Multipactor simulations and multipactor measurements with and without thermal baking for a RF component with different dielectric materials 18

Table 5-1: Characteristics Ku-band transformer of ESA TRP activity [5-19]..... 40

Table 5-2: Characteristics Ku-band transformer of ESA TRP activity [5-19]..... 43

Table 5-3: Multicarrier signal characteristics..... 43

Table 5-4: Predicted and testes multipactor breakdown levels 44

Table 5-5: SEY characteristics of KS3 sample 50

Table 5-6: Multipactor thresholds for KS3 sample 51

Table 5-7: SEY data for L-band sample..... 57

Table 5-8: Multipactor thresholds for L-band sample 57

Table 5-9: Multipactor threshold vs. manufacturing errors (samples S-3 and S-4)..... 60

Table 6-1: Error statistics in dB for silver and aluminium, and different values of carriers, frequency band and fxd product 69

Table 6-2: Rate and energy of injected electrons going through a particular aluminium wall [6-4]..... 76

Table 8-1: Example of Multipactor Test Specification Sheet 88

Table 8-2: Maximum RF power applied to the load range (margin in bold). 95

Table 8-3: Multipactor test report summary 97

Table 8-4: Test setup validation without sample 98

Table 8-5: Test setup validation with reference sample 98

Table 8-6: Test of DUT at reduced power level at ambient pressure just before closing the vacuum chamber (RECOMMENDED 99

Table 9-1: Average values of the main SEY parameters for all “as built” (mentioned, “Before RF testing” in the below table) and all the “as tested” SEY samples (mentioned, “After RF testing” in the below table) for a given SEY measurement facility 109

Table 9-2: Requirement in the experimental conditions for SEY measurement 119

Table 9-3: SEY parameters of the SEY curves of Al, Cu, Au and Ag samples..... 120

Table 9-4: SEY curve data for aluminium 123

Table 9-5: SEY curve data for copper..... 127

Table 9-6: SEY curve data for gold..... 131

Table 9-7: SEY curve data for silver 135

European Foreword

This document (CEN/CLC/TR 17603-20-01:2021) has been prepared by Technical Committee CEN/CLC/JTC 5 “Space”, the secretariat of which is held by DIN.

It is highlighted that this technical report does not contain any requirement but only collection of data or descriptions and guidelines about how to organize and perform the work in support of EN 16603-20-01:2020.

This Technical report (CEN/CLC/TR 17603-20-01:2021) originates from ECSS-E-HB-20-01A.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

This document has been developed to cover specifically space systems and has therefore precedence over any TR covering the same scope but with a wider domain of applicability (e.g.: aerospace).

Introduction

Multipactor is a well-understood RF breakdown mechanism in high vacuum conditions. It has been investigated both theoretically and experimentally over many years, as listed in references from [2-1] to [2-7]. Essential ingredient for multipactor is initial free electrons, also called primary electrons. Free electrons can be accelerated under the action of the high power electromagnetic signals inside the RF component. These accelerated electrons impact the RF internal surface with such a kinetic energy to knock out secondary electrons. This resonant process repeats until an avalanche-like growth of electrons is reached, and a multipactor discharge occurs. A multipactor discharge produces signal noise, power reflection and ultimately a local ionization that leads to a complete short circuit. In the worst case, this can develop to a complete system failure.

A typical multipactor event can be described as follows:

1. Free electrons exist within the RF field region of a component whose dimensions are small compared with the electron mean free path as a result of low pressure within the component.
2. The electric field within the component accelerates the free electrons towards a surface.
3. The electrons impact on the surface with appropriate energies to liberate more secondary electrons than the incident ones.
4. Under the specific condition of synchronism of the RF electric field and the electron impact time, resonance conditions are met and steps b. and c. repeat until multipactor discharge occurrence.

Beside the multipactor discharge, other electrical breakdown of different nature in RF components such as multipactor leading to corona due to local outgassing and discharge occurrence in intermediate pressure range can also arise [2-8], [2-9] and [2-10].

NOTE The Multipactor Handbook follows the same structure as the Standard. Where the WG has decided that the content of a clause of the Standard needs no supporting material this clause is left empty. The text "*No supporting material needed.*" is added there.

1 Scope

This Handbook describes the guidelines and recommendations for the design and test of RF components and equipment to achieve acceptable performance with respect to multipactor-free operation in service in space. This document is the mirror document of the ECSS-ST-20-01 normative document. Thus it includes the same contents as the normative text and has the same structure.

This Handbook is intended to result in the effective design and verification of the multipactor performance of the equipment and consequently in a high confidence in achieving successful product operation.

This Handbook covers multipactor events occurring in all classes of RF satellite components and equipment at all frequency bands of interest. Operation in single carrier CW and pulse modulated mode are included, as well as multi-carrier operations. A detailed chapter on secondary emission yield is also included.

This Handbook does not include breakdown processes caused by collisional processes, such as plasma formation.

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-