



NSAI
Standards

Irish Standard
I.S. EN 50059:2018

Electrostatic hand-held spraying equipment - Safety requirements - Hand-held spraying equipment for non-ignitable coating materials

I.S. EN 50059:2018

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard — national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation — recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces/revises/consolidates the NSAI adoption of the document(s) indicated on the CEN/CENELEC cover/Foreword and the following National document(s):

NOTE: The date of any NSAI previous adoption may not match the date of its original CEN/CENELEC document.

This document is based on:

EN 50059:2018

Published:

2018-07-27

*This document was published
under the authority of the NSAI
and comes into effect on:*

2018-08-14

ICS number:

87.100

NOTE: If blank see CEN/CENELEC cover page

NSAI
1 Swift Square,
Northwood, Santry
Dublin 9

T +353 1 807 3800
F +353 1 807 3838
E standards@nsai.ie
W NSAI.ie

Sales:
T +353 1 857 6730
F +353 1 857 6729
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

National Foreword

I.S. EN 50059:2018 is the adopted Irish version of the European Document EN 50059:2018, Electrostatic hand-held spraying equipment - Safety requirements - Hand-held spraying equipment for non-ignitable coating materials

This document does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

For relationships with other publications refer to the NSAI web store.

Compliance with this document does not of itself confer immunity from legal obligations.

In line with international standards practice the decimal point is shown as a comma (,) throughout this document.

This page is intentionally left blank

EUROPEAN STANDARD

EN 50059

NORME EUROPÉENNE

EUROPÄISCHE NORM

July 2018

ICS 87.100

Supersedes EN 50059:1990

English Version

Electrostatic hand-held spraying equipment - Safety requirements - Hand-held spraying equipment for non-ignitable coating materials

Équipement manuel de projection électrostatique -
Exigences de sécurité - Équipement manuel de projection
de revêtement ininflammable

Elektrostatische Handsprüheinrichtungen -
Sicherheitsanforderungen - Handsprüheinrichtungen für
nichtentzündbare Beschichtungsstoffe

This European Standard was approved by CENELEC on 2018-01-02. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels

Contents	Page
European foreword	4
0 Introduction.....	6
1 Scope	8
2 Normative references	8
3 Terms, definitions and symbols	9
3.1 Terms and definitions	9
3.2 Symbols	11
4 Requirements for hand-held spraying equipment for non-ignitable liquid coating materials	12
4.1 General requirements	12
4.2 Requirements for the accessories	14
5 Tests	15
5.1 General	15
5.2 General tests	15
5.2.1 Test of earth connections	15
5.2.2 Resistance test.....	15
5.2.3 Test of contact surface area	15
5.2.4 Test of OFF-position.....	15
5.3 Conditioning test.....	15
5.3.1 Cable pull test and hose pull test.....	15
5.3.2 Impact test	15
5.3.3 Drop test	16
5.4 Tests for electrical safety	16
5.4.1 Measurement of the parameters high voltage and short-circuit current	16
5.4.2 Voltage test.....	16
5.4.3 Test of the degree of protection of applicators	16
5.5 Test of the peak current values of discharges $I_C(p)$ with their associated pulse durations t_i	16
5.6 Tests of the accessories	17
5.6.1 Test of the degree of protection	17
5.6.2 Test of the coating material supply system	17
6 Information for use	17
6.1 General	17
6.2 Instruction manual.....	17
6.2.1 General.....	17
6.2.2 Cleaning, maintenance and repair	18
6.2.3 Test intervals of repeated tests	18
6.2.4 Additional information	18
6.3 Marking of electrostatic hand-held spraying equipment and associated control devices	19

6.3.1	Marking of applicators	19
6.3.2	Marking of the associated control devices	19
6.3.3	Reduced marking	20
Annex A	(normative) Test of a discharge with the peak current value $I_C(p)$ and the pulse duration t_i (type test)	21
Annex B	(informative) Example for discharge test	24
Annex C	(informative) Ignitability of water-based paints	26
Annex D	(informative) Quality assurance systems for electrostatic spraying equipment	28
Annex ZZ	(informative) Relationship between this European standard and the essential requirements of Directive 2006/42/EC aimed to be covered	30
Bibliography	31

Tables

Table 1 — Test intervals	18
Table ZZ.1 — Correspondence between this European Standard and Annex I of Directive 2006/42/EC	30

Figures

Figure 1 — Pulse duration - body current, ventricular fibrillation risk	12
Figure A.1 — Equivalent circuit diagram	22
Figure A.2 — Schematic discharge curve	23
Figure B.1 — Discharge plot	24

EN 50059:2018 (E)**European foreword**

This document (EN 50059:2018) has been prepared by Technical Committee CEN-CENELEC/TC 204 "Safety of electrostatic painting and finishing equipment".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2019-01-27
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2021-07-27

This document supersedes EN 50059:1990.

EN 50059:2018 includes the following significant technical changes with respect to EN 50059:1990:

- modification of the title of the standard;
- extension of introduction;
- extension of normative references;
- extension of terms and definitions;
- new arrangement, amendment and complement of the requirements for hand-held spraying equipment for non-ignitable liquid coating materials;
- definition of requirements for safety functions;
- new arrangement, amendment and complement of tests for hand-held spraying equipment for non-ignitable liquid coating materials;
- new arrangement and extension of the information for use;
- definition of requirements for repeated tests;
- introduction of the normative Annex A "Test of a discharge with the peak current value $I_{C(p)}$ and the pulse duration t_i (type test)";
- introduction of the informative Annex B "Example for discharge test";
- introduction of the informative Annex C "Ignitability of water-based paints";
- introduction of the informative Annex D "Quality assurance systems for electrostatic spraying equipment";
- introduction of the informative Annex ZZ "Relationship between this European standard and the essential requirements of Directive 2006/42/EC aimed to be covered".

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For the relationship with EU Directive(s) see informative Annex ZZ, which is an integral part of this document.

EN 50059:2018 (E)**0 Introduction****0.1 Process**

During the electrostatic coating process the non-ignitable liquid coating material is transported from a reservoir to an applicator where it is atomised by mechanical forces and by the influence of an electric field. The coating material is charged by high voltage of some 10 kV and a spray cloud is generated. The charged droplets of the coating materials are attracted by and applied to the earthed workpiece.

Droplets of the coating material, which are not applied to the workpiece (overspray) are removed by a suction device or by other means.

After the coating process the coated workpieces are introduced into a dryer or oven where a dry film of coating material is generated.

0.2 Fire hazards

0.2.1 Fire hazards can be caused by deposits of coating materials inside the spray booth, exhaust air ducts, the recovery system for coating materials, and filters. During operation, malfunctions or electrical faults may cause ignition of these residues. The propagation of the fire leads to hazards also in adjacent areas.

0.2.2 Particular attention should be paid to the prevention of electrostatic charges on different surfaces, which are in the vicinity of the spray cloud. This could apply both to workpieces during the coating process or the reciprocating devices and the mounting parts of the spraying system, etc.

0.2.3 When spraying non-ignitable coating material, the formation of an explosive atmosphere is not likely to occur. Electrostatic application equipment for ignitable coating materials are covered by EN 50050-1, EN 50050-2 and EN 50050-3.

0.3 Electric hazards

0.3.1 Electric shock (by direct or indirect contact) can be generated, for instance, by contact with

- live parts, which are not insulated for operational reasons,
- conductive parts, which are not connected to dangerous voltage during normal operation, but only in case of failure,
- insulated live parts with insufficient or damaged insulation due to external impact,
- charged passive parts with inadequate earthing.

0.3.2 Inadequate earthing may occur, for instance, due to

- faulty connections to the protective earthing system,
- a too high resistance to earth (e.g. contamination by coating materials).

0.3.3 Hazards could occur, for instance, if hazardous malfunctions (e.g. shortcut of electronic safety circuits) occur due to interferences of the electrostatic high voltage equipment and the components of the control and safety systems.

0.3.4 Hazardous electrostatic discharges could be generated, for instance, by non-earthed conductive components or by large insulating surfaces, especially if they are backed with conductive material.

0.3.5 Ventricular fibrillation is the primary risk of electric shock. The undercut of the current/time limit and the fibrillation limit are proven by current and time measurement. In this standard, $I(t)$ is used as a measure for falling below the current/time limit and the fibrillation limit. It is comparable to the amount of current $I t$ or the specific fibrillation energy $I^2 t$ in accordance with IEC/TS 60479-1 and IEC TS 60479-2. A power limit as given in the standards EN 50176, EN 50177, EN 50223 and EN 50348 is not applicable in this standard due to the characteristics of the equipment and the resulting hazard of electric current.

EN 50059:2018 (E)**1 Scope**

1.1 This European Standard specifies the requirements for hand-held or hand-operated electrostatic spraying equipment for non-ignitable liquid coating materials which

- do not generate an explosive atmosphere inside the spraying area;
- are used to process materials with a conductivity of less than 2 000 $\mu\text{S}/\text{cm}$;
- operate with direct current having a sinusoidal ripple of not more than 10 % of the rms value.

This European Standard deals with all electrical hazards significant for the electrostatic spraying of non-ignitable liquid coating materials, which could also contain small quantities of added metal particles, if the work is carried out under conditions recommended by the manufacturer.

This European Standard specifies the design-related and test requirements for electrostatic spraying equipment of type A-NL according to Table 1 of EN 50348:2010.

1.2 With regard to all other significant hazards relevant for applicators (e.g. ejection of fluids, mechanical strength, electrical - apart from electrostatic - hazards, noise, contact with or inhalation of dangerous substances, ergonomics) the requirements of EN 1953 apply.

1.3 This European Standard also gives details regarding quality assurance systems for electrostatic spraying equipment, see Annex D.

1.4 For electrostatic spraying equipment used in food and pharmaceutical industry, additional requirements may apply.

1.5 This document is not applicable to

- electrostatic hand-held spraying equipment for non-ignitable coating materials which are manufactured before the date of its publication as EN,
- cleaning of spraying areas, see instruction manual of the spraying booth,
- fire prevention and protection [for instance fire hazards due to other sources; see EN 12215, EN 12981],
- requirements for machinery for the supply and recirculation of coating material under pressure [see EN 12621].

The requirements of EN 12621 apply for specific requirements for machinery for the supply and recirculation of coating materials under pressure.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1149-5, *Protective clothing - Electrostatic properties - Part 5: Material performance and design requirements*

EN 1953, *Atomising and spraying equipment for coating materials - Safety requirements*

EN 12215, *Coating plants - Spray booths for application of organic liquid coating materials - Safety requirements*

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- Looking for additional Standards? Visit Intertek Inform Infostore
 - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-