



National Standards Authority of Ireland

STANDARD

I.S. EN 12489:2000

ICS 91.060.50

National Standards
Authority of Ireland
Dublin 9
Ireland

Tel: (01) 807 3800
Fax: (01) 807 3838

**INDUSTRIAL, COMMERCIAL AND GARAGE
DOORS AND GATES - RESISTANCE TO
WATER PENETRATION - TEST METHOD**

*This Irish Standard was
published under the
authority of the National
Standards Authority of
Ireland
and comes into effect on:
November 2, 2000*

**NO COPYING WITHOUT NSAI
PERMISSION EXCEPT AS
PERMITTED BY COPYRIGHT
LAW**

© NSAI 2000

Price Code F

Údarás um Chaighdeán Náisiúnta na hÉireann

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 12489

July 2000

ICS 91.060.50

English version

**Industrial, commercial and garage doors and gates - Resistance
to water penetration - Test method**

Portes équipant les locaux industriels, commerciaux et les
garages - Résistance à la pénétration de l'eau - Méthode
d'essai

Tore - Widerstand gegen eindringendes Wasser -
Prüfverfahren

This European Standard was approved by CEN on 19 July 2000.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

Contents

	Page
Foreword	2
1 Scope	3
2 Normative References	3
3 Terms and definitions	4
4 Principle of test	4
5 Apparatus	4
6 Preparation of test specimen	5
7 Test procedure	8
8 Failure criteria	9
9 Test report	9
Annex A (normative) Air pressure sequence for test rig	11
Annex B (informative) Test report for water resistance according to EN 12 489:2000	12

Foreword

This European Standard has been prepared by Technical Committee CEN/TC 33 " Doors, windows, shutters, building hardware and curtain walling", the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2001, and conflicting national standards shall be withdrawn at the latest by January 2001.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

No existing EN standard is superseded.

This standard is one of a series of performance standards identified within the product standard prEN 13 421:1998.

European Standards as well as relevant national regulations and standards will enable the actual exposure levels to be determined for the individual locations of the products.

Annex A is normative. Annex B is informative.

1 Scope

1.1 General

This European Standard specifies the test method for determining the resistance to water penetration for doors in a closed position.

The doors are intended for installation in areas in the reach of people, for which the main intended uses are giving safe access for goods, vehicles and persons in industrial, commercial or residential premises.

The doors may be manually or power operated.

This document applies to all doors provided in accordance with prEN 13 241:1998.

1.2 Exclusions

It does not apply to:

- lock gates and dock gates;
- doors on lifts;
- doors on vehicles;
- armoured doors;
- doors mainly for the retention of animals;
- theatre textile curtains;
- horizontally moving doors less than 2,5 m wide and 6,25 m² area, designed principally for pedestrian use;
- revolving doors of any size;
- doors outside the reach of people (such as crane gantry fences);
- railway barriers;
- barriers used solely for vehicles.

2 Normative References

This European Standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

EN 12 433-1	Industrial, commercial and garage doors and gates - Terminology - Part 1: Types of doors
EN 12 433-2	Industrial, commercial and garage doors and gates - Terminology - Part 2: Parts of doors
EN 12 425	Industrial, commercial and garage doors and gates - Resistance to water penetration - Classification
prEN 13 241:1998	Industrial, commercial and garage doors and gates - Product standard

3 Terms and definitions

For the purpose of this standard the terms and definitions in EN 12 433-1 and EN 12 433-2 apply. In addition the following definitions also apply:

- 3.1** Resistance to water penetration: ability of the test specimen, when in closed position, to resist water penetration under specified test conditions.
- 3.2** Water penetration: continuous or repeated wetting of the internal surface of the test specimen or parts which are not designed to be wetted.

4 Principle of test

Constant spraying of a specified quantity of water onto the external surface of the test specimen while increments of positive test pressure are applied at regular intervals. Details shall be recorded for test pressure and location of water penetration.

5 Apparatus

The basic test apparatus shall include:

- a) an opening to which the test specimen can be fitted, to simulate the structure of the product on site.
- b) device(s) to provide controlled air pressure, above atmospheric air pressure, to the exposed surface of the specimen, enabling rapid changes of air pressure, controlled between defined limits.
- c) device(s) to measure the amount of supplied water to an accuracy of $\pm 10\%$. If several rows of nozzles with different flows are set up, at least two are necessary.
- d) device(s) for measuring air pressure with an accuracy of $\pm 5\%$.
- e) a spraying system capable of applying a continuous regularly dispersed film of water all over the surface likely to be wetted in real exposure conditions by means of full circular nozzles according to figure 1 and with the following features:
 - angle of spray: $120^\circ + 0^\circ$
 -10°
 - air pressure working range: 2 bar to 3 bar according to manufacturers specifications
 - nozzle rate: top row $2 \pm 0,2$ l / min / nozzle
additional rows $1 \pm 0,1$ l / min / nozzle

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- Looking for additional Standards? Visit Intertek Inform Infostore
 - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-