



National Standards Authority of Ireland
Údarás um Chaighdeáin Náisiúnta na hÉireann

IRISH STANDARD

I.S. 258 : Parts 1 & 2 : 1984

ICS 97.040.20

**DOMESTIC SOLID FUEL COOKERS WITH
INTEGRAL BOILERS. PART 1: SAFETY
REQUIREMENTS, PART 2: GENERAL
REQUIREMENTS**

National Standards
Authority of Ireland
Glasnevin, Dublin 9
Ireland

Tel: +353 1 807 3800
Fax: +353 1 807 3838
<http://www.nsai.ie>

Sales
<http://www.standards.ie>

*This Irish Standard was
published under the authority
of the National Standards
Authority of Ireland and
comes into effect on:
November 2, 1984*

**NO COPYING WITHOUT NSAI
PERMISSION EXCEPT AS
PERMITTED BY COPYRIGHT
LAW**

© NSAI 1984

Price Code O

Údarás um Chaighdeáin Náisiúnta na hÉireann

This page is intentionally left BLANK.



National Standards Authority of Ireland
Údarás um Chaighdeán Náisiúnta na hÉireann

AMENDMENT

I.S. 258 : Parts 1 & 2 :1984:Amd 1:1986

ICS 97.040.20

**DOMESTIC SOLID FUEL COOKERS WITH
INTEGRAL BOILERS. PART 1: SAFETY
REQUIREMENTS, PART 2: GENERAL
REQUIREMENTS**

National Standards
Authority of Ireland
Glasnevin, Dublin 9
Ireland

Tel: +353 1 807 3800
Fax: +353 1 807 3838
<http://www.nsai.ie>

Sales
<http://www.standards.ie>

*This Amendment was
published under the authority
of the National Standards
Authority of Ireland and
comes into effect on:
July 29, 1986*

**NO COPYING WITHOUT NSAI
PERMISSION EXCEPT AS
PERMITTED BY COPYRIGHT
LAW**

© NSAI 1986

Price Code D

Údarás um Chaighdeán Náisiúnta na hÉireann

This page is intentionally left BLANK.

1,

AMENDMENT

No. 1 : 1986

OF

STANDARD SPECIFICATION (DOMESTIC SOLID FUEL COOKERS WITH INTEGRAL BOILERS,

PART 1 SAFETY REQUIREMENTS,

PART 2 GENERAL REQUIREMENTS) DECLARATION 1984

IRISH STANDARD 258 : Parts 1 and 2 : 1984

The Institute for Industrial Research and Standards in exercise of the power conferred by Section 20 (5) of the Industrial Research and Standards Act, 1961 (No. 20 of 1961), and with the consent of the Minister for Industry and Commerce, hereby declares as follows:

1. This instrument may be cited as the Standard Specification (Domestic Solid Fuel Cookers with Integral Boilers, Part 1 Safety Requirements, Part 2 General Requirements) Declaration 1984 (Amendment) No. 1 : 1986.

2. Irish Standard 258 : Parts 1 and 2 : 1984 set out in the Schedule to the Standard Specification (Domestic Solid Fuel Cookers with Integral Boilers, Part 1 Safety Requirements, Part 2 General Requirements) Declaration, 1984 is hereby amended as indicated in the Schedule hereto.

SCHEDULE

Page 5, 2.3.1.

Delete this subclause and substitute the following:

"2.3.1 Cooker flueways: Flueways shall be constructed of grey cast iron of minimum grade 150 to British Standard 1452* and not less than 3 mm thick or alternatively low carbon steel not less than 4 mm thick. Flueways may alternatively be constructed of 2 mm thick steel with enamelled surfaces which shall be capable of complying with the requirements specified in Parts 1,3,4 and 7 of B.S. 1344. Cookers fitted with enamel steel flueways shall be marked, in the information specified in 2.4 of Part 2 of this specification:-

"Fuel with dry seasoned** or smokeless fuels only".

* See Appendix D, Reference Standards.

** (Note: The likely moisture contents of peat and wood are indicated in Note 7 of "Notes to Users" of this specification)"

2.

Page 6, 2.3.3.

Delete the fourth line and substitute the following:

"... requirements of Table 1 except (1) the working surfaces, which include the cooker top plate and (2) any ..."

Page 8, 1.2.3.12

Delete the title of this subclause and substitute the following:

"Top plate (hob)".

Page 8, 1.2.3.13

Delete the following words on the second line: "...generally at the top..."

Page 9, 1.2.4.4

Delete the title of this subclause and substitute the following:

"Accidental over-heating test".

Page 14, 2.1.9.1

Delete the first paragraph of this subclause and substitute the following:

"Combustion air control shall be provided and the combustion air shall be controlled either manually or by water-activated thermostat. A water-activated thermostat shall be fitted if any integral boiler is rated above 7.5 kW output."

Page 15, 2.2.1

Delete the first sentence of the first paragraph and substitute the following:

"Both the roasting oven and the oven door opening shall be not less than 380 mm wide and 310 mm high."

Delete the first sentence of the second last paragraph and substitute the following:

"All side hinged doors shall open to an angle of at least 115°."

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- Looking for additional Standards? Visit Intertek Inform Infostore
 - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-