



National Standards Authority of Ireland

IRISH STANDARD

I.S. EN 2859:2006

ICS 49.030.20

**AEROSPACE SERIES - BOLTS, NORMAL
HEXAGONAL HEAD, CLOSE TOLERANCE
NORMAL SHANK, SHORT THREAD, IN ALLOY
STEEL, CADMIUM PLATED, METRIC SERIES -
CLASSIFICATION: 1 100 MPA (AT AMBIENT
TEMPERATURE) / 235 °C**

National Standards
Authority of Ireland
Glasnevin, Dublin 9
Ireland

Tel: +353 1 807 3800
Fax: +353 1 807 3838
<http://www.nsai.ie>

Sales
<http://www.standards.ie>

*This Irish Standard was
published under the
authority of the National
Standards Authority of
Ireland and comes into
effect on:
15 September 2006*

**NO COPYING WITHOUT NSAI
PERMISSION EXCEPT AS
PERMITTED BY COPYRIGHT
LAW**

© NSAI 2006

Price Code E

Údarás um Chaighdeán Náisiúnta na hÉireann

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 2859

July 2006

ICS 49.030.20

Supersedes EN 2859:1995

English Version

Aerospace series - Bolts, normal hexagonal head, close tolerance normal shank, short thread, in alloy steel, cadmium plated, metric series - Classification: 1 100 MPa (at ambient temperature) / 235 °C

Série aérospatiale - Vis à tête hexagonale normale, fût normal à tolérance serrée, filetage court, en acier allié, cadmiées - Classification : 1 100 MPa (à température ambiante) / 235 °C

Luft- und Raumfahrt - Sechskant-Paßschrauben, kurzes Gewinde, aus legiertem Stahl, verkadmet - Klasse: 1 100 MPa (bei Raumtemperatur) / 235 °C

This European Standard was approved by CEN on 13 January 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Page

Foreword	3
1 Scope	4
2 Normative references	4
3 Required characteristics	5
4 Designation	9
5 Marking	9
6 Technical specification	10
7 Oversized bolts	10

Foreword

This European Standard (EN 2859:2006) has been prepared by the European Association of Aerospace Manufacturers - Standardization (AECMA-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of AECMA, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2007, and conflicting national standards shall be withdrawn at the latest by January 2007.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 2859:1995.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

EN 2859:2006 (E)

1 Scope

This standard specifies the characteristics of bolts, normal hexagonal head, close tolerance normal shank, short thread, in alloy steel, cadmium plated, metric series.

Classification: 1 100 MPa ¹⁾ / 235 °C ²⁾.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3193, *Aerospace – Bolts, normal hexagonal head, normal shank, short or medium length MJ threads, metallic material, coated or uncoated, strength classes less than or equal to 1 100 MPa – Dimensions.*

ISO 3353-1, *Aerospace – Lead and runout threads – Part 1: Rolled external threads.*

ISO 5855-2, *Aerospace – MJ threads – Part 2: Limit dimensions for bolts and nuts.*

ISO 7689, *Aerospace – Alloy steel bolts with strength classification 1 100 MPa and MJ threads – Procurement specification.*

ISO 7913, *Aerospace – Bolts and screws, metric – Tolerances of form and position.*

EN 2133, *Aerospace series – Cadmium plating of steels with specified tensile strength $\leq 1\,450$ MPa, copper, copper alloys and nickel alloys.*

EN 2424, *Aerospace series – Marking of aerospace products.*

EN 4016, *Aerospace series – Oversized bolts.* ³⁾

EN 9100, *Aerospace series – Quality management systems – Requirements (based on ISO 9001:2000) and Quality systems – Model for quality assurance in design, development, production, installation and servicing (based on ISO 9001:1994).*

EN 9133, *Aerospace series – Quality management systems – Qualification Procedure for aerospace standard parts.*

TR 3775, *Aerospace series – Bolts and pins – Materials.* ⁴⁾

1) Minimum tensile strength of the material at ambient temperature.

2) Maximum temperature that the bolt can withstand without continuous change in its original characteristics, after return to ambient temperature. The maximum temperature is determined by the surface treatment.

3) Published as ASD Prestandard at the date of publication of this standard.

4) Published as ASD Technical Report at the date of publication of this standard.

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- Looking for additional Standards? Visit Intertek Inform Infostore
 - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-