



National Standards Authority of Ireland

IRISH STANDARD

I.S. EN 563:1994

ICS 13.110

**SAFETY OF MACHINERY – TEMPERATURES  
OF TOUCHABLE SURFACES –  
ERGONOMICS DATA TO ESTABLISH  
TEMPERATURE LIMIT VALUES FOR  
HOT SURFACES**

National Standards  
Authority of Ireland  
Dublin 9  
Ireland

Tel: (01) 807 3800  
Tel: (01) 807 3838

*This Irish Standard was  
published under the  
authority of the National  
Standards Authority of  
Ireland  
and comes into effect on:  
January 27, 1995*

**NO COPYING WITHOUT NSAI  
PERMISSION EXCEPT AS  
PERMITTED BY COPYRIGHT  
LAW**

© NSAI 1994

**Price Code J**

Údarás um Chaighdeán Náisiúnta na hÉireann





National Standards Authority of Ireland

IRISH STANDARD

I.S. EN 563/A1:1999

ICS 13.110

**SAFETY OF MACHINERY - TEMPERATURES  
OF TOUCHABLE SURFACES -  
ERGONOMICS DATA TO ESTABLISH  
TEMPERATURE LIMIT VALUES FOR  
HOT SURFACES**

National Standards  
Authority of Ireland  
Dublin 9  
Ireland

Tel: (01) 807 3800

Tel: (01) 807 3838

*This Irish Standard was  
published under the  
authority of the National  
Standards Authority of  
Ireland  
and comes into effect on:  
November 19, 1999*

**NO COPYING WITHOUT NSAI  
PERMISSION EXCEPT AS  
PERMITTED BY COPYRIGHT  
LAW**

© NSAI 1999

**Price Code E**

Údarás um Chaighdeáin Náisiúnta na hÉireann



EUROPEAN STANDARD

**EN 563:1994/A1:1999/AC**

NORME EUROPÉENNE

April 2000

EUROPÄISCHE NORM

Avril 2000

April 2000

---

English version  
Version Française  
Deutsche Fassung

Safety of machinery - Temperatures of touchable surfaces - Ergonomics  
data to establish temperature limit values for hot surfaces

Sécurité des machines - Températures des  
surfaces tangibles - Données  
ergonomiques pour la fixation de  
températures limites des surfaces chaudes

Sicherheit von Maschinen - Temperaturen  
berührbarer Oberflächen - Ergonomische  
Daten zur Festlegung von  
Temperaturgrenzwerten für heiße  
Oberflächen

This corrigendum becomes effective on 19 April 2000 for incorporation in the three official language versions of the EN.

Ce corrigendum prendra effet le 19 avril 2000 pour incorporation dans les trois versions linguistiques officielles de l'EN.

Die Berichtigung tritt am 19. April 2000 zur Einarbeitung in die drei offiziellen Sprachfassungen der EN in Kraft.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

Central Secretariat: rue de Stassart, 36 B-1050 Brussels

---

© 2000 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.  
Tous droits d'exploitation sous quelque forme et de quelque manière que ce soit réservés dans le monde entier aux membres nationaux du CEN.  
Alle Rechte der Verwertung, gleich in welcher Form und in welchem Verfahren, sind weltweit den nationalen Mitgliedern von CEN vorbehalten.

Ref. No. EN 563:1994/AC:2000 D/E/F

**4.2.1 Burn thresholds for a contact period below 1 s**

*1. Replace the content of 4.2.1 by:*

“For very short contacts burn threshold values are listed for a contact period of 0,5 s in tables 1 and 2.

Table 1 contains burn threshold spreads for different materials for a contact period of 0,5 s. The specified spreads are extensions of the shaded areas of figures 2, 4, 5 and 6.

**Table 1: Burn threshold spreads for a contact period of 0,5 s**

Material	Extension of figure No	Burn threshold spread for a contact period of 0,5 s [ °C ]
Bare (uncoated) metal	2	67 to 73
Ceramics, glass and stone	4	84 to 90
Plastics	5	91 to 99
Wood	6	128 to 155

Table 2 contains the rise of the burn threshold spread for coated metals for a contact period of 0,5 s. The specified values are extensions of the lines in figures 3 a) and 3 b). Absolute values for the burn threshold spreads for coated metals can be obtained by adding the values of table 2 to the burn threshold spread specified in table 1 for bare metal.”

**Table 2: Rise of burn threshold spread for coated metals for a contact period of 0,5 s**

Metals with a coating of	Extension of figure No	Rise of burn threshold spread for a contact period of 0,5 s [ °C ]
50 µm lac	3 a)	13
100 µm lac	3 a)	22
150 µm lac	3 a)	31
400 µm Rilsan	3 b)	34
90 µm powder	3 b)	11
60 µm powder, 160 µm porcelain enamel	3 b)	6

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

- 
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
  - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-