



National Standards Authority of Ireland

IRISH STANDARD

I.S. EN 12332-2:2002

ICS 59.080.40

National Standards
Authority of Ireland
Dublin 9
Ireland

Tel: (01) 807 3800
Tel: (01) 807 3838

**RUBBER- OR PLASTIC-COATED FABRICS -
DETERMINATION OF BURSTING STRENGTH -
PART 2: HYDRAULIC METHOD**

*This Irish Standard was
published under the
authority of the National
Standards Authority of
Ireland
and comes into effect on:
January 17, 2003*

**NO COPYING WITHOUT NSAI
PERMISSION EXCEPT AS
PERMITTED BY COPYRIGHT
LAW**

© NSAI 2002

Price Code E

Údarás um Chaighdeán Náisiúnta na hÉireann

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 12332-2

November 2002

ICS 59.080.40

English version

**Rubber- or plastic-coated fabrics - Determination of bursting
strength - Part 2: Hydraulic method**

Supports textiles revêtus de caoutchouc ou de plastique -
Détermination de la résistance à l'éclatement - Partie 2:
Méthode hydraulique

Mit Kautschuk oder Kunststoff beschichtete Textilien -
Bestimmung der Berstfestigkeit - Teil 2: Hydraulisches
Verfahren

This European Standard was approved by CEN on 3 August 2002.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

EN 12332-2:2002 (E)

Contents

	page
Foreword	3
1 Scope.....	4
2 Normative references.....	4
3 Principle	4
4 Apparatus and materials	4
5 Test specimens	5
6 Conditioning	5
7 Procedure.....	6
8 Test report.....	6
Bibliography	8

Foreword

This document (EN 12332-2:2002) has been prepared by Technical Committee CEN /TC 248, "Textiles and textiles products", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by May 2003, and conflicting national standards shall be withdrawn at the latest by May 2003.

EN 12332 "*Rubber- or plastic-coated fabrics – Determination of bursting strength*" consists of two Parts:

- *Part 1: Steel ball method.*
- *Part 2: Hydraulic method.*

NOTE Persons using this standard should be familiar with normal laboratory practice. This standard does not purport to address all of the safety problems, if any, associated with its use. It is the responsibility of the user to establish appropriate safety and health practices and to ensure compliance with any national regulatory conditions.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

EN 12332-2:2002 (E)

1 Scope

This Part of this European Standard specifies a method for determining the bursting strength of coated fabrics using a forcing fluid and a diaphragm machine.

2 Normative references

This European standard incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies (including amendments).

EN ISO 2231, *Rubber- or plastics - coated fabrics — Standard atmospheres for conditioning and testing (ISO 2231: 1989)*

EN ISO 2286-1, *Rubber- or plastics-coated fabrics — Determination of roll characteristics — Part 1: Methods for determination of length, width and net mass (ISO 2286-1:1998)*

3 Principle

A circular test specimen and an underlying elastic diaphragm are clamped around their edges over the top of a chamber. The specimen is gradually stretched into a dome shape by forcing fluid into the chamber at a constant rate. The pressure of the fluid at failure of the specimen and the distension, measured in terms of the height of the dome are recorded.

4 Apparatus and materials

A diaphragm machine¹⁾ with:

4.1 A rigid chamber filled with fluid and having a circular aperture of diameter equal to, or up to 0,5 mm greater than the diameter of the circular free area.

4.1.1 A circular elastic diaphragm mounted over the aperture in the chamber. The diaphragm and its seal with the chamber shall be able to withstand pressures greater than the burst strength of the material being assessed. The modulus of elasticity of the diaphragm shall be as low as possible, a value of 5 % of the modulus of the test specimen is recommended.

4.1.2 A means of clamping the test specimen around its edge, above the diaphragm and over the aperture in the chamber, leaving a central circular free area of diameter (113 ± 1) mm or preferably $(35,7 \pm 0,5)$ mm.

The design of the clamping system shall ensure that the test specimen does not slip during the test and shall neither stretch nor compress the central area of the specimen as it is clamped.

The following has been found to be suitable; six concentric grooves 2,5 mm apart and 1,25 mm deep, cut into the lower clamping surface so that the ridges between the grooves have 0,5 mm radius tops.

1) Often called "Mullen type machine".

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- Looking for additional Standards? Visit Intertek Inform Infostore
 - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-