



National Standards Authority of Ireland

STANDARD

I.S. EN 14430:2004

ICS 25.220.50

National Standards
Authority of Ireland
Dublin 9
Ireland

Tel: (01) 807 3800
Fax: (01) 807 3838

**VITREOUS AND PORCELAIN ENAMELS -
HIGH VOLTAGE TEST**

*This Irish Standard was
published under the
authority of the National
Standards Authority of
Ireland
and comes into effect on:
November 12, 2004*

**NO COPYING WITHOUT NSAI
PERMISSION EXCEPT AS
PERMITTED BY COPYRIGHT
LAW**

© NSAI 2004

Price Code E

Údarás um Chaighdeáin Náisiúnta na hÉireann

EUROPEAN STANDARD

EN 14430

NORME EUROPÉENNE

EUROPÄISCHE NORM

September 2004

ICS 25.220.50

English version

Vitreous and porcelain enamels - High voltage test

Emaux vitrifiés - Essai sous haute tension

Emails und Emailierungen - Hochspannungsprüfung

This European Standard was approved by CEN on 9 July 2004.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

	page
Foreword.....	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Principle	6
5 Apparatus	6
6 Specimens	6
7 Test voltage	6
7.1 Test A: Detection of defects (3.1) which extend down to the metal bases (e.g. open pores).....	6
7.2 Test B: Detection of defects and weak spots (3.2).....	8
8 Procedure	8
9 Test report	8
Bibliography	10

Foreword

This document (EN 14430:2004) has been prepared by Technical Committee CEN/TC 262 "Metallic and other inorganic coatings", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by March 2005, and conflicting national standards shall be withdrawn at the latest by March 2005.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

EN 14430:2004 (E)

Introduction

There are 2 different objectives for high voltage testing of vitreous and porcelain enamels.

Test A is used to detect and locate defects, which extend down to the metal base (e.g. open pores). This is a non-destructive test usually applied to thin enamel coatings. The test serves to monitor either that the parts produced are free from defects at the chosen test voltage, or to count the number of existing defects, e.g. to determine the defect density (defects/m²) of enamelled architecture panels.

Test B is used to detect and locate defects, which extend down to the metal base (e.g. open pores) and to detect weak spots. This is a destructive test, i.e. the test can generate open pores with an electric discharge through weak spots in the enamel coating. This test is usually applied to thick enamel coatings and serves:

a) to verify that an enamel coating is safe to be used under highly corrosive conditions, e.g. to test the enamel coating of vessels used in the chemical industry;

or

b) to verify that the enamel coating is safe to be used as a dielectric.

Test A and Test B require the same test equipment (see Clause 6) and follow the same test procedure (see Clause 9). However, for test B the applied voltage is higher than in test A (see Clause 7).

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-