

**IRISH STANDARD** 

I.S. CEN/TR 15019:2005

ICS 59.080.70

National Standards Authority of Ireland Glasnevin, Dublin 9 Ireland

Tel: +353 1 807 3800 Fax: +353 1 807 3838 http://www.nsai.ie

GEOTEXTILES AND GEOTEXTILE-RELATED PRODUCTS - ON-SITE QUALITY CONTROL

#### Sales

http://www.standards.ie

This Irish Standard was published under the authority of the National Standards Authority of Ireland and comes into effect on: May 5, 2005

NO COPYING WITHOUT NSAI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

© NSAI 2005 Price Code G

Údarás um Chaighdeáin Náisiúnta na hÉireann

This is a free page sample. Access the full version online.

# TECHNICAL REPORT RAPPORT TECHNIQUE TECHNISCHER BERICHT

**CEN/TR 15019** 

February 2005

ICS 59.080.70

#### English version

# Geotextiles and geotextile-related products - On-site quality control

Géotextiles et produits apparentés - Contrôle au chantier

Geotextilien und geotextilverwandte Produkte -Baustellenkontrolle

This Technical Report was approved by CEN on 9 January 2005. It has been drawn up by the Technical Committee CEN/TC 189.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

## CEN/TR 15019:2005 (E)

# Contents

		Page
Forew	ord	3
1	Scope	4
2	Terms and definitions	4
2.1	design specification	
2.2	product specification value	
2.3	sample	
2.4	specimen (test specimen)	
2.5	test result (of a sample)	
2.6 2.7	test lot	
2. <i>1</i> 2.8	delivery lotsafety standard high	
2.0 2.9	safety standard nightsafety standard normal	
_	•	
3	Principle	
4	Procedures	5
4.1	Evaluation of compliance of delivered product with the design specification (see Annex	
4.2	Evaluation of compliance of site conditions with the delivered product (see Annex A.3).	
4.3 4.4	Inspection of handling and storage conditionsInspection of product installation	6
+.4 4.5	Sampling for evaluation of compliance with the design specification (see Annex A 3 and	
4.5.1	Control of products delivered to the construction site	
4.5.2	Control tests by the client	
4.5.3	Test programme	
4.6	Sample installation and extraction to check damage during installation	8
4.7	Sample installation and extraction to check long-time behaviour	
5	Evaluation of conformity with the design specifications	8
5 5.1	Evaluation of conformity by a simplified procedure	8
5.2	Evaluation of conformity by statistic procedure	
6	Consequences	
6.1	Damage during transport, handling, storage and placing	
6.2	Evaluation of conformity	
7	Report	
, 7.1	Part 1: report on site conditions and sampling (see Annex A.1 to A.4)	
7.2	Part 2: Report on test results, evaluation and consequences (see Annex A.5)	
	A (informative) ON SITE CONDITIONS AND SAMPLING: EXAMPLES OF REPORTS	
Riblio	graphy	16

CEN/TR 15019:2005 (E)

### **Foreword**

This document (CEN/TR 15019:2005) has been prepared by Technical Committee CEN/TC 189 "Geosynthetics", the secretariat of which is held by IBN.

#### CEN/TR 15019:2005 (E)

#### 1 Scope

This document contains recommendations for on-site quality control of geotextiles and geotextile-related products as part of the site quality assurance system. It describes procedures for verifying that:

- the correct product is delivered to site;
- the product is handled and installed in the correct manner;
- the specifications are met.

This document contains an annex showing five examples of report forms for use on the site and a bibliography.

#### 2 Terms and definitions

For the purposes of this document, the terms and definitions given in prEN ISO 10318 and the following apply.

The term "product" used in this document refers to a geotextile or geotextile-related product.

#### 2.1

#### design specification

document which defines the application in which the product is to be used and where the functions, the characteristics and the design specification values of the characteristics required for use in the works are stated

#### 2.2

#### product specification value

value of a product characteristic as stated by the manufacturer, e.g. in the accompanying documents for CE marking. This value represents the mean value minus (and/or plus) one time the tolerance value(s) corresponding to the 95 % confidence level (as defined e.g. in EN 13249:2000, 5.2). By extension, this definition can also be applied to other characteristics described in Table 1 of the relevant product/application standard (see bibliography) and also to characteristics such as mass per unit area and thickness

#### 2.3

#### sample

part of the product, taken over the whole width, from which specimens are taken for testing

#### 2.4

#### specimen (test specimen)

part of the sample used for an individual test

#### 2.5

#### test result (of a sample)

mean of the results obtained on the specimens tested

#### 2.6

#### tost lot

quantity of products considered as one unit for sampling and testing. This can be the total area to be covered by the product in the works

#### 2.7

#### delivery lot

quantity of product delivered on site in a given period of time, which can be submitted to a single approval. Delivery lots are evaluated independently of each other



The is a new provider i arenade and chare publication at the limit below	This is a free preview.	Purchase the	entire publication	at the link below:
--	-------------------------	--------------	--------------------	--------------------

**Product Page** 

- Dooking for additional Standards? Visit Intertek Inform Infostore
- Dearn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation