



National Standards Authority of Ireland

IRISH STANDARD

I.S. EN 14830:2006

ICS 93.025
93.030

**THERMOPLASTICS INSPECTION CHAMBER
AND MANHOLE BASES - TEST METHODS
FOR BUCKLING RESISTANCE**

National Standards
Authority of Ireland
Glasnevin, Dublin 9
Ireland

Tel: +353 1 807 3800
Fax: +353 1 807 3838
<http://www.nsai.ie>

Sales
<http://www.standards.ie>

*This Irish Standard was
published under the
authority of the National
Standards Authority of
Ireland and comes into
effect on:*

10 November 2006

**NO COPYING WITHOUT NSAI
PERMISSION EXCEPT AS
PERMITTED BY COPYRIGHT
LAW**

© NSAI 2006

Price Code F

Údarás um Chaighdeán Náisiúnta na hÉireann

EUROPEAN STANDARD
NORME EUROPÉENNE
EUROPÄISCHE NORM

EN 14830

October 2006

ICS 93.025; 93.030

English Version

**Thermoplastics inspection chamber and manhole bases - Test
methods for buckling resistance**

Éléments de fond de boîtes d'inspection et de branchement
et de regards en thermoplastique - Méthodes d'essai de
résistance au flambage

Böden von Kontroll- und Einsteigschächten aus
thermoplastischen Kunststoffen - Prüfverfahren für die
Widerstandsfähigkeit gegen Einbeulen

This European Standard was approved by CEN on 28 August 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Page

| | |
|--|----|
| Foreword..... | 3 |
| 1 Scope..... | 4 |
| 2 Normative references | 4 |
| 3 Terms and definitions | 4 |
| 4 Principle | 4 |
| 5 Apparatus..... | 5 |
| 6 Conditioning | 6 |
| 7 Test environment | 6 |
| 8 Procedure..... | 6 |
| 8.1 Internal negative pressure testing using a free standing test assembly | 6 |
| 8.2 Internal negative pressure testing using a soil box..... | 8 |
| 8.3 External pressure testing with the assembly submerged in a water tank..... | 9 |
| 8.4 Evaluation | 10 |
| 9 Test report..... | 11 |
| Bibliography | 13 |

Foreword

This European Standard (EN 14830:2006) has been prepared by Technical Committee CEN/TC 155 "Plastics piping systems and ducting systems", the secretariat of which is held by NEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2007, and conflicting national standards shall be withdrawn at the latest by April 2007.

The relevant performance requirements are contained within the referring standard(s) concerned.

This European Standard is one of a series of standards on test methods that support System Standards for plastics piping systems and ducting systems.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

EN 14830:2006 (E)**1 Scope**

This European Standard specifies methods of test for the resistance of the base of thermoplastics inspection chambers and manholes to external soil and ground-water pressure after installation.

NOTE This is intended as a test of the durability and structural integrity of manhole and inspection chamber bases supporting product standards prEN 13598-2 [1] and prEN 15229 [2].

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ENV 1046:2001, *Plastics piping and ducting systems — Systems outside building structures for the conveyance of water or sewage — Practices for installation above and below ground*

EN ISO 9967:1995, *Thermoplastics pipes — Determination of creep ratio (ISO 9967:1994)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1**inspection chamber**

drainage or sewerage fitting used for the to connection of drainage or sewerage installations and/or for changing the direction of drainage or sewerage runs. An inspection chamber terminates at ground level, permitting the introduction of cleaning, inspection and test equipment and the removal of debris but it does not provide access for personnel. The riser shaft connected to these fittings has a minimum outer diameter of 200 mm and a maximum inside diameter of less than 800 mm (see also EN 476:1997 [3] for non circular chambers)

NOTE The termination at ground level permits the introduction of cleaning, inspection and test equipment and the removal of debris but does not provide access for personnel.

3.2**manhole**

drainage or sewerage fitting used for the connection of drainage or sewerage installations and/or for changing the direction of drainage or sewerage runs. A manhole terminates at ground level, permitting the introduction of cleaning, inspection and test equipment and the removal of debris and also providing access for personnel. The minimum inside diameter of a manhole riser shaft is 800 mm (see also EN 476:1997 [3] for non circular manholes)

NOTE The termination at ground level permits the introduction of cleaning, inspection and test equipment and the removal of debris and provides access for personnel.

4 Principle

A sealed test assembly comprising an inspection chamber or manhole base with a minimum height of 300 mm above the top of the main channel, is placed free standing, or buried in a test box on a 100 mm sand or granular bed and covered with granular backfill to a level of minimum 300 mm above the top of the outlets and inlets of the main channel(s). In some cases the first section of the riser may be required in order to achieve the minimum height of 300 mm.

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- Looking for additional Standards? Visit Intertek Inform Infostore
 - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-