

Irish Standard I.S. EN 817:2008

Sanitary tapware - Mechanical mixing valves (PN 10) - General technical specifications

© NSAI 2008

No copying without NSAI permission except as permitted by copyright law.

Incorporating amendments/corrigenda issued since publication:				

This standard replaces: I.S. EN 817:2008

This standard is based on: EN 817:2008

EN 817:2008 EN 817:2008 Published:

13 August, 2008

This Irish Standard was published under the authority of the NSAI and comes into effect on: 4 September, 2008 ICS number: 91.140.70

NSAI 1 Swift Square, Northwood, Santry Dublin 9

T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie Price Code:

Údarás um Chaighdeáin Náisiúnta na hÉireann

# EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

**EN 817** 

June 2008

ICS 91.140.70

Supersedes EN 817:1997

#### **English Version**

# Sanitary tapware - Mechanical mixing valves (PN 10) - General technical specifications

Robinetterie sanitaire - Mitigeurs mécaniques (PN 10) - Spécifications techniques générales Sanitärarmaturen - Mechanisch einstellbare Mischer (PN 10) - Allgemeine technische Spezifikation

This European Standard was approved by CEN on 29 May 2008.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

# EN 817:2008 (E)

# **Contents**

		oage
Forew	vord	6
Introd	luction	7
1	Scope	8
2	Normative references	10
3	Terms, definitions and designation	10
3.1	Terms and definitions	
3.2	Designation	11
4	Marking and identification	
4.1	Marking	
4.2	Identification	
5	Materials	
5.1	Chemical and hygiene requirements	
5.2	Exposed surface conditions	
6	Dimensional characteristics	
6.1 6.2	General remarksInlet dimensions	
ნ.∠ 6.3	Outlet dimensions	
6.4	Mounting dimensions	
6.5	Special cases	20
6.6	Flexible hoses for shower outlets	
6.7	Shower outlets	20
7	Sequence of testing	21
8	Leaktightness characteristics	
8.1	General	
8.2 8.3	Test methodsLeaktightness of the obturator and of the mixing valve upstream of the obturators with the	
0.3	obturator in the closed position	22
8.4	Leaktightness of the mixing valve downstream of the obturator with the obturator open	
8.5	Leaktightness of manually operated diverter	
8.6	Leaktightness and operation of diverter with automatic return	
8.7	Leaktightness of the obturator: cross flow between hot water and cold water	
9	Pressure resistance characteristics – mechanical performance under pressure	
9.1 9.2	General Principle	
9.2 9.3	Apparatus	
9.4	Mechanical behaviour upstream of the obturator – obturator in the closed position	
9.5	Mechanical behaviour downstream of the obturator – obturator in the open position	26
10	Hydraulic characteristics	27
10.1	General	
10.2	Initial settings	
10.3	Principle	
10.4 10.5	Apparatus Procedure	
10.5	Determination of flow rate	
10.7	Determination of sensitivity	
11	Mechanical strength characteristics - torsion test for operating mechanism	33

# EN 817:2008 (E)

11.1 General	33
11.2 Test method	33
12 Mechanical endurance characteristics	34
12.1 Mechanical endurance of the control device	34
12.2 Mechanical endurance of diverters	38
12.3 Mechanical endurance of swivel spouts	
13 Backflow protection	41
14 Acoustic characteristics	41
14.1 General	41
14.2 Procedure	41
14.3 Requirements	41
Annex A (informative) Apparatus	43
Annex B (informative) Pressure take-off tee	47
Bibliography	50

# EN 817:2008 (E)

# **Figures**

Figure 1	Supply system with a pressure range of (0,05 to 1,0) MPa [(0,5 to 10) bar]	9
Figure 2	Flexible hoses and plain tube	14
Figure 3	Multi-hole mechanical mixing valve	15
Figure 4	Supply connections for mechanical mixing valve and remote outlets	16
Figure 5	Remote outlet	18
Figure 6	Single hole mechanical mixing valve	18
Figure 7	Two hole mechanical mixing valve	18
Figure 8	Single hole mechanical mixing valve	19
Figure 9	Two hole mechanical mixing valve	20
Figure 10	Sensitivity curve	31
Figure 11	Radius for the determination of sensitivity	32
Figure 12	Rectangular movement	34
Figure 13	Triangular movement	35
Figure 14	Test bench adjustment torque for conventionnal mixing valve	37
Figure 15	Test bench adjustment torque for joystick mixing valve	37
Figure 16	Test bench adjustment torque for sequential mixing valve	37
Figure A 1	Supply circuits	43
Figure A 2	Test circuit	45
Figure A 3	Mounting of the mixing valve	46
Figure B 1	Pressure take-off tee	47
Figure B 2	Schematic examples of pressure take-off tees	48



The is a new provider i arenade and chare publication at the limit below	This is a free preview.	Purchase the	entire publication	at the link below:
--	-------------------------	--------------	--------------------	--------------------

**Product Page** 

- Dooking for additional Standards? Visit Intertek Inform Infostore
- Dearn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation