



National Standards Authority of Ireland

IRISH STANDARD

I.S. ENV 13381-7:2002

ICS 13.220.50

**TEST METHODS FOR DETERMINING THE  
CONTRIBUTION TO THE FIRE RESISTANCE  
OF STRUCTURAL MEMBERS - PART 7:  
APPLIED PROTECTION TO TIMBER  
MEMBERS**

National Standards  
Authority of Ireland  
Dublin 9  
Ireland

Tel: (01) 807 3800

Tel: (01) 807 3838

*This Irish Standard was  
published under the  
authority of the National  
Standards Authority of  
Ireland  
and comes into effect on  
October 22, 2002*

**NO COPYING WITHOUT NSAI  
PERMISSION EXCEPT AS  
PERMITTED BY COPYRIGHT  
LAW**

© NSAI 2002

**Price Code K**

Údarás um Chaighdeáin Náisiúnta na hÉireann



EUROPEAN PRESTANDARD  
PRÉNORME EUROPÉENNE  
EUROPÄISCHE VORNORM

**ENV 13381-7**

July 2002

---

ICS 13.220.50

English version

**Test methods for determining the contribution to the fire  
resistance of structural members - Part 7: Applied protection to  
timber members**

This European Prestandard (ENV) was approved by CEN on 1 March 2002 as a prospective standard for provisional application.

The period of validity of this ENV is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the ENV can be converted into a European Standard.

CEN members are required to announce the existence of this ENV in the same way as for an EN and to make the ENV available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the ENV) until the final decision about the possible conversion of the ENV into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**Management Centre: rue de Stassart, 36 B-1050 Brussels**

**ENV 13381-7:2002 (E)**

**Contents**

	page
Foreword.....	3
1 Scope .....	4
2 Normative references.....	5
3 Terms and definitions, symbols and units .....	5
4 Test equipment .....	7
5 Test conditions.....	7
6 Test specimens.....	8
7 Installation of the test construction.....	12
8 Conditioning of the test construction.....	12
9 Application of instrumentation.....	13
10 Test procedure .....	14
11 Test results .....	15
12 Test report.....	16
13 Assessment .....	16
14 Report of the assessment .....	18
15 Limits of applicability of the results of the assessment.....	18
Annex A (normative) Test method to the smouldering fire or slow heating curve.....	23
Annex B (informative) Guidelines for fire protection of timber structures according to ENV 1995-1-2 - Loadbearing function.....	26
Annex C (normative) Measurement of properties of fire protection materials .....	29
Annex D (informative) Alternative construction for loaded beam test specimen .....	32
Bibliography .....	34

## Foreword

This document ENV 13381-7:2002 has been prepared by Technical Committee CEN/TC127 "Fire safety in buildings", the secretariat of which is held by BSI.

This document has been prepared under the mandate given to CEN/TC127 by the Commission and the European Free Trade Association.

As there was little experience in carrying out these tests in Europe CEN/TC127 agreed that more experience should be built up during a prestandardization period before agreeing text as European Standards. Consequently all parts are being prepared as European Prestandards.

This European Prestandard is one of a series of standards for evaluating the contribution to the fire resistance of structural members by applied fire protection materials. Other parts of this ENV are:

- Part 1: Horizontal protective membranes.
- Part 2: Vertical protective membranes.
- Part 3: Applied protection to concrete members.
- Part 4: Applied protection to steel members.
- Part 5: Applied protection to concrete/profiled sheet steel composite members.
- Part 6: Applied protection to concrete filled hollow steel columns.

Annexes A and C are normative. Annexes B and D are informative.

### Caution

The attention of all persons concerned with managing and carrying out this fire resistance test, is drawn to fact that fire testing can be hazardous and that there is a possibility that toxic and/or harmful smoke and gases can be evolved during the test. Mechanical and operational hazards can also arise during the construction of test elements or structures, their testing and the disposal of test residues.

An assessment of all potential hazards and risks to health should be made and safety precautions should be identified and provided. Written safety instructions should be issued. Appropriate training should be given to relevant personnel. Laboratory personnel should ensure that they follow written safety instructions at all times.

The specific health and safety instructions contained within this prestandard should be followed.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to announce this European Prestandard: Austria, Belgium, Czech Republic, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Malta, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and the United Kingdom.

## ENV 13381-7:2002 (E)

### 1 Scope

This Part of this European Prestandard specifies a test method to be followed for determining the contribution of fire protection systems to the fire resistance of structural timber members.

Such fire protection systems include claddings, sprayed fire protection and coatings.

The method is applicable to all fire protection systems used for the protection of timber members. These can be fixed directly, totally or in part, to the timber member and can include an air gap between the fire protection system and the timber member, as an integral part of its design.

Evaluation of timber constructions protected by horizontal or vertical protective membranes are the subject of ENV 13381-1 or ENV 13381-2 respectively.

The test method is applicable to the determination of the contribution of fire protection systems to the fire resistance of loadbearing timber structural members and non-loadbearing parts of the works, including floors, roofs, walls, beams and columns. It is also applicable to timber structural members incorporating insulating materials between the timber members, e.g. between timber joists in floor constructions.

The test method and its assessment procedure is designed to permit direct application of the results to cover a range of thicknesses of the applied fire protection material.

This European Prestandard contains the fire test which specifies the test to be carried out to determine the ability of the fire protection system to delay the temperature rise throughout the timber member, to determine the ability of the fire protection system to remain coherent and fixed to the timber member and to provide data of the temperature profile throughout the timber test member, when exposed to the standard temperature/time curve according to the procedures defined herein.

In special circumstances, where specified in national building regulations, there can be a need to subject reactive protection material to a smouldering curve. The test for this and the special circumstances for its use are detailed in annex A.

The fire test methodology makes provision for the collection and presentation of data which can be used as direct input to the calculation of fire resistance of timber members in accordance with the procedures given in ENV 1995-1-2.

A description of the relationship of this test method and the assessment of the results obtained therefrom to ENV 1995-1-2 and guidelines for the use of this test method in accordance with that standard are given in annex B.

This European Prestandard also contains the assessment which prescribes how the analysis of the test data should be made and gives guidance to the procedures by which interpolation should be undertaken.

The limits of applicability of the results of the assessment arising from the fire test are defined, together with permitted direct application of the results to different timber constructions over the range of thicknesses of the applied fire protection system tested.

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

- 
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
  - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-