



National Standards Authority of Ireland

IRISH STANDARD

I.S. CLC/TS 50458:2006

ICS 29.080.20

**CAPACITANCE GRADED OUTDOOR
BUSHING 52 KV UP TO 420 KV FOR OIL
IMMERSED TRANSFORMERS**

National Standards
Authority of Ireland
Glasnevin, Dublin 9
Ireland

Tel: +353 1 807 3800
Fax: +353 1 807 3838
<http://www.nsai.ie>

Sales
<http://www.standards.ie>

*This Irish Standard was
published under the
authority of the National
Standards Authority of
Ireland and comes into
effect on:
June 2, 2006*

**NO COPYING WITHOUT NSAI
PERMISSION EXCEPT AS
PERMITTED BY COPYRIGHT
LAW**

© NSAI 2006

Price Code K

Údarás um Chaighdeáin Náisiúnta na hÉireann

TECHNICAL SPECIFICATION
SPÉCIFICATION TECHNIQUE
TECHNISCHE SPEZIFIKATION

CLC/TS 50458

April 2006

ICS 29.080.20

English version

**Capacitance graded outdoor bushing 52 kV up to 420 kV
for oil immersed transformers**

Traversées à répartition capacitive
immergées d'extérieur, 52 kV à 420 kV
pour transformateurs
immergés dans l'huile

Kapazitiv gesteuerte
Freiluftdurchführungen 52 kV bis 420 kV
für ölgefüllte Transformatoren

This Technical Specification was approved by CENELEC on 2005-10-15.

CENELEC members are required to announce the existence of this TS in the same way as for an EN and to make the TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

Foreword

This Technical Specification was prepared by the Technical Committee CENELEC TC 36A, Insulated bushings.

The text of the draft was submitted to vote in accordance with Subclause 11.3.3.3 of Part 2 of the CENELEC Internal Regulations and was approved by CENELEC as CLC/TS 50458 on 2005-10-15.

The following date was fixed:

- latest date by which the existence of the CLC/TS
has to be announced at national level (doa) 2006-07-01

The purpose of this Technical Specification is to ensure the interchange ability between capacitance graded bushings, with comparable technical requirements, from different manufacturers.

The aim is, to reduce the multiplicity of the different designs, only regarding the interchange ability. The document gives recommendations for mounting flange dimensions, lower part details, current conductor connections and limits for the overall dimensions. This allows, on the one hand, the manufacturers of bushings to use normalised solutions within their own type series and on the other, the users to exchange bushings from different manufacturers and with different years of manufacture.

In the preparation of this Technical Specification information about existing types (especially details of the design and the dimensions taken mostly from catalogues of the European manufacturers) was the basis for discussion in WG 4 of TC 36A. The following restrictions were applied:

- technical aspects of the design of different manufacturers and the requirements of users must be considered for the values of the new Technical Specification regarding the state of art;
- there should be no single effort for one manufacturer or to the exclusion of another;
- no restriction for the technical evolution.

Conformance will require design changes for not only the manufacturer of the bushings but also transformers. Some changes may require significant modifications along with type tests which are time consuming and costly. Purchasers of transformers should also review its contents for its impact on their procurement process. For these reasons, this document will act as a guide or Technical Specification (TS) during a transitional period. During this period, the contents will act as a guide to manufacturers while allowing debate in the industry on its effectiveness and value. This transition period will not exceed ten years at which time its contents should be amended if necessary and submitted for approval as a European Standard.

Contents

	Page
Introduction	4
1 Scope	4
2 Normative references	4
3 Definitions	4
3.1 Draw-lead conductor	4
3.2 Solid rod conductor	4
3.3 Bottom terminal - current connection	5
4 Requirements	5
4.1 Application	5
4.2 Standard values of highest voltage for equipment (U_m)	5
4.3 Standard values of rated current (I_r)	5
4.4 Compliance	5
4.4.1 Test tap	5
4.4.2 Creepage distance	5
4.4.3 Insulating level	5
4.4.4 Operating conditions, test requirements	5
4.5 Additional requirements	5
4.6 Designation	6
4.6.1 Electrical design of oil end	6
4.6.2 Conductor principles and mechanical design of oil end	6
4.6.3 Conductor arrangement	6
4.6.4 Complete bushing designation	7
4.7 Design details	8
Annex A (informative) Example of bushing documentation	17
Figure 1 – Bushing dimensions (general)	8
Figure 2 – Bushing oil end dimensions	9
Figure 3 – Examples of current leader principles and mechanical design of oil end	10
Figure 4 – Jointing of split rod conductor	15
Figure 5 – Example of bottom connection	16
Table 1 – Dimensions of air terminal stems according to IEC/TR 62271-301	8
Table 2 – Dimensions	11
Table 3 – Two examples of data for split rod type inside the bore	15

Introduction

The object of this Technical Specification is to specify details and dimensions of capacitance graded outdoor bushings for highest voltages for equipment from 52 kV up to 420 kV as far as it is necessary to ensure the interchange ability of bushings with comparable technical requirements. Additionally, some technical items are site specific, and are rarely able to be standardised, e.g. airside length of a bushing which depends on the different air side material, shed profiles and pollution level. This Technical Specification defines additional data or information, which must be included, by the bushing or the transformer manufacturer, in the transformer manual for the purpose of interchange ability.

1 Scope

This Technical Specification is applicable to capacitance graded outdoor bushings with values of highest voltage for equipment (U_m) from 52 kV up to 420 kV and with values of rated current (I_r) up to 3 150 A and frequencies from 15 Hz up to 60 Hz for oil immersed transformers.

The major insulation of these bushings consists either of oil-impregnated or resin-impregnated paper or other suitable insulating systems.

This Technical Specification establishes essential details and dimensions to ensure interchange ability and adequate mounting of the bushings.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 60059	1999	IEC standard currents (IEC 60059:1999)
EN 60076-3	2001	Power transformers – Part 3: Insulation levels and dielectric tests and external clearances in air (IEC 60076-3:2000 + corrigendum Dec. 2000)
EN 60137	2003	Insulated bushings for alternating voltages above 1 000 V (IEC 60137:2003)
EN 60296		Specification for unused mineral oil for transformers and switchgear (IEC 60296)
IEC 60038	1983	IEC standard voltages
IEC 60815	1986	Guide for the selection of insulators in respect of polluted conditions
IEC/TR 62271-301	2004	High-voltage switchgear and controlgear – Part 301: Dimensional standardization of terminals

3 Definitions

For the definitions of generally used terms in the present Technical Specification reference should be made to EN 60137.

For the purposes of this Technical Specification the following additional definitions apply:

3.1

draw-lead conductor

conductor consisting of one or more flexible leads in parallel drawn into the central tube of the major insulation body of the bushing (preferred up to 1 000 A)

3.2

solid rod or tube conductor

conductor consisting of a round rod either removable and drawn into the central tube of the major insulation body of the bushing or fixed rod or tube and not removable (preferred from 1 250 A up to 3 150 A)

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-