This is a free page sample. Access the full version online.



Irish Standard I.S. EN 3475-417:2009

Aerospace series - Cables, electrical, aircraft use - Test methods - Part 417: Fire resistance of cables confined inside a harness

 $\ensuremath{\mathbb{C}}$ NSAI 2009 No copying without NSAI permission except as permitted by copyright law.

Incorporating amendments/corrigenda issued since publication:

This document replaces:	<i>This document is based on:</i> EN 3475-417:2009		<i>Published:</i> 11 March, 2009			
This document was published under the authority of the NSAI and comes into effect on: 11 May, 2009				ICS number: 49.060		
NSAI 1 Swift Square, T +3 Northwood, Santry F +3 Dublin 9 E st W N	53 1 807 3800 53 1 807 3838 andards@nsai.ie I SAI.ie	Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie		Price Code: E		
Údarás um Chaighdeáin Náisiúnta na hÉireann						

EUROPEAN STANDARD

EN 3475-417

NORME EUROPÉENNE

EUROPÄISCHE NORM

March 2009

ICS 49.060

English Version

Aerospace series - Cables, electrical, aircraft use - Test methods - Part 417: Fire resistance of cables confined inside a harness

Série aérospatiale - Câbles électriques à usage aéronautique - Méthodes d'essais - Partie 417: Tenue au feu des câbles confinés dans un harnais Luft- und Raumfahrt - Elektrischen Leitungen für Luftfahrt Verwendung - Prüfverfahren - Teil 417: Feuerbeständigkeit von Leitungen eingebunden in Bündeln

This European Standard was approved by CEN on 30 August 2008.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Ref. No. EN 3475-417:2009: E

EN 3475-417:2009 (E)

Contents

Page

Forewo	ord	3
1	Scope	4
2	Normative references	4
3	Preparation of specimens	4
4	Apparatus	4
5	Method	5
6	Requirements/Acceptance criteria	6
Annex	A (normative) Circuit diagram principle for measurement of equipotentials	7

Foreword

This document (EN 3475-417:2009) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by September 2009, and conflicting national standards shall be withdrawn at the latest by September 2009.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

EN 3475-417:2009 (E)

1 Scope

This standard specifies a method of testing the fire resistance of fire resistance or fire-proof electrical cables inside a harness.

The objective of this test is to **qualify these cables** when they are confined inside harnesses defined hereafter. Described configurations try to be representative of various cables configuration installed in Aircraft.

It shall be used together with EN 3475-100.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 2346-002, Aerospace series — Cable, electrical, fire resistant — Operating temperatures between – 65 °C and 260 °C — Part 002 : General.

EN 3475-100, Aerospace series — Cables, electrical, aircraft use — Test methods — Part 100: General.

EN 3475-408, Aerospace series — Cables, electrical, aircraft use — Test methods — Part 408: Fire resistance.

ISO 2685, Aircraft — Environmental test procedure for airborne equipment — Resistance to fire in designated fire zones.

3 Preparation of specimens

Three specimens per configuration 0,75 m length shall be tested. See Figure 1.

4 Apparatus

The test equipment shall be as required in EN 3475-408.

Reminder of apparatus requirements:

- a) **Burner**: according with ISO 2685 or any other burner or assembly of burners satisfying the following conditions:
 - The minimum width of the burner shall be 50 mm;
 - Cable length exposed to the flame: 152 mm;
 - Diameter or width of the flame at the base of the burner $\ge 2 D$ (D = diameter of the harness under test);
 - Flame temperature: $(1 \ 100 \pm 80)$ °C;
 - Heat flux density received by the calorimeter: $(116 \pm 10) \text{ kW/m}^2$.
- b) **Test fixture**: according with ISO 2685:
 - The frame of the test fixture shall be vibrated with the following characteristics:
 - Direction perpendicular to the axis of the cable;
 - Frequency : (30 ± 5) Hz;
 - Minimum acceleration: 4 g.
- c) Circuit diagram (see Annex A, Figures A.1 and A.2)



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation