



National Standards Authority of Ireland

IRISH STANDARD

I.S. EN 15112:2006

ICS 23.040.99
77.060

National Standards
Authority of Ireland
Glasnevin, Dublin 9
Ireland

Tel: +353 1 807 3800
Fax: +353 1 807 3838
<http://www.nsai.ie>

**EXTERNAL CATHODIC PROTECTION OF
WELL CASINGS**

Sales
<http://www.standards.ie>

*This Irish Standard was
published under the
authority of the National
Standards Authority of
Ireland and comes into
effect on:
4 October 2006*

**NO COPYING WITHOUT NSAI
PERMISSION EXCEPT AS
PERMITTED BY COPYRIGHT
LAW**

© NSAI 2006

Price Code L

Údarás um Chaighdeán Náisiúnta na hÉireann

EUROPEAN STANDARD

EN 15112

NORME EUROPÉENNE

EUROPÄISCHE NORM

July 2006

ICS 23.040.99; 77.060

English Version

External cathodic protection of well casings

Protection cathodique externe des cuvelages de puits

Äußerer kathodischer Korrosionsschutz von
Bohrlochverrohrungen

This European Standard was approved by CEN on 19 June 2006.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents	Page
Foreword.....	3
Introduction	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Description and assessment of corrosion risks	9
4.1 General.....	9
4.2 Description of corrosion risks.....	9
4.3 Corrosion risk assessment.....	9
5 Prerequisites for application of cathodic protection	10
5.1 General.....	10
5.2 Electrical continuity.....	10
5.3 Electrical isolation	10
5.4 Cathodic protection equipment.....	11
5.5 Groundbed.....	11
5.6 Safety requirements	11
6 Design of the cathodic protection.....	12
6.1 General.....	12
6.2 Voltage drop profile method.....	12
6.3 Polarisation curve method.....	13
6.4 Mathematical approach based on a field test.....	13
6.5 Simulation of the cathodic protection for a well	13
7 Measurement of the well-casing-to-soil potential at the wellhead	14
7.1 General.....	14
7.2 Measuring points	14
7.3 Method used for potential measurement - Interpretation.....	15
8 Additional cathodic protection equipment	15
Annex A (normative) Voltage drop profile	16
Annex B (informative) Polarisation curve method applied to a well	23
Annex C (informative) Determination by calculation of the potential shift at the bottom of the well and the well to soil resistance.....	26
Bibliography	36

Foreword

This document (EN 15112:2006) has been prepared by Technical Committee CEN/TC 219 “Cathodic protection”, the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by January 2007, and conflicting national standards shall be withdrawn at the latest by January 2007.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

EN 15112:2006 (E)

Introduction

Gas, oil and water well casings are usually cemented for the purposes of anchoring the pipes in the borehole and isolating the various geological layers from each other. This is necessary to avoid liquid exchanges between these.

Steels in contact with the cement are in a passivation status and, thus, protected from any kind of external corrosion, except if the cement contains chloride ions. However, it is not always possible to obtain a continuous cementation on all the external steel surfaces. These bare residual surfaces may be in contact with more or less aggressive layers. Furthermore, these surfaces may constitute electrochemical cells with the cemented metallic parts. The anodic areas, which are the poor cemented parts, correspond to corrosion areas.

In general, external corrosion effects are rare, particularly on recent wells, since most of them are well cemented. However, borehole cementation programmes sometimes result in cementation failures, and studies have shown that, corrosion phenomena being progressive, the mean time for the appearance of leaks is dependent on different factors such as geological formation, thickness of the layers and of the steel casing.

Experience has also shown that the situation may be significantly improved by applying external cathodic protection to wells.

Environmental aspects with regard to gas, oil or water wells should be considered when deciding on whether or not to apply cathodic protection.

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-