

Irish Standard I.S. EN 12299:2009

Railway applications - Ride comfort for passengers - Measurement and evaluation

© NSAI 2009

No copying without NSAI permission except as permitted by copyright law.

Incorporating amendments/corrigenda issued since publication:

This document replaces: ENV 12299:1999

This document is based on: EN 12299:2009 ENV 12299:1999 *Published:* 8 April, 2009 14 April, 2000

This document was published under the authority of the NSAI and comes into effect on: 3 July, 2009 ICS number: 45.060.20

NSAI 1 Swift Square, Northwood, Santry Dublin 9

T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAl.ie Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie Price Code:

Údarás um Chaighdeáin Náisiúnta na hÉireann

This is a free page sample. Access the full version online.

I.S. EN 12299:2009

EUROPEAN STANDARD

EN 12299

NORME EUROPÉENNE EUROPÄISCHE NORM

April 2009

ICS 45.060.20

Supersedes ENV 12299:1999

English Version

Railway applications - Ride comfort for passengers - Measurement and evaluation

Applications ferroviaires - Confort de marche des voyageurs - Mesurage et évalutation

Bahnanwendungen - Fahrkomfort für Fahrgäste - Messung und Auswertung

This European Standard was approved by CEN on 7 March 2009.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

EN 12299:2009 (E)

Cont	Contents Pa		
Forew	ord	6	
1	Scope	7	
2	Normative references	7	
3	Terms and definitions		
4	Symbols, units and abbreviations		
5	General description		
5.1	General		
5.2 5.3	Passenger exposure to vibrations		
5.4	Characteristics of railway vehicle motions		
5.5	Ride comfort		
5.6	Direct and indirect measurements		
5.7	Summary table of procedures		
5.8	Application of comfort indices	15	
6	Mean Comfort and Continuous Comfort	15	
6.1	General		
6.2	Base of the method		
6.3	Methodology		
6.4	Test conditions		
6.4.1	General		
6.4.2 6.4.3	Selection of test sections Test speed		
6.4.4	Wheel-rail contact geometry		
6.4.5	Vehicle condition		
6.5	Parameters to be measured		
6.5.1	General		
6.5.2	Location of measuring points		
6.5.3	Filtering		
6.6	Definition of intermediate quantities		
6.6.1 6.6.2	Symbols and indices		
6.6.3	95th and 50th percentiles		
6.7	Definition of comfort indexes		
6.7.1	Continuous Comfort		
6.7.2	Mean Comfort Standard Method	21	
6.7.3	Mean Comfort Complete Method		
6.8	Test report	21	
7	Comfort on Curve Transitions	21	
7.1	General	21	
7.2	Base of the method		
7.3	Methodology		
7.4	Test conditions		
7.4.1 7.4.2	General		
7.4.2 7.4.3	Selection of test sections		
7.4.4	Wheel-rail contact geometry		
7.4.5	Vehicle condition		
7.5	Parameters to be measured		
7.5.1	General		
7.5.2	Location of measuring points		
7.5.3	Filtering		
7.6	Definition of intermediate quantities	23	

7.6.2	Averaging procedure			
7.6.3 7.6.4	Identification of transition periods			
7.7	Definition of comfort index $P_{ m CT}$	25		
7.8	Test report			
7.9	Example diagrams			
8	Comfort on Discrete Events			
o 8.1	General			
8.2	Base of the method			
8.3	Methodology	28		
8.4	Test conditions			
8.4.1	General			
8.4.2 8.4.3	Selection of test sections			
6.4.3 8.4.4	Wheel-rail contact geometry			
8.4.5	Vehicle condition			
8.5	Parameters to be measured			
8.5.1	General			
8.5.2	Location of measuring points			
8.5.3 8.6	Filtering Definition of intermediate quantities			
o.o 8.6.1	Symbols and indices			
8.6.2	Averaging procedure			
8.6.3	Intermediate quantities			
8.7	Definition of comfort index P_{DF}	31		
8.8	Test report			
8.9	Example diagrams			
۵	Guide for the interpretation of the results (Informative)	21		
9.1	General			
9.2	Mean Comfort			
9.3	Continuous Comfort			
9.4	Comfort on Curve Transitions			
9.5	Comfort on Discrete Events			
Annex	A (normative) Reference system	34		
Annex	B (normative) Measurement techniques	36		
	General			
B.2	Measuring equipment			
B.2.1 B.2.2	GeneralAccelerometers and processing amplifiers			
B.2.2 B.2.3	Recording equipment			
B.2.4	Fixing transducers to the floor			
B.3	Seat measuring devices and their applications	37		
Annex	C (normative) Weighting curves	40		
C.1	General			
C.2	Filter functions			
C.2.1	General			
C.2.2	Band-limiting filter			
C.2.3 C.2.4	Acceleration to velocity transition			
C.2.4 C.2.5	Overall frequency weighting			
C.2.6	Reduction of the upper limit of the frequency range in vertical direction			
C.3	Tolerances	42		
C.4	Diagrams	44		
Annex	Annex D (informative) Presentation of test report47			
D.1	General	47		
D.2	Aim of test			
D.3 D.4	Test performer			
	MATATARAGE	л 7		

EN 12299:2009 (E)

D.5	Test conditions	
D.5.1	General information	
D.5.2	Vehicle	
D.5.3 D.5.4	Seat (for Mean Comfort Complete Method)	48
D.5.4 D.5.5	Seat occupant (for Mean Comfort Complete Method)	
D.5.6	Speed profile	
D.5.7	Test configurations	
D.6	Measurements and processing	
D.6.1	Measurements	
D.6.2	Processing	
D.7	Report on Mean Comfort and Continuous Comfort	
D.7.1 D.7.2	General Time series	
D.7.2 D.7.3	Statistical results	
D.7.4	Comfort evaluation	
D.7.5	Spectral analyses	
D.7.6	Examples of diagrams	. 50
D.8	Report on comfort in curve transitions	
D.9	Reporting on Comfort on Discrete Events	. 53
Annex	E (normative) Vehicle assessment with respect to Mean Comfort Standard Method	. 55
E.1	General	. 55
E.2	Track geometric quality	
E.3	Test conditions	
E.3.1	Selection of test sections and test zones	
E.3.2 E.3.3	Test speedWheel-rail contact geometry	
E.3.4	Vehicle condition	
E.4	Acceptable modifications of the methods for Mean Comfort evaluation	
E.5	Test report	
Annov	F (informative) Guideline for the application of direct tests	
	G (informative) Workflow for numerical integration	
	H (informative) Determining quantities	
Bibliog	raphy	. 62
Figures	S .	
Figure	1 — Locations of measuring points Passenger coach (Conventional or articulated)	. 18
_	2 — Location of measuring points Double-Deck vehicle (Conventional or articulated)	
rigure	2 — Location of measuring points bouble-beck vehicle (Conventional or articulated)	. 10
Figure	3 — Interpretation of the terms, $ \ddot{y}_{1s} _{\max}$ and $ \ddot{y}_{1s} _{\max}$ in the P_{CT} formula	26
Figure	4 — Interpretation of the term $\left \dot{arphi}_{ m 1s} ight _{ m max}$ in the $P_{ m CT}$ formula	. 27
Figure	5 — Relevant time periods $A_{ m i}$ on curve transition	. 27
	6 — Interpretation of $\left \ddot{y}_{2s}(t)\right $ and $\left \ddot{y}_{pp}(t)\right $ for calculation of P_{DE}	
Figure	A.1 — Local reference system for a vehicle body	. 34
Figure	A.2 — Local reference systems for a person in a seated position	. 35
Figure	A.3 — Local reference system for a person in standing position	. 35
Figure	B.1 — Seat pan measuring device (for y- and z-direction)	. 37
Figure	B.2 — Seat pan measuring device	. 38
Figure	B.3 — Seat back measurement device	. 39
Figure	C.1 — Tolerances for $W_{ t b}$. 42

Figure C.2 — Tolerances for $W_{ m c}$	43
Figure C.3 — Tolerances $W_{\sf d}$	43
Figure C.4 — Tolerances for W_{p}	44
Figure C.5 — Magnitude of the alternative frequency weighting $W_{\mathtt{b}}$ for vertical vibration along to on the floor and seat pan	
Figure C.6 — Magnitude of the frequency weighting $W_{ m c}$ for horizontal vibration along the x-axis	
Figure C.7 — Magnitude of the frequency weighting $W_{ m d}$ for horizontal vibration along the x- or y the floor, or along the y-axis on the seat pan	
Figure C.8 —Magnitude of the frequency weighting $W_{ m p}$ for lateral acceleration for $P_{ m CT}$ and $P_{ m DE}$ roll velocity for $P_{ m CT}$ evaluation	_
Figure D.1 — Continuous Comfort - Collection of five-minute periods (selected periods marked	grey)50
Figure D.2 — Example of Continuous Comfort and statistical distribution for a five-minute perio	od51
Figure D.3 — Example of weighted (bold line) and un-weighted (thin line) power spectral densit level acceleration in x, y and z directions (Duration: 307,2 s / Sampling rate: 400 Hz / FF 2048 points)	Ť:
Figure D.4 —Example of time series for $P_{ extsf{DE}}$ evaluation	54
Tables	
Table 1 — Symbols, units and abbreviation	9
Table 2 — Items considered by this standard	
Table 3 — Motion quantities and measurement position for estimation of ride comfort	14
Table 4 — Specification of different comfort indices for estimations of ride comfort and Vehicle assessment with respect to ride comfort	
Table 5 — Guidance to use the different comfort indices for other applications	
Table 6 — Constants for $P_{ t CT}$ comfort index	
Table 7 — Constants for $P_{ t DE}$ comfort index	
Table 8 — Scale for the $N_{ m MV}$ comfort index	32
Table 9 — Preliminary scale for the $C_{ m Cy}(t)$ and $C_{ m Cz}(t)$ comfort indexes	32
Table B.1 — Frequency range for the global transfer function	36
Table C.1 — Weighting curves	40
Table C.2 — Parameters and transfer functions of the frequency weightings	40
Table C.3 — Tolerances on weighting curves	42
Table H.1 — Determining quantities for Mean Comfort	60
Table H.2 — Determining quantities for Comfort in Curve Transitions and Discrete Events	61

EN 12299:2009 (E)

Foreword

This document (EN 12299:2009) has been prepared by Technical Committee CEN/TC 256 "Railway applications", the secretariat of which is held by DIN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2009, and conflicting national standards shall be withdrawn at the latest by October 2009.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes ENV 12299:1999.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

1 Scope

This standard specifies methods for quantifying the effects of vehicle body motions on ride comfort for passengers and vehicle assessment with respect to ride comfort. The effect considered is:

discomfort, associated with relatively low levels of acceleration and roll velocity.

Other effects, not included in the standard, are associated with higher acceleration levels:

health risk effect: physical damage and psychological deterioration.

The standard applies to passengers travelling in railway vehicles on railway lines, including main, secondary and suburban lines. This standard could be used as a guide for other railway vehicles, for example locomotives, metros, trams, etc.

The standard applies to passengers in good health.

This standard applies to measurements of motions. It also applies to simulated motions.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 14363, Railway applications — Testing for the acceptance of running characteristics of railway vehicles — Testing of running behaviour and stationary tests

EN ISO 5353, Earth-moving machinery, and tractors and machinery for agriculture and forestry - Seat index point (ISO 5353:1995)

EN ISO 8041, Human response to vibration - Measuring instrumentation (ISO 8041:2005)

ISO 2631-1, Mechanical vibration and shock — Evaluation of human exposure to whole-body vibration — Part 1: General requirements

ISO 5348, Mechanical vibration and shock — Mechanical mounting of accelerometers

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

passengers

people travelling in a railway vehicle, without specific activities related to the transport

3.2

ride comfort

complex sensation produced during the application of oscillations and/or inertia forces, via whole-body transmission caused by the railway vehicle body motions

3.3

interfaces

contact parts between the vehicle body or seat and the passenger with the function of sustaining and guiding the passenger and of transmitting the weight of the same to the vehicle body itself, e.g. floor-feet



This is a free preview	 Purchase the entire 	e publication at the link below:
------------------------	---	----------------------------------

Product Page

- Dooking for additional Standards? Visit Intertek Inform Infostore
- Dearn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation