



National Standards Authority of Ireland
Údarás um Chaighdeáin Náisiúnta na hÉireann

IRISH STANDARD

I.S. EN 14637:2007

ICS 91.060.50
91.190

**BUILDING HARDWARE - ELECTRICALLY
CONTROLLED HOLD-OPEN SYSTEMS FOR
FIRE/SMOKE DOOR ASSEMBLIES -
REQUIREMENTS, TEST METHODS,
APPLICATION AND MAINTENANCE**

National Standards
Authority of Ireland
Glasnevin, Dublin 9
Ireland

Tel: +353 1 807 3800
Fax: +353 1 807 3838
<http://www.nsai.ie>

Sales
<http://www.standards.ie>

*This Irish Standard was
published under the authority
of the National Standards
Authority of Ireland and
comes into effect on:
7 December 2007*

**NO COPYING WITHOUT NSAI
PERMISSION EXCEPT AS
PERMITTED BY COPYRIGHT
LAW**

© NSAI 2007

Price Code R

Údarás um Chaighdeáin Náisiúnta na hÉireann

This page is intentionally left BLANK.

ICS 91.060.50; 91.190

English Version

**Building hardware - Electrically controlled hold-open systems for
fire/smoke door assemblies - Requirements, test methods,
application and maintenance**

Quincaillerie pour le bâtiment - Systèmes de retenue
contrôlés électriquement pour blocs-portes, coupe-feu ou
pare-fumée - Exigences, méthode d'essai, mise en œuvre
et maintenance

Schlösser und Baubeschläge - Elektrisch gesteuerte
Feststellanlagen für Feuer-/Rauchschutztüren -
Anforderungen, Prüfverfahren, Anwendung und Wartung

This European Standard was approved by CEN on 30 September 2007.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Page

| | |
|--|----|
| Foreword..... | 5 |
| Introduction | 6 |
| 1 Scope | 9 |
| 2 Normative references | 9 |
| 3 Terms, definitions and abbreviated term | 11 |
| 4 Classification..... | 13 |
| 4.1 Coding system | 13 |
| 4.2 Category of use (first digit)..... | 13 |
| 4.3 Durability (second digit)..... | 13 |
| 4.4 Door type (third digit) | 13 |
| 4.5 Suitability for use on fire/smoke door assemblies (fourth digit)..... | 14 |
| 4.6 Safety (fifth digit) | 14 |
| 4.7 Corrosion resistance (sixth digit) | 14 |
| 4.8 Example of classification | 14 |
| 5 Requirements and test methods for components of a hold-open system | 15 |
| 5.1 General..... | 15 |
| 5.2 Fire detectors | 15 |
| 5.2.1 Smoke detectors | 15 |
| 5.2.2 Heat detectors | 15 |
| 5.2.3 Resetting the detectors | 15 |
| 5.3 Power supply units | 16 |
| 5.3.1 All power supply units | 16 |
| 5.3.2 For power supply units with stand-by parallel operation..... | 16 |
| 5.4 Control units..... | 17 |
| 5.4.1 General..... | 17 |
| 5.4.2 Control units in stand-alone hold-open systems (single-line systems) | 17 |
| 5.4.3 Control units in fire detection and fire alarm systems (multi-line systems) | 17 |
| 5.5 Hold-open devices | 18 |
| 5.5.1 General..... | 18 |
| 5.5.2 Hold-open devices for swing doors..... | 18 |
| 5.5.3 Hold-open devices for sliding doors, lifting doors, industrial doors and roller shutters | 18 |
| 5.5.4 Automatic door operators..... | 19 |
| 5.5.5 Low energy/power assisted swing door operators..... | 19 |
| 5.5.6 Free-swing door closers | 20 |
| 5.6 Auxiliary equipment | 20 |
| 5.6.1 Manual control push-buttons and switches | 20 |
| 5.6.2 Presence sensors (electro-sensitive protective equipment) | 20 |
| 5.6.3 Door position sensors..... | 21 |
| 5.6.4 Remote indicating devices | 21 |
| 5.6.5 Manual reset..... | 21 |
| 6 Requirements for the hold-open system..... | 21 |
| 6.1 Design and performance..... | 21 |
| 6.2 Product information..... | 22 |
| 6.2.1 General..... | 22 |
| 6.2.2 For installation and maintenance..... | 22 |
| 6.2.3 For initial hold-open system test | 23 |
| 6.3 Requirements not covered under Clause 5 | 23 |
| 6.4 Electromagnetic compatibility (EMC) | 23 |

| | | |
|---------|--|----|
| 6.5 | Additional design requirements for connection of components to fire alarm systems | 24 |
| 6.6 | Electrical safety | 24 |
| 6.7 | Durability | 24 |
| 6.8 | Environmental behaviour | 25 |
| 6.8.1 | Dry heat | 25 |
| 6.8.2 | Cold | 25 |
| 6.8.3 | Damp heat, steady state (operational) | 25 |
| 6.8.4 | Corrosion | 25 |
| 6.8.5 | Vibration | 25 |
| 6.9 | Supply voltage variations | 25 |
| 7 | System tests | 25 |
| 7.1 | General | 25 |
| 7.2 | Test apparatus | 26 |
| 7.3 | Theoretical analysis | 27 |
| 7.4 | Test methods | 27 |
| 7.4.1 | General | 27 |
| 7.4.2 | Design verification | 28 |
| 7.4.3 | Performance tests | 28 |
| 7.4.4 | Check of switching device capabilities of the control unit | 30 |
| 7.4.5 | Short-circuit test | 30 |
| 7.4.6 | Electrical safety tests | 30 |
| 7.4.7 | Electromagnetic compatibility (EMC) tests | 30 |
| 7.4.8 | Environmental tests | 31 |
| 7.4.9 | Corrosion test | 32 |
| 7.4.10 | Vibration test, sinusoidal (operational) | 33 |
| 7.4.11 | Vibration test, sinusoidal (endurance) | 33 |
| 8 | Marking | 35 |
| 8.1 | Components | 35 |
| 8.2 | Hold-open system | 35 |
| Annex A | (informative) Recommendations for planning and design of the hold-open system | 36 |
| A.1 | General | 36 |
| A.2 | Restrictions | 36 |
| A.3 | Detectors | 36 |
| A.3.1 | Selection of detector type | 36 |
| A.3.2 | Positioning and number of detectors | 37 |
| A.4 | Selection of hold-open device | 43 |
| A.4.1 | General | 43 |
| A.4.2 | Swing doors | 43 |
| A.4.3 | Sliding doors | 44 |
| A.4.4 | Roller shutter and lifting doors | 44 |
| A.4.5 | Automatic doors | 44 |
| A.5 | Manual release and manual control | 44 |
| A.5.1 | General | 44 |
| A.5.2 | Location of switch/push-button | 45 |
| A.6 | Interconnecting cables | 45 |
| A.7 | Guidance on competence and responsibilities for individual installations in individual buildings | 45 |
| A.7.1 | Planning | 45 |
| A.7.2 | Installation | 45 |
| Annex B | (informative) Recommendations for installation and fixing of the hold-open system | 46 |
| Annex C | (informative) Recommendations for acceptance inspection of the hold-open system | 47 |
| Annex D | (informative) Acceptance inspection report form | 48 |
| Annex E | (informative) Recommendations for usage and maintenance of the hold-open system | 50 |
| E.1 | Usage of installations | 50 |
| E.1.1 | General | 50 |
| E.1.2 | Periodic inspection | 50 |

| | | |
|------------------------------|--|-----------|
| E.2 | Routine site inspection report form | 50 |
| Annex F (informative) | Evaluation of conformity | 52 |
| F.1 | General | 52 |
| F.1.1 | Introduction | 52 |
| F.1.2 | Initial type test | 52 |
| F.1.3 | Characteristics | 52 |
| F.1.4 | Use of historical data | 53 |
| F.1.5 | Treatment of calculated values and design | 53 |
| F.1.6 | Sampling, testing and conformity criteria | 53 |
| F.2 | Factory production control (FPC) | 53 |
| F.2.1 | General | 53 |
| F.2.2 | FPC requirements for all manufacturers | 54 |
| F.3 | Further testing of sample systems | 54 |
| F.3.1 | Periodic testing | 54 |
| F.3.2 | Yearly testing | 54 |
| F.3.3 | Manufacturer-specific FPC system requirements | 54 |
| Annex G (informative) | Type test report and list of approved components | 57 |
| G.1 | Test report | 57 |
| G.2 | List of approved components | 57 |
| Annex H (informative) | Example methodology for theoretical analysis | 58 |
| H.1 | Introduction | 58 |
| H.2 | Points for analysis | 58 |
| H.2.1 | General | 58 |
| H.2.2 | List of characteristics | 58 |
| Bibliography | | 62 |
| | | |
| Figure 1 | — Basic system components with essential functions | 6 |
| Figure 2 | — Typical system with additional functions and components | 7 |
| Figure 3 | — Logic diagram for modes of operation of an electrically controlled hold-open system | 8 |
| Figure A.1 | — Ceiling types and critical dimensions | 38 |
| Figure A.2 | — Installation area in accordance with A.3.2.1 | 39 |
| Figure A.3 | — Flow chart to determine the requisite number of detectors | 40 |
| Figure A.4 | — Typical electrically controlled hold-open system with release of connected hold-open devices triggered directly by the FDAS (see A.3.2.2 a))..... | 41 |
| Figure A.5 | — Typical electrically controlled hold-open system with release of connected hold-open devices by the control unit of the hold-open system driven by the information coming from the FDAS (see A.3.2.2 b)) | 42 |
| Table G.1 | — List of approved components | 57 |

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-