

Irish Standard I.S. EN 62267:2009

Railway applications - Automated urban guided transport (AUGT) - Safety requirements (IEC 62267:2009 (EQV))

© NSAI 2009

No copying without NSAI permission except as permitted by copyright law.

Incorporating amendments/corrigenda issued since publication:	
	Incorporating amendments/corrigenda issued since publication:

This document replaces:

This document is based on:
EN 62267:2009

This document was published
under the authority of the NSAI and
comes into effect on:

This document is based on:
EN 62267:2009

Published:
4 December, 2009

2 February, 2010

NSAI T +353 1 807 3800 Sales:

 1 Swift Square,
 F +353 1 807 3838
 T +353 1 857 6730

 Northwood, Santry
 E standards@nsai.ie
 F +353 1 857 6729

 Dublin 9
 W NSAI.ie
 W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

EUROPEAN STANDARD

EN 62267

NORME EUROPÉENNE EUROPÄISCHE NORM

December 2009

ICS 45.060

English version

# Railway applications Automated urban guided transport (AUGT) Safety requirements

(IEC 62267:2009)

Applications ferroviaires -Transports guidés urbains automatiques (AUGT) -Exigences de sécurité (CEI 62267:2009) Bahnanwendungen - Automatischer städtischer schienengebundener Personennahverkehr (AUGT) -Sicherheitsanforderungen (IEC 62267:2009)

This European Standard was approved by CENELEC on 2009-10-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

# **CENELEC**

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: Avenue Marnix 17, B - 1000 Brussels

EN 62267:2009 - 2 -

#### **Foreword**

The text of document 9/1261/FDIS, future edition 1 of IEC 62267, prepared by IEC TC 9, Electrical equipment and systems for railways, was submitted to the IEC-CENELEC parallel vote and was approved by CENELEC as EN 62267 on 2009-10-01.

The following dates were fixed:

 latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement

(dop) 2010-07-01

 latest date by which the national standards conflicting with the EN have to be withdrawn

(dow) 2012-10-01

Annex ZA has been added by CENELEC.

#### **Endorsement notice**

The text of the International Standard IEC 62267:2009 was approved by CENELEC as a European Standard without any modification.

In the official version, for Bibliography, the following notes have to be added for the standards indicated:

IEC 61508 NOTE Harmonized in EN 61508 series (not modified).

IEC 62128-1 NOTE Identical to EN 50122-1:1997.

IEC 62236 NOTE In Europe, the series EN 50121 applies.

IEC 62279 NOTE In Europe, EN 50128 applies.

- 3 - EN 62267:2009

# Annex ZA (normative)

# Normative references to international publications with their corresponding European publications

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE 1 When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

NOTE 2 Where a standard cited below belongs to the EN 50000 series, this European Standard applies instead of the relevant International Standard.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	EN/HD	<u>Year</u>
IEC 62278	2002	Railway applications - Specification and demonstration of reliability, availability, maintainability and safety (RAMS)	EN 50126-1 + corr. May	1999 2006
IEC 62290-1	_1)	Railway applications - Urban guided transport management and command/control systems - Part 1: System principles and fundamental concepts		2006 <sup>2)</sup>
IEC 62425	_1)	Railway applications - Communication, signalling and processing systems - Safety related electronic systems for signalling	EN 50129	2003 <sup>2)</sup>

<sup>1)</sup> Undated reference.

<sup>&</sup>lt;sup>2)</sup> Valid edition at date of issue.

This is a free page sample. Access the full version online.

I.S. EN 62267:2009

This page is intentionally left BLANK.

- 2 -

# 62267 © IEC:2009

# **CONTENTS**

FOI	REWO	DRD		5
INT	RODU	JCTION		7
1	Scop	e		8
2	Norm	ative re	ferences	10
3	Term	s, defini	itions and abbreviations	10
	3.1	Terms	and definitions	11
	3.2		iations	
4	Meth			
	4.1	System	n definition and application conditions	. 14
	4.2	-	l analysis at top system level	
	4.3	Safety	requirements	14
5	Syste	em desc	ription	14
	5.1	Station		15
	5.2	Train		15
	5.3	Guidev	vay between stations	16
	5.4	System	n boundaries	. 17
6	Entiti	es to be	protected	18
	6.1	Person	s	18
		6.1.1	Passengers	18
		6.1.2	Staff	18
		6.1.3	External emergency services	
		6.1.4	Public	
	6.2	-	ty	
7	Ident		zardous situations and possible safeguards	
	7.1	Superv	ising guideway	
		7.1.1	Prevent collisions with obstacles	
		7.1.2	Prevent collisions with persons	
	7.2	•	ising passenger transfer	
		7.2.1	Control passenger doors	
		7.2.2	Prevent injuries to persons between cars or between platform and train	
		7.2.3	Ensure safe starting conditions	
	7.3	Operat	ing a train	
		7.3.1	Put in or take out of operation	
		7.3.2	Supervise the status of the train	. 26
	7.4	Ensurir	ng detection and management of emergency situations	. 27
8	Safet	y requir	ements	.30
	8.1	Genera	al requirements	30
		8.1.1	Public works regulations to protect the guideway	. 30
		8.1.2	Fire protection	.31
		8.1.3	Systems and equipment	. 31
		8.1.4	Rules for passenger behaviour	32
	8.2	Monito	ring the AUGT system	32
		8.2.1	Monitoring by the OCC staff	
		8.2.2	Action of operational staff	
		8.2.3	Communication systems	33

62267 © IEC:2009

- 3 -

8.3	•	tional rules	
	8.3.1	Rules for rescue of passengers	
	8.3.2	Rules for fire emergency	
	8.3.3	Rules for foreseeable vandalism	
	8.3.4	Rules for checking guideway clearance	
	8.3.5	Rules for start-up and shut down of operations	
	8.3.6	Rules for train operations in the depot	
	8.3.7	Rules for trains to be put in or taken out of operation	
	8.3.8	Rules for stranded train removal	
8.4	_	uards on platforms	
	8.4.1	Common safeguards for enclosed and open platforms	
	8.4.2	Enclosed platforms	
	8.4.3	Open platforms with detection systems	
8.5	•	uards in trains	
	8.5.1	Door closed supervision	
	8.5.2	Door release for passenger transfer	
	8.5.3	Door release for emergency opening	
	8.5.4	Emergency exits	
	8.5.5	On board obstacle detection device	
	8.5.6	Derailment detection device	
	8.5.7	On board video surveillance	
	8.5.8	Public address system (train)	
	8.5.9	On board announcement for taking a train out of operation	
		Emergency stop demand on board	
		Emergency call device on board	
		Fire and smoke detection (train)	
		Train status supervision and testing	
		Manual operation	
		Safe speed during automatic coupling	
		Reaction to unexpected train movement	
		Warning means in the train for evacuation	
8.6	•	uards for passenger transfer area	
	8.6.1	Train immobilisation during passenger transfer	
	8.6.2	Safeguards related to the opening of the doors	
	8.6.3	Safeguards related to the closing of the doors	
	8.6.4	Marking of train door areas on the platform	
	8.6.5	Surveillance by operational staff	
	8.6.6	Safeguards related to gap between train and platform	
	8.6.7	Safeguards related to coupling area between cars	
	8.6.8	Safeguards related to space between train and platform screen	51
	8.6.9	Safeguards to protect passengers from electrocution after falling into	<b>-</b> 4
0.7	0 - (	the gap	
8.7	_	Jards for guideway	
	8.7.1	Segregated guideway	
	8.7.2	Warning means along the guideway	
	8.7.3	Physical barriers along the track	
	8.7.4	Physical barriers beside bridges	52
	8.7.5	Intrusion detection device between platform track and guideway between stations	52
		2020 0	52

- 4 - 62267 © IEC:2009

		8.7.6	Guideway intrusion detection device	53
		8.7.7	Wayside obstacle detection device	53
		8.7.8	Platform end door with controlled access	53
		8.7.9	Emergency exit from physically segregated guideway	53
		8.7.10	Fire and smoke detection (guideway between stations)	53
			Water flooding protection	
			Level crossing	
			Work zones	
_	8.8		ards for transfer areas and depots	
9			or use	
10	Spec	ific safe	ty requirements for upgrading existing lines to DTO or UTO	56
11	Verifi	cation o	of safety	57
	11.1	Docum	entation and responsibilities	58
			ation process	
		•	ative) Role of the OCC	
Bib	liogra	ohy		61
Fig	ure 1 -	- Life C	ycle Phases covered by this standard (see Figure 10 of IEC 62278)	13
Fig	ure 2 -	– Bound	lary of the station subsystem	15
Fig	ure 3 -	– Bound	lary of the "guideway between stations" subsystem	16
Fig	ure 4 -	– Bound	lary of the "guideway between stations" subsystem with level crossing	17
_			lary of the "guideway between stations" subsystem with sidings	
_			cation of safety	
_			e of the OCC in the safety of the system	
' '9	u10 / (.	1 1000	of the GGG in the surety of the system	00
Tak	nla 1 _	Grades	s of automation	o
			at collisions with obstacles	
			t collisions with persons	
			t injuries to persons associated with opening and closing passenger	
			it injuries to persons between cars or between platform and train	
			it passenger injury during train starting	
			It harm to passengers in relation to taking the train out of operation or	
			n operation	26
Tal	ole 8 –	Preven	it injury to person resulting from train failures	26
Tak	۵ مار	Dravan	at injury to persons related to emergency situations	27

62267 © IEC:2009

- 5 -

# INTERNATIONAL ELECTROTECHNICAL COMMISSION

# RAILWAY APPLICATIONS – AUTOMATED URBAN GUIDED TRANSPORT (AUGT) – SAFETY REQUIREMENTS

### **FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international
  consensus of opinion on the relevant subjects since each technical committee has representation from all
  interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

This International Standard has been prepared by IEC technical committee 9: Electrical equipment and systems for railways.

This standard cancels and replaces IEC/PAS 62267:2005.

The text of this standard is based on the following documents:

FDIS	Report on voting
9/1261/FDIS	9/1272/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

**-6-**

62267 © IEC:2009

The committee has decided that the contents of this publication will remain unchanged until the maintenance result date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- · reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

62267 © IEC:2009

**-7-**

### INTRODUCTION

This International Standard is a generic guideline providing recommendations to assist railway authorities and safety regulatory authorities to define safety requirements appropriate to AUGT systems. The generic requirements recommended in this standard are based on the experience gained from AUGT systems already in operation. Safety requirements for each specific application, however, can only be defined from the results of a risk analysis, taking into consideration the conditions in which the AUGT system is to be set up and based on the risk acceptance principles prevailing in the local environment. The standard applicable for conducting a mandatory and comprehensive risk analysis of an AUGT system is IEC 62278 (RAMS).

In view of the diversity of the technical solutions that may be adopted for new AUGT systems and the diversity of operational conditions, the list of generic hazardous situations considered in this standard should be regarded as a minimum list. The requirements for a safeguard as described in this standard are intended as minimum requirements in case a specific safeguard is applied to mitigate the related hazardous situation. However, the specific risk analysis may show that some requirements of a chosen safeguard should be modified to take into account some specific conditions. Each specific design of the new AUGT system and each aspect of the specific topographic, environmental, social or legal environment of the new AUGT system can also generate new hazards and therefore may require additional safety requirements. A specific hazard analysis to identify additional requirements or requirements to be modified is therefore always a necessity.

This standard, therefore, does not and could not prescribe any specific means that could, without a fail, mitigate risks arising from hazardous situations. Rather, it identifies a list of foreseeable hazardous situations, derived from the elementary consideration that functions assumed by the driver and staff in conventional systems are replaced in AUGT systems by automated functions or other safeguards. It is the purpose of this standard that this list of hazardous situations should be carefully considered during the risk analysis carried out for any new AUGT system.

In addition to generic hazardous situations, this standard also describes possible and widely implemented safeguards that the specific risk analysis may well show to be adapted to the specific application.

It should be noted that not all hazardous situations identified in the context of one or other of the large number of different AUGT systems already in operation in the world have necessarily been covered in this standard. Nor would it have been necessarily helpful. Neither could this standard describe all the possible safeguards demanded by each and every specific application.

This standard does not require that a safeguard be put in place for every generic hazardous situation identified. This is because often, the risk associated with a hazardous situation may be assessed as tolerable without the need for a safeguard. According to IEC 62278, it is the responsibility of the railway authority, in agreement with the Safety Regulatory Authority having jurisdiction, to decide on the tolerability of each risk and on the necessity of a specific safeguard, taking into account their specific risk acceptance criteria and legal requirements that are applicable for the specific AUGT application.

**-8-**

62267 © IEC:2009

# RAILWAY APPLICATIONS – AUTOMATED URBAN GUIDED TRANSPORT (AUGT) – SAFETY REQUIREMENTS

### 1 Scope

This International Standard covers high-level safety requirements applicable to automated urban guided transport systems, with driverless or unattended self-propelled trains, operating on an exclusive guideway.

This standard only deals with the safety requirements needed to compensate for the absence of a driver or attendant staff who would otherwise be responsible for some or all of train operation functions (see Table 1), depending on the level of automation of the system (see shaded areas in Table 1 and see 3.1 for a definition of the different grades of automation).

The requirements of this standard are restricted to transports systems as defined in Clause 5 and to DTO and UTO as defined in 3.1.4 and 3.1.20, respectively (see the shaded areas in Table 1).

62267 © IEC:2009

**-** 9 **-**

Table 1 - Grades of automation

Basic functions of train operation		On-sight train operation	Non- automated train operation	Semi- automated train operation	Driverless train operation	Unattended train operation
		TOS	NTO	STO	DTO	UTO
			GOA1	GOA2	GOA3	GOA4
Ensuring safe	Ensure safe route	X (points command/ control in system)	S	S	S	S
movement of trains	Ensure safe separation of trains	Х	S	S	S	S
	Ensure safe speed	х	X (partly supervised by system)	S	S	S
Driving	Control acceleration and braking	Х	Х	S	S	S
Supervising	Prevent collision with obstacles	X	Х	Х	S	S
guideway	Prevent collision with persons	X	X	X	S	S
	Control passengers doors	X	Х	Х	X or S	S
Supervising passenger transfer	Prevent injuries to persons between cars or between platform and train	Х	X	Х	X or S	S
	Ensure safe starting conditions	X	X	X	X or S	S
Operating a	Put in or take out of operation	X	Χ	Х	X	S
train	Supervise the status of the train	Х	Х	Х	Х	S
Ensuring detection and management of emergency situations	Perform train diagnostic, detect fire/smoke and detect derailment, handle emergency situations (call/evacuation, supervision)	Х	Х	Х	Х	S and/or staff in OCC

#### NOTE

X = responsibility of operations staff (may be realised by technical system).

S = realised by technical system.

This standard does not specifically look at security issues. However, aspects of safety requirements may apply to assuring security within the transport system.

NOTE The definitions of "security" and "safety" are given by IEC 62278.

Application of this standard is subsidiary to the responsibility of the transport authority and the safety regulatory authority (see IEC 62278) and to the specific laws and decrees applicable within the prevailing environment (economic, social, political, etc.) where the transport system is located, taking into account:

- social risk acceptance in different cultures or different national legal regulations (e.g. SHOREI, BOStrab) or principles (e.g. GAME, ALARP);
- · laws and decrees in different states;
- special or different requirements specified by the safety regulatory authority or by an independent assessor in charge of the specific application;

the responsibility for "safe operation" by the transport authority.

This standard does not apply to the following types of transport systems, unless specifically required by the Transport Authority:

- APMs (Automated People Movers) operating entirely inside a privileged environment such as an airport, a commercial centre or a leisure resort;
- amusement rides and roller-coasters, generally featuring a single station so that passengers board and alight the system at the same location;
- intercity and mainline train services, generally operating in a rural environment on part of their routes;
- cable-driven systems;
- systems featuring electronically guided vehicles with optical sensors, magnetic sensors, or similar devices/systems.

This standard is not concerned with risks arising during works for construction, installation, modification and dismantling of a system.

This standard is not concerned with pre-existing DTO or UTO systems (see definitions in 3.1) that were designed before this standard took effect.

In the case of upgrading an existing transport system to a DTO or UTO system, the risks associated with the existing system are outside the scope of this standard. However, this standard and the risk analysis process described are relevant for the additional subsystems and possibly for the transition process itself. Therefore, the application of the standard is at the discretion of the safety regulatory authority.

In the case of extending or modifying an existing DTO or UTO system in operation, this standard applies only if the change is significant as determined by the safety regulatory authority. However, the risks due to the relationship with the unchanged parts of existing systems (e.g. rolling stock, traction power supply, signalling and platforms) should be taken into account.

# 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62278:2002, Railway applications – Specification and demonstration of reliability, availability, maintainability and safety (RAMS)

IEC 62290-1, Railway applications – Urban guided transport management and command/control systems – Part 1: System principles and fundamental concepts

IEC 62425, Railway applications – Communication, signalling and processing systems – Safety related electronic systems for signalling

## 3 Terms, definitions and abbreviations

For the purposes of this document, the following terms, definitions and abbreviations apply.

**- 10 -**

62267 © IEC:2009



**Product Page** 

- Dooking for additional Standards? Visit Intertek Inform Infostore
- Dearn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation