This is a free page sample. Access the full version online.



National Standards Authority of Ireland

IRISH STANDARD

I.S. EN 1894:2005

ICS 81.060.30

ADVANCED TECHNICAL CERAMICS -

MECHANICAL PROPERTIES OF CERAMIC

COMPOSITES AT HIGH TEMPERATURE

UNDER INERT ATMOSPHERE -

DETERMINATION OF SHEAR STRENGTH BY

COMPRESSION LOADING OF

NOTCHED SPECIMENS

National Standards Authority of Ireland Glasnevin, Dublin 9 Ireland

Tel: +353 1 807 3800 Fax: +353 1 807 3838 http://www.nsai.ie

Sales http://www.standards.ie

This Irish Standard was published under the authority of the National Standards Authority of Ireland and comes into effect on: June 22, 2005

NO COPYING WITHOUT NSAI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

© NSAI 2005

Price Code F

Údarás um Chaighdeáin Náisiúnta na hÉireann

This is a free page sample. Access the full version online.

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 1894

April 2005

ICS 81.060.30

Supersedes ENV 1894:1996

English version

Advanced technical ceramics - Mechanical properties of ceramic composites at high temperature under inert atmosphere -Determination of shear strength by compression loading of notched specimens

Céramiques techniques avancées - Propriétés mécaniques des céramiques composites à haute température sous atmosphère neutre - Détermination de la résistance au cisaillement par compression d'éprouvettes entaillées Hochleistungskeramik - Mechanische Eigenschaften von keramischen Verbundwerkstoffen bei hoher Temperatur in inerter Atmosphäre - Bestimmung der Scherfestigkeit durch Druckbeanspruchung von gekerbten Proben

This European Standard was approved by CEN on 15 March 2005.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the Central Secretariat has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

EN 1894:2005 (E)

Contents

		Page
Foreword		3
1	Scope	4
2	Normative references	4
3	Definitions and symbols	4
4	Principle	4
5	Apparatus	5
6	Test specimens	6
7	Test specimen preparation	7
8	Test procedures	8
9	Calculation of results	9
10	Test report	10
Annex	A (informative) Examples of types of rupture	11

Foreword

This document (EN 1894:2005) has been prepared by Technical Committee CEN/TC 184 "Advanced technical ceramics", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2005, and conflicting national standards shall be withdrawn at the latest by October 2005.

This document supersedes ENV 1894:1996.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.

1 Scope

This document specifies the conditions for determination of the inter-laminar shear strength of ceramic matrix composite materials with continuous fibre reinforcement for temperatures up to 2 000 °C under a vacuum, or a gas atmosphere, which is inert to the material under test, by loading of notched specimens in compression.

NOTE 1 The use of a vacuum or a gas atmosphere is aimed at avoiding changes of the material to be tested due to chemical reaction with its environment during the test.

This document applies to all ceramic matrix composites with continuous fibre reinforcement, unidirectional (1D), bidirectional (2D), and tridirectional (xD, with 2 < x < 3), loaded along one principal axis of reinforcement.

NOTE 2 Care should be exercised in interpreting the results of the test method to obtain absolute values of the interlaminar shear strength of ceramic matrix composites for design purposes.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 60584-1, Thermocouples; Part 1: Reference tables (IEC 60584-1:1995)

EN 60584-2, Thermocouples; Part 2: Tolerances (IEC 60584-2:1982 + A1:1989)

EN ISO 7500-1, Metallic materials — Verification of static uniaxial testing machines — Part 1: Tension/compression testing machines - Verification and calibration of the force-measuring system (ISO 7500-1:2004)

ISO 3611, Micrometer callipers for external measurement

3 Definitions and symbols

For the purposes of this document, the following definitions and symbols apply.

3.1

```
test temperature, T
temperature at the centre of the test piece
```

3.2

shear failure force, F

maximum force required during a test carried out up to failure

3.3

interlaminar shear strength, ILSS

ratio calculated on the basis of the shear failure force and the shear loaded area

4 Principle

The test consists of measuring the force required to fracture a transversely notched test specimen of defined shape and dimensions, heated to the test temperature and subjected to compressive loading in direction 1 or 2, such that failure occurs in the form of inter-laminar shear in plane 12. The test is performed at constant crosshead displacement rate.

NOTE The test duration is limited to reduce creep effects.



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation