



NSAI
Standards

Irish Standard
I.S. EN 1634-2:2008

Fire resistance and smoke control tests for door, shutter and openable window assemblies and elements of building hardware - Part 2: Fire resistance characterisation test for elements of building hardware

I.S. EN 1634-2:2008

Incorporating amendments/corrigenda issued since publication:

<i>This document replaces:</i>	<i>This document is based on:</i> EN 1634-2:2008	<i>Published:</i> 12 November, 2008	
This document was published under the authority of the NSAI and comes into effect on: 16 January, 2009		ICS number: 13.220.50 91.060.50	
NSAI 1 Swift Square, Northwood, Santry Dublin 9	T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie	Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie	Price Code: R
Údarás um Chaighdeáin Náisiúnta na hÉireann			

ICS 13.220.50; 91.060.50

English Version

Fire resistance and smoke control tests for door, shutter and
openable window assemblies and elements of building hardware
- Part 2: Fire resistance characterisation test for elements of
building hardware

Feuerwiderstands- und Rauchleckageprüfungen für Tür-
und Abschlusseinrichtungen, Fenster sowie Beschläge -
Teil 2: Charakterisierungsprüfungen zum Feuerwiderstand
von Beschlägen

This European Standard was approved by CEN on 13 September 2008.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: rue de Stassart, 36 B-1050 Brussels

Contents

Page

Foreword	6
Introduction	7
1 Scope.....	9
2 Normative references	9
3 Terms and definitions.....	10
4 Test conditions.....	11
4.1 Ambient conditions within laboratory	11
4.2 Heating conditions	12
4.3 Pressure conditions.....	12
4.3.1 General.....	12
4.3.2 Pressure conditions for testing single axis hinges on side hung doors or openable windows	12
4.3.3 Pressure conditions for testing securing devices	12
4.3.4 Pressure conditions for testing non-edge mounted items of building hardware	13
4.3.5 Pressure conditions for testing surface mounted overhead closing devices.....	13
4.3.6 Pressure conditions for the ignitibility test.....	13
5 Test construction	13
5.1 General.....	13
5.2 Test construction for evaluating single axis hinges	13
5.3 Test construction for evaluating securing devices	14
5.4 Test construction for evaluating non-edge mounted items of building hardware	14
5.5 Test construction for evaluating ignition risk for items attached to the unexposed face of uninsulating steel or glazed doors	14
5.6 Test construction for evaluating surface mounted overhead controlled door closing devices for use on unlatched doorsets	14
6 Test specimen	15
6.1 Associated construction	15
6.2 Conditioning	15
6.3 Fixings.....	15
6.4 Test specimen for evaluating single axis hinges	15
6.4.1 Design of test specimen.....	15
6.4.2 Number of specimens.....	16
6.4.3 Gap sizes	16
6.4.4 Installation	17
6.5 Test specimen for evaluating securing devices	17
6.5.1 Design of test specimen.....	17
6.5.2 Number of test specimens	17
6.5.3 Gap sizes	17
6.5.4 Installation	17
6.6 Test specimen for the evaluation of non-edge mounted items of building hardware (including air transfer grilles)	18
6.6.1 Design of test specimen.....	18
6.6.2 Number of test specimens	18
6.6.3 Gap sizes	18
6.6.4 Installation	18
6.7 Test specimen for evaluation of ignition risk for surface mounted controlled overhead door closing devices	18
6.7.1 Design of test specimen.....	18

6.7.2	Number of test specimens	19
6.7.3	Gap sizes	19
6.7.4	Installation	19
6.8	Test specimen for evaluating surface mounted overhead controlled door closing devices for their ability to retain an unlatched timber door closed.....	19
6.8.1	Design	19
6.8.2	Number of specimens.....	19
6.8.3	Gap sizes	19
6.8.4	Installation	19
7	Loading and restraint	20
7.1	General.....	20
7.2	Loading and restraint conditions for evaluating single axis hinges	20
7.2.1	Leaf mass.....	20
7.2.2	Applied point load to simulate distortion forces	20
7.3	Loading and restraint conditions for evaluating securing devices.....	20
7.3.1	Leaf mass.....	20
7.3.2	Applied point load to simulate distortion forces	20
8	Test equipment.....	21
8.1	Furnace	21
8.2	Measurement of ambient conditions	21
8.3	Measurement of furnace conditions	21
8.4	Loading equipment.....	21
8.4.1	Types of loading.....	21
8.4.2	Method of loading	21
8.5	Monitoring instrumentation	21
8.5.1	Measurement of unexposed surface temperature.....	21
8.5.2	Measurement of displacement	22
8.5.3	Measurement of force.....	22
9	Pre-test examination/characterization of the specimen	22
9.1	General.....	22
9.2	Characterization of the test specimen for evaluating a single axis hinge	22
9.2.1	Dimension of the components	22
9.2.2	Location of the hinges.....	22
9.2.3	Materials.....	23
9.2.4	Fixing of hinge to the associated construction	23
9.3	Characterization of the test specimen for evaluating securing devices.....	23
9.3.1	Dimensions of the components	23
9.3.2	Location of the securing device	23
9.3.3	Materials.....	23
9.3.4	Fixing of securing device.....	23
9.4	Characterisation of the test specimen for evaluating non-edge mounted items.....	23
9.5	Characterisation of the test specimen for evaluating the ignition risk of surface mounted overhead controlled door closing devices	23
9.6	Characterisation of the test specimen for evaluating surface mounted overhead controlled door closing devices.....	24
9.6.1	Dimensions of the components	24
9.6.2	Materials.....	24
9.6.3	Fixing of the surface mounted overhead controlled door closing device.....	24
10	Test procedure	24
10.1	Common procedures	24
10.1.1	General.....	24
10.1.2	Fixing of unexposed face thermocouples	24
10.1.3	Ambient air temperature.....	24
10.1.4	Application of loading	25
10.1.5	Force measurement	25
10.1.6	Displacement measurement	25
10.1.7	Establishment of datum values	25

10.2	Commencement of heating and control of heating conditions	25
10.3	Test protocols	25
10.3.1	Single axis hinges	25
10.3.2	Securing devices	25
10.3.3	Non edge mounted items	26
10.3.4	Face fixed controlled door closing devices	26
10.4	Monitoring of criteria	26
10.5	Termination of test	26
11	Performance criteria	26
11.1	General	26
11.2	Resistance to loading	27
11.3	Maintenance of closing force	27
11.4	Integrity (E)	27
11.5	Insulation (I)	27
11.6	Criteria relevant to each item under evaluation	27
11.6.1	Single axis hinges	27
11.6.2	Securing devices	27
11.6.3	Non-edge mounted items of building hardware	28
11.6.4	Surface mounted overhead controlled door closing devices	28
12	Expression of results	28
12.1	General	28
12.2	Single axis hinges and securing devices	28
12.3	Non-edge mounted items of building hardware	29
12.4	Evaluating the ignition risk from attaching surface mounted overhead controlled door closing devices to the unexposed face of uninsulating steel or glazed doors	29
12.5	Surface mounted overhead controlled door closing devices for use on unlatched door assemblies	29
13	Test report	29
14	Field of direct application	30
14.1	General	30
14.1.1	Introduction	30
14.1.2	Basis of the field of direct application	30
14.2	Single action hinges	31
14.2.1	General	31
14.2.2	Frame	31
14.2.3	Door leaf	31
14.2.4	Configuration of the assembly	32
14.2.5	Door lipping/leaf edge construction	32
14.2.6	Intumescent protection	33
14.2.7	Hinge blade clearance	33
14.2.8	Fixings	33
14.2.9	Gaps	33
14.3	Securing devices	33
14.3.1	General	33
14.3.2	Frames	34
14.3.3	Door leaves and openable windows	34
14.3.4	Configuration of the assembly	35
14.3.5	Door lipping/leaf or window edge construction	35
14.3.6	Intumescent protection	35
14.3.7	Fixings	36
14.3.8	Position of locking plate and forend	36
14.3.9	Gap	36
14.4	Surface mounted overhead controlled door closing devices	36
14.4.1	Maintenance of closing force for unlatched door assemblies	36
14.4.2	Power size	37
14.4.3	Closer cover	37
14.5	Non edge-mounted items of building hardware	37

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-