



NSAI
Standards

Standard Recommendation
S.R. CEN/TR 15068:2009

Gas welding equipment -
Measurement of noise emitted by
blowpipe for welding, cutting,
heating, brazing and soldering -
Measurement method

S.R. CEN/TR 15068:2009

Incorporating amendments/corrigenda issued since publication:

<i>This document replaces:</i>	<i>This document is based on:</i> CEN/TR 15068:2009	<i>Published:</i>	
This document was published under the authority of the NSAI and comes into effect on: 26 May, 2009		ICS number: 25.160.30	
NSAI 1 Swift Square, Northwood, Santry Dublin 9	T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie	Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie	Price Code: D
Údarás um Chaighdeáin Náisiúnta na hÉireann			

ICS 25.160.30

English Version

**Gas welding equipment - Measurement of noise emitted by
blowpipe for welding, cutting, heating, brazing and soldering -
Measurement method**

Matériel de soudage aux gaz - Mesurage du bruit émis par
les chalumeaux destinés au soudage, brasage, coupage et
chauffage - Méthode de mesurage

Gasschweißgeräte - Messungen für von Brennern für
Schweißen, Schneiden, Wärmen, Hartlöten und Weichlöten
erzeugte Geräusche - Messverfahren

This Technical Report was approved by CEN on 17 February 2009. It has been drawn up by the Technical Committee CEN/TC 121.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	4
4 Measurement conditions	4
5 Procedure	6
6 Test results	6
7 Test report	6

Foreword

This document (CEN/TR 15068:2009) has been prepared by Technical Committee CEN/TC 121 "Welding", the secretariat of which is held by DIN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

1 Scope

This Technical Report specifies a test method for measuring the noise emitted by manual blowpipes according to EN ISO 5172 used for welding, cutting and allied processes.

This test method is used only for comparative purposes between manual blowpipes when tested under nominal conditions under clause 5.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 13622:2002, *Gas welding equipment — Terminology — Terms used for gas welding equipment*

EN 61260, *Electroacoustics — Octave-band and fractional-octave-band filters (IEC 61260:1995)*

EN 61672-1:2003, *Electroacoustics — Sound level meters — Part 1: Specifications (IEC 61672-1:2002)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in EN 13622:2002 and EN 61672-1:2003 apply.

4 Measurement conditions

4.1 General

Measurement can be performed indoors only.

To measure the maximum emitted noise, the blowpipe under test is set in such a way that flame axis be horizontal, at least 1,5 m above the ground level, at least 1,5 m from the ceiling and at least at 5 m from the walls. Noise is measured for each type of nozzle which can be fitted on the blowpipe under nominal gas supply conditions indicated by the manufacturer. Microphone of sound level meter is placed at 1 m from the nozzle tip (see 4.4, Figure 1).

4.2 Measurement and correction of background noise

Measurements of background noises shall be performed in order to guarantee that measurements of noise emitted by blowpipes are not influenced by interferences. Background sound pressure level shall be lower than noise level emitted by the blowpipe and background together by more than 6 dB.

If difference of level is within 6 dB and 15 dB, calculate corrections of noise level according to Equation (1):

$$L_{pA} = 10 \lg(10^{L_{pA, sb}/10} - 10^{L_{pA, b}/10}) \text{dB} \quad (1)$$

where

L_{pA} is the corrected noise level emitted by the blowpipe, in decibels;

$L_{pA, sb}$ is the sound pressure level of the blowpipe and the background noise together, in decibels;

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-