



NSAI
Standards

Irish Standard
I.S. EN ISO 3741:2010

Acoustics - Determination of sound power levels and sound energy levels of noise sources using sound pressure - Precision methods for reverberation test rooms (ISO 3741:2010)

I.S. EN ISO 3741:2010

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

<i>This document replaces:</i> EN ISO 3741:2009	<i>This document is based on:</i> EN ISO 3741:2010 EN ISO 3741:2009	<i>Published:</i> 1 October, 2010 29 July, 2009
This document was published under the authority of the NSAI and comes into effect on: 21 October, 2010		ICS number: 17.140.01
NSAI 1 Swift Square, Northwood, Santry Dublin 9	T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie	Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie
Údarás um Chaighdeáin Náisiúnta na hÉireann		

English Version

Acoustics - Determination of sound power levels and sound energy levels of noise sources using sound pressure - Precision methods for reverberation test rooms (ISO 3741:2010)

Acoustique - Détermination des niveaux de puissance et des niveaux d'énergie acoustiques émis par les sources de bruit à partir de la pression acoustique - Méthodes de laboratoire en salles d'essais réverbérantes (ISO 3741:2010)

Akustik - Bestimmung der Schalleistungs- und Schallenergiepegel von Geräusch- quellen aus Schalldruckmessungen - Hallraumverfahren der Genauigkeitsklasse 1 (ISO 3741:2010)

This European Standard was approved by CEN on 14 August 2010.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	3
Annex ZA	4

Foreword

The text of ISO 3741:2010 has been prepared by Technical Committee ISO/TC 43 "Acoustics" of the International Organization for Standardization (ISO) and has been taken over as EN ISO 3741:2010 by Technical Committee CEN/TC 211 "Acoustics" the secretariat of which is held by DS.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by April 2011, and conflicting national standards shall be withdrawn at the latest by April 2011.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN ISO 3741:2009.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive.

For relationship with EU Directive, see informative Annex ZA, which is an integral part of this document.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

Endorsement notice

The text of ISO 3741:2010 has been approved by CEN as a EN ISO 3741:2010 without any modification.

Annex ZA
(informative)

**Relationship between this European Standard and the
Essential Requirements of EU Directive 2006/42/EC**

This European Standard has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association to provide one means of conforming to Essential Requirements of the New Approach Directive 2006/42/EC on machinery.

Once this standard is cited in the Official Journal of the European Communities under that Directive and has been implemented as a national standard in at least one Member State, compliance with the normative clauses of this standard confers, within the limits of the scope of this standard, a presumption of conformity with the relevant Essential Requirements of that Directive and associated EFTA regulations.

WARNING — Other requirements and other EU Directives may be applicable to the products falling within the scope of this standard.

I.S. EN ISO 3741:2010
**INTERNATIONAL
STANDARD**

**ISO
3741**

Fourth edition
2010-10-01

**Acoustics — Determination of sound
power levels and sound energy levels of
noise sources using sound pressure —
Precision methods for reverberation test
rooms**

*Acoustique — Détermination des niveaux de puissance et des niveaux
d'énergie acoustiques émis par les sources de bruit à partir de la
pression acoustique — Méthodes de laboratoire en salles d'essais
réverbérantes*



Reference number
ISO 3741:2010(E)

© ISO 2010

PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction.....	v
1 Scope	1
2 Normative references	2
3 Terms and definitions	2
4 Reference meteorological conditions	6
5 Reverberation test room	6
6 Instrumentation and measurement equipment	10
7 Definition, location, installation, and operation of noise source under test.....	10
8 Measurements in the reverberation test room	12
9 Determination of sound power levels and sound energy levels	19
10 Measurement uncertainty	27
11 Information to be recorded.....	30
12 Test report.....	31
Annex A (informative) Guidelines for the design of reverberation test rooms	32
Annex B (informative) Guidelines for the design of rotating diffusing vanes	34
Annex C (normative) Reverberation test room qualification procedure for the measurement of broad-band sound	35
Annex D (normative) Reverberation test room qualification procedure for the measurement of discrete-frequency components.....	37
Annex E (informative) Extension of frequency range to frequencies below 100 Hz.....	42
Annex F (normative) Calculation of octave band sound power levels and sound energy levels, A-weighted sound power levels and A-weighted sound energy levels from one-third-octave band levels	45
Annex G (informative) Guidelines on the development of information on measurement uncertainty	48
Bibliography.....	60

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 3741 was prepared by Technical Committee ISO/TC 43, *Acoustics*, Subcommittee SC 1, *Noise*.

This fourth edition cancels and replaces the third edition (ISO 3741:1999), which has been technically revised. It also incorporates the Technical Corrigendum ISO 3741:1999/Cor.1:2001.

Introduction

This International Standard is one of the series ISO 3740^[2] to ISO 3747^[8], which specify various methods for determining the sound power levels and sound energy levels of noise sources including machinery, equipment and their sub-assemblies. The selection of one of the methods from the series for use in a particular application depends on the purpose of the test to determine the sound power level or sound energy level and on the facilities available. General guidelines to assist in the selection are provided in ISO 3740^[2]. ISO 3740^[2] to ISO 3747^[8] give only general principles regarding the operating and mounting conditions of the machinery or equipment for the purposes of the test. It is important that test codes be established for individual kinds of noise source, in order to give detailed requirements for mounting, loading, and operating conditions under which the sound power levels or sound energy levels are to be obtained.

The methods given in this International Standard require the source under test to be mounted in a reverberation test room having specified acoustical characteristics. The methods are then based on the premise that the sound power or sound energy of the source under test is directly proportional to the mean-square sound pressure averaged in space and time, and otherwise depends only on the acoustical and geometric properties of the room and on the physical constants of air.

For a source emitting sound in narrow bands of frequency or at discrete frequencies, a precise determination of the radiated sound power level or sound energy level in a reverberation test room requires greater effort than for a source emitting sound more evenly over a wide range of frequencies, because:

- a) the space- and time-averaged sound pressure along a short microphone path, or as determined with an array of a small number of microphones, is not always a good estimate of the space- or time-averaged mean-square pressure throughout the room;
- b) the sound power or sound energy radiated by the source is more strongly influenced by the normal modes of the room and by the position of the source within the room.

The increased measurement effort in the case of a source emitting narrow bands of sound or discrete tones consists of either the optimization and qualification of the test room or the use of a greater number of source locations and microphone positions (or increased path length for a moving microphone). The addition of low-frequency absorbers or the installation of rotating diffusers in the test room can help to reduce the measurement effort.

The methods specified in this International Standard permit the determination of the sound power level and the sound energy level in one-third-octave frequency bands, from which octave band data, A-weighted frequency data, and total unweighted sound can be computed.

This International Standard describes methods of accuracy grade 1 (precision grade) as defined in ISO 12001. The resulting sound power levels and sound energy levels include corrections to allow for any differences that might exist between the meteorological conditions under which the tests are conducted and reference meteorological conditions. For applications in reverberant environments where reduced accuracy is acceptable, reference can be made to ISO 3743-1^[3], ISO 3743-2^[4] or ISO 3747^[8].

Acoustics — Determination of sound power levels and sound energy levels of noise sources using sound pressure — Precision methods for reverberation test rooms

1 Scope

1.1 General

This International Standard specifies methods for determining the sound power level or sound energy level of a noise source from sound pressure levels measured in a reverberation test room. The sound power level (or, in the case of noise bursts or transient noise emission, the sound energy level) produced by the noise source, in frequency bands of width one-third-octave, is calculated using those measurements, including corrections to allow for any differences between the meteorological conditions at the time and place of the test and those corresponding to a reference characteristic impedance. Measurement and calculation procedures are given for both a direct method and a comparison method of determining the sound power level and the sound energy level.

In general, the frequency range of interest includes the one-third-octave bands with mid-band frequencies from 100 Hz to 10 000 Hz. Guidelines for the application of the specified methods over an extended frequency range in respect to lower frequencies are given in Annex E. This International Standard is not applicable to frequency ranges above the 10 000 Hz one-third-octave band.

NOTE For higher frequencies, the methods specified in ISO 9295 can be used.

1.2 Types of noise and noise sources

The methods specified in this International Standard are suitable for all types of noise (steady, non-steady, fluctuating, isolated bursts of sound energy, etc.) defined in ISO 12001.

The noise source under test can be a device, machine, component or sub-assembly. This International Standard is applicable to noise sources with a volume not greater than 2 % of the volume of the reverberation test room. For a source with a volume greater than 2 % of the volume of the test room, it is possible that the achievement of results as defined in ISO 12001:1996, accuracy grade 1 (precision grade) is not feasible.

NOTE In specific cases, the source volume can be increased to a maximum of 5 % of the room volume. In such cases, the relevant noise test code indicates the possible consequences on the measurement uncertainty.

1.3 Reverberation test room

The test rooms that are applicable for measurements made in accordance with this International Standard are reverberation test rooms meeting specified requirements (see Clause 5).

1.4 Measurement uncertainty

Information is given on the uncertainty of the sound power levels and sound energy levels determined in accordance with this International Standard, for measurements made in specific frequency bands and for the A-weighted sum of all frequency bands. The uncertainty conforms to ISO 12001:1996, accuracy grade 1 (precision grade).

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-