

Irish Standard I.S. EN ISO 12180-2:2011

Geometrical product specifications (GPS) -Cylindricity - Part 2: Specification operators (ISO 12180-2:2011)

© NSAI 2011

No copying without NSAI permission except as permitted by copyright law.

Incorporating amendments	/corrigenda/National Anne.	xes issued since public	ration:	
The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:				
I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.				
S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.				
SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.				
<i>This document replaces:</i> CEN ISO/TS 12180-2:2007				
This document is based on: EN ISO 12180-2:2011	. Published: 18 April, 2011			
This document was publish under the authority of the and comes into effect on: 18 April, 2011			ICS number: 17.040.20	
NSAI 1 Swift Square, Northwood, Santry Dublin 9	T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie	Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie		
Údarás um Chaighdeáin Náisiúnta na hÉireann				

EUROPEAN STANDARD

EN ISO 12180-2

NORME EUROPÉENNE EUROPÄISCHE NORM

April 2011

ICS 17.040.20

Supersedes CEN ISO/TS 12180-2:2007

English Version

Geometrical product specifications (GPS) - Cylindricity - Part 2: Specification operators (ISO 12180-2:2011)

Spécification géométrique des produits (GPS) - Cylindricité - Partie 2: Opérateurs de spécification (ISO 12180-2:2011)

Geometrische Produktspezifikation (GPS) - Zylindrizität -Teil 2: Spezifikationsoperatoren (ISO 12180-2:2011)

This European Standard was approved by CEN on 26 February 2011.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

EN ISO 12180-2:2011 (E)

Contents	Page
Foreword	3

Foreword

This document (EN ISO 12180-2:2011) has been prepared by Technical Committee ISO/TC 213 "Dimensional and geometrical product specifications and verification" in collaboration with Technical Committee CEN/TC 290 "Dimensional and geometrical product specification and verification" the secretariat of which is held by AFNOR.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by October 2011, and conflicting national standards shall be withdrawn at the latest by October 2011.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes CEN ISO/TS 12180-2:2007.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

Endorsement notice

The text of ISO 12180-2:2011 has been approved by CEN as a EN ISO 12180-2:2011 without any modification.

This is a free page sample. Access the full version online.

I.S. EN ISO 12180-2:2011

This page is intentionally left BLANK.

This is a free page sample. Access the full version online.

I.S. EN ISO 12180-2:2011 INTERNATIONAL STANDARD

ISO 12180-2

First edition 2011-04-01

Geometrical product specifications (GPS) — Cylindricity —

Part 2: **Specification operators**

Spécification géométrique des produits (GPS) — Cylindricité — Partie 2: Opérateurs de spécification



ISO 12180-2:2011(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2011

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

ISO 12180-2:2011(E)

Cont	tents	Page
Forew	ord	iv
Introd	uction	v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4 4.1 4.2	Complete specification operator	2
5	Compliance with the specification	2
	A (informative) Harmonic content of nominally cylindrical workpiece and extraction strategy	3
Annex	B (informative) Extraction strategies	7
Annex	C (informative) Relationship to the GPS matrix model	10
Biblio	graphy	12

ISO 12180-2:2011(E)

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12180-2 was prepared by Technical Committee ISO/TC 213, Dimensional and geometrical product specifications and verification.

This first edition of ISO 12180-2 cancels and replaces ISO/TS 12180-2:2003, which has been technically revised.

ISO 12180 consists of the following parts, under the general title *Geometrical product specifications (GPS)* — *Cylindricity*:

- Part 1: Vocabulary and parameters of cylindrical form
- Part 2: Specification operators

Introduction

This part of ISO 12180 is a geometrical product specification (GPS) standard and is to be regarded as a general GPS standard (see ISO/TR 14638). It influences chain link 3 of the chain of standards on form of a surface (independent of a datum).

The ISO/GPS Masterplan given in ISO/TR 14638 gives an overview of the ISO/GPS system of which this part of ISO 12180 is a part. The fundamental rules of ISO/GPS given in ISO 8015 apply to this part of ISO 12180 and the default decision rules given in ISO 14253-1 apply to specifications made in accordance with this part of ISO 12180, unless otherwise indicated.

For more detailed information on the relationship of this part of ISO 12180 to other standards and the GPS matrix model, see Annex C.

This part of ISO 12180 specifies the specification operators according to ISO 17450-2 for cylindricity of integral features.

At the time of publication of this part of ISO 12180, ISO/TC 213 has not been able to reach consensus on defaults for filter undulation per revolution (UPR), probe tip radius and method of association (reference cylinder). This means that it is necessary for a cylindricity specification to explicitly state which values are intended for use with these specification operations in order for it to be unique.

Consequently, if a specification does not explicitly state which values are to be used for one or more of these operators, the specification is ambiguous (see ISO 17450-2) and a supplier can use any value for the operator(s) not specified when proving conformance.

Extracting data always involves applying a certain filtering process. An additional filtering of the extracted data might or might not be applied. This additional filter can be a mean line filter (Gaussian, spline, wavelet, etc.) or a non-linear filter (e.g. morphological filter). The type of filtering influences the definition of cylindricity and the specification operators and, therefore, needs to be stated unambiguously.

- NOTE 1 Stylus filtering is not sufficient on its own to smooth a profile. In certain circumstances, it can create spurious high-frequency content, thus giving incorrect values. To correct this, a longwave pass filter is employed. A Gaussian filter is used, since this is the state-of-the-art in International Standards. This filter has some shortcomings, e.g. it can distort, rather than eliminate some roughness features and it can distort, rather than transmit correctly some waviness features. It is envisioned that new filters under development within ISO provide better solutions for several of these issues.
- NOTE 2 If a smaller tip radius than the one specified is used for a given cut-off length, the resulting measured value is generally higher. This effect is usually insignificant. If a larger tip radius is used, the resulting measured value is generally lower. The amount of change is heavily dependent on the surface measured.
- NOTE 3 The measuring force of 0 N is chosen to eliminate effects of elastic deformation of the workpiece from the specification operator. On metal surfaces with adequate thickness, the effect of normally occurring measuring forces is negligible.
- NOTE 4 Aliasing and other problems during extraction (see Annex A) due to the higher harmonic content of the skin model, in the roundness and straightness directions, can cause specification uncertainty.

This part of ISO 12180 is not intended to disallow any means of measuring cylindricity.

This is a free page sample. Access the full version online.

I.S. EN ISO 12180-2:2011



Product Page

- Dooking for additional Standards? Visit Intertek Inform Infostore
- Dearn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation