Irish Standard
I.S. EN 50516-2-1:2011

Industrial connector sets and interconnect components to be used in optical fibre control and communication systems - Product specifications -- Part 2-1: Type ODVA PC industrial terminated on EN 60793-2-10 category A1a and A1b multimode fibre to meet the requirements of category I (industrial environments) as specified in EN 50173-1 and IEC 61753-1-3

I.S. EN 50516-2-1:2011

Incorporating amendments/corrigenda issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces:	*This document is based on:* EN 50516-2-1:2011	*Published:* 4 November, 2011

This document was published
under the authority of the NSAI and comes into effect on:

21 November, 2011

ICS number:
33.180.20

NSAI
1 Swift Square,
Northwood, Santry
Dublin 9

T +353 1 807 3800
F +353 1 807 3838
E standards@nsai.ie

W NSAI.ie

Sales:
T +353 1 857 6730
F +353 1 857 6729
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

I.S. EN 50516-2-1:2011

EUROPEAN STANDARD

NORME EUROPÉENNE

EUROPÄISCHE NORM

EN 50516-2-1

November 2011

ICS 33.180.20

English version

Industrial connector sets and interconnect components to be used in optical fibre control and communication systems - Product specifications - Part 2-1: Type ODVA PC industrial terminated on EN 60793-2-10 category A1a and A1b multimode fibre to meet the requirements of category I (industrial environments) as specified in EN 50173-1 and IEC 61753-1-3

Industrie-Steckverbindersätze und Verbindungsbauelemente für Lichtwellenleiter-Steuerungs- und Datenübertragungssysteme - Produktnormen - Teil 2-1: Industriesteckverbinder der Bauart ODVA-PC zum Anschluss an Mehrmodenfasern der Typen A1a und A1b nach EN 60793-2-10 für die Kategorie I (Industrieumgebung) nach den Festlegungen in EN 50173-1 und IEC 61753-1-3

This European Standard was approved by CENELEC on 2011-07-19. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

Ref. No. EN 50516-2-1:2011 E

Contents

1 Scope **7**
1.1 Product definition 7
1.2 Intermateability 7
1.3 Operating environment 7
1.4 Reliability 7
1.5 Quality assurance 7
2 Normative references **7**
3 Description **9**
3.1 General 9
3.2 Plug 9
3.3 Adaptor 9
3.4 Materials 9
3.5 Dimensions 9
3.6 Colour and marking 10
4 Variants **11**
4.1 Terminated plug 11
4.2 Adaptor 11
4.3 Identification of variants 11
5 Dimensional requirements **12**
5.1 Outline dimensions 12
5.2 Mating face and other limit dimensions 15
6 Tests **23**
6.1 Sample size 23
6.2 Test and measurement methods 24
6.3 Test sequence 24
6.4 Pass/fail criteria 24
7 Test report **24**
8 Product qualification requirements **24**
8.1 Dimensional and marking requirements 24
8.2 Optical performance requirements 25
8.3 Mechanical performance requirements 26
8.4 Environmental performance requirements 30
Annex A (informative) **Attenuation against reference** **33**
A.1 Test details 33
A.2 Reference LC connector details 33
Annex B (normative) **Sample size and product sourcing requirements** **34**
Annex C (normative) **Requirements for launch condition (Encircled flux)** **35**
Annex D (informative) **Details of environmental classification out of EN 50173-1 (MICE)** **36**
Annex E (informative) **Details of sample construction** **37**
Annex F (informative) **Patent statement concerning ODVA industrial connectors** **38**
Bibliography **40**

Figures

Figure 1 – Outline dimensions – Plug 12
Figure 2 – Outline dimensions – Fixed adaptor 13
Figure 3 – Cut out for fixed adaptor mounting Variant 01 13
Figure 4 – Cut out for fixed adaptor mounting Variant 02 14
Figure 5 – Plug mating face and other limit dimensions 15
Figure 6 – Variant Bm2, LC connector interface 16
Figure 7 – Ferrule endface geometry – After termination 17
Figure 8 – Positioning of fibre core 17
Figure 9 – Ferrule endface geometry – Allowable undercut 19
Figure 10 – Variant 01, fixed adapter 20
Figure 11 – Variant M 01, LC adapter interface 21
Figure 12 – Pin gauge for adaptor 23
Figure E.1 – Example of test specimen for Tests 1 – 13 37
Figure E.2 – Example of test specimen for Tests 14 – 19 37

Tables

Table 1 – Preferred colour scheme 10
Table 2 – Terminated plug – Plug variants 11
Table 3 – Terminated plug – Adaptor variants 11
Table 4 – Identification of plug variants 11
Table 5 – Identification of adaptor variants 11
Table 6 – Geometrical parameters 18
Table 7 – Optical performance requirements 25
Table 8 – Mechanical performance requirements 26
Table 9 – Environmental performance requirements 30
Table A.1 – Attenuation measurement: Test details 33
Table B.1 – Sample size and product sourcing requirements 34
Table C.1 – Requirements for 50 µm fibre core diameter at 850 nm 35
Table D.1 36

Foreword

This European Standard was prepared by the Technical Committee CENELEC TC 86BXA, Fibre optic interconnect, passive and connectorised components. The text of the draft was submitted to the formal vote and was approved by CENELEC as EN 50516-2-1 on 2011-07-19.

The following dates were fixed:

– latest date by which the EN has to be implemented at national level by publication of an identical national standard or by endorsement	(dop)	2012-07-19
– latest date by which the national standards conflicting with the EN have to be withdrawn	(dow)	2014-07-19

CENELEC draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent concerning ODVA industrial connectors (see declaration in Annex F).

All potential patent issues concerning this product are covered by IEC patent statement (see EN 61754-24-21).

Introduction

CENELEC draws attention to the fact that it is claimed that compliance with this document may involve the use of a patent concerning ODVA industrial connectors given in Annex F.

CENELEC takes no position concerning the evidence, validity and scope of this patent right.

The holder of this patent right has assured CENELEC that he/she is willing to negotiate licences under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statement of the holder of this patent right is registered with CENELEC.

Information may be obtained from:

The Siemon Company
101 Siemon Company Drive
Watertown, CT 06795

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. CENELEC shall not be held responsible for identifying any or all such patent rights.

Industrial connector sets and interconnect components to be used in optical fibre control and communication systems – Product specifications

Part 2-1: Type ODVA PC industrial terminated on EN 60793-2-10 category A1a and A1b multimode fibre to meet the requirements of category I (industrial environments) as specified in EN 50173-1 and IEC 61753-1-3

Description		Performance	
Coupling mechanism:	Twist and lock with sealing	Application:	For the use in category I (industrial environment)
Configuration:	Plug / adaptor / with one side of the configuration having a seal and a protective shell	Attenuation (random mate):	Bm Mean ≤ 0,35 dB and ≤ 0,60 dB for ≥ 97 % of measurements
Fibre category:	EN 60793-2-10 Type A1a		
Cable type:	See Table 3	Return loss:	2m ≥ 20 dB

Related documents:

EN 50173-1	Information technology – Generic cabling systems – Part 1: General requirements
EN 50173-3	Information technology – Generic cabling systems – Part 3: Industrial premises
EN 60529	Degrees of protection provided by enclosures (IP Code) (IEC 60529)
EN 60794-3	Optical fibre cables – Part 3: Sectional specification – Outdoor cables (IEC 60794-3)
EN 61300 series	Fibre optic interconnecting devices and passive components – Basic test and measurement procedures (IEC 61300 series)
EN 61753-1	Fibre optic interconnecting devices and passive components performance standard – Part 1: General and guidance for performance standards (IEC 61753-1)
EN 61754-20	Fibre optic connector interfaces – Part 20: Type LC connector family (IEC 61754-20)
IEC 61753-1-3 [1)]	Fibre optic interconnecting devices and passive components – Performance standard – Part 1-3: General and guidance for single-mode fibre optic connector performance for harsh industrial operating conditions

Outline and maximum dimensions: ODVA connector plug with protective shell in sealed adaptor.



1) At draft stage.

1 Scope

1.1 Product definition

This European Standard contains the initial, start of life dimensional, optical, mechanical and environmental performance requirements that an ODVA connector terminated with cylindrical zirconia PC ferrules with one side protected by an industrial housing, an adaptor fitted with resilient alignment sleeve and patchcord shall meet in order for it to be categorised as an EN standard product. The product is rated IP67.

Since different variants are permitted, product marking details are given in 3.6.

1.2 Intermateability

Products conforming to the requirements of this specification will intermate and give the specified level of random attenuation and random return loss performance, provided that the same fibre type is used. The intention is that this will be true irrespective of the manufacturing source(s) of the product.

1.3 Operating environment

The tests selected combined with the severities and durations, specified as Category I, are intended to reflect, although they do not necessarily satisfy all the requirements of the boundary conditions of $M_3I_3C_3E_3$.

1.4 Reliability

Whilst the anticipated service life expectancy of the product in this environment is 20 years, compliance with this specification does not guarantee the reliability of the product. This should be predicted using a recognised reliability assessment programme.

1.5 Quality assurance

Compliance with this specification does not guarantee the manufacturing consistency of the product. This should be maintained using a recognised quality assurance programme.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 60068-2-60	Environmental testing – Part 2: Tests – Test Ke: Flowing mixed gas corrosion test (IEC 60068-2-60)
EN 60529	Degrees of protection provided by enclosures (IP Code) (IEC 60529)
EN 60874-1	Connectors for optical fibres and cables – Generic specification (IEC 60874-1)
EN 61280-1-4	Fibre optic communication subsystem test procedures – Part 1-4: General communication subsystems – Light source encircled flux measurement method (IEC 61280-1-4)
EN 61300-1	Fibre optic interconnecting devices and passive components – Basic test and measurement procedures – Part 1: General and guidance (IEC 61300-1)
EN 61300-2-1	Part 2-1: Tests – Vibration (sinusoidal) (IEC 61300-2-1)
EN 61300-2-2	Part 2-2: Tests – Mating durability (IEC 61300-2-2)
EN 61300-2-4	Part 2-4: Tests – Fibre/cable retention (IEC 61300-2-4)
EN 61300-2-5	Part 2-5: Tests – Torsion (IEC 61300-2-5)