

Irish Standard I.S. EN 4608-003:2012

Aerospace series - Cable, electrical, fire resistant - Single and twisted multicore assembly, screened (braided) and jacketed - Operating temperatures between -65 °C and 260 °C - Part 003: DN family - Lightweight - UV Laser printable - Product standard

© NSAI 2012

No copying without NSAI permission except as permitted by copyright law.

I.S. EN 4608-003:2012

| Incorporating amendments/ | corrigenda/National Annex | ves issued since public | cation: | |
|--|--|--|-----------------------|--|
| The National Standards Authori [.] documents: | ty of Ireland (NSAI) produc | es the following cate | gories of formal | |
| I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation. | | | | |
| S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation. | | | | |
| SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop. | | | | |
| This document replaces: | | | | |
| This document is based on: EN 4608-003:2012 | <i>Published:</i> 24 February, 2012 | | | |
| This document was publish under the authority of the N and comes into effect on: 24 February, 2012 | | | ICS number: 49.060 | |
| NSAI 1 Swift Square, Northwood, Santry Dublin 9 | T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie | Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie | | |
| Údarás um Chaighdeáin Náisiúnta na hÉireann | | | | |

I.S. EN 4608-003:2012

EUROPEAN STANDARD NORME EUROPÉENNE EUROPÄISCHE NORM

EN 4608-003

February 2012

ICS 49.060

English Version

Aerospace series - Cable, electrical, fire resistant - Single and twisted multicore assembly, screened (braided) and jacketed - Operating temperatures between -65 °C and 260 °C - Part 003: DN family - Lightweight - UV Laser printable - Product standard

Série aérospatiale - Câbles électriques blindés résistant au feu - Simple et multifilaire blindé (tressé) et gainé - Températures de fonctionnement comprises entre - 65 °C et 260 °C - Partie 003: Famille DN - Fil allégé - Marquable laser UV - Norme de produit

Luft- und Raumfahrt - Feuerberständige elecktrische Leitungen - Einzel- und mehradrig verdrillte Leitungen, geschirmt (Geflecht) und ummantelt -Betriebstemperaturen zwischen -65 °C und 260 °C - Teil 003: DN Familie - leichte Bauweise - UV Laser bedruckbar - Produktnorm

This European Standard was approved by CEN on 27 August 2011.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

I.S. EN 4608-003:2012

EN 4608-003:2012 (E)

| Con | tents | Page |
|------------------------|---|--------|
| Forew | vord | |
| 1 | Scope | 4 |
| 2 | Normative references | 4 |
| 3 | Terms and definitions | 4 |
| 4 4.1 4.2 4.3 | Materials and construction | 4 5 |
| 5 | Required characteristics | 6 |
| 6 | Tests | 6 |
| 7 | Quality assurance | 8 |
| 8 | Designation | 9 |
| 9 | Identification and marking | 9 |
| 10 | Packaging, labelling and delivery lengths | 9 |
| 11 | Technical specification | |
| Biblio | graphy | 10 |

EN 4608-003:2012 (E)

Foreword

This document (EN 4608-003:2012) has been prepared by the Aerospace and Defence Industries Association of Europe - Standardization (ASD-STAN).

After enquiries and votes carried out in accordance with the rules of this Association, this Standard has received the approval of the National Associations and the Official Services of the member countries of ASD, prior to its presentation to CEN.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by August 2012, and conflicting national standards shall be withdrawn at the latest by August 2012.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

According to the CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.



| The is a new provider i arenade and chare publication at the limit below | This is a free preview. | Purchase the | entire publication | at the link below: |
|--|-------------------------|--------------|--------------------|--------------------|
|--|-------------------------|--------------|--------------------|--------------------|

Product Page

- Dooking for additional Standards? Visit Intertek Inform Infostore
- Dearn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation