

Standard Recommendation S.R. CEN/TS 15718:2011

Railway applications - Wheelsets and bogies - Product requirements for cast wheels

© NSAI 2011

No copying without NSAI permission except as permitted by copyright law.

Incorporating amendments	/corrigenda/National Anne	xes issued since public	cation:		
The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:					
I.S. xxx: Irish Standard – subject to public consultation.	national specification base	ed on the consensus of	an expert panel and		
S.R. xxx: Standard Recompanel and subject to public con	mendation - recommendat sultation.	ion based on the cons	ensus of an expert		
SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.					
This document replaces:					
This document is based on CEN/TS 15718:2011	. Published: 23 September, 201	1			
This document was publis under the authority of the and comes into effect on: 23 September, 2011			ICS number: 45.040		
NSAI 1 Swift Square, Northwood, Santry Dublin 9	T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie	Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie			
Údarás um Chaighdeáin Náisiúnta na hÉireann					

TECHNICAL SPECIFICATION

CEN/TS 15718

SPÉCIFICATION TECHNIQUE

TECHNISCHE SPEZIFIKATION

September 2011

ICS 45.040

English Version

Railway applications - Wheelsets and bogies - Product requirements for cast wheels

Applications ferroviaires - Essieux montés et bogies - Exigences pour roues en acier moulé

Bahnanwendungen - Radsätze und Drehgestelle - Produktanforderungen für Gussräder

This Technical Specification (CEN/TS) was approved by CEN on 3 January 2011 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

CEN/TS 15718:2011 (E)

Cont	ents ents	Page
Forewo	ord	4
Introdu	ıction	5
1	Scope	6
2	Normative references	
3	Product definition	
3.1	Chemical composition	
3.1.1	Values to be achieved	
3.1.2 3.1.3	Location of the sample	
3.1.3 3.2	Chemical analysis Mechanical characteristics	
3.2.1	Tensile test characteristics	
3.2.1	Hardness characteristics in the rim	
3.2.2	Impact test characteristics	
3.2.3	Fatigue characteristics	
3.2.4	Fracture toughness characteristics of the rim	
3.2.5	Heat treatment homogeneity	
3.3.1	Location of measurement	
3.3.1	Values to be achieved	
3.3.3	Test method	
3.4	Metallurgical structure	
3.5	Material cleanliness	
3.5.1	Micrographic cleanliness	
3.5.2	Internal integrity	
3.6	Residual stresses	
3.6.1	General	
3.6.2	Values to be achieved	
3.6.3	Test piece	
3.6.4	Measurement methods	
3.7	Surface characteristics	
3.7.1	Surface appearance	
3.7.2	Surface integrity	
3.8	Geometric tolerances	
3.9	Static imbalance	
3.10	Shot peening - Requirements	
3.10.1		
3.10.2	Values to be achieved	
3.10.3	Measurement method	
3.11	Protection against corrosion	21
3.12	Wheel maintenance capacity	
3.13	Manufacture's markings	
Δηηον	A (normative) Hydrogen control at the point of steel melt for monobloc wheels	23
Aillex A.1	Sampling	
A.1 A.2	Analysis methods	
A.2 A.3	Operating precautions	
	B (informative) Example of a test method for the determination of fatigue characteristics	
B.1	Test piece	
B.2	Test rig	
B.3	Test monitoring	
B.4	Analysis of results	24

CEN/TS 15718:2011 (E)

Annex	C (informative) Strain gauge method for determining the variation of circumferential	
	residual stresses located deep under the tread (destructive method)	.25
C.1	Principle	
C.2	Procedure	.25
C.2.1	Fitting of a rim cross section with strain gauges prior to wheel cutting	.25
C.2.2	Execution of cutting	.25
C.2.3	Operations to be executed during cutting	.26
C.3	Expression of results	
C.3.1	Calculation of the variation of the circumferential residual stress located deep under the tread	
C.3.2	Calculation of the variation of the circumferential stress created by cutting operation 1	.26
C.3.3	Calculation of the variation of the circumferential stress created by cutting operation 2	
C.3.4	Calculation of the variation of the circumferential stress created by cutting operation 3	
C.3.5	Final diagram representing the variation of the circumferential stress located deep under	
0.0.0	the tread	.27
_		
	D (informative) Product qualification	
D.1	General	
D.2	Requirements	
D.2.1	Requirements for the producer	
D.2.2	Requirements for the product	
D.3	Qualification procedure	
D.3.1	General	
D.3.2	Documentation required	
D.3.3	Evaluation of manufacturing equipment and of the production processes	
D.3.4	Laboratory tests	
D.3.5	Testing of wheels	
D.4	Qualification certificate	
D.4.1	Condition of the validity	
D.4.2	Modification and extension	
D.4.3	Transference	
D.4.4	Lapsed certificate	
D.4.5	Cancellation	
D.5	Qualification documents	. 35
Annov	E (informative) Product delivery	36
E.1	General	
E.2	Delivery condition	
E.2 E.3	Controls on each wheel	
E.3 E.4	Batch control	
E.4.1		
	Controls	
E.4.2	Uniformity of batches by measurement of rim hardness	
E.4.3	Orientation of residual stresses on rim chilled wheels	
E.4.4	Shot peening	
E.4.5	Visual inspection	
E.4.6	Quality plan	
E.5	Allowable rectification	.41
Bibliog	raphy	.42

CEN/TS 15718:2011 (E)

Foreword

This document (CEN/TS 15718:2011) has been prepared by Technical Committee CEN/TC 256 "Railway applications", the secretariat of which is held by DIN.

Your attention is drawn to the fact that certain elements in this document may be subject to intellectual property or similar rights. CEN and/or CENELEC cannot be held responsible for not identifying such property rights and providing a warning of their existence.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive 2008/57/CE.

According to CEN/CENELEC Internal Regulations, the national standards organizations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Cyprus, Croatia, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Ireland, Iceland, Italy, Latvia, Lithuania, Luxembourg, Malta, Norway, the Netherlands, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CEN/TS 15718:2011 (E)

Introduction

Prior to the publication of this Technical Specification, the only European Standard available to define quality requirements for monobloc wheels was EN 13262, which applies only to forged and rolled wheels. Forging and rolling was the only authorized process to be used by the UIC regulation that was applicable in the recent past for European countries.

Cast wheels are commonly used by AAR networks and have been introduced into Europe on some applications for freight wagons. As a reference document, this standard defines the product requirements of a monobloc cast wheel. In order for a cast wheel to maintain the same level of safety as for a forged and rolled wheel, for the product characteristics, the main content of this document is derived from EN 13262.

This standard addresses a complete definition of the product and delivery procedures for cast wheels by:

- a) defining all the wheel characteristics;
- NOTE 1 These are either verified during the qualification or for the delivery of the product (see Clause 3).
- b) defining qualification procedures (see Annex D);
- c) defining delivery conditions (see Annex E).
- NOTE 2 A choice is given to the supplier, of either:
 - 1) a traditional delivery procedure with a control by batch sampling as in existing documents (see E.4) or;
 - 2) delivery procedure using quality assurance concepts (see E.4.6).



Product Page

- Dooking for additional Standards? Visit Intertek Inform Infostore
- Dearn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation