

Irish Standard I.S. EN 61076-2-101:2012

Connectors for electronic equipment -Product requirements -- Part 2-101: Circular connectors - Detail specification for M12 connectors with screw-locking (IEC 61076-2-101:2012 (EQV))

 $\ensuremath{\mathbb{C}}$ NSAI 2012 No copying without NSAI permission except as permitted by copyright law.

Incorporating amendments/corrigenda issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

<i>This document replaces:</i> EN 61076-2-101:2008	<i>This document is based on</i> EN 61076-2-101:2012 EN 61076-2-101:2008	3 Augu	<i>hed:</i> ıst, 2012 ember, 2008
This document was published under the authority of the NSAI and 10 August, 2012	omes into effect on:		ICS number: 31.220.10
1 Swift Square, F +35 Northwood, Santry E sta Dublin 9	ndards@nsai.ie F +353	8 1 857 6730 8 1 857 6729 dards.ie	
Údarás um Chaighdeáin Náisiúnta na hÉireann			

EUROPEAN STANDARD

EN 61076-2-101

NORME EUROPÉENNE EUROPÄISCHE NORM

August 2012

ICS 31.220.10

Supersedes EN 61076-2-101:2008

English version

Connectors for electronic equipment -Product requirements -Part 2-101: Circular connectors -Detail specification for M12 connectors with screw-locking (IEC 61076-2-101:2012)

Connecteurs pour équipements électroniques - Exigences de produit -Partie 2-101: Connecteurs circulaires -Spécification particulière pour les connecteurs M12 à vis (CEI 61076-2-101:2012) Steckverbinder für elektronische Einrichtungen - Produktanforderungen -Teil 2-101: Rundsteckverbinder -Bauartspezifikation für Steckverbinder M12 mit Schraubverriegelung (IEC 61076-2-101:2012)

This European Standard was approved by CENELEC on 2012-05-25. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Management Centre: Avenue Marnix 17, B - 1000 Brussels

© 2012 CENELEC - All rights of exploitation in any form and by any means reserved worldwide for CENELEC members.

EN 61076-2-101:2012

I.S. EN 61076-2-101:2012 - 2 -

Foreword

The text of document 48B/2279/FDIS, future edition 3 of IEC 61076-2-101, prepared by SC 48B "Connectors" of IEC/TC 48 "Electromechanical components and mechanical structures for electronic equipment" was submitted to the IEC-CENELEC parallel vote and approved by CENELEC as EN 61076-2-101:2012.

The following dates are fixed:

- latest date by which the document has (dop) 2013-02-25 to be implemented at national level by publication of an identical national standard or by endorsement
 latest date by which the national (dow) 2015-05-25
- standards conflicting with the document have to be withdrawn

This document supersedes EN 61076-2-101:2008.

EN 61076-2-101:2012 includes the following significant technical changes with respect to EN 61076-2-101:2008:

- the drawings of some styles have been corrected;
- a new style with maximum 17 poles, with A-coding, has been added, as new applications for the industrial process measurement and control require a high number of poles in M12 circular connectors. The existing styles and dimensions which were specified in EN 61076-2-101:2008 are further applicable for the added interface dimension of the 17 poles versions;
- removal of the type designation and ordering information, former Tables 6 and 7 have been updated accordingly;
- inclusion of the technical content of IEC/PAS 61076-2-108, which will be withdrawn after the publication of this European Standard. The drawings have been updated and correction to the title of Figure 9 was made.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

Endorsement notice

The text of the International Standard IEC 61076-2-101:2012 was approved by CENELEC as a European Standard without any modification.

I.S. EN 61076-2-101:2012 - 3 -

EN 61076-2-101:2012

Annex ZA (normative)

Normative references to international publications with their corresponding European publications

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

Publication	Year	Title	<u>EN/HD</u>	Year
IEC 60050-581	2008	International Electrotechnical Vocabulary (IEV) - Part 581: Electromechanical components for electronic equipment	-	-
IEC 60068-1	-	Environmental testing - Part 1: General and guidance	EN 60068-1	-
IEC 60068-2-60	-	Environmental testing - Part 2: Tests - Test Ke: Flowing mixed gas corrosion test	EN 60068-2-60	-
IEC 60352	Series	Solderless connections	EN 60352	Series
IEC 60423	2007	Conduit systems for cable management - Outside diameters of conduits for electrical installations and threads for conduits and fittings	EN 60423	2007
IEC 60512	Series	Connectors for electronic equipment - Tests and measurements	EN 60512	Series
IEC 60512-1-100	-	Connectors for electronic equipment - Tests and measurements - Part 1-100: General - Applicable publications		-
IEC 60529	1989	Degrees of protection provided by enclosures (IP Code)	EN 60529 + corr. May	1991 1993
IEC 60664-1	-	Insulation coordination for equipment within low-voltage systems - Part 1: Principles, requirements and tests	EN 60664-1	-
IEC 60998-2-1	-	Connecting devices for low-voltage circuits for household and similar purposes - Part 2-1: Particular requirements for connecting devices as separate entities with screw-type clamping units	EN 60998-2-1	-
IEC 60999	Series	Connecting devices - Electrical copper conductors - Safety requirements for screw- type and screwless-type clamping units	EN 60999	Series
IEC 61076-1	2006	Connectors for electronic equipment - Product requirements - Part 1: Generic specification	EN 61076-1	2006
IEC 61984	-	Connectors - Safety requirements and tests	EN 61984	-
ISO 1302	-	Geometrical Product Specifications (GPS) - Indication of surface texture in technical product documentation	EN ISO 1302	-

This page is intentionally left BLANK.

– 2 – 61076-2-101 © IEC:2012

CONTENTS

FO	REWO	DRD	5	
1	Scop	e	8	
2	Norm	Iormative references		
3	Tech	echnical information		
	3.1	Terms and definitions	9	
	3.2	Recommended method of termination		
		3.2.1 General	9	
		3.2.2 Number of contacts or contact cavities	.10	
	3.3	Ratings and characteristics	.10	
	3.4	Marking	.10	
	3.5	Safety aspects	.10	
4	Dime	ensional information	.11	
	4.1	General	.11	
	4.2	Survey of styles and variants	.11	
		4.2.1 Fixed connectors	.11	
		4.2.2 Free connectors	22	
	4.3	Interface dimensions	.27	
		4.3.1 Pin front view A-coding		
		4.3.2 Pin front view B-coding		
		4.3.3 Pin front view C-coding		
		4.3.4 Pin front view D-coding		
		4.3.5 Pin front view P-coding		
	4.4	Engagement (mating) information		
_	4.5	Gauges		
5		acteristics		
	5.1	Climatic category		
	5.2	Electrical characteristics		
		5.2.1 Rated voltage – Rated impulse voltage – Pollution degree		
		5.2.2 Voltage proof		
		5.2.3 Current-carrying capacity5.2.4 Contact resistance		
		5.2.4 Contact resistance		
	5.3	Mechanical characteristics		
	5.5	5.3.1 IP degree of protection		
		5.3.2 Mechanical operation		
		5.3.3 Insertion and withdrawal forces		
		5.3.4 Contact retention in insert		
		5.3.5 Polarizing method		
		5.3.6 Vibration (sinusoidal)		
		5.3.7 Pressure differential		
6	Test	schedule		
	6.1	General		
	6.2	Arrangement for contact resistance measurements		
	6.3	Arrangement for dynamic stress tests (vibration)		
	6.4	Test schedule		

61076-2-101 © IEC:2012

6.4.1 Test group P – Preliminary	48
6.4.2 Test group AP – Dynamic/ Climatic	
6.4.3 Test group BP – Mechanical endurance	
6.4.4 Test group CP – Electrical load	
 6.4.5 Test group DP – Chemical resistivity 6.4.6 Test group EP – Connection method tests 	
6.4.7 Test group FP – Electrical transmission requirements	
Annex A (informative) Diameter of the female connector body	
Annex B (informative) Steel conduit thread, sizes	
	4.0
Figure 1 – Tube insert, male contacts, mounting without thread (thread on tube)	
Figure 2 – Tube insert, male contacts, mounting with thread M12 \times 1	12
Figure 3 – Fixed connector, male contacts, mounting with thread M12 \times 1, square flange front mounting	13
Figure 4 – Fixed connector, male contacts, mounting with thread M12 \times 1, with wire ends, single hole mounting thread M16 \times 1,5	14
Figure 5 – Fixed connector, male contacts, mounting with thread M12 \times 1, with wire ends, single hole mounting thread M20 \times 1,5	14
Figure 6 – Fixed connector, male contacts, mounting with thread M12 \times 1 with wire ends, single hole mounting thread M16 \times 1,5, mounting orientation	15
Figure 7 – Fixed connector, male contacts, mounting with thread M12 \times 1, with wire ends, single hole mounting thread M20 \times 1,5, mounting orientation	15
Figure 8 – Fixed connector, glass to metal seal, square flange front mounting, male contacts	16
Figure 9 – Fixed connector, glass to metal seal, single hole front mounting, male contacts	17
Figure 10 – Fixed connector, glass to metal seal, jam nut rear mounting, male contacts	18
Figure 11 – Fixed connector, glass to metal seal, through flange mounting, male contacts	19
Figure 12 – Fixed connector, female contacts, mounting with thread M12 \times 1, with wire ends, single hole mounting thread M16 \times 1,5	19
Figure 13 – Fixed connector, female contacts, mounting with thread M12 \times 1, with wire ends, single hole mounting thread M20 \times 1,5	20
Figure 14 – Fixed connector, female contacts, mounting with thread M12 \times 1, with wire ends, single hole mounting thread M16 \times 1,5, mounting orientation	21
Figure 15 – Fixed connector, female contacts, mounting with thread M12 \times 1, with wire ends, single hole mounting thread M20 \times 1,5, mounting orientation	21
Figure 16 – Rewireable connector, male contacts, straight version, with locking nut	22
Figure 17 – Rewireable connector, male contacts, right angled version, with locking nut	23
Figure 18 – Non-rewireable connector, male contacts, straight version, with locking nut	23
Figure 19 – Non-rewireable connector, male contacts, right angled version, with locking nut	24
Figure 20 – Non-rewireable connector, male contacts, right angled higher version, with locking nut	
Figure 21 – Rewireable connector, female contacts, straight version, with locking nut	
Figure 22 – Rewireable connector, female contacts, right angled version, with locking nu	
Figure 23 – Non-rewireable connector, female contacts, straight version, with locking nut	

Figure 24 – Non-rewireable connector, female contacts, right angled version, wir locking nut	
Figure 25 – Pin front view A-coding, up to 12 ways	27
Figure 26 – Pin front view A-coding, 13 up to 17 ways	
Figure 27 – Contact position A-coding front view	
Figure 28 – Pin front view B-coding	
Figure 29 – Contact position B-coding front view	
Figure 30 – Pin front view 3 way with C-coding	
Figure 31 – Pin front view 4 way with C-coding	
Figure 32 – Pin front view 5 way with C-coding	
Figure 33 – Pin front view 6 way with C-coding	
Figure 34 – Contact position C-coding front view	35
Figure 35 – Pin front view D-coding	
Figure 36 – Contact position D-coding front view	
Figure 37 – Pin front view P-coding	
Figure 38 – Contact position P-coding front view	
Figure 39 – Engagement (mating) information	
Figure 40 – Gauge dimensions	41
Figure 41 – Contact resistance arrangement	
Figure 42 – Dynamic stress test arrangement	
Figure A.1 – Diameter of the female connector body	57
Figure B.1 – Dimensions Pg thread	58
Table 1 – Ratings of connectors	
Table 2 – Styles of fixed connectors	11
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectors	11 22
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked position	11 22
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – Gauges	11 22 39 41
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic category	11 22 39 41 41
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic categoryTable 7 – Rated voltage – Rated impulse voltage – Pollution degree	11 22 39 41 41 42
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic categoryTable 7 – Rated voltage – Rated impulse voltage – Pollution degreeTable 8 – Voltage proof.	11 22 39 41 41 41 42 43
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic categoryTable 7 – Rated voltage – Rated impulse voltage – Pollution degreeTable 8 – Voltage proof.Table 9 – Number of mechanical operations	11 22 39 41 41 42 43 43 44
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic categoryTable 7 – Rated voltage – Rated impulse voltage – Pollution degreeTable 8 – Voltage proofTable 9 – Number of mechanical operationsTable 10 – Insertion and withdrawal forces	11 22 39 41 41 42 43 43 44 44
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic categoryTable 7 – Rated voltage – Rated impulse voltage – Pollution degreeTable 8 – Voltage proofTable 9 – Number of mechanical operationsTable 10 – Insertion and withdrawal forcesTable 11 – Number of test specimens	11 22 39 41 41 42 43 43 44 44 44
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic categoryTable 7 – Rated voltage – Rated impulse voltage – Pollution degreeTable 8 – Voltage proof.Table 9 – Number of mechanical operationsTable 10 – Insertion and withdrawal forcesTable 11 – Number of test specimensTable 12 – Test group P	11 22 39 41 41 42 43 43 44 44 44 44 44 44
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic categoryTable 7 – Rated voltage – Rated impulse voltage – Pollution degreeTable 8 – Voltage proof.Table 9 – Number of mechanical operationsTable 10 – Insertion and withdrawal forcesTable 11 – Number of test specimensTable 12 – Test group PTable 13 – Test group AP	11 22 39 41 41 42 43 43 44 44 44 44 44 44 44 44 44 49
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic categoryTable 7 – Rated voltage – Rated impulse voltage – Pollution degreeTable 8 – Voltage proof.Table 9 – Number of mechanical operationsTable 10 – Insertion and withdrawal forcesTable 11 – Number of test specimensTable 12 – Test group PTable 14 – Test group BP	11 22 39 41 41 42 43 43 44 44 44 44 44 44 44 52
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic categoryTable 7 – Rated voltage – Rated impulse voltage – Pollution degreeTable 8 – Voltage proof.Table 9 – Number of mechanical operationsTable 10 – Insertion and withdrawal forcesTable 11 – Number of test specimensTable 12 – Test group PTable 13 – Test group APTable 14 – Test group BPTable 15 – Test group CP	11 22 39 41 41 42 43 43 44 44 44 44 44 44 44 52 52 54
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic categoryTable 7 – Rated voltage – Rated impulse voltage – Pollution degreeTable 8 – Voltage proof.Table 9 – Number of mechanical operationsTable 10 – Insertion and withdrawal forcesTable 11 – Number of test specimensTable 12 – Test group PTable 13 – Test group APTable 14 – Test group BPTable 15 – Test group CPTable 16 – Test group DP	11 22 39 41 41 42 43 43 44 44 44 44 44 44 44 52 52 55
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic categoryTable 7 – Rated voltage – Rated impulse voltage – Pollution degreeTable 8 – Voltage proofTable 9 – Number of mechanical operationsTable 10 – Insertion and withdrawal forcesTable 12 – Test group PTable 13 – Test group APTable 15 – Test group DPTable 16 – Test group DPTable 17 – Test group EP	11 22 39 41 41 42 43 44 44 44 44 44 44 44 52 52 54 55 55
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic categoryTable 7 – Rated voltage – Rated impulse voltage – Pollution degreeTable 8 – Voltage proof.Table 9 – Number of mechanical operationsTable 10 – Insertion and withdrawal forcesTable 11 – Number of test specimensTable 12 – Test group PTable 13 – Test group APTable 14 – Test group BPTable 15 – Test group CPTable 17 – Test group EPTable 17 – Test group FP	11 22 39 41 41 42 43 43 44 44 44 44 44 44 44 52 52 54 55 55 55 55
Table 2 – Styles of fixed connectorsTable 3 – Styles of free connectorsTable 4 – Connectors dimensions in mated and locked positionTable 5 – GaugesTable 6 – Climatic categoryTable 7 – Rated voltage – Rated impulse voltage – Pollution degreeTable 8 – Voltage proofTable 9 – Number of mechanical operationsTable 10 – Insertion and withdrawal forcesTable 12 – Test group PTable 13 – Test group APTable 15 – Test group DPTable 16 – Test group DPTable 17 – Test group EP	11 22 39 41 41 42 43 43 44 44 44 44 44 44 44 52 52 54 55 55 55 55

61076-2-101 © IEC:2012

- 5 -

INTERNATIONAL ELECTROTECHNICAL COMMISSION

CONNECTORS FOR ELECTRONIC EQUIPMENT – PRODUCT REQUIREMENTS –

Part 2-101: Circular connectors – Detail specification for M12 connectors with screw-locking

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 61076-2-101 has been prepared by sub-committee 48B: Connectors, of Technical Committee 48: Electromechanical components and mechanical structures for electronic equipment.

This third edition cancels and replaces the second edition published in 2008 and its corrigendum published in 2010. It constitutes a technical revision.

This edition includes the following significant technical changes with respect to the previous edition:

- The drawings of some styles have been corrected.
- A new style with maximum 17 poles, with A-coding, has been added, as new applications for the industrial process measurement and control require a high number of poles in M12 circular connectors. The existing styles and dimensions which were

- 6 -

61076-2-101 © IEC:2012

specified in IEC 61076-2-101 Ed. 2 are further applicable for the added interface dimension of the 17 poles versions.

- Removal of the type designation and ordering information, former Tables 6 and 7 have been updated accordingly.
- Inclusion of the technical content of IEC PAS 61076-2-108, which will be withdrawn after publication of this International Standard. The drawings have been updated and correction to the title of Figure 9 was made.

The text of this standard is based on the following documents:

FDIS	Report on voting
48B/2279/FDIS	48B/2288/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

A list of all parts of IEC 61076 series, under the general title *Connectors for electronic equipment – Product requirements*, can be found on the IEC website.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC web site under "http://webstore.iec.ch" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

61076-2-101 © IEC:2012

- 7 -

IEC SC 48B – Connectors Specification available from: IEC General secretariat or from the addresses shown on the inside cover.	IEC 61076-2-101 Ed. 3.0
ELECTRONIC COMPONENTS DETAIL SPECIFICATION in accordance with IEC 61076-1	
FC 23503	Circular connectors M12 2 to 17 way Male and female contacts Male and female connectors Rewireable – Non-rewireable Free cable connectors Straight and right angle connectors Fixed connectors Fixed connectors with glass to metal seals (pin contacts only) Flange mounting Single hole mounting Pin sockets
IEC 2336/03	Pin sockets

- 8 -

61076-2-101 © IEC:2012

CONNECTORS FOR ELECTRONIC EQUIPMENT – PRODUCT REQUIREMENTS –

Part 2-101: Circular connectors – Detail specification for M12 connectors with screw-locking

1 Scope

This part of IEC 61076 describes M12 circular connectors typically used for industrial process measurement and control. These connectors consist of fixed and free connectors either rewireable or non-rewireable, with screw-locking. The connectors with glass to metal seal are fixed connectors only which consist of fixed glass to metal sealed styles with rewireable male contacts and are intermateable with corresponding free connectors according to this International Standard. Male connectors have round contacts \emptyset 0,6 mm, \emptyset 0,76 mm, \emptyset 0,8 mm and \emptyset 1,0 mm.

The different codings prevent the mating of these coded male or female connectors to any other interfaces and cross-mating between the different codings.

NOTE M12 is the dimension of the thread of the screw-locking mechanism of these circular connectors.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-581: 2008, International Electrotechnical Vocabulary (IEV) – Part 581: Electromechanical components for electronic equipment

IEC 60068-1, Environmental testing – Part 1: General and guidance

IEC 60068-2-60, Environmental testing – Part 2: Tests –Test Ke: Flowing mixed gas corrosion test

IEC 60352 (all parts), Solderless connections

IEC 60423:2007, Conduit systems for cable management – Outside diameters of conduits for electrical installations and threads for conduits and fittings

IEC 60512 (all parts), Connectors for electronic equipment – Tests and measurements

IEC 60512-1-100, Connectors for electronic equipment – Tests and measurements – Part 1-100: General – Applicable publications

IEC 60529:1989, Degrees of protection provided by enclosures (IP code)

IEC 60664-1, Insulation coordination for equipment within low-voltage systems – Part 1: *Principles, requirements and tests*



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation