no ma uga sum a



National Standards Authority of Ireland

IRISH STANDARD

## I.S. HD 625.1 S1:1999

ICS 29 080

----

a new searchester it a

Natoria Statist Authoria a transformation

Tel (C) con oco Tel (C) con oco

INSULATION COORDINATION FOR EQUIPMENT WITHIN LOW-VOLTAGE SYSTEMS. PART 1: PRINCIPLES. REQUIREMENTS AND TESTS (IEC 664-1:1992, MODIFIED)

This lifsh Standard was published under the authority of the National Standards Authority of lifeland and comes into effect on January 29, 1999

NO COPYING WITHOUT NSAI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

© NSAI 1999

Price Code U

Údarás um Chaighdeáin Náisiúnta na hÉireann

This is a free page sample. Access the full version online.

l

# HARMONIZATION DOCUMENT DOCUMENT D'HARMONISATION HARMONISIERUNGSDOKUMENT

September 1996

HD 625.1 S1

ICS 29.040.20

Descriptors: Low-voltage equipment, insulation, definitions, coordination, requirements, dimensioning rules, tests, measurements

English version

# Insulation coordination for equipment within low-voltage systems Part 1: Principles, requirements and tests (IEC 664-1:1992, modified)

Coordination de l'isolement des matériels dans les systèmes (réseaux) à basse tension Partie 1: Principes, prescriptions et essais (CEI 664-1:1992, modifiée) Isolationskoordination für elektrische Betriebsmittel in Niederspannungsanlagen Teil 1: Grundsätze, Anforderungen und Prüfungen (IEC 664-1:1992, modifiziert)

This Harmonization Document was approved by CENELEC on 1996-03-05. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for implementation of this Harmonization Document on a national level.

Up-to-date lists and bibliographical references concerning such national implementation may be obtained on application to the Central Secretariat or to any CENELEC member.

This Harmonization Document exists in three official versions (English, French, German).

CENELEC members are the national electrotechnical committees of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland and United Kingdom.

# CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

<sup>©</sup> 1996 Copyright reserved to CENELEC members

Ref. No. HD 625.1 S1:1996 E

Page 2 HD 625.1 S1:1996

#### Foreword

The text of the International Standard IEC 664-1:1992, prepared by SC 28A, Insulation coordination for low-voltage equipment, of IEC TC 28, Insulation coordination, together with common modifications prepared by the Technical Committee CENELEC TC 28A, Insulation coordination for low-voltage equipment, was submitted to the formal vote and was approved by CENELEC as HD 625.1 S1 on 1996-03-05.

The following dates were fixed:

<ul> <li>latest date by which the existence of the HD has to be announced at national level</li> </ul>	(doa)	1996-09-01
<ul> <li>latest date by which the HD has to be implemented at national level by publication of a harmonized national standard or by endorsement</li> </ul>	(dop)	1997-03-01
<ul> <li>latest date by which the national standards conflicting with the HD have to be withdrawn</li> </ul>	(dow)	1997-03-01

For products which have complied with the relevant national standard before 1997-03-01, as shown by the manufacturer or by a certification body, this previous standard may continue to apply for production until 2002-03-01.

Annexes designated "normative" are part of the body of the standard. Annexes designated "informative" are given for information only. In this standard, annex ZA is normative and annexes A, B, C, and D are informative. Annex ZA has been added by CENELEC.

Page 3 HD 625.1 S1:1996

#### Endorsement notice

The text of the International Standard IEC 664-1:1992 was approved by CENELEC as a Harmonization Document with agreed common modifications as given below.

#### COMMON MODIFICATIONS

- 1.3.10 Overvoltage category

   A numeral defining an impulse withstand level.
   No change in the note.
- 2.2 Voltages and voltage ratings Second alinea: Instead of "an overvoltage category according ..." Read "an impulse withstand category (overvoltage category) ..."

### 2.2.2.1 Impulse withstand categories (overvoltage categories)

Impulse withstand categories are means to distinguish different degrees of availability of equipment with regard to required expectations on continuity of service and on an acceptable risk of failure. By selection of impulse withstand levels of equipment, insulation coordination can be achieved in the whole installation, reducing the risk of failure to an acceptable level providing a basis for overvoltage control.

A higher characteristic numeral of an impulse withstand category indicates a higher specific impulse withstand of the equipment and offers a wider choice of methods for overvoltage control.

The concept of impulse withstand categories is used for equipment energised directly from the mains. The application of impulse withstand categories is based on the requirement with regard to additional protection against overvoltages as specified in IEC 364-4-443.

NOTE: Overvoltages of atmospheric origin are not significantly physically attenuated downstream in most installations. Investigations have shown that the concept of a probabilistic approach has proven reasonable and useful.

#### 2.2.2.1.1 Equipment energised directly from the low-voltage mains

Specification of a specific impulse withstand category (overvoltage category) shall be based on the following general explanation:

- Equipment of impulse withstand category I is equipment which is intended to be connected to the fixed electrical installations of buildings. Protective means are taken outside the equipment either in the fixed installation or between the fixed installation and the equipment to limit transient overvoltages to the specific level.
- Equipment of impulse withstand category II is equipment to be connected to the fixed electrical installations of buildings.

NOTE: Examples of such equipment are household appliances, portable tools and similar loads.

### Page 4 HD 625.1 S1:1996

- Equipment of impulse withstand category III is equipment which is part of the fixed electrical installations and other equipment where a higher degree of availability is expected.

NOTE: Examples of such equipment are distribution boards, circuit breakers, wiring systems (IEV 826-06-01, including cables, bus-bars, junction boxes, switches, socket-outlets) in the fixed installation, and equipment for industrial use and some other equipment, e.g. stationary motors with permanent connection to the fixed installation.

- Equipment of impulse withstand category IV is for use at or in the proximity of the origin of the electrical installations of buildings upstream of the main distribution board.
  - NOTE: Examples of such equipment are electricity meters, primary overcurrent protection devices and ripple control units.

### 2.2.2 Table I

Nominal voltage of the installa- tion * (V)		Required impulse withstand voltage (kV) for				
Three-phase systems	Single-phase systems with middle point	Equipment at the origin of the installation	Equipment which is part of the fixed installation	Equipment to be connected to the fixed installation	Specially pro- tected equip- ment	
		(impulse with- stand category	(impulse with- stand category	(impulse with- stand category	(impulse with- stand category	
		IV)	)	II)	l)	
	120- 240	4	2,5	1,5	0,8	
230/400 277/480		6	4	2,5	1,5	
400/690		8	6	4	2,5	
1000		Values subject to systems engineers or for lack of information, the va- lues of the above line can be chosen				
* According to IEC	C 38					
Category I is addr category II is addr	essed to particula essed to product	committees for equ	lipment for connec	ction to the mains, and some special		

# Table I - Rated impulse voltage of equipment

tees, category IV is addressed to supply authorities and systems engineers (see also introduction).

#### **4.1.2** Paragraph above the last one - Read:

"Partial discharge tests shall be specified unless it can be shown that PD are not likely to appear (the peak value of the voltage is below 500 V) or that insulation, for example ceramics, has an adequate life in the presence of partial discharges.

#### Annex B Delete



This is a free preview. Purchase the entire publication at the link below:

**Product Page** 

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation