



NSAI
Standards

Irish Standard
S.R. CR 1030-1:1995

Hand-arm vibration - Guidelines for vibration hazards reduction - Part 1: Engineering methods by design of machinery

S.R. CR 1030-1:1995

Incorporating amendments/corrigenda issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces:

This document is based on:
CR 1030-1:1995

Published:
2 June, 1995

This document was published under the authority of the NSAI and comes into effect on:
24 September, 2011

ICS number:
13.160

NSAI
1 Swift Square,
Northwood, Santry
Dublin 9

T +353 1 807 3800
F +353 1 807 3838
E standards@nsai.ie
W NSAI.ie

Sales:
T +353 1 857 6730
F +353 1 857 6729
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

REPORT
RAPPORT
BERICHT

CR 1030-1:1995

June 1995

English version

**Hand-arm vibration - Guidelines for vibration
hazards reduction - Part 1: Engineering methods
by design of machinery**

**Vibrations main-bras - Guide pour la
réduction des risques de vibrations -
Partie 1: Mesures techniques lors de
la conception des machines**

**Hand-Arm-Schwingungen-Leitfaden
zur Verringerung der Gefährdung
durch Schwingungen - Teil 1:
Technische Maßnahmen durch die
Gestaltung von Maschinen**

This CEN REPORT has been prepared by Technical Committee CEN/TC 231 "Mechanical vibration and shock" and has been approved by CEN on 1995-04-05.

CEN members are the national standards bodies of Austria, Belgium, Denmark, Finland, France, Germany, Greece, Iceland, Ireland, Italy, Luxembourg, Netherlands, Norway, Portugal, Spain, Sweden, Switzerland, United Kingdom.

CEN

**European Committee for Standardization
Comité Européen de Normalisation
Europäisches Komitee für Normung**

Rue de Stassart 36, B - 1050 Brussels

© CEN 1995 All rights of reproduction and communication in any form and by any means reserved in all countries to CEN and its members

Ref. no. CR 1030-1:1995 E

Foreword

This CEN report has been drawn up by CEN/TC 231 "Mechanical vibration and shock", working group 2 "Hand-arm vibration".

Contents

Introduction

1 Scope

2 Normative references

3 Reduction of vibration magnitude at source

3.1 Reduction of vibration by changing the technical principle of operation

3.2 Reduction of vibration by better balance

3.3 Reduction of vibration by introducing reactive forces

3.4 Reduction of vibration due to oscillating forces by use of alternative mechanisms or materials

3.5 Avoiding resonance effects

4 Reducing vibration transmission

4.1 General

4.2 Reduction of vibration by the use of suspended handles

4.3 Use of resilient materials

5 Optimisation of posture and minimisation of forces acting on, or through, the hand

6 Design to optimise hand temperature

Annex A (informative)

Bibliography

Introduction

The habitual and prolonged use of machinery which transmits vibration to the hand may cause disorders of the upper limbs. The effects of vibration depend on its frequency, direction, intensity and magnitude, and on the exposure time and coupling of the hand-arm system to the machine. The effects also depend on the hand-arm position caused by the design of the grip and the working task. They are also affected by forces exerted by the operator such as gripping, pushing and pulling forces, and by the skill and practical experience of the operator. Exposure to cold may be relevant to the vascular symptoms caused by hand-transmitted vibration.

Limiting vibration by design, is one the measures which EN 292-2 suggests machine manufacturers and designers should consider as part of a strategy to achieve safety by design of machinery in conformity with European Legislation.

The reduction of vibration by design of machinery can make an important contribution to the effective protection of persons at work from the harmful effects of vibration. In practical situations however, a combination of measures may be necessary which can be categorised under the headings:

- engineering measures;
- management measures;
- personal protection;
- hygiene measures (law, directives, etc.).

These guidelines only deal with engineering methods and in particular with comments to designers and manufacturers of machinery which transmits vibration to the hand leaving to others, the task of defining specific guidelines on management, personal or hygiene protection (see CR 1030-2).

Engineering methods

Machinery vibration may be due to oscillating forces generated internally by the intermittent, impulsive or cyclic way in which machines are designed to work, by unbalance, and/or by impacts in gears, bearings and other mechanisms.

Vibration can also be caused by unbalance of an inserted tool. For example, unbalance of the grinding disc is one factor that determines the vibration values of a hand-held grinder.

Vibration can also be caused by the interaction between operator, machinery and material being worked: for example when the shocks or impulses of a pneumatic chisel, as it hits the surface being chiselled, are reflected into the body of the tool.

In the case of machinery, such as pedestal grinders and finishers, at which the workpiece is hand-held or hand-guided during working, the interaction between workpiece and machine is likely to be the chief source of vibration. The transmission through the workpiece is the principal route by which vibration reaches the operator's hands.

The above parameters should be taken into account by designers, manufacturers, and suppliers of equipment for use at work, who are obliged to ensure that their designs and products satisfy safety requirements; in particular, to design machinery so that the risks from vibration produced by the machinery are reduced to the lowest level, taking into account technical progress and the availability of means of reducing vibration, in particular at source (see annex A of EN 292-2).

To reduce the vibration stress for the user, it is essential to pay attention not only to the vibration magnitude but also to the coupling of the machine to the hand-arm system and to the exposure time. All three parameters can be influenced by technical measures (e. g. coupling can be influenced by an ergonomic design of machinery; the exposure time can be reduced by increasing the performance of the machine).

1 Scope

These guidelines outline feasible ways in which possible hand-arm vibration hazard associated with hand-held, hand-guided and other machinery, may be reduced by machinery design in order to provide practical professional aid to designers and manufacturers of machinery. The document covers four principal aspects of the reduction of the effects arising from exposure to hazardous machinery vibration:

- reduction of vibration magnitude at source;
- reduction of vibration transmission from the source to handles and other surfaces in contact with the hands;
- reduction of vibration transmission from the grips or handles of the machine to the hand-arm system of the operator by ergonomic design measures;
- thermal design to optimise hand temperature.

NOTE: These guidelines are not intended to be universal or detailed solutions but only technical methods which may be used to solve problems.

2 Normative references

This CEN report incorporates by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this CEN report only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

- | | |
|------------|----------------------------------------------------------------------------------------------------------------------------------|
| EN 563 | Safety of machinery – Temperature of touchable surfaces – Ergonomics data to establish temperature limit values for hot surfaces |
| prEN 894-3 | Safety of machinery – Ergonomic requirements for the design of displays and control actuators – Part 3: Control actuators |

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-