

Irish Standard I.S. HD 22.11 S2:2007

Cables of rated voltages up to and including 450/750 V and having crosslinked insulation -- Part 11: EVA cords and flexible cables

 $\ensuremath{\mathbb C}$ NSAI 2007 $\hfill No copying without NSAI permission except as permitted by copyright law.$

I.S. HD 22.11 S2:2007

Incorporating amendments/corrigenda issued since publication:

<i>This document replaces:</i> I.S. HD 22.11 S1:1995	<i>This document is</i> HD 22.11 S2:200 HD 22.11 S1:199	7		<i>red:</i> ruary, 2007 ruary, 2007
This document was published under the authority of the NSAI and comes into effect on: 16 September, 2009		ICS number: 29.060.20		
NSAI 1 Swift Square, Northwood, Santry Dublin 9	T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie	Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie		Price Code: E
Údarás um Chaighdeáin Náisiúnta na hÉireann				

I.S. HD 22.11 S2:2007

HARMONIZATION DOCUMENT

HD 22.11 S2

DOCUMENT D'HARMONISATION HARMONISIERUNGSDOKUMENT

February 2007

ICS 29.060.20

Supersedes HD 22.11 S1:1995 + A1:1999

English version

Cables of rated voltages up to and including 450/750 V and having cross-linked insulation – Part 11: EVA cords and flexible cables

Conducteurs et câbles isolés avec des matériaux réticulés de tension assignée au plus égale à 450/750 V – Partie 11: Câbles souples à isolation EVA Starkstromleitungen mit vernetzter Isolierhülle für Nennspannungen bis 450/750 V – Teil 11: EVA-Schlauchleitungen

This Harmonization Document was approved by CENELEC on 2006-12-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for implementation of this Harmonization Document at national level.

Up-to-date lists and bibliographical references concerning such national implementations may be obtained on application to the Central Secretariat or to any CENELEC member.

This Harmonization Document exists in three official versions (English, French, German).

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization Comité Européen de Normalisation Electrotechnique Europäisches Komitee für Elektrotechnische Normung

Central Secretariat: rue de Stassart 35, B - 1050 Brussels

© 2007 CENELEC - All rights of exploitation in any form and by any means reserved worldwide for CENELEC members.

I.S. HD 22.11 S2:2007

- 2 -

Foreword

This Harmonization Document was prepared by the Technical Committee CENELEC TC 20, Electric cables.

The text of the draft was submitted to the Unique Acceptance Procedure and was approved by CENELEC as HD 22.11 S2 on 2006-12-01.

This Harmonization Document supersedes HD 22.11 S1:1995 + A1:1999.

The following dates were fixed:

 latest date by which the existence of the HD has to be announced at national level 	(doa)	2007-06-01
 latest date by which the HD has to be implemented at national level by publication of a harmonized national standard or by endorsement 	(dop)	2007-12-01
 latest date by which the national standards conflicting with the HD have to be withdrawn 	(dow)	2008-12-01

HD 22, Cables of rated voltages up to and including 450/750 V and having cross-linked insulation, now has the following parts:

HD 22.1 S4	General requirements
HD 22.2 S3 ¹⁾	Test methods
HD 22.3 S4	Heat resistant silicone rubber insulated cables
HD 22.4 S4	Cords and flexible cables
HD 22.5	(Spare)
HD 22.6 S2	Arc welding cables
HD 22.7 S2	Cables with increased heat resistance for internal wiring for a conductor temperature of 110 °C
HD 22.8 S2	Polychloroprene or equivalent synthetic elastomer sheathed cable for decorative chains
HD 22.9 S3	Single core halogen-free non-sheathed cables for fixed wiring having low emission of smoke
HD 22.10 S2	EPR insulated and polyurethane sheathed flexible cables
HD 22.11 S2	EVA cords and flexible cables
HD 22.12 S2	Heat resistant EPR cords and flexible cables
HD 22.13 S2	Halogen-free flexible cables having low emission of smoke
HD 22.14 S3	Cords for applications requiring high flexibility
HD 22.15 S2	Multicore cables insulated and sheathed with heat resistant silicone rubber
HD 22.16 S2	Water resistant polychloroprene or equivalent synthetic elastomer sheathed cables

 $^{^{\}rm 1)}$ HD 22.2 is superseded by EN 50395 and EN 50396.

I.S. HD 22.11 S2:2007 - 3 -

HD 22.11 S2:2007

Contents

		Pa	age
1	Scop	e	4
2	Normative references4		
3	EVA	ary heat-resistant EVA or equivalent synthetic elastomer insulated and or equivalent synthetic elastomer sheathed cord and cable for a maximum luctor temperature of 110 °C	4
	3.1	Code designation	4
	3.2	Rated voltage	4
	3.3	Construction	4
	3.4	Tests	5
	3.5	Guide to use (informative)	5
An	nex A	(normative) Requirements for compatibility test	8
Bił	oliogra	aphy	9
Та	ble 1 -	Dimensions of Type H05GG-F and H05GGH2-F	6
Та	ble 2 -	Tests for types H05GG-F and H05GGH2-F	7
Та	ble A. ²	I - Requirements	8

1 Scope

This Part 11 of the HD details the particular specifications for cross-linked EVA or equivalent synthetic elastomer insulated and vulcanised EVA or equivalent synthetic elastomer sheathed cords and flexible cables of rated voltages up to and including 300/500 V for use with a conductor temperature not exceeding 110 °C.

Each cable shall comply with the appropriate requirements given in Part 1 of this HD and the particular requirements of this part.

NOTE The overall dimensions of the cables in this part of HD 22 have been calculated in accordance with EN 60719.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 50363-1	Insulating, sheathing and covering materials for low voltage energy cables - Part 1: Cross-linked elastomeric insulating compounds
EN 50363-2-1	Insulating, sheathing and covering materials for low voltage energy cables - Part 2-1: Cross-linked elastomeric sheathing compounds
EN 50395	Electrical test methods for low voltage energy cables
EN 50396	Non electrical test methods for low voltage energy cables
EN 60228	Conductors of insulated cables (IEC 60228)
EN 60811 series	Insulating and sheathing materials of electric and optical cables – Common test methods (IEC 60811 series)

3 Ordinary heat-resistant EVA or equivalent synthetic elastomer insulated and EVA or equivalent synthetic elastomer sheathed cord and cable for a maximum conductor temperature of 110 °C

3.1 Code designation

H05GG-F for circular cables. H05GGH2-F for flat cables.

3.2 Rated voltage

300/500 V.

3.3 Construction

3.3.1 Conductor

Number of conductors: 2, 3, 4 or 5.

The conductors shall be in accordance with the requirements given in EN 60228 for Class 5 conductors. The wires may be plain or tinned.

3.3.2 Separator

A separator of suitable material shall be applied around each conductor if the conductors are plain. If the conductors are tinned the use of a separator is optional.



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation