



NSAI
Standards

Irish Standard
I.S. EN 15280:2013

Evaluation of a.c. corrosion likelihood of buried pipelines applicable to cathodically protected pipelines

I.S. EN 15280:2013

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWIFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces:
CEN/TS 15280:2006

This document is based on:
EN 15280:2013

Published:
20 August, 2013

This document was published
under the authority of the NSAI
and comes into effect on:
20 August, 2013

ICS number:

23.040.99

77.060

NSAI
1 Swift Square,
Northwood, Santry
Dublin 9

T +353 1 807 3800
F +353 1 807 3838
E standards@nsai.ie

W NSAI.ie

Sales:
T +353 1 857 6730
F +353 1 857 6729
W standards.ie

Údarás um Chaighdeáin Náisiúnta na hÉireann

I.S. EN 15280:2013

EUROPEAN STANDARD

EN 15280

NORME EUROPÉENNE

EUROPÄISCHE NORM

August 2013

ICS 23.040.99; 77.060

Supersedes CEN/TS 15280:2006

English Version

Evaluation of a.c. corrosion likelihood of buried pipelines applicable to cathodically protected pipelines

Évaluation du risque de corrosion occasionnée par les
courants alternatifs des canalisations enterrées protégées
cathodiquement

Beurteilung der Korrosionswahrscheinlichkeit durch
Wechselstrom an erdverlegten Rohrleitungen anwendbar
für kathodisch geschützte Rohrleitungen

This European Standard was approved by CEN on 5 July 2013.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

Management Centre: Avenue Marnix 17, B-1000 Brussels

Contents

Page

Foreword.....	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	5
4 Cathodic protection personnel competence	8
5 Assessment of the a.c. influence	9
5.1 General.....	9
5.2 Assessment of the level of interference.....	9
6 Evaluation of the likelihood of a.c. corrosion.....	10
6.1 Prerequisite	10
6.1.1 General.....	10
6.1.2 A.c. voltage on the structure	10
6.2 A.c. and d.c. current density.....	11
6.2.1 General.....	11
6.2.2 A.c. current density	11
6.2.3 High cathodic d.c. current density.....	11
6.2.4 Low cathodic d.c. current density.....	11
6.2.5 Current ratio " $I_{a.c.}/I_{d.c.}$ "	12
6.2.6 Soil resistivity.....	12
6.3 Corrosion rate	12
6.4 Pipeline coatings	12
6.5 Evaluation of the metal loss	12
7 Acceptable interference levels	12
8 Measurement techniques.....	13
8.1 Measurements.....	13
8.1.1 General.....	13
8.1.2 Selection of test sites	13
8.1.3 Selection of measurement parameter	14
8.1.4 Sampling rate for the recording of interference levels	14
8.1.5 Accuracy of measuring equipment.....	14
8.1.6 Installation of coupons or probes to calculate current densities.....	14
8.2 D.c. potential measurements.....	14
8.3 A.c. voltage measurements	15
8.4 Measurements on coupons and probes.....	15
8.4.1 Installation of coupons or probes	15
8.4.2 Current measurements	15
8.4.3 Corrosion rate measurements.....	16
8.5 Pipeline metal loss techniques	17
9 Mitigation measures	17
9.1 General.....	17
9.2 Construction measures.....	17
9.2.1 Modification of bedding material	17
9.2.2 Installation of isolating joints	17
9.2.3 Installation of mitigation wires	17
9.2.4 Optimisation of pipeline and/or powerline route.....	18
9.2.5 Power line or pipeline construction.....	18
9.3 Operation measures	18
9.3.1 Earthing	18
9.3.2 Adjustment of cathodic protection level	19

9.3.3	Repair of coating defects	19
10	Commissioning.....	19
10.1	Commissioning.....	19
10.2	Preliminary checking	20
10.2.1	General	20
10.2.2	Start up	20
10.2.3	Verification of effectiveness.....	21
10.2.4	Installation and commissioning documents	21
11	Monitoring and maintenance	21
Annex A	(informative) Simplified description of the a.c. corrosion phenomenon	23
A.1	Cathodically protected pipeline	23
A.2	Cathodically protected pipeline with a.c. voltage	23
A.2.1	Description of the phenomena.....	23
A.2.2	Reduction of the a.c. corrosion rate.....	24
Annex B	(informative) Coupons and probes	25
B.1	Use and sizes of coupons and probes	25
B.1.1	Use of coupons or probes	25
B.1.2	Sizes of coupons or probes	25
B.2	Installation of buried coupons and probes.....	25
B.2.1	General	25
B.2.2	Before installing the coupon or probe	25
B.2.3	Installation of the buried coupon or probe	26
B.3	ER probes principles.....	27
B.3.1	Assessment of the corrosion using the electrical resistance (ER) probe technique	27
B.3.2	ER probe application in the field	29
B.4	Perforation probes	29
Annex C	(informative) Coulometric oxidation	31
Annex D	(informative) Influence of soil characteristics on the a.c. corrosion process	32
D.1	Influence of electrical parameters	32
D.2	Influence of the electrochemical process.....	32
D.3	Influence of alkaline ions and cations.....	32
Annex E	(informative) Other criteria that have been used in the presence of a.c. influence	33
E.1	General	33
E.2	ON-potential approach.....	33
E.2.1	General	33
E.2.2	More negative (Eon) cathodic protection level	33
E.2.3	Less negative (Eon) cathodic protection level	33
E.2.4	Criteria	34
Annex F	(informative) Parameters to take into account to choose a d.c. decoupling device.....	36
F.1	General aspects to be taken into account	36
F.2	Electrical parameters	36
Annex G	(informative) Method to determine the reference electrode location to remote earth	37
Bibliography	38

Foreword

This document (EN 15280:2013) has been prepared by Technical Committee CEN/TC 219 "Cathodic protection", the secretariat of which is held by BSI.

This European Standard shall be given the status of a national standard, either by publication of an identical text or by endorsement, at the latest by February 2014 and conflicting national standards shall be withdrawn at the latest by February 2014.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document supersedes CEN/TS 15280:2006.

With this document, CEN/TS 15280:2006 is converted into a European Standard.

The main modification concerns the criteria assumed in the presence of a.c. interference on a pipeline. While CEN/TS 15280:2006 represented a collection of various experiences in the field of a.c. corrosion, this European Standard has incorporated these criteria and thresholds together with experience gained from the most recent data. Various European countries have a different approach to the prevention of a.c. corrosion depending primarily on the d.c. interference situation. These different approaches are taken into account in two different ways:

- either in the presence of "low" ON-potentials (less negative than -1,2 V CSE), which allows a certain level of a.c. voltage (up to 15 V),
- or in the presence of "high" ON-potentials (more negative than -1,2 V CSE ; with d.c. stray current interference on the pipeline for instance) which requires the reduction of the a.c. voltage towards the lowest possible levels.

This European Standard gives also some parameters to consider when evaluating the a.c. corrosion likelihood, as well as detailed measurement techniques, mitigation measures and measurements to carry out for commissioning of any a.c corrosion mitigation system. Note that Annex E proposes other parameters and thresholds that require further validation based on practical experiences.

According to the CEN/CENELEC Internal Regulations, the national standards organisations of the following countries are bound to implement this European Standard: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

1 Scope

This European Standard is applicable to buried cathodically protected metallic structures that are influenced by a.c. traction systems and/or a.c. power lines.

In this document, a buried pipeline (or structure) is a buried or immersed pipeline (or structure), as defined in EN 12954.

In the presence of a.c. interference, the protection criteria given in EN 12954:2001, Table 1, are not sufficient to demonstrate that the steel is being protected against corrosion.

This European Standard provides limits, measurement procedures, mitigation measures and information to deal with long term a.c. interference for a.c. voltages at frequencies between 16,7 Hz and 60 Hz and the evaluation of a.c. corrosion likelihood.

This European Standard deals with the possibility of a.c. corrosion of metallic pipelines due to a.c. interferences caused by inductive, conductive or capacitive coupling with a.c. power systems and the maximum tolerable limits of these interference effects. It takes into account the fact that this is a long-term effect, which occurs during normal operating conditions of the a.c. power system.

This European Standard does not cover the safety issues associated with a.c. voltages on pipelines. These are covered in national standards and regulations (see EN 50443).

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 12954:2001, *Cathodic protection of buried or immersed metallic structures — General principles and application for pipelines*

EN 13509:2003, *Cathodic protection measurement techniques*

EN 50443, *Effects of electromagnetic interference on pipelines caused by high voltage a.c. electric traction systems and/or high voltage a.c. power supply systems*

EN 61010-1, *Safety requirements for electrical equipment for measurement, control and laboratory use — Part 1: General requirements (IEC 61010-1)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

a.c. electric traction system

a.c. railway electrical distribution network used to provide energy for rolling stock

Note 1 to entry: The system can comprise:

- contact line systems;
- return circuit of electric railway systems;
- running rails of non-electric railway systems, which are in the vicinity of, or conductively connected to, the running rails of an electric railway system.

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- Looking for additional Standards? Visit Intertek Inform Infostore
 - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-