This is a free page sample. Access the full version online.



Standard Recommendation S.R. CEN/TS 16516:2013

Construction products - Assessment of release of dangerous substances -Determination of emissions into indoor air

© CEN 2013

No copying without NSAI permission except as permitted by copyright law.

Incorporating amendments/corrigenda/National Annexes issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWIFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

This document replaces:					
<i>This document is based o</i> CEN/TS 16516:2013	<i>n: Published:</i> 11 October, 2013				
This document was publi under the authority of the and comes into effect on 11 October, 2013	shed e NSAI :		ICS number: 13.040.20 91.100.01		
NSAI 1 Swift Square, Northwood, Santry Dublin 9	T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie	Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie			
Údarás um Chaighdeáin Náisiúnta na hÉireann					

TECHNICAL SPECIFICATION SPÉCIFICATION TECHNIQUE TECHNISCHE SPEZIFIKATION

CEN/TS 16516

October 2013

ICS 13.040.20; 91.100.01

English Version

Construction products - Assessment of release of dangerous substances - Determination of emissions into indoor air

Produits de construction - Détermination des émissions de substances dangereuses - Détermination des émissions dans l'air intérieur Bauprodukte - Bewertung der Freisetzung von gefährlichen Stoffen - Bestimmung von Emissionen in die Innenraumluft

This Technical Specification (CEN/TS) was approved by CEN on 25 May 2013 for provisional application.

The period of validity of this CEN/TS is limited initially to three years. After two years the members of CEN will be requested to submit their comments, particularly on the question whether the CEN/TS can be converted into a European Standard.

CEN members are required to announce the existence of this CEN/TS in the same way as for an EN and to make the CEN/TS available promptly at national level in an appropriate form. It is permissible to keep conflicting national standards in force (in parallel to the CEN/TS) until the final decision about the possible conversion of the CEN/TS into an EN is reached.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION COMITÉ EUROPÉEN DE NORMALISATION EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels

© 2013 CEN All rights of exploitation in any form and by any means reserved worldwide for CEN national Members.

Ref. No. CEN/TS 16516:2013: E

CEN/TS 16516:2013 (E)

Contents

Introdu	Introduction				
1	Scope	7			
2	Normative references	7			
3	Terms, definitions and abbreviations	7			
3.1	Terms relating to sampling and products	8			
3.2	Terms relating to emissions into indoor air and associated laboratory testing	10			
3.4	Abbreviations	14			
4	Intended conditions of use, emission scenarios and European reference room	15			
4.1	Intended conditions of use and emission scenario	15			
4.2	Reference room and emission scenario	15			
4.3	Time schedule of emission(s) determination	16			
5	Product sampling and transport to the laboratory	17			
5.1 5.2	Introduction	17 17			
5.3	Preparation of a sampling plan and sampling strategy	17			
5.4	Information from the testing laboratory needed to complement the product sampling plan	19			
5.5	Packaging and transport of laboratory sample	19			
5.0 5.7	Chain of custody report	20			
5.8	Dispatch of product samples, time schedule	20			
6	Handling of product samples in the laboratory	21			
6.1	Storage of sample in the testing laboratory	21			
6.2	Preparation of the test specimen	21			
7	Test chamber conditions	22			
7.1	Principles	22			
7.2 7.3	Loading factor	22			
7.4	Ventilation	22			
7.5	Air velocity	23			
7.6 7.7	Cleanliness of test chamber	23			
7.8	Storage of test specimen	23			
7.9	Large bulk products	23			
7.10	Volume of test chamber	23			
7.11		24			
8	Determination of volatile organic compounds in test chamber air	24			
8.2	Determination of VOCs and SVOCs in test chamber air	24			
8.3	Determination of formaldehyde and some other volatile carbonyl compounds in test				
	chamber air	27			
8.4	Quality control – External references	21			
9	Calculation of specific emission rates and expression of results at the reference room	28			
10	Reporting for the horizontal reference method	31			
10.1 10.2	General	31 31			
10.2	Handling of samples in the laboratory, preparation of test specimen	31			
10.4	Test chamber conditions	31			

10.5	Determination	of vapour-phase organic compounds in test chamber air	31
10.6	Calculation ar	nd reporting of test results	32
11	Indirect metho	ods	32
Annex	A (informative)	Repeatability	33
Annex	B (informative) secondary, de	Examples of indirect methods (also called simplified, screening, rived or alternative methods)	34
Annex	C (informative)	Information on very volatile organic compound (VVOC) testing	36
Annex	D (informative)	Key concepts for product sampling	37
Annex	E (informative)	Example of a form for the sampling report	49
Annex	F (informative)	Example form for a chain of custody report	50
Annex	G (informative)	Benzene artefact generation on Tenax	51
Annex	H (informative) dangerous su	Information on regulations concerning the emission into indoor air of bstances from construction products	52
Bibliog	raphy		54

Foreword

This document (CEN/TS 16516:2013) has been prepared by Technical Committee CEN/TC 351 "Construction products - Assessment of release of dangerous substances", the secretariat of which is held by NEN.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN [and/or CENELEC] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CEN by the European Commission and the European Free Trade Association.

According to the CEN-CENELEC Internal Regulations, the national standards organisations of the following countries are bound to announce this Technical Specification: Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

Introduction

This Technical Specification was developed in the frame of the Mandate M/366 "Development of horizontal standardized assessment methods for harmonised approaches relating to dangerous substances under the Construction Products Regulation (CPR)" addressing the preparation of horizontal measurement/test methods for the determination of emission of regulated dangerous substances from construction products into indoor air. This mandate is a complement to the product mandates granted by the European Commission to CEN under the Construction Products Regulation. The harmonised products standards (hEN) developed in CEN under mandates from the European Commission specify construction product(s) as put on the market and address their intended conditions of use.

This Technical Specification has gone through a robustness validation for identifying how small changes in specific testing parameters can influence the test result. This study also delivered data on repeatability within one testing laboratory (see Annex A). It is planned to convert the TS into an EN standard immediately after publication of this TS taking into account any relevant information provided during that process. This may include data from further round robin tests.

It is vital that such information is clearly linked to a specified product in a product standard. The responsibility of product specification is with the product TCs, as described in CEN/TR 16496. This determination of emission into indoor air is to be carried out on products under their intended conditions of use. The intended use of a construction product is generally specified in the corresponding harmonised product standard. The specific emission rates determined using this Technical Specification are associated with application of the product in a defined European Reference Room under specified climate (temperature and humidity) and ventilation conditions. A reference room is needed since it is not possible to evaluate emissions by testing in all possible use scenarios.

The reference room dimensions, resulting product loading factors, as well as climate and ventilation conditions are selected to represent the general indoor environment (see Clause 4). Based on the huge amount of available European experience, it was possible to identify one emission scenario and one reference room and associated set of product loading factors to be used.

This Technical Specification specifies the horizontal reference method for testing the emission (release) of dangerous substances from construction products into indoor air. This method uses a test chamber in which emissions are generated under conditions which are kept constant during the test. These conditions are selected so that the test results can be expressed in terms of chemical concentrations in the air of the reference room (see Clause 7 and Clause 9). It is to be noted that the test chamber is defined in terms of performance requirements. This responds to the requirement of Mandate M/366 for a horizontal approach but still maintains sufficient flexibility on chamber dimensions to ensure representative samples of different materials can be accommodated (see Clause 5). Clause 8 of this Technical Specification specifies how emitted regulated dangerous substances should be analysed.

This Technical Specification also addresses separately (see Clause 11 and Annex B) indirect methods that provide, within their specific field of application, a result that is comparable or that correlates with the result of the reference method. Such methods may be easier to apply and/or be cheaper. They are in accordance with mandate M/366 provided that their comparability or correlation to the reference test method has been demonstrated in their specific field of application. They are especially suitable for Factory Production Control testing (FPC).

The selection of one emission scenario and one reference room for evaluating emissions to indoor air is in general accordance with the approach taken in existing European national regulations and voluntary schemes relating to emissions from construction products into indoor air. It also accords with the horizontal requirements of mandate M/366. The aim of this Technical Specification is not to develop a new testing method but to combine by normative references the use of existing standards complemented, when necessary, with additional and/or modified requirements so that – according to the horizontal concept specified in mandate M/366 – construction products can be evaluated under comparable conditions with regard to emissions into indoor air.

In summary, the horizontal test method specified in this Technical Specification determines the specific emission rate of volatile organic compounds from a construction product into indoor air. This can be converted into a concentration in the air of the reference room by calculation.

This Technical Specification has not been evaluated for the determination of 'steady state' concentration of formaldehyde.

NOTE A European Standard (EN 717-1) exists for the determination of formaldehyde emissions from wood-based panels, in terms of 'steady state' concentration.

1 Scope

This Technical Specification specifies a horizontal reference method for the determination of emissions of regulated dangerous substances from construction products into indoor air. This method is applicable to volatile organic compounds, semi-volatile organic compounds, and volatile aldehydes. It is based on the use of a test chamber and subsequent analysis of the organic compounds by GC-MS or HPLC.

NOTE 1 Supplemental information is given on indirect test methods (Annex B) and on measuring very volatile organic compounds (see informative Annex C).

NOTE 2 This Technical Specification describes the overall procedure and makes use of existing standards mainly by normative reference, complemented when necessary with additional or modified normative requirements.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CEN/TR 16220:2011, Construction products — Assessment of release of dangerous substances — Complement to sampling

CEN/TR 16496:2013, Construction Products — Assessment of release of dangerous substances — Use of harmonised horizontal assessment methods

EN ISO 13137, Workplace atmospheres — Pumps for personal sampling of chemical and biological agents — Requirements and test methods

EN ISO 16000-9:2006, Indoor air — Part 9: Determination of the emission of volatile organic compounds from building products and furnishing — Emission test chamber method (ISO 16000-9:2006)

EN ISO 16000-11:2006, Indoor air — Part 11: Determination of the emission of volatile organic compounds from building products and furnishing — Sampling, storage of samples and preparation of test specimens (ISO 16000-11:2006)

EN ISO 16017-1, Indoor, ambient and workplace air — Sampling and analysis of volatile organic compounds by sorbent tube/thermal desorption/capillary gas chromatography — Part 1: Pumped sampling (ISO 16017-1)

ISO 554, Standard atmospheres for conditioning and/or testing — Specifications

ISO 16000-3:2011, Indoor air — Part 3: Determination of formaldehyde and other carbonyl compounds in indoor air and test chamber air — Active sampling method

ISO 16000-6:2011, Indoor air — Part 6: Determination of volatile organic compounds in indoor and test chamber air by active sampling on Tenax TA sorbent, thermal desorption and gas chromatography using MS or MS-FID

3 Terms, definitions and abbreviations

For the purposes of this document, the following terms, definitions and abbreviations apply.

NOTE Several of the defined terms on product sampling are closely related, which is also depicted in Figure 1. This figure and the relevant definitions are taken from CEN/TR 16220:2011.



This is a free preview. Purchase the entire publication at the link below:

Product Page

S Looking for additional Standards? Visit Intertek Inform Infostore

> Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation