



**NSAI**  
Standards

Irish Standard  
I.S. EN 55022:2010

# Information technology equipment - Radio disturbance characteristics - Limits and methods of measurement (CISPR 22:2008 (MOD))

## I.S. EN 55022:2010

*Incorporating amendments/corrigenda issued since publication:*

EN 55022:2010/AC:2011

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

<i>This document replaces:</i> EN 55022:2006, EN 55022:2006/A1:2007, EN 55022:2006/A2:2010	<i>This document is based on:</i> EN 55022:2010	<i>Published:</i> 10 December, 2010
This document was published under the authority of the NSAI and comes into effect on:  9 March, 2011		ICS number: 33.100.10
<b>NSAI</b> 1 Swift Square, Northwood, Santry Dublin 9	T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie  W NSAI.ie	<b>Sales:</b> T +353 1 857 6730 F +353 1 857 6729 W standards.ie
Údarás um Chaighdeáin Náisiúnta na hÉireann		



## Corrigendum to EN 55022:2010

English version

*In the common modifications regarding 8.4, replace on page 3 "2nd paragraph" with "3rd paragraph" to read: "Replace the last sentence of original 3rd paragraph by:".*

*Replace the entire Annex ZA with the following:*

"

### **Annex ZA** (normative)

#### **Normative references to international publications with their corresponding European publications**

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

NOTE When an international publication has been modified by common modifications, indicated by (mod), the relevant EN/HD applies.

<u>Publication</u>	<u>Year</u>	<u>Title</u>	<u>EN/HD</u>	<u>Year</u>
IEC/TR 60083	2006	Plugs and socket-outlets for domestic and similar general use standardized in member countries of IEC	-	-
IEC 61000-4-6 + A1 + A2	2003 2004 2006	Electromagnetic compatibility (EMC) - Part 4-6: Testing and measurement techniques - Immunity to conducted disturbances, induced by radio-frequency fields	EN 61000-4-6 + corr. August <sup>1) 2)</sup>	2007 2007
CISPR 11 (mod) + A1	2003 2004	Industrial scientific and medical (ISM) radio- frequency equipment - Electromagnetic disturbance characteristics - Limits and methods of measurement	EN 55011 <sup>3)</sup>	2007
CISPR 13 (mod)	2001	Sound and television broadcast receivers and	EN 55013	2001

<sup>1)</sup> EN 61000-4-6 includes A1 + A2 to IEC 61000-4-6.

<sup>2)</sup> EN 61000-4-6 is superseded by EN 61000-4-6:2009, which is based on IEC 61000-4-6:2008.

<sup>3)</sup> EN 55011 includes A1 to CISPR 11 (mod).

**I.S. EN 55022:2010**

+ A1	2003	associated equipment - Radio disturbance	+ A1	2003
+ A2	2006	characteristics - Limits and methods of measurement	+ A2	2006
CISPR 16-1-1 + A1	-	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-1: Radio disturbance and immunity measuring apparatus - Measuring apparatus	EN 55016-1-1 + A1	-
CISPR 16-1-2 + A1	2003	Specification for radio disturbance and immunity measuring apparatus and methods -	EN 55016-1-2 + A1	2004
+ A2	2004	Part 1-2: Radio disturbance and immunity measuring apparatus - Ancillary equipment -	+ A2	2005
+ corr. January	2006	Conducted disturbances		2006
CISPR 16-1-4	-	Specification for radio disturbance and immunity measuring apparatus and methods - Part 1-4: Radio disturbance and immunity measuring apparatus - Ancillary equipment - Radiated disturbances	EN 55016-1-4	-
CISPR 16-2-3 + A1	2003	Specification for radio disturbance and immunity measuring apparatus and methods -	EN 55016-2-3 + A1	2004
+ A2	2005	Part 2-3: Methods of measurement of disturbances and immunity - Radiated disturbance measurements	+ A2	2005
CISPR 16-4-2	2003	Specification for radio disturbance and immunity measuring apparatus and methods - Part 4-2: Uncertainties, statistics and limit modelling - Uncertainty in EMC measurements	EN 55016-4-2	2004

"

October 2011

EUROPEAN STANDARD  
NORME EUROPÉENNE  
EUROPÄISCHE NORM

**EN 55022**

December 2010

ICS 33.100.10

Supersedes EN 55022:2006 + A1:2007 + A2:2010

English version

**Information technology equipment -  
Radio disturbance characteristics -  
Limits and methods of measurement  
(CISPR 22:2008, modified)**

Appareils de traitement de l'information -  
Caractéristiques des perturbations  
radioélectriques -  
Limites et méthodes de mesure  
(CISPR 22:2008, modifiée)

Einrichtungen der Informationstechnik -  
Funkstöreigenschaften -  
Grenzwerte und Messverfahren  
(CISPR 22:2008, modifiziert)

This European Standard was approved by CENELEC on 2010-12-01. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the Central Secretariat or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the Central Secretariat has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland and the United Kingdom.

**CENELEC**

European Committee for Electrotechnical Standardization  
Comité Européen de Normalisation Electrotechnique  
Europäisches Komitee für Elektrotechnische Normung

**Management Centre: Avenue Marnix 17, B - 1000 Brussels**

## Foreword

The text of the International Standard CISPR 22:2008, prepared by CISPR SC I, "Electromagnetic compatibility of information technology equipment, multimedia equipment and receivers", together with common modifications prepared by the Technical Committee CENELEC TC 210, "Electromagnetic compatibility (EMC)", was submitted to the Unique Acceptance Procedure and was approved by CENELEC as EN 55022 on 2010-12-01.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CEN and CENELEC shall not be held responsible for identifying any or all such patent rights.

This document supersedes EN 55022:2006 + A1:2007 + FprA2:2009.

The following dates were fixed:

- latest date by which the EN has to be implemented  
at national level by publication of an identical  
national standard or by endorsement (dop) 2011-12-01
- latest date by which the national standards conflicting  
with the EN have to be withdrawn (dow) 2013-12-01

This European Standard has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association and covers essential requirements of EC Directives 2004/108/EC and 1999/5/EC. See Annex ZZ.

Annexes ZA and ZZ have been added by CENELEC.

---

## Endorsement notice

The text of the International Standard CISPR 22:2008 was approved by CENELEC as a European Standard with agreed common modifications as given below.

### COMMON MODIFICATIONS

#### 4 Classification of ITE

##### 4.2 Class A ITE

**Replace the 1<sup>st</sup> paragraph by:**

Class A ITE is a category of all other ITE which satisfies the class A ITE limits but not the class B ITE limits. The following warning shall be included in the instructions for use:

#### 8 General measurement conditions

##### 8.4 Operation of the EUT

**Delete the final sentence in the 1<sup>st</sup> paragraph so that it reads:**

The operational conditions of the EUT shall be determined by the manufacturer according to the typical use of the EUT with respect to the expected highest level of emission. The determined operational mode and the rationale for the conditions shall be stated in the test report.

SC CIS/II/Publication CISPR 22 (2008), Sixth edition/I-SH 01

**INFORMATION TECHNOLOGY EQUIPMENT –  
RADIO DISTURBANCE CHARACTERISTICS –  
LIMITS AND METHODS OF MEASUREMENT**

**INTERPRETATION SHEET 1**

This interpretation sheet has been prepared by CISPR subcommittee I: Electromagnetic compatibility of information technology equipment, multimedia equipment and receivers, of IEC technical committee CISPR: International special committee on radio interference.

The text of this interpretation sheet is based on the following documents:

ISH	Report on voting
CISPR/II/299/ISH	CISPR/II/312/RVD

Full information on the voting for the approval of this interpretation sheet can be found in the report on voting indicated in the above table.

---

**Introduction:**

At the CISPR SC I plenary, held on the 27<sup>th</sup> October 2007, a decision was taken to set the maintenance date for CISPR 22, Edition 6 to 2012. As a result the work identified within CISPR/II/279/MCR will not be started for the time being. At the subsequent meeting of CISPR SC I WG3 it was decided that certain items within the MCR would benefit now from further clarification and an interpretation sheet would be helpful to users of the standard, with the intent of including this information in a future amendment to the standard.

This information does not change the standard; it serves only to clarify the points noted.

CISPR SC I WG3 hopes that these clarifications will be of use to users and especially laboratories testing to CISPR 22, Edition 6.0. The document is based on the comments received on CISPR/II/290/DC.

**Interpretation:**

**1. Selection of Average detector**

CISPR 22 defines limits for radiated emissions at frequencies between 1 GHz and 6 GHz with respect to both average and peak detectors. CISPR 16-1-1 defines two types of Average detector for use above 1 GHz. For the limits given in CISPR 22 the appropriate average detector is the linear average detector defined in 6.4.1 of CISPR 16-1-1:2006 with its Amendments 1:2006 and 2:2007.

## **2. Measurement of conducted emissions on cabinets containing multiple items of equipment**

Where the EUT is a cabinet or rack that contains multiple items of equipment that are powered from an AC power distribution strip and where the AC power distribution strip is an integral part of the EUT as declared by the manufacturer, the AC power line conducted emissions should be measured on the input cable of power distribution strip that leaves the cabinet or rack, not the power cables from the individual items of equipment. This is consistent with the requirements in 9.5.1 paragraph 1 and sub paragraph c).

---



SC CIS I/Publication CISPR 22:2008, Sixth edition/I-SH 02

**INFORMATION TECHNOLOGY EQUIPMENT –  
RADIO DISTURBANCE CHARACTERISTICS –  
LIMITS AND METHODS OF MEASUREMENT****INTERPRETATION SHEET 2**

This interpretation sheet has been prepared by CISPR subcommittee I: Electromagnetic compatibility of information technology equipment, multimedia equipment and receivers, of IEC technical committee CISPR: International special committee on radio interference.

The text of this interpretation sheet is based on the following documents:

ISH	Report on voting
CISPR/I/323/ISH	CISPR/I/326/RVD

Full information on the voting for the approval of this interpretation sheet can be found in the report on voting indicated in the above table.

---

**Introduction**

At the CISPR SC I plenary, held on the 27<sup>th</sup> October 2007, a decision was taken to set the maintenance date for CISPR 22, Edition 6 to 2012. As a result the work identified within CISPR/I/279/MCR will not be started for the time being. At the subsequent meeting of CISPR SC I WG3 it was decided that 3 items within the MCR would benefit now from further clarification and an interpretation sheet would be helpful to users of the standard, with the intent of including this information in a future amendment to the standard.

The first draft of an interpretation sheet CISPR/I/290/DC addressed the 3 items, however it was clear from the comments received (CISPR/I/293A/INF) that further work was required on the 3<sup>rd</sup> item related to ISN selection, and it was decided that this would be the subject of a separate document.

This information does not change the standard; it serves only to clarify the points noted.

CISPR SC I WG3 hopes that these clarifications will be of use to users and especially laboratories testing to CISPR 22:2008 (Edition 6.0).

**Selection of ISN for unscreened balanced multi-pair cables**

Subclause 9.6.3.1 of CISPR 22 states that:

*“When disturbance voltage measurements are performed on a single unscreened balanced pair, an adequate ISN for two wires shall be used; when performed on unscreened cables containing two balanced pairs, an adequate ISN for four wires shall be used; when performed on unscreened cables containing four balanced pairs, an adequate ISN for eight wires shall be used (see Annex D)”*

Therefore the selection of ISN is based on the number of pairs physically in the cable, not the number of pairs actually used by the interface in question.

However, selection of a suitable ISN design from the examples given in Annex D requires further consideration. The ISN designs given in Figures D.4 to D.7 are only appropriate for use where all of the balanced pairs in the cable are 'active' and hence their use requires a more detailed knowledge of the EUT port being tested. The ISN designs given in Figures D.1 to D.3 have no such limitation and are better suited to applications where the actual use of the pairs is unknown.

The ISN designs given in Figures D.2 and D.3 are also suitable for measurements on unscreened cables containing fewer balanced pairs than the maximum number of pairs the ISN is designed for (see example 2).

The following definitions have been developed to help in determining what should be considered an 'active' pair of conductors:

An **active pair** is a pair of conductors that completes an active digital, analogue, or power circuit, or is terminated in a defined impedance, or is connected to earth or the equipment frame/chassis.

NOTE These circuits include such applications as "Power over Ethernet".

A circuit is an **active circuit** when it is in a state that is performing its intended function, which may include communications, voltage/current sensing, impedance matching or power supply.

NOTE A conductor with no intended function is not part of an active circuit.

A measurement using an ISN described in Figures D.4 to D.7, when not all of the pairs are 'active', may result in a significant error in the measured emissions. It is therefore important that test laboratories determine on which of the designs given in the annexes their particular ISNs are based. From this they can then determine if they need to establish the number of 'active' pairs within the cable or not and then whether their ISNs are suitable for the port being measured or whether an alternative measurement technique needs to be used.

This is applicable when measuring in accordance with 9.6.3.1 or 9.6.3.2.

It is recommended that test reports should make reference to:

- the ISN category used;
- the Annex D figure corresponding to their particular ISN design;
- the total number of pairs in the cable and number of these that were active.

#### Example 1:

The EUT has an Ethernet port to which either a CAT 5 or 6 cable is connected. Typically these cables have four pairs requiring use of a four pair ISN. Transmission using 1000Base-T Ethernet protocol uses all four pairs of a typical cable. Transmission using 10Base-T and 100Base-T Ethernet protocol uses only two of the four pairs for communication. One of the following ISNs could therefore be used:

- 1) ISN as shown in Figure D.3, or
- 2) ISN as shown in Figures D.6 or D.7 if it is known that all the pairs within the cable are 'active'. This would be the case if a 1000BaseT Ethernet protocol were being used. These ISNs would also be suitable for 10BaseT or 100BaseT protocol if the unused pairs have controlled terminations in the EUT port by design, making all pairs 'active' from an EMC perspective.

Should an EUT with an Ethernet port be provided with a cable that contains only 2 pairs within it, then any of the following types of ISN could be used: D2, D3, D4 or D5.

**Example 2:**

The EUT has a single ADSL port and is provided with a cable containing 2 pairs. ADSL is a single pair system so only 1 pair is active. The following ISNs could be used:

- 1) ISN as shown in Figure D.2 or D.3.

**Cable length between ISN and EUT when measuring telecommunication ports**

Subclause 9.5.1 of CISPR 22 requires that the distance between the ISN and the EUT be nominally 0.8m and also clause 9.5.2 states that:

*“Signal cables shall be positioned for their entire lengths, as far as possible, at a nominal distance of 0,4 m from the ground reference plane (using a non-conductive fixture, if necessary).”*

No other requirement is given on the actual length of the cable to be used.

Measurements have shown that non-inductive bundling of any excess cable can result in slightly higher emission levels measured at the ISN.

It is therefore recommended that the cable between the telecommunication port and the ISN should be kept as short as possible, in order to avoid the need to bundle any excess, while maintaining the requirements given in 9.5.1 and 9.5.2.

## CONTENTS

FOREWORD.....	5
INTRODUCTION.....	7
1 Scope and object.....	8
2 Normative references.....	8
3 Definitions .....	9
4 Classification of ITE.....	10
4.1 Class B ITE .....	11
4.2 Class A ITE .....	11
5 Limits for conducted disturbance at mains terminals and telecommunication ports.....	11
5.1 Limits of mains terminal disturbance voltage .....	11
5.2 Limits of conducted common mode (asymmetric mode) disturbance at telecommunication ports .....	12
6 Limits for radiated disturbance .....	13
6.1 Limits below 1 GHz.....	13
6.2 Limits above 1 GHz .....	13
7 Interpretation of CISPR radio disturbance limit .....	14
7.1 Significance of a CISPR limit .....	14
7.2 Application of limits in tests for conformity of equipment in series production.....	14
8 General measurement conditions.....	15
8.1 Ambient noise.....	15
8.2 General arrangement.....	15
8.3 EUT arrangement .....	18
8.4 Operation of the EUT.....	20
9 Method of measurement of conducted disturbance at mains terminals and telecommunication ports .....	21
9.1 Measurement detectors .....	21
9.2 Measuring receivers .....	21
9.3 Artificial mains network (AMN).....	21
9.4 Ground reference plane .....	22
9.5 EUT arrangement .....	22
9.6 Measurement of disturbances at telecommunication ports.....	24
9.7 Recording of measurements .....	28
10 Method of measurement of radiated disturbance .....	28
10.1 Measurement detectors .....	28
10.2 Measuring receiver below 1 GHz.....	28
10.3 Antenna below 1 GHz .....	28
10.4 Measurement site below 1 GHz.....	29
10.5 EUT arrangement below 1 GHz.....	30
10.6 Radiated emission measurements above 1 GHz.....	30
10.7 Recording of measurements .....	30
10.8 Measurement in the presence of high ambient signals.....	31
10.9 User installation testing.....	31
11 Measurement uncertainty.....	31
Annex A (normative) Site attenuation measurements of alternative test sites .....	42
Annex B (normative) Decision tree for peak detector measurements.....	48

Annex C (normative) Possible test set-ups for common mode measurements .....	49
Annex D (informative) Schematic diagrams of examples of impedance stabilization networks (ISN) .....	56
Annex E (informative) Parameters of signals at telecommunication ports .....	65
Annex F (informative) Rationale for disturbance measurements and methods on telecommunications ports .....	68
Annex G (informative) Operational modes for some types of ITE .....	77
Bibliography .....	78
Figure 1 – Test site .....	32
Figure 2 – Minimum alternative measurement site .....	33
Figure 3 – Minimum size of metal ground plane .....	33
Figure 4 – Example test arrangement for tabletop equipment (conducted and radiated emissions) (plan view) .....	34
Figure 5 – Example test arrangement for tabletop equipment (conducted emission measurement - alternative 1a) .....	35
Figure 6 – Example test arrangement for tabletop equipment (conducted emission measurement – alternative 1b) .....	35
Figure 7 – Example test arrangement for tabletop equipment (conducted emission measurement – alternative 2) .....	36
Figure 8 – Example test arrangement for floor-standing equipment (conducted emission measurement) .....	37
Figure 9 – Example test arrangement for combinations of equipment (conducted emission measurement) .....	38
Figure 10 – Example test arrangement for tabletop equipment (radiated emission measurement) .....	38
Figure 11 – Example test arrangement for floor-standing equipment (radiated emission measurement) .....	39
Figure 12 – Example test arrangement for floor-standing equipment with vertical riser and overhead cables (radiated and conducted emission measurement) .....	40
Figure 13 – Example test arrangement for combinations of equipment (radiated emission measurement) .....	41
Figure A.1 – Typical antenna positions for alternate site NSA measurements .....	45
Figure A.2 – Antenna positions for alternate site measurements for minimum recommended volume .....	46
Figure B.1 – Decision tree for peak detector measurements .....	48
Figure C.1 – Using CDNs described in IEC 61000-4-6 as CDN/ISNs .....	50
Figure C.2 – Using a 150 $\Omega$ load to the outside surface of the shield ("in situ CDN/ISN") .....	51
Figure C.3 – Using a combination of current probe and capacitive voltage probe with a table top EUT .....	52
Figure C.4 – Calibration fixture .....	54
Figure C.5 – Flowchart for selecting test method .....	55
Figure D.1 – ISN for use with unscreened single balanced pairs .....	56
Figure D.2 – ISN with high longitudinal conversion loss (LCL) for use with either one or two unscreened balanced pairs .....	57
Figure D.3 – ISN with high longitudinal conversion loss (LCL) for use with one, two, three, or four unscreened balanced pairs .....	58

Figure D.4 – ISN, including a 50 $\Omega$ source matching network at the voltage measuring port, for use with two unscreened balanced pairs .....	59
Figure D.5 – ISN for use with two unscreened balanced pairs .....	60
Figure D.6 – ISN, including a 50 $\Omega$ source matching network at the voltage measuring port, for use with four unscreened balanced pairs .....	61
Figure D.7 – ISN for use with four unscreened balanced pairs .....	62
Figure D.8 – ISN for use with coaxial cables, employing an internal common mode choke created by bifilar winding an insulated centre-conductor wire and an insulated screen-conductor wire on a common magnetic core (for example, a ferrite toroid).....	62
Figure D.9 – ISN for use with coaxial cables, employing an internal common mode choke created by miniature coaxial cable (miniature semi-rigid solid copper screen or miniature double-braided screen coaxial cable) wound on ferrite toroids .....	63
Figure D.10 – ISN for use with multi-conductor screened cables, employing an internal common mode choke created by bifilar winding multiple insulated signal wires and an insulated screen-conductor wire on a common magnetic core (for example, a ferrite toroid) .....	63
Figure D.11 – ISN for use with multi-conductor screened cables, employing an internal common mode choke created by winding a multi-conductor screened cable on ferrite toroids .....	64
Figure F.1 – Basic circuit for considering the limits with defined TCM impedance of 150 $\Omega$ ....	71
Figure F.2 – Basic circuit for the measurement with unknown TCM impedance .....	71
Figure F.3 – Impedance layout of the components used in Figure C.2.....	73
Figure F.4 – Basic test set-up to measure combined impedance of the 150 $\Omega$ and ferrites .....	74
Table 1 – Limits for conducted disturbance at the mains ports of class A ITE .....	11
Table 2 – Limits for conducted disturbance at the mains ports of class B ITE.....	12
Table 3 – Limits of conducted common mode (asymmetric mode) disturbance at telecommunication ports in the frequency range 0,15 MHz to 30 MHz for class A equipment.....	12
Table 4 – Limits of conducted common mode (asymmetric mode) disturbance at telecommunication ports in the frequency range 0,15 MHz to 30 MHz for class B equipment.....	12
Table 5 – Limits for radiated disturbance of class A ITE at a measuring distance of 10 m.....	13
Table 6 – Limits for radiated disturbance of class B ITE at a measuring distance of 10 m.....	13
Table 7 – Limits for radiated disturbance of Class A ITE at a measurement distance of 3 m...	13
Table 8 – Limits for radiated disturbance of Class B ITE at a measurement distance of 3 m...	14
Table 9 – Acronyms used in figures .....	32
Table A.1 – Normalized site attenuation ( $A_N$ (dB)) for recommended geometries with broadband antennas .....	44
Table F.1 – Summary of advantages and disadvantages of the methods described in Annex C.....	69

**INTERNATIONAL ELECTROTECHNICAL COMMISSION  
INTERNATIONAL SPECIAL COMMITTEE ON RADIO INTERFERENCE**

---

**INFORMATION TECHNOLOGY EQUIPMENT –  
RADIO DISTURBANCE CHARACTERISTICS –  
LIMITS AND METHODS OF MEASUREMENT**

**FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard CISPR 22 has been prepared by CISPR subcommittee 1: Electromagnetic compatibility of information technology equipment, multimedia equipment and receivers.

This sixth edition of CISPR 22 cancels and replaces the fifth edition published in 2005, its Amendment 1 (2005) and Amendment 2 (2006). This edition constitutes a minor revision.

The document CISPR/1/265/FDIS, circulated to the National Committees as Amendment 3, led to the publication of the new edition.

The text of this standard is based on the fifth edition, Amendment 1, Amendment 2 and the following documents:

FDIS	Report on voting
CISPR/II/265/FDIS	CISPR/II/271/RVD

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed;
- withdrawn;
- replaced by a revised edition; or
- amended.



**I.S. EN 55022:2010**

CISPR 22 © IEC:2008

– 7 –

## INTRODUCTION

The scope is extended to the whole radio-frequency range from 9 kHz to 400 GHz, but limits are formulated only in restricted frequency bands, which is considered sufficient to reach adequate emission levels to protect radio broadcast and telecommunication services, and to allow other apparatus to operate as intended at reasonable distance.

# INFORMATION TECHNOLOGY EQUIPMENT – RADIO DISTURBANCE CHARACTERISTICS – LIMITS AND METHODS OF MEASUREMENT

## 1 Scope and object

This International Standard applies to ITE as defined in 3.1.

Procedures are given for the measurement of the levels of spurious signals generated by the ITE and limits are specified for the frequency range 9 kHz to 400 GHz for both class A and class B equipment. No measurements need be performed at frequencies where no limits are specified.

The intention of this publication is to establish uniform requirements for the radio disturbance level of the equipment contained in the scope, to fix limits of disturbance, to describe methods of measurement and to standardize operating conditions and interpretation of results.

## 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60083:2006, *Plugs and socket-outlets for domestic and similar general use standardized in member countries of IEC*

IEC 61000-4-6:2003, *Electromagnetic compatibility (EMC) – Part 4-6: Testing and measurement techniques – Immunity to conducted disturbances, induced by radio-frequency fields*<sup>1</sup>

Amendment 1 (2004)

Amendment 2 (2006)

CISPR 11:2003, *Industrial, scientific, and medical (ISM) radio-frequency equipment – Electromagnetic disturbance characteristics – Limits and methods of measurement*<sup>2</sup>

Amendment 1 (2004)

CISPR 13:2001, *Sound and television broadcast receivers and associated equipment – Radio disturbance characteristics – Limits and methods of measurement*<sup>3</sup>

Amendment 1 (2003)

Amendment 2 (2006)

CISPR 16-1-1:2006, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1-1: Radio disturbance and immunity measuring apparatus – Measuring apparatus*<sup>4</sup>

Amendment 1 (2006)

Amendment 2 (2007)

---

<sup>1</sup> There exists a consolidated edition 2.2 (2006) including edition 2.0, its Amendment 1 (2004) and its Amendment 2 (2006).

<sup>2</sup> There exists a consolidated edition 4.1 (2004) including edition 4.0 and its Amendment 1 (2004).

<sup>3</sup> There exists a consolidated edition 4.2 (2006) including edition 4.0, its Amendment 1 (2003) and its Amendment 2 (2006).

<sup>4</sup> There exists a consolidated edition 2.2 (2007) including edition 2.0, its Amendment 1 (2006) and its Amendment 2 (2007).

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

- 
- Looking for additional Standards? Visit Intertek Inform Infostore
  - Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation
-