



NSAI
Standards

Irish Standard
I.S. EN 50050-1:2013

Electrostatic hand-held spraying equipment - Safety requirements -- Part 1: Hand-held spraying equipment for ignitable liquid coating materials

I.S. EN 50050-1:2013

Incorporating amendments/corrigenda issued since publication:

The National Standards Authority of Ireland (NSAI) produces the following categories of formal documents:

I.S. xxx: Irish Standard – national specification based on the consensus of an expert panel and subject to public consultation.

S.R. xxx: Standard Recommendation - recommendation based on the consensus of an expert panel and subject to public consultation.

SWiFT xxx: A rapidly developed recommendatory document based on the consensus of the participants of an NSAI workshop.

<i>This document replaces:</i> EN 50050:2006 (partially)	<i>This document is based on:</i> EN 50050-1:2013	<i>Published:</i> 8 November, 2013
This document was published under the authority of the NSAI and comes into effect on: 12 November, 2013		ICS number: 87.100
NSAI 1 Swift Square, Northwood, Santry Dublin 9	T +353 1 807 3800 F +353 1 807 3838 E standards@nsai.ie W NSAI.ie	Sales: T +353 1 857 6730 F +353 1 857 6729 W standards.ie
Údarás um Chaighdeáin Náisiúnta na hÉireann		

English version

**Electrostatic hand-held spraying equipment -
Safety requirements -
Part 1: Hand-held spraying equipment for ignitable liquid coating
materials**

Équipement manuel de projection
électrostatique - Exigences de sécurité -
Partie 1 : Équipement manuel de
projection de liquides de revêtement
inflammable

Elektrostatische Handsprüheinrichtungen -
Sicherheitsanforderungen -
Teil 1: Handsprüheinrichtungen für
entzündbare flüssige Beschichtungsstoffe

This European Standard was approved by CENELEC on 2013-10-14. CENELEC members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration.

Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CENELEC member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CENELEC member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CENELEC members are the national electrotechnical committees of Austria, Belgium, Bulgaria, Croatia, Cyprus, the Czech Republic, Denmark, Estonia, Finland, Former Yugoslav Republic of Macedonia, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, the Netherlands, Norway, Poland, Portugal, Romania, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and the United Kingdom.

CENELEC

European Committee for Electrotechnical Standardization
Comité Européen de Normalisation Electrotechnique
Europäisches Komitee für Elektrotechnische Normung

CEN-CENELEC Management Centre: Avenue Marnix 17, B - 1000 Brussels

Contents

Page

Foreword		3
0	Introduction	5
0.1	Process	5
0.2	Explosion hazards	5
0.3	Electric hazards	5
1	Scope	6
2	Normative references	7
3	Terms and definitions	8
4	Requirements for hand-held spraying equipment for ignitable liquid coating materials	10
4.1	General requirements	10
4.2	Requirements for the accessories	11
5	Tests	12
5.1	General	12
5.2	General tests	12
5.3	Conditioning test	13
5.4	Tests for electrical safety	13
5.5	Ignition test	14
5.6	Tests of the accessories	14
6	Information for use	15
6.1	General	15
6.2	Instruction manual	15
6.3	Marking of electrostatic hand-held spraying equipment and associated control devices	17
Annex A (normative)	Test for ignition protection using a shunt and an oscilloscope	20
Annex B (normative)	Ignition test within the gas mixture	21
B.1	General	21
B.2	Preparations	21
B.3	Preliminary test	21
B.4	Test	22
B.5	Result	22
Annex C (informative)	Quality assurance systems for electrostatic spraying equipment	23
C.1	General	23
C.2	Electrical assembly	23
C.3	Mechanical assembly	24
C.4	Tests	24
Annex D (normative)	Requirements for explosion protection and prevention for ionisators	25
Annex E (informative)	Ignitability of water-based paints	26
E.1	General	26
E.2	Non-ignitable	26
E.3	Hard to ignite	26
E.4	Ignitable	26
Annex ZY (informative)	Significant changes between this European Standard and EN 50050:2006	27
Annex ZZ (informative)	Coverage of Essential Requirements of EU Directives	29
Bibliography		30
Figure		
Figure B.1	— Example of a test arrangement	21
Tables		

Table 1 — Test intervals.....	17
Table D.1 — Requirements for ionisators	25

Foreword

This document (EN 50050-1:2013) has been prepared by SC 31-8, "Electrostatic painting and finishing equipment", of CLC/TC 31, "Electrical apparatus for potentially explosive atmospheres".

The following dates are fixed:

- latest date by which this document has to be implemented at national level by publication of an identical national standard or by endorsement (dop) 2014-10-14
- latest date by which the national standards conflicting with this document have to be withdrawn (dow) 2016-10-14

In combination with EN 50050-2:2013 and EN 50050-3:2013, this document supersedes EN 50050:2006.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. CENELEC [and/or CEN] shall not be held responsible for identifying any or all such patent rights.

This document has been prepared under a mandate given to CENELEC by the European Commission and the European Free Trade Association, and supports essential requirements of EU Directive(s).

For the relationship with EU Directive(s) see informative Annex ZZ, which is an integral part of this document.

0 Introduction

0.1 Process

During the electrostatic coating process the liquid coating material is transported to an applicator where it is atomised and converted to droplets by mechanical forces and by the influence of an electric field. During this atomising process the droplets are charged by high voltage of some 10 kV and a spray cloud is generated. The charged droplets are attracted by and applied to the earthed workpiece.

Droplets, which are not applied to the workpiece (overspray) are removed by a suction device or by other means.

After the coating process the coated workpieces are introduced into a dryer where the solvent is evaporated and a dry film of coating material is generated.

0.2 Explosion hazards

0.2.1 An explosion could occur, if

- the concentration of sprayed ignitable liquid coating material in air is within the explosion limits,
- an ignition source of appropriate energy for this explosive atmosphere is present.

Ignition sources could be, for instance, a hot surface, a naked flame, an electric arc or a spark.

An explosion could be prevented, if at least one condition is avoided. Because it is very difficult to exclude the possibility of ignitable discharges completely, the main focus should be the prevention of an explosive atmosphere.

0.2.2 An explosive atmosphere can only explode within a given range of concentration, but not, if the concentration is above or below this range.

NOTE If an explosive mixture of coating materials and air is trapped into a closed room, an explosion can lead to a fatal increase of pressure.

0.2.3 Particular attention should be paid to the prevention of electrostatic charges on different surfaces located in the vicinity of the spraying cloud. This could apply to e.g. workpieces during the coating process. Grounding is critical to the prevention of electrostatic charge to any conductive objects in the spray area.

0.3 Electric hazards

0.3.1 Electric shock (by direct or indirect contact) can be generated, for instance, by contact with

- live parts, which are not insulated for operational reasons,
- conductive parts, which are not connected to dangerous voltage during normal operation, but only in case of failure,
- insulated live parts with insufficient or damaged insulation due to external impact.

0.3.2 Inadequate earthing may occur, for instance, due to

- faulty connections to the protective earthing system,
- a too high resistance to earth (e. g. contamination by coating materials).

0.3.3 Hazards could occur, for instance, if hazardous malfunctions (e.g. shortcut of electronic safety circuits) occur due to interferences of the electrostatic high voltage equipment and the components of the control and safety systems.

0.3.4 Hazardous electrostatic discharges could be generated, for instance, by non-earthed conductive components or by large insulating surfaces, especially if they are backed with conductive material.

1 Scope

1.1 This European Standard specifies the requirements for hand-held or hand-operated electrostatic spraying equipment for ignitable liquid coating materials to be used in explosive atmospheres generated by their own spray cloud within a temperature range from 5 °C to 40 °C.

This European Standard deals with all hazards significant for the electrostatic spraying of liquid coating materials, which could also contain small quantities of added metal particles, if the work is carried out under conditions recommended by the manufacturer. In particular, this includes ignition hazards resulting from the generated explosive atmosphere.

This European Standard specifies the design-related and test requirements for electrostatic spraying equipment of type A-L according to Table 1 of EN 50176:2009.

1.2 With regard to explosion protection and prevention measures, this European Standard also applies to ionisators with high voltage corona charging. Ionisators in conformity with EN 50050-1 provide equipment category 2G. Parts of ionisators, which are intended to be used or installed in Zone 2, provide equipment category 3G in conformity with EN 50050-1:2013, see Annex D.

1.3 Electrostatic applicators are considered to be equipment of group II, category 2G for use in potentially explosive areas of zone 1 or 2, which have been generated by the equipment itself. All other parts of hand-held electrostatic spraying equipment are considered to be equipment of category 3G if they are installed or used in potentially explosive areas of zone 2.

1.4 All other significant hazards relevant for applicators (e.g. ejection of fluids, mechanical strength, electrical hazards (apart from the electrostatic hazards), noise, explosion, contact with or inhalation of dangerous substances, ergonomics) are covered by EN 1953.

1.5 This European Standard also gives details regarding quality assurance systems for electrostatic spraying equipment, see Annex C.

1.6 Additional requirements may be applicable to equipment designed for use in food and pharmaceutical industry.

1.7 This European Standard does not apply to

- zone classification of the areas in and around spray booths [see EN 12215],
- zone classification of other areas with potentially explosive atmosphere [see EN 60079-10-1],
- selection, erection and application of other electrical and non-electrical equipment in areas with explosion hazard [see EN 60079-14 and EN 12215],
- cleaning of spraying areas, see instruction manual of the spray booth,
- fire prevention and protection, for instance fire hazards due to other sources [see EN 12215],
- requirements for machinery for the supply and recirculation of coating material under pressure [see EN 12621].

1.8 When processing coating materials having specific electrical properties (conductivity, resistivity) the function of the hand-held spraying equipment to charge coating materials electrostatically may be affected as a result of a voltage drop at the charging electrode.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

EN 1149-5	<i>Protective clothing – Electrostatic properties – Part 5: Material performance and design requirements</i>
EN 1953	<i>Atomising and spraying equipment for coating materials – Safety requirements</i>
EN 12215	<i>Coating plants – Spray booths for application of organic liquid coating materials – Safety requirements</i>
prEN 50059:2011	<i>Electrostatic hand-held spraying equipment – Safety requirements – Hand-held spraying equipment for non-ignitable coating materials</i>
EN 50176:2009	<i>Stationary electrostatic application equipment for ignitable liquid coating material – Safety requirements</i>
EN 60079-0	<i>Explosive atmospheres – Part 0: Equipment - General requirements (IEC 60079-0)</i>
EN 60079-7:2007	<i>Explosive atmospheres – Part 7: Equipment protection by increased safety "e" (IEC 60079-7:2006)</i>
EN 60204-1	<i>Safety of machinery – Electrical equipment of machines – Part 1: General requirements (IEC 60204-1)</i>
EN 60529	<i>Degrees of protection provided by enclosures (IP code) (IEC 60529)</i>
EN 61340-4-1	<i>Electrostatics – Part 4-1: Standard test methods for specific applications – Electrical resistance of floor coverings and installed floors (IEC 61340-4-1)</i>
EN 62061	<i>Safety of machinery – Functional safety of safety-related electrical, electronic and programmable electronic control systems (IEC 62061)</i>
EN ISO 12100	<i>Safety of machinery - General principles for design - Risk assessment and risk reduction (ISO 12100)</i>
EN ISO 13849-1	<i>Safety of machinery – Safety-related parts of control systems – Part 1: General principles for design (ISO 13849-1)</i>
EN ISO 20344	<i>Personal protective equipment – Test methods for footwear (ISO 20344)</i>

This is a free preview. Purchase the entire publication at the link below:

[Product Page](#)

-
- [Looking for additional Standards? Visit Intertek Inform Infostore](#)
 - [Learn about LexConnect, All Jurisdictions, Standards referenced in Australian legislation](#)
-